



The Open Source CFD Toolbox

User Guide

Version 3.0.1
13th December 2015

Copyright © 2011-2015 OpenFOAM Foundation Ltd.
Author: Christopher J. Greenshields, CFD Direct Ltd.

This work is licensed under a
Creative Commons Attribution-NonCommercial-NoDerivs 3.0 Unported License.

Typeset in L^AT_EX.

License

THE WORK (AS DEFINED BELOW) IS PROVIDED UNDER THE TERMS OF THIS CREATIVE COMMONS PUBLIC LICENSE (“CCPL” OR “LICENSE”). THE WORK IS PROTECTED BY COPYRIGHT AND/OR OTHER APPLICABLE LAW. ANY USE OF THE WORK OTHER THAN AS AUTHORIZED UNDER THIS LICENSE OR COPYRIGHT LAW IS PROHIBITED.

BY EXERCISING ANY RIGHTS TO THE WORK PROVIDED HERE, YOU ACCEPT AND AGREE TO BE BOUND BY THE TERMS OF THIS LICENSE. TO THE EXTENT THIS LICENSE MAY BE CONSIDERED TO BE A CONTRACT, THE LICENSOR GRANTS YOU THE RIGHTS CONTAINED HERE IN CONSIDERATION OF YOUR ACCEPTANCE OF SUCH TERMS AND CONDITIONS.

1. Definitions

- a. “Adaptation” means a work based upon the Work, or upon the Work and other pre-existing works, such as a translation, adaptation, derivative work, arrangement of music or other alterations of a literary or artistic work, or phonogram or performance and includes cinematographic adaptations or any other form in which the Work may be recast, transformed, or adapted including in any form recognizably derived from the original, except that a work that constitutes a Collection will not be considered an Adaptation for the purpose of this License. For the avoidance of doubt, where the Work is a musical work, performance or phonogram, the synchronization of the Work in timed-relation with a moving image (“synching”) will be considered an Adaptation for the purpose of this License.
- b. “Collection” means a collection of literary or artistic works, such as encyclopedias and anthologies, or performances, phonograms or broadcasts, or other works or subject matter other than works listed in Section 1(f) below, which, by reason of the selection and arrangement of their contents, constitute intellectual creations, in which the Work is included in its entirety in unmodified form along with one or more other contributions, each constituting separate and independent works in themselves, which together are assembled into a collective whole. A work that constitutes a Collection will not be considered an Adaptation (as defined above) for the purposes of this License.
- c. “Distribute” means to make available to the public the original and copies of the Work through sale or other transfer of ownership.
- d. “Licensor” means the individual, individuals, entity or entities that offer(s) the Work under the terms of this License.
- e. “Original Author” means, in the case of a literary or artistic work, the individual, individuals, entity or entities who created the Work or if no individual or entity can be identified, the

publisher; and in addition (i) in the case of a performance the actors, singers, musicians, dancers, and other persons who act, sing, deliver, declaim, play in, interpret or otherwise perform literary or artistic works or expressions of folklore; (ii) in the case of a phonogram the producer being the person or legal entity who first fixes the sounds of a performance or other sounds; and, (iii) in the case of broadcasts, the organization that transmits the broadcast.

- f. “Work” means the literary and/or artistic work offered under the terms of this License including without limitation any production in the literary, scientific and artistic domain, whatever may be the mode or form of its expression including digital form, such as a book, pamphlet and other writing; a lecture, address, sermon or other work of the same nature; a dramatic or dramatico-musical work; a choreographic work or entertainment in dumb show; a musical composition with or without words; a cinematographic work to which are assimilated works expressed by a process analogous to cinematography; a work of drawing, painting, architecture, sculpture, engraving or lithography; a photographic work to which are assimilated works expressed by a process analogous to photography; a work of applied art; an illustration, map, plan, sketch or three-dimensional work relative to geography, topography, architecture or science; a performance; a broadcast; a phonogram; a compilation of data to the extent it is protected as a copyrightable work; or a work performed by a variety or circus performer to the extent it is not otherwise considered a literary or artistic work.
- g. “You” means an individual or entity exercising rights under this License who has not previously violated the terms of this License with respect to the Work, or who has received express permission from the Licensor to exercise rights under this License despite a previous violation.
- h. “Publicly Perform” means to perform public recitations of the Work and to communicate to the public those public recitations, by any means or process, including by wire or wireless means or public digital performances; to make available to the public Works in such a way that members of the public may access these Works from a place and at a place individually chosen by them; to perform the Work to the public by any means or process and the communication to the public of the performances of the Work, including by public digital performance; to broadcast and rebroadcast the Work by any means including signs, sounds or images.
- i. “Reproduce” means to make copies of the Work by any means including without limitation by sound or visual recordings and the right of fixation and reproducing fixations of the Work, including storage of a protected performance or phonogram in digital form or other electronic medium.

2. Fair Dealing Rights.

Nothing in this License is intended to reduce, limit, or restrict any uses free from copyright or rights arising from limitations or exceptions that are provided for in connection with the copyright protection under copyright law or other applicable laws.

3. License Grant.

Subject to the terms and conditions of this License, Licensor hereby grants You a worldwide, royalty-free, non-exclusive, perpetual (for the duration of the applicable copyright) license to exercise the rights in the Work as stated below:

- a. to Reproduce the Work, to incorporate the Work into one or more Collections, and to Reproduce the Work as incorporated in the Collections;

- b. and, to Distribute and Publicly Perform the Work including as incorporated in Collections.

The above rights may be exercised in all media and formats whether now known or hereafter devised. The above rights include the right to make such modifications as are technically necessary to exercise the rights in other media and formats, but otherwise you have no rights to make Adaptations. Subject to 8(f), all rights not expressly granted by Licensor are hereby reserved, including but not limited to the rights set forth in Section 4(d).

4. Restrictions.

The license granted in Section 3 above is expressly made subject to and limited by the following restrictions:

- a. You may Distribute or Publicly Perform the Work only under the terms of this License. You must include a copy of, or the Uniform Resource Identifier (URI) for, this License with every copy of the Work You Distribute or Publicly Perform. You may not offer or impose any terms on the Work that restrict the terms of this License or the ability of the recipient of the Work to exercise the rights granted to that recipient under the terms of the License. You may not sublicense the Work. You must keep intact all notices that refer to this License and to the disclaimer of warranties with every copy of the Work You Distribute or Publicly Perform. When You Distribute or Publicly Perform the Work, You may not impose any effective technological measures on the Work that restrict the ability of a recipient of the Work from You to exercise the rights granted to that recipient under the terms of the License. This Section 4(a) applies to the Work as incorporated in a Collection, but this does not require the Collection apart from the Work itself to be made subject to the terms of this License. If You create a Collection, upon notice from any Licensor You must, to the extent practicable, remove from the Collection any credit as required by Section 4(c), as requested.
- b. You may not exercise any of the rights granted to You in Section 3 above in any manner that is primarily intended for or directed toward commercial advantage or private monetary compensation. The exchange of the Work for other copyrighted works by means of digital file-sharing or otherwise shall not be considered to be intended for or directed toward commercial advantage or private monetary compensation, provided there is no payment of any monetary compensation in connection with the exchange of copyrighted works.
- c. If You Distribute, or Publicly Perform the Work or Collections, You must, unless a request has been made pursuant to Section 4(a), keep intact all copyright notices for the Work and provide, reasonable to the medium or means You are utilizing: (i) the name of the Original Author (or pseudonym, if applicable) if supplied, and/or if the Original Author and/or Licensor designate another party or parties (e.g., a sponsor institute, publishing entity, journal) for attribution (“Attribution Parties”) in Licensor’s copyright notice, terms of service or by other reasonable means, the name of such party or parties; (ii) the title of the Work if supplied; (iii) to the extent reasonably practicable, the URI, if any, that Licensor specifies to be associated with the Work, unless such URI does not refer to the copyright notice or licensing information for the Work. The credit required by this Section 4(c) may be implemented in any reasonable manner; provided, however, that in the case of a Collection, at a minimum such credit will appear, if a credit for all contributing authors of Collection appears, then as part of these credits and in a manner at least as prominent as the credits for the other contributing authors. For the avoidance of doubt, You may only use the credit required by this Section for the purpose of attribution in the manner set out above and, by exercising Your rights under this License, You may not implicitly or explicitly assert or imply any connection with, sponsorship or endorsement by the Original Author, Licensor and/or

Attribution Parties, as appropriate, of You or Your use of the Work, without the separate, express prior written permission of the Original Author, Licensor and/or Attribution Parties.

d. For the avoidance of doubt:

- i. **Non-waivable Compulsory License Schemes.** In those jurisdictions in which the right to collect royalties through any statutory or compulsory licensing scheme cannot be waived, the Licensor reserves the exclusive right to collect such royalties for any exercise by You of the rights granted under this License;
- ii. **Waivable Compulsory License Schemes.** In those jurisdictions in which the right to collect royalties through any statutory or compulsory licensing scheme can be waived, the Licensor reserves the exclusive right to collect such royalties for any exercise by You of the rights granted under this License if Your exercise of such rights is for a purpose or use which is otherwise than noncommercial as permitted under Section 4(b) and otherwise waives the right to collect royalties through any statutory or compulsory licensing scheme; and,
- iii. **Voluntary License Schemes.** The Licensor reserves the right to collect royalties, whether individually or, in the event that the Licensor is a member of a collecting society that administers voluntary licensing schemes, via that society, from any exercise by You of the rights granted under this License that is for a purpose or use which is otherwise than noncommercial as permitted under Section 4(b).

e. Except as otherwise agreed in writing by the Licensor or as may be otherwise permitted by applicable law, if You Reproduce, Distribute or Publicly Perform the Work either by itself or as part of any Collections, You must not distort, mutilate, modify or take other derogatory action in relation to the Work which would be prejudicial to the Original Author's honor or reputation.

5. Representations, Warranties and Disclaimer

UNLESS OTHERWISE MUTUALLY AGREED BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

6. Limitation on Liability.

EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. Termination

a. This License and the rights granted hereunder will terminate automatically upon any breach by You of the terms of this License. Individuals or entities who have received Collections

from You under this License, however, will not have their licenses terminated provided such individuals or entities remain in full compliance with those licenses. Sections 1, 2, 5, 6, 7, and 8 will survive any termination of this License.

- b. Subject to the above terms and conditions, the license granted here is perpetual (for the duration of the applicable copyright in the Work). Notwithstanding the above, Licensor reserves the right to release the Work under different license terms or to stop distributing the Work at any time; provided, however that any such election will not serve to withdraw this License (or any other license that has been, or is required to be, granted under the terms of this License), and this License will continue in full force and effect unless terminated as stated above.

8. Miscellaneous

- a. Each time You Distribute or Publicly Perform the Work or a Collection, the Licensor offers to the recipient a license to the Work on the same terms and conditions as the license granted to You under this License.
- b. If any provision of this License is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this License, and without further action by the parties to this agreement, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.
- c. No term or provision of this License shall be deemed waived and no breach consented to unless such waiver or consent shall be in writing and signed by the party to be charged with such waiver or consent.
- d. This License constitutes the entire agreement between the parties with respect to the Work licensed here. There are no understandings, agreements or representations with respect to the Work not specified here. Licensor shall not be bound by any additional provisions that may appear in any communication from You.
- e. This License may not be modified without the mutual written agreement of the Licensor and You. The rights granted under, and the subject matter referenced, in this License were drafted utilizing the terminology of the Berne Convention for the Protection of Literary and Artistic Works (as amended on September 28, 1979), the Rome Convention of 1961, the WIPO Copyright Treaty of 1996, the WIPO Performances and Phonograms Treaty of 1996 and the Universal Copyright Convention (as revised on July 24, 1971). These rights and subject matter take effect in the relevant jurisdiction in which the License terms are sought to be enforced according to the corresponding provisions of the implementation of those treaty provisions in the applicable national law. If the standard suite of rights granted under applicable copyright law includes additional rights not granted under this License, such additional rights are deemed to be included in the License; this License is not intended to restrict the license of any rights under applicable law.

Trademarks

ANSYS is a registered trademark of ANSYS Inc.

CFX is a registered trademark of Ansys Inc.

CHEMKIN is a registered trademark of Reaction Design Corporation

EnSight is a registered trademark of Computational Engineering International Ltd.

Fieldview is a registered trademark of Intelligent Light

Fluent is a registered trademark of Ansys Inc.

GAMBIT is a registered trademark of Ansys Inc.

Icem-CFD is a registered trademark of Ansys Inc.

I-DEAS is a registered trademark of Structural Dynamics Research Corporation

JAVA is a registered trademark of Sun Microsystems Inc.

Linux is a registered trademark of Linus Torvalds

OpenFOAM is a registered trademark of ESI Group

ParaView is a registered trademark of Kitware

STAR-CD is a registered trademark of Computational Dynamics Ltd.

UNIX is a registered trademark of The Open Group

Contents

| | |
|--|-------------|
| Copyright Notice | U-2 |
| 1. Definitions | U-2 |
| 2. Fair Dealing Rights. | U-3 |
| 3. License Grant. | U-3 |
| 4. Restrictions. | U-4 |
| 5. Representations, Warranties and Disclaimer | U-5 |
| 6. Limitation on Liability. | U-5 |
| 7. Termination | U-5 |
| 8. Miscellaneous | U-6 |
| Trademarks | U-7 |
| Contents | U-9 |
| 1 Introduction | U-15 |
| 2 Tutorials | U-17 |
| 2.1 Lid-driven cavity flow | U-17 |
| 2.1.1 Pre-processing | U-18 |
| 2.1.1.1 Mesh generation | U-18 |
| 2.1.1.2 Boundary and initial conditions | U-20 |
| 2.1.1.3 Physical properties | U-21 |
| 2.1.1.4 Control | U-22 |
| 2.1.1.5 Discretisation and linear-solver settings | U-23 |
| 2.1.2 Viewing the mesh | U-23 |
| 2.1.3 Running an application | U-24 |
| 2.1.4 Post-processing | U-25 |
| 2.1.4.1 Isosurface and contour plots | U-25 |
| 2.1.4.2 Vector plots | U-27 |
| 2.1.4.3 Streamline plots | U-29 |
| 2.1.5 Increasing the mesh resolution | U-29 |
| 2.1.5.1 Creating a new case using an existing case | U-29 |
| 2.1.5.2 Creating the finer mesh | U-31 |
| 2.1.5.3 Mapping the coarse mesh results onto the fine mesh | U-31 |
| 2.1.5.4 Control adjustments | U-32 |
| 2.1.5.5 Running the code as a background process | U-32 |
| 2.1.5.6 Vector plot with the refined mesh | U-32 |
| 2.1.5.7 Plotting graphs | U-33 |

| | | |
|----------|--|-------------|
| 2.1.6 | Introducing mesh grading | U-35 |
| 2.1.6.1 | Creating the graded mesh | U-36 |
| 2.1.6.2 | Changing time and time step | U-37 |
| 2.1.6.3 | Mapping fields | U-38 |
| 2.1.7 | Increasing the Reynolds number | U-38 |
| 2.1.7.1 | Pre-processing | U-39 |
| 2.1.7.2 | Running the code | U-39 |
| 2.1.8 | High Reynolds number flow | U-40 |
| 2.1.8.1 | Pre-processing | U-40 |
| 2.1.8.2 | Running the code | U-42 |
| 2.1.9 | Changing the case geometry | U-42 |
| 2.1.10 | Post-processing the modified geometry | U-46 |
| 2.2 | Stress analysis of a plate with a hole | U-46 |
| 2.2.1 | Mesh generation | U-47 |
| 2.2.1.1 | Boundary and initial conditions | U-50 |
| 2.2.1.2 | Mechanical properties | U-51 |
| 2.2.1.3 | Thermal properties | U-51 |
| 2.2.1.4 | Control | U-51 |
| 2.2.1.5 | Discretisation schemes and linear-solver control | U-52 |
| 2.2.2 | Running the code | U-54 |
| 2.2.3 | Post-processing | U-54 |
| 2.2.4 | Exercises | U-55 |
| 2.2.4.1 | Increasing mesh resolution | U-56 |
| 2.2.4.2 | Introducing mesh grading | U-56 |
| 2.2.4.3 | Changing the plate size | U-56 |
| 2.3 | Breaking of a dam | U-56 |
| 2.3.1 | Mesh generation | U-57 |
| 2.3.2 | Boundary conditions | U-59 |
| 2.3.3 | Setting initial field | U-59 |
| 2.3.4 | Fluid properties | U-60 |
| 2.3.5 | Turbulence modelling | U-61 |
| 2.3.6 | Time step control | U-62 |
| 2.3.7 | Discretisation schemes | U-62 |
| 2.3.8 | Linear-solver control | U-63 |
| 2.3.9 | Running the code | U-64 |
| 2.3.10 | Post-processing | U-64 |
| 2.3.11 | Running in parallel | U-64 |
| 2.3.12 | Post-processing a case run in parallel | U-67 |
| 3 | Applications and libraries | U-69 |
| 3.1 | The programming language of OpenFOAM | U-69 |
| 3.1.1 | Language in general | U-69 |
| 3.1.2 | Object-orientation and C++ | U-70 |
| 3.1.3 | Equation representation | U-70 |
| 3.1.4 | Solver codes | U-71 |
| 3.2 | Compiling applications and libraries | U-71 |
| 3.2.1 | Header <i>.H</i> files | U-71 |
| 3.2.2 | Compiling with <i>wmake</i> | U-73 |

| | | |
|----------|--|--------------|
| 3.2.2.1 | Including headers | U-73 |
| 3.2.2.2 | Linking to libraries | U-74 |
| 3.2.2.3 | Source files to be compiled | U-75 |
| 3.2.2.4 | Running <code>wmake</code> | U-75 |
| 3.2.2.5 | <code>wmake</code> environment variables | U-76 |
| 3.2.3 | Removing dependency lists: <code>wclean</code> and <code>rmdepall</code> | U-76 |
| 3.2.4 | Compilation example: the <code> pisoFoam </code> application | U-77 |
| 3.2.5 | Debug messaging and optimisation switches | U-79 |
| 3.2.6 | Linking new user-defined libraries to existing applications | U-80 |
| 3.3 | Running applications | U-81 |
| 3.4 | Running applications in parallel | U-81 |
| 3.4.1 | Decomposition of mesh and initial field data | U-82 |
| 3.4.2 | Running a decomposed case | U-84 |
| 3.4.3 | Distributing data across several disks | U-84 |
| 3.4.4 | Post-processing parallel processed cases | U-85 |
| 3.4.4.1 | Reconstructing mesh and data | U-85 |
| 3.4.4.2 | Post-processing decomposed cases | U-85 |
| 3.5 | Standard solvers | U-85 |
| 3.6 | Standard utilities | U-90 |
| 3.7 | Standard libraries | U-97 |
| 4 | OpenFOAM cases | U-105 |
| 4.1 | File structure of OpenFOAM cases | U-105 |
| 4.2 | Basic input/output file format | U-106 |
| 4.2.1 | General syntax rules | U-106 |
| 4.2.2 | Dictionaries | U-107 |
| 4.2.3 | The data file header | U-107 |
| 4.2.4 | Lists | U-108 |
| 4.2.5 | Scalars, vectors and tensors | U-109 |
| 4.2.6 | Dimensional units | U-109 |
| 4.2.7 | Dimensioned types | U-110 |
| 4.2.8 | Fields | U-110 |
| 4.2.9 | Directives and macro substitutions | U-111 |
| 4.2.10 | The <code>#include</code> and <code>#inputMode</code> directives | U-112 |
| 4.2.11 | The <code>#codeStream</code> directive | U-112 |
| 4.3 | Time and data input/output control | U-113 |
| 4.4 | Numerical schemes | U-116 |
| 4.4.1 | Interpolation schemes | U-117 |
| 4.4.1.1 | Schemes for strictly bounded scalar fields | U-118 |
| 4.4.1.2 | Schemes for vector fields | U-118 |
| 4.4.2 | Surface normal gradient schemes | U-119 |
| 4.4.3 | Gradient schemes | U-120 |
| 4.4.4 | Laplacian schemes | U-120 |
| 4.4.5 | Divergence schemes | U-121 |
| 4.4.6 | Time schemes | U-122 |
| 4.4.7 | Flux calculation | U-122 |
| 4.5 | Solution and algorithm control | U-123 |
| 4.5.1 | Linear solver control | U-123 |

| | | |
|----------|---|--------------|
| 4.5.1.1 | Solution tolerances | U-124 |
| 4.5.1.2 | Preconditioned conjugate gradient solvers | U-125 |
| 4.5.1.3 | Smooth solvers | U-125 |
| 4.5.1.4 | Geometric-algebraic multi-grid solvers | U-125 |
| 4.5.2 | Solution under-relaxation | U-126 |
| 4.5.3 | PISO and SIMPLE algorithms | U-127 |
| 4.5.3.1 | Pressure referencing | U-127 |
| 4.5.4 | Other parameters | U-128 |
| 5 | Mesh generation and conversion | U-129 |
| 5.1 | Mesh description | U-129 |
| 5.1.1 | Mesh specification and validity constraints | U-129 |
| 5.1.1.1 | Points | U-130 |
| 5.1.1.2 | Faces | U-130 |
| 5.1.1.3 | Cells | U-131 |
| 5.1.1.4 | Boundary | U-131 |
| 5.1.2 | The <code>polyMesh</code> description | U-131 |
| 5.1.3 | The <code>cellShape</code> tools | U-132 |
| 5.1.4 | 1- and 2-dimensional and axi-symmetric problems | U-133 |
| 5.2 | Boundaries | U-133 |
| 5.2.1 | Specification of patch types in OpenFOAM | U-135 |
| 5.2.2 | Base types | U-136 |
| 5.2.3 | Primitive types | U-138 |
| 5.2.4 | Derived types | U-138 |
| 5.3 | Mesh generation with the <code>blockMesh</code> utility | U-140 |
| 5.3.1 | Writing a <code>blockMeshDict</code> file | U-140 |
| 5.3.1.1 | The <code>vertices</code> | U-141 |
| 5.3.1.2 | The <code>edges</code> | U-142 |
| 5.3.1.3 | The <code>blocks</code> | U-142 |
| 5.3.1.4 | Multi-grading of a block | U-143 |
| 5.3.1.5 | The <code>boundary</code> | U-145 |
| 5.3.2 | Multiple blocks | U-146 |
| 5.3.3 | Creating blocks with fewer than 8 vertices | U-148 |
| 5.3.4 | Running <code>blockMesh</code> | U-149 |
| 5.4 | Mesh generation with the <code>snappyHexMesh</code> utility | U-149 |
| 5.4.1 | The mesh generation process of <code>snappyHexMesh</code> | U-149 |
| 5.4.2 | Creating the background hex mesh | U-151 |
| 5.4.3 | Cell splitting at feature edges and surfaces | U-152 |
| 5.4.4 | Cell removal | U-154 |
| 5.4.5 | Cell splitting in specified regions | U-154 |
| 5.4.6 | Snapping to surfaces | U-155 |
| 5.4.7 | Mesh layers | U-155 |
| 5.4.8 | Mesh quality controls | U-158 |
| 5.5 | Mesh conversion | U-158 |
| 5.5.1 | <code>fluentMeshToFoam</code> | U-159 |
| 5.5.2 | <code>starToFoam</code> | U-160 |
| 5.5.2.1 | General advice on conversion | U-160 |
| 5.5.2.2 | Eliminating extraneous data | U-160 |

| | | |
|----------|---|--------------|
| 5.5.2.3 | Removing default boundary conditions | U-161 |
| 5.5.2.4 | Renumbering the model | U-162 |
| 5.5.2.5 | Writing out the mesh data | U-163 |
| 5.5.2.6 | Problems with the <i>.vrt</i> file | U-163 |
| 5.5.2.7 | Converting the mesh to OpenFOAM format | U-164 |
| 5.5.3 | <i>gambitToFoam</i> | U-164 |
| 5.5.4 | <i>ideasToFoam</i> | U-164 |
| 5.5.5 | <i>cfx4ToFoam</i> | U-165 |
| 5.6 | Mapping fields between different geometries | U-165 |
| 5.6.1 | Mapping consistent fields | U-165 |
| 5.6.2 | Mapping inconsistent fields | U-166 |
| 5.6.3 | Mapping parallel cases | U-167 |
| 6 | Post-processing | U-169 |
| 6.1 | <i>paraFoam</i> | U-169 |
| 6.1.1 | Overview of <i>paraFoam</i> | U-169 |
| 6.1.2 | The Parameters panel | U-171 |
| 6.1.3 | The Display panel | U-172 |
| 6.1.4 | The button toolbars | U-173 |
| 6.1.5 | Manipulating the view | U-173 |
| 6.1.5.1 | View settings | U-173 |
| 6.1.5.2 | General settings | U-174 |
| 6.1.6 | Contour plots | U-174 |
| 6.1.6.1 | Introducing a cutting plane | U-174 |
| 6.1.7 | Vector plots | U-174 |
| 6.1.7.1 | Plotting at cell centres | U-175 |
| 6.1.8 | Streamlines | U-175 |
| 6.1.9 | Image output | U-175 |
| 6.1.10 | Animation output | U-175 |
| 6.2 | Function Objects | U-176 |
| 6.2.1 | Using function objects | U-177 |
| 6.2.2 | Packaged function objects | U-179 |
| 6.3 | Post-processing with <i>Fluent</i> | U-181 |
| 6.4 | Post-processing with <i>Fieldview</i> | U-182 |
| 6.5 | Post-processing with <i>EnSight</i> | U-183 |
| 6.5.1 | Converting data to <i>EnSight</i> format | U-183 |
| 6.5.2 | The <i>ensight74FoamExec</i> reader module | U-183 |
| 6.5.2.1 | Configuration of <i>EnSight</i> for the reader module | U-183 |
| 6.5.2.2 | Using the reader module | U-184 |
| 6.6 | Sampling data | U-184 |
| 6.7 | Monitoring and managing jobs | U-186 |
| 6.7.1 | The <i>foamJob</i> script for running jobs | U-188 |
| 6.7.2 | The <i>foamLog</i> script for monitoring jobs | U-188 |
| 7 | Models and physical properties | U-191 |
| 7.1 | Thermophysical models | U-191 |
| 7.1.1 | Thermophysical and mixture models | U-192 |
| 7.1.2 | Transport model | U-193 |

| | | |
|--------------|---|--------------|
| 7.1.3 | Thermodynamic models | U-193 |
| 7.1.4 | Composition of each constituent | U-194 |
| 7.1.5 | Equation of state | U-195 |
| 7.1.6 | Selection of energy variable | U-196 |
| 7.1.7 | Thermophysical property data | U-196 |
| 7.2 | Turbulence models | U-197 |
| 7.2.1 | Model coefficients | U-198 |
| 7.2.2 | Wall functions | U-198 |
| 7.3 | Transport/rheology models | U-199 |
| 7.3.1 | Newtonian model | U-199 |
| 7.3.2 | Bird-Carreau model | U-200 |
| 7.3.3 | Cross Power Law model | U-200 |
| 7.3.4 | Power Law model | U-200 |
| 7.3.5 | Herschel-Bulkley model | U-201 |
| Index | | U-203 |

Chapter 1

Introduction

This guide accompanies the release of version 3.0.1 of the Open Source Field Operation and Manipulation (OpenFOAM) C++ libraries. It provides a description of the basic operation of OpenFOAM, first through a set of tutorial exercises in chapter 2 and later by a more detailed description of the individual components that make up OpenFOAM.

OpenFOAM is first and foremost a *C++ library*, used primarily to create executables, known as *applications*. The applications fall into two categories: *solvers*, that are each designed to solve a specific problem in continuum mechanics; and *utilities*, that are designed to perform tasks that involve data manipulation. The OpenFOAM distribution contains numerous solvers and utilities covering a wide range of problems, as described in chapter 3.

One of the strengths of OpenFOAM is that new solvers and utilities can be created by its users with some pre-requisite knowledge of the underlying method, physics and programming techniques involved.

OpenFOAM is supplied with pre- and post-processing environments. The interface to the pre- and post-processing are themselves OpenFOAM utilities, thereby ensuring consistent data handling across all environments. The overall structure of OpenFOAM is shown in Figure 1.1. The pre-processing and running of OpenFOAM cases is described in chapter 4.




Figure 1.1: Overview of OpenFOAM structure.

In chapter 5, we cover both the generation of meshes using the mesh generator supplied with OpenFOAM and conversion of mesh data generated by third-party products. Post-processing is described in chapter 6.

Chapter 2

Tutorials

In this chapter we shall describe in detail the process of setup, simulation and post-processing for some OpenFOAM test cases, with the principal aim of introducing a user to the basic procedures of running OpenFOAM. The `$FOAM_TUTORIALS` directory contains many more cases that demonstrate the use of all the solvers and many utilities supplied with OpenFOAM. Before attempting to run the tutorials, the user must first make sure that they have installed OpenFOAM correctly.

The tutorial cases describe the use of the `blockMesh` pre-processing tool, case setup and running OpenFOAM solvers and post-processing using `paraFoam`. Those users with access to third-party post-processing tools supported in OpenFOAM have an option: either they can follow the tutorials using `paraFoam`; or refer to the description of the use of the third-party product in chapter 6 when post-processing is required.

Copies of all tutorials are available from the `tutorials` directory of the OpenFOAM installation. The tutorials are organised into a set of directories according to the type of flow and then subdirectories according to solver. For example, all the `icoFoam` cases are stored within a subdirectory `incompressible/icoFoam`, where *incompressible* indicates the type of flow. If the user wishes to run a range of example cases, it is recommended that the user copy the `tutorials` directory into their local `run` directory. They can be easily copied by typing:

```
mkdir -p $FOAM_RUN
cp -r $FOAM_TUTORIALS $FOAM_RUN
```

2.1 Lid-driven cavity flow

This tutorial will describe how to pre-process, run and post-process a case involving isothermal, incompressible flow in a two-dimensional square domain. The geometry is shown in Figure 2.1 in which all the boundaries of the square are walls. The top wall moves in the x -direction at a speed of 1 m/s while the other 3 are stationary. Initially, the flow will be assumed laminar and will be solved on a uniform mesh using the `icoFoam` solver for laminar, isothermal, incompressible flow. During the course of the tutorial, the effect of increased mesh resolution and mesh grading towards the walls will be investigated. Finally, the flow Reynolds number will be increased and the `pisoFoam` solver will be used for turbulent, isothermal, incompressible flow.




Figure 2.1: Geometry of the lid driven cavity.

2.1.1 Pre-processing

Cases are setup in OpenFOAM by editing case files. Users should select an editor of choice with which to do this, such as `emacs`, `vi`, `gedit`, `kate`, `nedit`, *etc.* Editing files is possible in OpenFOAM because the I/O uses a dictionary format with keywords that convey sufficient meaning to be understood by even the least experienced users.

A case being simulated involves data for mesh, fields, properties, control parameters, etc. As described in section 4.1, in OpenFOAM this data is stored in a set of files within a case directory rather than in a single case file, as in many other CFD packages. The case directory is given a suitably descriptive name, *e.g.* the first example case for this tutorial is simply named `cavity`. In preparation of editing case files and running the first `cavity` case, the user should change to the case directory

```
cd $FOAM_RUN/tutorials/incompressible/icoFoam/cavity
```

2.1.1.1 Mesh generation

OpenFOAM always operates in a 3 dimensional Cartesian coordinate system and all geometries are generated in 3 dimensions. OpenFOAM solves the case in 3 dimensions by default but can be instructed to solve in 2 dimensions by specifying a ‘special’ `empty` boundary condition on boundaries normal to the (3rd) dimension for which no solution is required.

The `cavity` domain consists of a square of side length $d = 0.1$ m in the x - y plane. A uniform mesh of 20 by 20 cells will be used initially. The block structure is shown in Figure 2.2. The mesh generator supplied with OpenFOAM, `blockMesh`, generates meshes from a description specified in an input dictionary, `blockMeshDict` located in the `system` (or `constant/polyMesh`) directory for a given case. The `blockMeshDict` entries for this case are as follows:

```

1  /*-----*-----*-----*-----*-----*-----*-----*-----*-----*\
2  |=====|
3  |  \ \  /  | F i e l d           | OpenFOAM: The Open Source CFD Toolbox
4  |   \ \ /   | O p e r a t i o n   | Version: 3.0.1
5  |    \ \ /   | A n d               | Web:      www.OpenFOAM.org
6  |     \ \ /   | M a n i p u l a t i o n |

```




Figure 2.2: Block structure of the mesh for the cavity.

```

7  \*-----*/
8  FoamFile
9  {
10     version      2.0;
11     format       ascii;
12     class        dictionary;
13     object       blockMeshDict;
14 }
15 // * * * * * //
16
17 convertToMeters 0.1;
18
19 vertices
20 (
21     (0 0 0)
22     (1 0 0)
23     (1 1 0)
24     (0 1 0)
25     (0 0 0.1)
26     (1 0 0.1)
27     (1 1 0.1)
28     (0 1 0.1)
29 );
30
31 blocks
32 (
33     hex (0 1 2 3 4 5 6 7) (20 20 1) simpleGrading (1 1 1)
34 );
35
36 edges
37 (
38 );
39
40 boundary
41 (
42     movingWall
43     {
44         type wall;
45         faces
46         (
47             (3 7 6 2)
48         );
49     }
50     fixedWalls
51     {
52         type wall;
53         faces
54         (
55             (0 4 7 3)
56             (2 6 5 1)
57             (1 5 4 0)
58         );
59     }

```

```

60     frontAndBack
61     {
62         type empty;
63         faces
64         (
65             (0 3 2 1)
66             (4 5 6 7)
67         );
68     }
69 );
70
71 mergePatchPairs
72 (
73 );
74
75 // ***** //

```

The file first contains header information in the form of a banner (lines 1-7), then file information contained in a *FoamFile* sub-dictionary, delimited by curly braces (`{...}`).

For the remainder of the manual:

For the sake of clarity and to save space, file headers, including the banner and *FoamFile* sub-dictionary, will be removed from verbatim quoting of case files

The file first specifies coordinates of the block **vertices**; it then defines the **blocks** (here, only 1) from the vertex labels and the number of cells within it; and finally, it defines the boundary patches. The user is encouraged to consult section 5.3 to understand the meaning of the entries in the *blockMeshDict* file.

The mesh is generated by running `blockMesh` on this *blockMeshDict* file. From within the case directory, this is done, simply by typing in the terminal:

```
blockMesh
```

The running status of `blockMesh` is reported in the terminal window. Any mistakes in the *blockMeshDict* file are picked up by `blockMesh` and the resulting error message directs the user to the line in the file where the problem occurred. There should be no error messages at this stage.

2.1.1.2 Boundary and initial conditions

Once the mesh generation is complete, the user can look at this initial fields set up for this case. The case is set up to start at time $t = 0$ s, so the initial field data is stored in a *0* sub-directory of the *cavity* directory. The *0* sub-directory contains 2 files, *p* and *U*, one for each of the pressure (*p*) and velocity (*U*) fields whose initial values and boundary conditions must be set. Let us examine file *p*:

```

17 dimensions      [0 2 -2 0 0 0 0];
18
19 internalField    uniform 0;
20
21 boundaryField
22 {
23     movingWall
24     {
25         type      zeroGradient;
26     }
27     fixedWalls
28     {
29         type      zeroGradient;
30     }
31 }

```

```

32     frontAndBack
33     {
34         type          empty;
35     }
36 }
37
38 // ***** //
39

```

There are 3 principal entries in field data files:

dimensions specifies the dimensions of the field, here *kinematic* pressure, *i.e.* $\text{m}^2 \text{s}^{-2}$ (see section 4.2.6 for more information);

internalField the internal field data which can be **uniform**, described by a single value; or **nonuniform**, where all the values of the field must be specified (see section 4.2.8 for more information);

boundaryField the boundary field data that includes boundary conditions and data for all the boundary patches (see section 4.2.8 for more information).

For this case *cavity*, the boundary consists of walls only, split into 2 patches named: (1) **fixedWalls** for the fixed sides and base of the cavity; (2) **movingWall** for the moving top of the cavity. As walls, both are given a **zeroGradient** boundary condition for **p**, meaning “the normal gradient of pressure is zero”. The **frontAndBack** patch represents the front and back planes of the 2D case and therefore must be set as **empty**.

In this case, as in most we encounter, the initial fields are set to be uniform. Here the pressure is kinematic, and as an incompressible case, its absolute value is not relevant, so is set to **uniform 0** for convenience.

The user can similarly examine the velocity field in the *0/U* file. The **dimensions** are those expected for velocity, the internal field is initialised as uniform zero, which in the case of velocity must be expressed by 3 vector components, *i.e.* **uniform (0 0 0)** (see section 4.2.5 for more information).

The boundary field for velocity requires the same boundary condition for the **frontAndBack** patch. The other patches are walls: a no-slip condition is assumed on the **fixedWalls**, hence a **fixedValue** condition with a **value** of **uniform (0 0 0)**. The top surface moves at a speed of 1 m/s in the *x*-direction so requires a **fixedValue** condition also but with **uniform (1 0 0)**.

2.1.1.3 Physical properties

The physical properties for the case are stored in dictionaries whose names are given the suffix *...Properties*, located in the **Dictionaries** directory tree. For an **icoFoam** case, the only property that must be specified is the kinematic viscosity which is stored from the **transportProperties** dictionary. The user can check that the kinematic viscosity is set correctly by opening the **transportProperties** dictionary to view/edit its entries. The keyword for kinematic viscosity is **nu**, the phonetic label for the Greek symbol ν by which it is represented in equations. Initially this case will be run with a Reynolds number of 10, where the Reynolds number is defined as:

$$Re = \frac{d|\mathbf{U}|}{\nu} \quad (2.1)$$

where d and $|\mathbf{U}|$ are the characteristic length and velocity respectively and ν is the kinematic viscosity. Here $d = 0.1$ m, $|\mathbf{U}| = 1$ m s⁻¹, so that for $Re = 10$, $\nu = 0.01$ m² s⁻¹. The correct file entry for kinematic viscosity is thus specified below:

```

17
18  nu          [0 2 -1 0 0 0 0] 0.01;
19
20
21  // ***** //

```

2.1.1.4 Control

Input data relating to the control of time and reading and writing of the solution data are read in from the *controlDict* dictionary. The user should view this file; as a case control file, it is located in the *system* directory.

The start/stop times and the time step for the run must be set. OpenFOAM offers great flexibility with time control which is described in full in section 4.3. In this tutorial we wish to start the run at time $t = 0$ which means that OpenFOAM needs to read field data from a directory named *0* — see section 4.1 for more information of the case file structure. Therefore we set the `startFrom` keyword to `startTime` and then specify the `startTime` keyword to be 0.

For the end time, we wish to reach the steady state solution where the flow is circulating around the cavity. As a general rule, the fluid should pass through the domain 10 times to reach steady state in laminar flow. In this case the flow does not pass through this domain as there is no inlet or outlet, so instead the end time can be set to the time taken for the lid to travel ten times across the cavity, *i.e.* 1 s; in fact, with hindsight, we discover that 0.5 s is sufficient so we shall adopt this value. To specify this end time, we must specify the `stopAt` keyword as `endTime` and then set the `endTime` keyword to 0.5.

Now we need to set the time step, represented by the keyword `deltaT`. To achieve temporal accuracy and numerical stability when running `icoFoam`, a Courant number of less than 1 is required. The Courant number is defined for one cell as:

$$Co = \frac{\delta t |\mathbf{U}|}{\delta x} \quad (2.2)$$

where δt is the time step, $|\mathbf{U}|$ is the magnitude of the velocity through that cell and δx is the cell size in the direction of the velocity. The flow velocity varies across the domain and we must ensure $Co < 1$ everywhere. We therefore choose δt based on the worst case: the *maximum* Co corresponding to the combined effect of a large flow velocity and small cell size. Here, the cell size is fixed across the domain so the maximum Co will occur next to the lid where the velocity approaches 1 m s⁻¹. The cell size is:

$$\delta x = \frac{d}{n} = \frac{0.1}{20} = 0.005 \text{ m} \quad (2.3)$$

Therefore to achieve a Courant number less than or equal to 1 throughout the domain the time step `deltaT` must be set to less than or equal to:

$$\delta t = \frac{Co \delta x}{|\mathbf{U}|} = \frac{1 \times 0.005}{1} = 0.005 \text{ s} \quad (2.4)$$

As the simulation progresses we wish to write results at certain intervals of time that we can later view with a post-processing package. The `writeControl` keyword presents several

options for setting the time at which the results are written; here we select the `timeStep` option which specifies that results are written every n th time step where the value n is specified under the `writeInterval` keyword. Let us decide that we wish to write our results at times 0.1, 0.2, ..., 0.5 s. With a time step of 0.005 s, we therefore need to output results at every 20th time step and so we set `writeInterval` to 20.

OpenFOAM creates a new directory *named after the current time, e.g.* 0.1 s, on each occasion that it writes a set of data, as discussed in full in section 4.1. In the `icoFoam` solver, it writes out the results for each field, `U` and `p`, into the time directories. For this case, the entries in the `controlDict` are shown below:

```

17
18 application      icoFoam;
19
20 startFrom        startTime;
21
22 startTime        0;
23
24 stopAt           endTime;
25
26 endTime          0.5;
27
28 deltaT           0.005;
29
30 writeControl     timeStep;
31
32 writeInterval    20;
33
34 purgeWrite       0;
35
36 writeFormat      ascii;
37
38 writePrecision   6;
39
40 writeCompression off;
41
42 timeFormat       general;
43
44 timePrecision    6;
45
46 runtimeModifiable true;
47
48 // ***** //

```

2.1.1.5 Discretisation and linear-solver settings

The user specifies the choice of finite volume discretisation schemes in the `fvSchemes` dictionary in the `system` directory. The specification of the linear equation solvers and tolerances and other algorithm controls is made in the `fvSolution` dictionary, similarly in the `system` directory. The user is free to view these dictionaries but we do not need to discuss all their entries at this stage except for `pRefCell` and `pRefValue` in the `PISO` sub-dictionary of the `fvSolution` dictionary. In a closed incompressible system such as the cavity, pressure is relative: it is the pressure range that matters not the absolute values. In cases such as this, the solver sets a reference level by `pRefValue` in cell `pRefCell`. In this example both are set to 0. Changing either of these values will change the absolute pressure field, but not, of course, the relative pressures or velocity field.

2.1.2 Viewing the mesh

Before the case is run it is a good idea to view the mesh to check for any errors. The mesh is viewed in `paraFoam`, the post-processing tool supplied with OpenFOAM. The `paraFoam` post-processing is started by typing in the terminal from within the case directory

```
paraFoam
```

Alternatively, it can be launched from another directory location with an optional `-case` argument giving the case directory, *e.g.*

```
paraFoam -case $FOAM_RUN/tutorials/incompressible/icoFoam/cavity
```

This launches the ParaView window as shown in Figure 6.1. In the Pipeline Browser, the user can see that ParaView has opened `cavity.OpenFOAM`, the module for the `cavity` case. **Before clicking the Apply button**, the user needs to select some geometry from the Mesh Parts panel. Because the case is small, it is easiest to select all the data by checking the box adjacent to the Mesh Parts panel title, which automatically checks all individual components within the respective panel. The user should then click the Apply button to load the geometry into ParaView.

The user should then scroll down to the Display panel that controls the visual representation of the selected module. Within the Display panel the user should do the following as shown in Figure 2.3: (1) set Coloring Solid Color; (2) click Set Ambient Color and select an appropriate colour *e.g.* black (for a white background); (3) select Wireframe from the Representation menu. The background colour can be set in the View Render panel below the Display panel in the Properties window.

Especially the first time the user starts ParaView, **it is recommended** that they manipulate the view as described in section 6.1.5. In particular, since this is a 2D case, it is recommended that Use Parallel Projection is selected near the bottom of the View Render panel, available only with the Advanced Properties gearwheel button pressed at the top of the Properties window, next to the search box. View Settings window selected from the Edit menu. The Orientation Axes can be toggled on and off in the Annotation window or moved by drag and drop with the mouse.

2.1.3 Running an application

Like any UNIX/Linux executable, OpenFOAM applications can be run in two ways: as a foreground process, *i.e.* one in which the shell waits until the command has finished before giving a command prompt; as a background process, one which does not have to be completed before the shell accepts additional commands.

On this occasion, we will run `icoFoam` in the foreground. The `icoFoam` solver is executed either by entering the case directory and typing

```
icoFoam
```

at the command prompt, or with the optional `-case` argument giving the case directory, *e.g.*

```
icoFoam -case $FOAM_RUN/tutorials/incompressible/icoFoam/cavity
```

The progress of the job is written to the terminal window. It tells the user the current time, maximum Courant number, initial and final residuals for all fields.




Figure 2.3: Viewing the mesh in paraFoam.

2.1.4 Post-processing

As soon as results are written to time directories, they can be viewed using `paraFoam`. Return to the `paraFoam` window and select the Properties panel for the `cavity.OpenFOAM` case module. If the correct window panels for the case module do not seem to be present at any time, please ensure that: `cavity.OpenFOAM` is highlighted in blue; eye button alongside it is switched on to show the graphics are enabled;

To prepare `paraFoam` to display the data of interest, we must first load the data at the required run time of 0.5 s. If the case was run while `ParaView` was open, the output data in time directories will not be automatically loaded within `ParaView`. To load the data the user should click Refresh Times in the Properties window. The time data will be loaded into `ParaView`.

2.1.4.1 Isosurface and contour plots

To view pressure, the user should go to the Display panel since it controls the visual representation of the selected module. To make a simple plot of pressure, the user should select the following, as described in detail in Figure 2.4: select **Surface** from the Representation menu; select $\circ P$ in Coloring and Rescale to Data Range. Now in order to view the solution at $t = 0.5$ s, the user can use the VCR Controls or Current Time Controls to change the




Figure 2.4: Displaying pressure contours for the cavity case.




Figure 2.5: Pressures in the cavity case.

current time to 0.5. These are located in the toolbars below the menus at the top of the ParaView window, as shown in Figure 6.4. The pressure field solution has, as expected, a region of low pressure at the top left of the cavity and one of high pressure at the top right of the cavity as shown in Figure 2.5.

With the point icon () the pressure field is interpolated across each cell to give a continuous appearance. Instead if the user selects the cell icon, , from the Color by menu, a single value for pressure will be attributed to each cell so that each cell will be denoted by a single colour with no grading.

A colour bar can be included by either by clicking the Toggle Color Legend Visibility button in the Active Variable Controls toolbar or the Coloring section of the Display panel. Clicking the Edit Color Map button, either in the Active Variable Controls toolbar or in the Coloring panel of the Display panel, the user can set a range of attributes of the colour bar, such as text size, font selection and numbering format for the scale. The colour bar can be located in the image window by drag and drop with the mouse.

ParaView defaults to using a colour scale of blue to white to red rather than the more common blue to green to red (rainbow). Therefore *the first time* that the user executes ParaView, they may wish to change the colour scale. This can be done by selecting the Choose Preset button (with the heart icon) in the Color Scale Editor and selecting Blue to Red Rainbow. After clicking the OK confirmation button, the user can click the Make Default button so that ParaView will always adopt this type of colour bar.

If the user rotates the image, they can see that they have now coloured the complete geometry surface by the pressure. In order to produce a genuine contour plot the user should first create a cutting plane, or ‘slice’, through the geometry using the Slice filter as described in section 6.1.6.1. The cutting plane should be centred at (0.05, 0.05, 0.005) and its normal should be set to (0, 0, 1) (click the Z Normal button). Having generated the cutting plane, the contours can be created using by the Contour filter described in section 6.1.6.

2.1.4.2 Vector plots

Before we start to plot the vectors of the flow velocity, it may be useful to remove other modules that have been created, *e.g.* using the Slice and Contour filters described above. These can: either be deleted entirely, by highlighting the relevant module in the Pipeline Browser and clicking Delete in their respective Properties panel; or, be disabled by toggling the eye button for the relevant module in the Pipeline Browser.

We now wish to generate a vector glyph for velocity at the centre of each cell. We first need to filter the data to cell centres as described in section 6.1.7.1. With the cavity.OpenFOAM module highlighted in the Pipeline Browser, the user should select Cell Centers from the Filter->Alphabetical menu and then click Apply.

With these Centers highlighted in the Pipeline Browser, the user should then select Glyph from the Filter->Common menu. The Properties window panel should appear as shown in Figure 2.6. Note that newly selected filters are moved to the Filter->Recent menu and are unavailable in the menus from where they were originally selected. In the resulting Properties panel, the velocity field, U, is automatically selected in the vectors menu, since it is the only vector field present. By default the Scale Mode for the glyphs will be Vector Magnitude of velocity but, since we may wish to view the velocities throughout the domain, the user should instead select off and Set Scale Factor to 0.005. On clicking Apply, the glyphs appear but, probably as a single colour, *e.g.* white. The user should colour the glyphs by velocity magnitude which, as usual, is controlled by setting Color by U in the




Figure 2.6: Properties panel for the Glyph filter.




Figure 2.7: Velocities in the cavity case.

Display panel. The user should also select **Show Color Legend** in **Edit Color Map**. The output is shown in Figure 2.7, in which uppercase Times Roman fonts are selected for the **Color Legend** headings and the labels are specified to 2 fixed significant figures by deselecting **Automatic Label Format** and entering `%-#6.2f` in the **Label Format** text box. The background colour is set to white in the **General** panel of **View Settings** as described in section 6.1.5.1.

Note that at the left and right walls, glyphs appear to indicate flow through the walls. On closer examination, however, the user can see that while the flow direction is normal to the wall, its magnitude is 0. This slightly confusing situation is caused by ParaView choosing to orientate the glyphs in the x -direction when the glyph scaling **off** and the velocity magnitude is 0.

2.1.4.3 Streamline plots

Again, before the user continues to post-process in ParaView, they should disable modules such as those for the vector plot described above. We now wish to plot streamlines of velocity as described in section 6.1.8.

With the `cavity.OpenFOAM` module highlighted in the **Pipeline Browser**, the user should then select **Stream Tracer** from the **Filter** menu and then click **Apply**. The **Properties** window panel should appear as shown in Figure 2.8. The **Seed** points should be specified along a **High Resolution Line Source** running vertically through the centre of the geometry, *i.e.* from $(0.05, 0, 0.005)$ to $(0.05, 0.1, 0.005)$. For the image in this guide we used: a point **Resolution** of 21; **Maximum Step Length** of 0.5; **Initial Step Length** of 0.2; and, **Integration Direction** BOTH. The **Runge-Kutta 4/5 IntegratorType** was used with default parameters.

On clicking **Apply** the tracer is generated. The user should then select **Tube** from the **Filter** menu to produce high quality streamline images. For the image in this report, we used: **Num. sides** 6; **Radius** 0.0003; and, **Radius factor** 10. The streamtubes are coloured by velocity magnitude. On clicking **Apply** the image in Figure 2.9 should be produced.

2.1.5 Increasing the mesh resolution

The mesh resolution will now be increased by a factor of two in each direction. The results from the coarser mesh will be mapped onto the finer mesh to use as initial conditions for the problem. The solution from the finer mesh will then be compared with those from the coarser mesh.

2.1.5.1 Creating a new case using an existing case

We now wish to create a new case named `cavityFine` that is created from `cavity`. The user should therefore clone the `cavity` case and edit the necessary files. First the user should create a new case directory at the same directory level as the `cavity` case, *e.g.*

```
cd $FOAM_RUN/tutorials/incompressible/icoFoam
mkdir cavityFine
```

The user should then copy the base directories from the `cavity` case into `cavityFine`, and then enter the `cavityFine` case.

```
cp -r cavity/constant cavityFine
```

Scroll to Properties title
 Set Initial Step Length to Cell Length 0.01
 Set Integration Direction to BOTH
 Specify Line Source and set points and resolution

Figure 2.8: Properties panel for the Stream Tracer filter.




Figure 2.9: Streamlines in the cavity case.

```
cp -r cavity/system cavityFine
cd cavityFine
```

2.1.5.2 Creating the finer mesh

We now wish to increase the number of cells in the mesh by using `blockMesh`. The user should open the `blockMeshDict` file in an editor and edit the block specification. The blocks are specified in a list under the `blocks` keyword. The syntax of the block definitions is described fully in section 5.3.1.3; at this stage it is sufficient to know that following `hex` is first the list of vertices in the block, then a list (or vector) of numbers of cells in each direction. This was originally set to `(20 20 1)` for the `cavity` case. The user should now change this to `(40 40 1)` and save the file. The new refined mesh should then be created by running `blockMesh` as before.

2.1.5.3 Mapping the coarse mesh results onto the fine mesh

The `mapFields` utility maps one or more fields relating to a given geometry onto the corresponding fields for another geometry. In our example, the fields are deemed ‘consistent’ because the geometry and the boundary types, or conditions, of both source and target fields are identical. We use the `-consistent` command line option when executing `mapFields` in this example.

The field data that `mapFields` maps is read from the time directory specified by `startFrom` and `startTime` in the `controlDict` of the target case, *i.e.* those **into which** the results are being mapped. In this example, we wish to map the final results of the coarser mesh from case `cavity` onto the finer mesh of case `cavityFine`. Therefore, since these results are stored in the `0.5` directory of `cavity`, the `startTime` should be set to 0.5 s in the `controlDict` dictionary and `startFrom` should be set to `startTime`.

The case is ready to run `mapFields`. Typing `mapFields -help` quickly shows that `mapFields` requires the source case directory as an argument. We are using the `-consistent` option, so the utility is executed from within the `cavityFine` directory by

```
mapFields ../cavity -consistent
```

The utility should run with output to the terminal including:

```
Source: "." "cavity"
Target: "." "cavityFine"

Create databases as time
Case   : ../cavity
nProcs : 1

Source time: 0.5
Target time: 0.5

Create meshes

Source mesh size: 400   Target mesh size: 1600

Consistently creating and mapping fields for time 0.5

Creating mesh-to-mesh addressing ...
  Overlap volume: 0.0001
Creating AMI between source patch movingWall and target patch movingWall ...
```

```
interpolating p
interpolating U
```

End

2.1.5.4 Control adjustments

To maintain a Courant number of less than 1, as discussed in section 2.1.1.4, the time step must now be halved since the size of all cells has halved. Therefore `deltaT` should be set to 0.0025 s in the *controlDict* dictionary. Field data is currently written out at an interval of a fixed number of time steps. Here we demonstrate how to specify data output at fixed intervals of time. Under the `writeControl` keyword in *controlDict*, instead of requesting output by a fixed number of time steps with the `timeStep` entry, a fixed amount of run time can be specified between the writing of results using the `runTime` entry. In this case the user should specify output every 0.1 and therefore should set `writeInterval` to 0.1 and `writeControl` to `runTime`. Finally, since the case is starting with a the solution obtained on the coarse mesh we only need to run it for a short period to achieve reasonable convergence to steady-state. Therefore the `endTime` should be set to 0.7 s. Make sure these settings are correct and then save the file.

2.1.5.5 Running the code as a background process

The user should experience running `icoFoam` as a background process, redirecting the terminal output to a *log* file that can be viewed later. From the *cavityFine* directory, the user should execute:

```
icoFoam > log &
cat log
```

2.1.5.6 Vector plot with the refined mesh

The user can open multiple cases simultaneously in `ParaView`; essentially because each new case is simply another module that appears in the `Pipeline Browser`. There is one minor inconvenience when opening a new case in `ParaView` because there is a prerequisite that the selected data is a file with a name that has an extension. However, in `OpenFOAM`, each case is stored in a multitude of files with no extensions within a specific directory structure. The solution, that the `paraFoam` script performs automatically, is to create a dummy file with the extension *.OpenFOAM*—hence, the *cavity* case module is called `cavity.OpenFOAM`.

However, if the user wishes to open another case directly from within `ParaView`, they need to create such a dummy file. For example, to load the *cavityFine* case the file would be created by typing at the command prompt:

```
cd $FOAM_RUN/tutorials/incompressible/icoFoam
touch cavityFine/cavityFine.OpenFOAM
```

Now the *cavityFine* case can be loaded into `ParaView` by selecting `Open` from the `File` menu, and having navigated the directory tree, selecting `cavityFine.OpenFOAM`. The user can now make a vector plot of the results from the refined mesh in `ParaView`. The plot can be compared with the *cavity* case by enabling glyph images for both case simultaneously.




Figure 2.10: Selecting fields for graph plotting.

2.1.5.7 Plotting graphs

The user may wish to visualise the results by extracting some scalar measure of velocity and plotting 2-dimensional graphs along lines through the domain. OpenFOAM is well equipped for this kind of data manipulation. There are numerous utilities that do specialised data manipulations, and some, simpler calculations are incorporated into a single utility `foamCalc`. As a utility, it is unique in that it is executed by

```
foamCalc <calcType> <fieldName1 ... fieldNameN>
```

The calculator operation is specified in `<calcType>`; at the time of writing, the following operations are implemented: `addSubtract`; `randomise`; `div`; `components`; `mag`; `magGrad`; `magSqr`; `interpolate`. The user can obtain the list of `<calcType>` by deliberately calling one that does not exist, so that `foamCalc` throws up an error message and lists the types available, *e.g.*

```
>> foamCalc xxxx
Selecting calcType xxxx
    unknown calcType type xxxx, constructor not in hash table
    Valid calcType selections are:

8
(
randomise
magSqr
magGrad
addSubtract
div
mag
interpolate
components
)
```

The `components` and `mag` `calcTypes` provide useful scalar measures of velocity. When “foamCalc components U” is run on a case, say *cavity*, it reads in the velocity vector field from each time directory and, in the corresponding time directories, writes scalar fields U_x , U_y and U_z representing the x , y and z components of velocity. Similarly “foamCalc mag U” writes a scalar field `magU` to each time directory representing the magnitude of velocity.

The user can run `foamCalc` with the `components calcType` on both *cavity* and *cavityFine* cases. For example, for the *cavity* case the user should do into the *cavity* directory and execute `foamCalc` as follows:

```
cd $FOAM_RUN/tutorials/incompressible/icoFoam/cavity
foamCalc components U
```

The individual components can be plotted as a graph in `ParaView`. It is quick, convenient and has reasonably good control over labelling and formatting, so the printed output is a fairly good standard. However, to produce graphs for publication, users may prefer to write raw data and plot it with a dedicated graphing tool, such as `gnuplot` or `Grace/xmgr`. To do this, we recommend using the `sample` utility, described in section 6.6 and section 2.2.3.

Before commencing plotting, the user needs to load the newly generated U_x , U_y and U_z fields into `ParaView`. To do this, the user should click the `Refresh Times` at the top of the `Properties` panel for the `cavity.OpenFOAM` module which will cause the new fields to be loaded into `ParaView` and appear in the `Volume Fields` window. Ensure the new fields are selected and the changes are applied, *i.e.* click `Apply` again if necessary. *Also*, data is interpolated incorrectly at boundaries if the boundary regions are selected in the `Mesh Parts` panel. Therefore the user should *deselect the patches* in the `Mesh Parts` panel, *i.e.* `movingWall`, `fixedWall` and `frontAndBack`, and apply the changes.

Now, in order to display a graph in `ParaView` the user should select the module of interest, *e.g.* `cavity.OpenFOAM` and apply the `Plot Over Line` filter from the `Filter->Data Analysis` menu. This opens up a new `XY Plot` window below or beside the existing `3D View` window. A `PlotOverLine` module is created in which the user can specify the end points of the line in the `Properties` panel. In this example, the user should position the line vertically up the centre of the domain, *i.e.* from $(0.05, 0, 0.005)$ to $(0.05, 0.1, 0.005)$, in the `Point1` and `Point2` text boxes. The `Resolution` can be set to 100.

On clicking `Apply`, a graph is generated in the `XY Plot` window. In the `Display` panel, the user should set `Attribute Mode` to `Point Data`. The `Use Data Array` option can be selected for the `X Axis Data`, taking the `arc_length` option so that the x-axis of the graph represents distance from the base of the cavity.




Figure 2.11: Plotting graphs in paraFoam.

The user can choose the fields to be displayed in the **Line Series** panel of the **Display** window. From the list of scalar fields to be displayed, it can be seen that the magnitude and components of vector fields are available by default, *e.g.* displayed as **U_X**, so that it was not necessary to create **Ux** using **foamCalc**. Nevertheless, the user should deselect all series except **Ux** (or **U_x**). A square colour box in the adjacent column to the selected series indicates the line colour. The user can edit this most easily by a double click of the mouse over that selection.

In order to format the graph, the user should modify the settings below the **Line Series** panel, namely **Line Color**, **Line Thickness**, **Line Style**, **Marker Style** and **Chart Axes**.

Also the user can click one of the buttons above the top left corner of the **XY Plot**. The third button, for example, allows the user to control **View Settings** in which the user can set title and legend for each axis, for example. Also, the user can set font, colour and alignment of the axes titles, and has several options for axis range and labels in linear or logarithmic scales.

Figure 2.11 is a graph produced using **ParaView**. The user can produce a graph however he/she wishes. For information, the graph in Figure 2.11 was produced with the options for axes of: **Standard** type of Notation; **Specify Axis Range** selected; titles in **Sans Serif 12** font. The graph is displayed as a set of points rather than a line by activating the **Enable Line Series** button in the **Display** window. Note: if this button appears to be inactive by being “greyed out”, it can be made active by selecting and deselecting the sets of variables in the **Line Series** panel. Once the **Enable Line Series** button is selected, the **Line Style** and **Marker Style** can be adjusted to the user’s preference.

2.1.6 Introducing mesh grading

The error in any solution will be more pronounced in regions where the form of the true solution differ widely from the form assumed in the chosen numerical schemes. For example a numerical scheme based on linear variations of variables over cells can only generate an exact solution if the true solution is itself linear in form. The error is largest in regions where the true solution deviates greatest from linear form, *i.e.* where the change in gradient is largest. Error decreases with cell size.

It is useful to have an intuitive appreciation of the form of the solution before setting

up any problem. It is then possible to anticipate where the errors will be largest and to grade the mesh so that the smallest cells are in these regions. In the *cavity* case the large variations in velocity can be expected near a wall and so in this part of the tutorial the mesh will be graded to be smaller in this region. By using the same number of cells, greater accuracy can be achieved without a significant increase in computational cost.

A mesh of 20×20 cells with grading towards the walls will be created for the lid-driven cavity problem and the results from the finer mesh of section 2.1.5.2 will then be mapped onto the graded mesh to use as an initial condition. The results from the graded mesh will be compared with those from the previous meshes. Since the changes to the *blockMeshDict* dictionary are fairly substantial, the case used for this part of the tutorial, *cavityGrade*, is supplied in the *\$FOAM_RUN/tutorials/incompressible/icoFoam* directory.

2.1.6.1 Creating the graded mesh

The mesh now needs 4 blocks as different mesh grading is needed on the left and right and top and bottom of the domain. The block structure for this mesh is shown in Figure 2.12. The




Figure 2.12: Block structure of the graded mesh for the cavity (block numbers encircled).

user can view the *blockMeshDict* file in the *system* (or *constant/polyMesh*) subdirectory of *cavityGrade*; for completeness the key elements of the *blockMeshDict* file are also reproduced below. Each block now has 10 cells in the *x* and *y* directions and the ratio between largest and smallest cells is 2.

```

17   convertToMeters 0.1;
18
19   vertices
20   (
21       (0 0 0)
22       (0.5 0 0)
23       (1 0 0)
24       (0 0.5 0)
25       (0.5 0.5 0)
26       (1 0.5 0)
27       (0 1 0)
28       (0.5 1 0)
29       (1 1 0)
30       (0 0 0.1)
31       (0.5 0 0.1)
32       (1 0 0.1)
33       (0 0.5 0.1)
34       (0.5 0.5 0.1)
35       (1 0.5 0.1)

```

```

36     (0 1 0.1)
37     (0.5 1 0.1)
38     (1 1 0.1)
39 );
40
41 blocks
42 (
43     hex (0 1 4 3 9 10 13 12) (10 10 1) simpleGrading (2 2 1)
44     hex (1 2 5 4 10 11 14 13) (10 10 1) simpleGrading (0.5 2 1)
45     hex (3 4 7 6 12 13 16 15) (10 10 1) simpleGrading (2 0.5 1)
46     hex (4 5 8 7 13 14 17 16) (10 10 1) simpleGrading (0.5 0.5 1)
47 );
48
49 edges
50 (
51 );
52
53 boundary
54 (
55     movingWall
56     {
57         type wall;
58         faces
59         (
60             (6 15 16 7)
61             (7 16 17 8)
62         );
63     }
64     fixedWalls
65     {
66         type wall;
67         faces
68         (
69             (3 12 15 6)
70             (0 9 12 3)
71             (0 1 10 9)
72             (1 2 11 10)
73             (2 5 14 11)
74             (5 8 17 14)
75         );
76     }
77     frontAndBack
78     {
79         type empty;
80         faces
81         (
82             (0 3 4 1)
83             (1 4 5 2)
84             (3 6 7 4)
85             (4 7 8 5)
86             (9 10 13 12)
87             (10 11 14 13)
88             (12 13 16 15)
89             (13 14 17 16)
90         );
91     }
92 );
93
94 mergePatchPairs
95 (
96 );
97
98 // ***** //

```

Once familiar with the *blockMeshDict* file for this case, the user can execute `blockMesh` from the command line. The graded mesh can be viewed as before using `paraFoam` as described in section 2.1.2.

2.1.6.2 Changing time and time step

The highest velocities and smallest cells are next to the lid, therefore the highest Courant number will be generated next to the lid, for reasons given in section 2.1.1.4. It is therefore useful to estimate the size of the cells next to the lid to calculate an appropriate time step for this case.

When a nonuniform mesh grading is used, `blockMesh` calculates the cell sizes using a geometric progression. Along a length l , if n cells are requested with a ratio of R between the last and first cells, the size of the smallest cell, δx_s , is given by:

$$\delta x_s = l \frac{r - 1}{\alpha r - 1} \quad (2.5)$$

where r is the ratio between one cell size and the next which is given by:

$$r = R^{\frac{1}{n-1}} \quad (2.6)$$

and

$$\alpha = \begin{cases} R & \text{for } R > 1, \\ 1 - r^{-n} + r^{-1} & \text{for } R < 1. \end{cases} \quad (2.7)$$

For the `cavityGrade` case the number of cells in each direction in a block is 10, the ratio between largest and smallest cells is 2 and the block height and width is 0.05 m. Therefore the smallest cell length is 3.45 mm. From Equation 2.2, the time step should be less than 3.45 ms to maintain a Courant of less than 1. To ensure that results are written out at convenient time intervals, the time step `deltaT` should be reduced to 2.5 ms and the `writeInterval` set to 40 so that results are written out every 0.1 s. These settings can be viewed in the `cavityGrade/system/controlDict` file.

The `startTime` needs to be set to that of the final conditions of the case `cavityFine`, *i.e.* 0.7. Since `cavity` and `cavityFine` converged well within the prescribed run time, we can set the run time for case `cavityGrade` to 0.1 s, *i.e.* the `endTime` should be 0.8.

2.1.6.3 Mapping fields

As in section 2.1.5.3, use `mapFields` to map the final results from case `cavityFine` onto the mesh for case `cavityGrade`. Enter the `cavityGrade` directory and execute `mapFields` by:

```
cd $FOAM_RUN/tutorials/incompressible/icoFoam/cavityGrade
mapFields ../cavityFine -consistent
```

Now run `icoFoam` from the case directory and monitor the run time information. View the converged results for this case and compare with other results using post-processing tools described previously in section 2.1.5.6 and section 2.1.5.7.

2.1.7 Increasing the Reynolds number

The cases solved so far have had a Reynolds number of 10. This is very low and leads to a stable solution quickly with only small secondary vortices at the bottom corners of the cavity. We will now increase the Reynolds number to 100, at which point the solution takes a noticeably longer time to converge. The coarsest mesh in case `cavity` will be used initially. The user should make a copy of the `cavity` case and name it `cavityHighRe` by typing:

```
cd $FOAM_RUN/tutorials/incompressible/icoFoam
cp -r cavity cavityHighRe
```

2.1.7.1 Pre-processing

Enter the `cavityHighRe` case and edit the `transportProperties` dictionary. Since the Reynolds number is required to be increased by a factor of 10, decrease the kinematic viscosity by a factor of 10, *i.e.* to $1 \times 10^{-3} \text{ m}^2 \text{ s}^{-1}$. We can now run this case by restarting from the solution at the end of the `cavity` case run. To do this we can use the option of setting the `startFrom` keyword to `latestTime` so that `icoFoam` takes as its initial data the values stored in the directory corresponding to the most recent time, *i.e.* `0.5`. The `endTime` should be set to `2 s`.

2.1.7.2 Running the code

Run `icoFoam` for this case from the case directory and view the run time information. When running a job in the background, the following UNIX commands can be useful:

`nohup` enables a command to keep running after the user who issues the command has logged out;

`nice` changes the priority of the job in the kernel's scheduler; a niceness of `-20` is the highest priority and `19` is the lowest priority.

This is useful, for example, if a user wishes to set a case running on a remote machine and does not wish to monitor it heavily, in which case they may wish to give it low priority on the machine. In that case the `nohup` command allows the user to log out of a remote machine he/she is running on and the job continues running, while `nice` can set the priority to `19`. For our case of interest, we can execute the command in this manner as follows:

```
cd $FOAM_RUN/tutorials/incompressible/icoFoam/cavityHighRe
nohup nice -n 19 icoFoam > log &
cat log
```

In previous runs you may have noticed that `icoFoam` stops solving for velocity `U` quite quickly but continues solving for pressure `p` for a lot longer or until the end of the run. In practice, once `icoFoam` stops solving for `U` and the initial residual of `p` is less than the tolerance set in the `fvSolution` dictionary (typically 10^{-6}), the run has effectively converged and can be stopped once the field data has been written out to a time directory. For example, at convergence a sample of the `log` file from the run on the `cavityHighRe` case appears as follows in which the velocity has already converged after `1.395 s` and initial pressure residuals are small; `No Iterations 0` indicates that the solution of `U` has stopped:

```
1 Time = 1.43
2
3 Courant Number mean: 0.221921 max: 0.839902
4 smoothSolver: Solving for Ux, Initial residual = 8.73381e-06, Final residual = 8.73381e-06, No Iterations 0
5 smoothSolver: Solving for Uy, Initial residual = 9.89679e-06, Final residual = 9.89679e-06, No Iterations 0
6 DICPCG: Solving for p, Initial residual = 3.67506e-06, Final residual = 8.62986e-07, No Iterations 4
7 time step continuity errors : sum local = 6.57947e-09, global = -6.6679e-19, cumulative = -6.2539e-18
8 DICPCG: Solving for p, Initial residual = 2.60898e-06, Final residual = 7.92532e-07, No Iterations 3
9 time step continuity errors : sum local = 6.26199e-09, global = -1.02984e-18, cumulative = -7.28374e-18
10 ExecutionTime = 0.37 s ClockTime = 0 s
11
12 Time = 1.435
13
14 Courant Number mean: 0.221923 max: 0.839903
15 smoothSolver: Solving for Ux, Initial residual = 8.53935e-06, Final residual = 8.53935e-06, No Iterations 0
16 smoothSolver: Solving for Uy, Initial residual = 9.71405e-06, Final residual = 9.71405e-06, No Iterations 0
17 DICPCG: Solving for p, Initial residual = 4.0223e-06, Final residual = 9.89693e-07, No Iterations 3
18 time step continuity errors : sum local = 8.15199e-09, global = 5.33614e-19, cumulative = -6.75012e-18
19 DICPCG: Solving for p, Initial residual = 2.38807e-06, Final residual = 8.44595e-07, No Iterations 3
20 time step continuity errors : sum local = 7.48751e-09, global = -4.42707e-19, cumulative = -7.19283e-18
21 ExecutionTime = 0.37 s ClockTime = 0 s
```

2.1.8 High Reynolds number flow

View the results in `paraFoam` and display the velocity vectors. The secondary vortices in the corners have increased in size somewhat. The user can then increase the Reynolds number further by decreasing the viscosity and then rerun the case. The number of vortices increases so the mesh resolution around them will need to increase in order to resolve the more complicated flow patterns. In addition, as the Reynolds number increases the time to convergence increases. The user should monitor residuals and extend the `endTime` accordingly to ensure convergence.

The need to increase spatial and temporal resolution then becomes impractical as the flow moves into the turbulent regime, where problems of solution stability may also occur. Of course, many engineering problems have very high Reynolds numbers and it is infeasible to bear the huge cost of solving the turbulent behaviour directly. Instead Reynolds-averaged simulation (RAS) turbulence models are used to solve for the mean flow behaviour and calculate the statistics of the fluctuations. The standard $k - \varepsilon$ model with wall functions will be used in this tutorial to solve the lid-driven cavity case with a Reynolds number of 10^4 . Two extra variables are solved for: k , the turbulent kinetic energy; and, ε , the turbulent dissipation rate. The additional equations and models for turbulent flow are implemented into a OpenFOAM solver called `pisoFoam` .

2.1.8.1 Pre-processing

Change directory to the `cavity` case in the `$FOAM_RUN/tutorials/incompressible/pisoFoam/-ras` directory (N.B: the `pisoFoam/ras` directory). Generate the mesh by running `blockMesh` as before. Mesh grading towards the wall is not necessary when using the standard $k - \varepsilon$ model with wall functions since the flow in the near wall cell is modelled, rather than having to be resolved.

A range of wall function models is available in OpenFOAM that are applied as boundary conditions on individual patches. This enables different wall function models to be applied to different wall regions. The choice of wall function models are specified through the turbulent viscosity field, ν_t in the `0/nut` file:

```

17
18     dimensions      [0 2 -1 0 0 0 0];
19
20     internalField    uniform 0;
21
22     boundaryField
23     {
24         movingWall
25         {
26             type      nutkWallFunction;
27             value      uniform 0;
28         }
29         fixedWalls
30         {
31             type      nutkWallFunction;
32             value      uniform 0;
33         }
34         frontAndBack
35         {
36             type      empty;
37         }
38     }
39
40
41     // ***** //

```

This case uses standard wall functions, specified by the `nutWallFunction` type on the

`movingWall` and `fixedWalls` patches. Other wall function models include the rough wall functions, specified though the `nutRoughWallFunction` keyword.

The user should now open the field files for k and ε ($0/k$ and $0/epsilon$) and examine their boundary conditions. For a wall boundary condition, ε is assigned a `epsilonWallFunction` boundary condition and a `kqRwallFunction` boundary condition is assigned to k . The latter is a generic boundary condition that can be applied to any field that are of a turbulent kinetic energy type, *e.g.* k , q or Reynolds Stress R . The initial values for k and ε are set using an estimated fluctuating component of velocity \mathbf{U}' and a turbulent length scale, l . k and ε are defined in terms of these parameters as follows:

$$k = \frac{1}{2} \overline{\mathbf{U}' \cdot \mathbf{U}'} \quad (2.8)$$

$$\varepsilon = \frac{C_\mu^{0.75} k^{1.5}}{l} \quad (2.9)$$

where C_μ is a constant of the $k - \varepsilon$ model equal to 0.09. For a Cartesian coordinate system, k is given by:

$$k = \frac{1}{2} (U_x'^2 + U_y'^2 + U_z'^2) \quad (2.10)$$

where $U_x'^2$, $U_y'^2$ and $U_z'^2$ are the fluctuating components of velocity in the x , y and z directions respectively. Let us assume the initial turbulence is isotropic, *i.e.* $U_x'^2 = U_y'^2 = U_z'^2$, and equal to 5% of the lid velocity and that l , is equal to 5% of the box width, 0.1 m, then k and ε are given by:

$$U_x' = U_y' = U_z' = \frac{5}{100} 1 \text{ m s}^{-1} \quad (2.11)$$

$$\Rightarrow k = \frac{3}{2} \left(\frac{5}{100} \right)^2 \text{ m}^2 \text{ s}^{-2} = 3.75 \times 10^{-3} \text{ m}^2 \text{ s}^{-2} \quad (2.12)$$

$$\varepsilon = \frac{C_\mu^{0.75} k^{1.5}}{l} \approx 7.54 \times 10^{-3} \text{ m}^2 \text{ s}^{-3} \quad (2.13)$$

These form the initial conditions for k and ε . The initial conditions for \mathbf{U} and p are $(0, 0, 0)$ and 0 respectively as before.

Turbulence modelling includes a range of methods, *e.g.* RAS or large-eddy simulation (LES), that are provided in OpenFOAM. The choice of turbulence modelling method is selectable at run-time through the `simulationType` keyword in `turbulenceProperties` dictionary. The user can view this file in the `constant` directory:

```

17
18 simulationType RAS;
19
20 RAS
21 {
22     RASModel      kOmega;
23
24     turbulence    on;
25
26     printCoeffs   on;
27 }
28
29 // ***** //

```

The options for `simulationType` are `laminar`, `RAS` and `LES` (`RASModel` and `LESModel` in OpenFOAM versions prior to v3.0.0). With RAS selected in this case, the choice of RAS

modelling is specified in a `RAS` subdictionary (or separate `RASProperties` file in OpenFOAM versions prior to v3.0.0). The turbulence model is selected by the `RASModel` entry from a long list of available models that are listed in Table 3.9. The `kEpsilon` model should be selected which is the standard $k - \varepsilon$ model; the user should also ensure that `turbulence` calculation is switched on.

The coefficients for each turbulence model are stored within the respective code with a set of default values. Setting the optional switch called `printCoeffs` to `on` will make the default values be printed to standard output, *i.e.* the terminal, when the model is called at run time. The coefficients are printed out as a sub-dictionary whose name is that of the model name with the word `Coeffs` appended, *e.g.* `kEpsilonCoeffs` in the case of the `kEpsilon` model. The coefficients of the model, *e.g.* `kEpsilon`, can be modified by optionally including (copying and pasting) that sub-dictionary within the `RAS` sub-dictionary and adjusting values accordingly.

The user should next set the laminar kinematic viscosity in the `transportProperties` dictionary. To achieve a Reynolds number of 10^4 , a kinematic viscosity of 10^{-5} m is required based on the Reynolds number definition given in Equation 2.1.

Finally the user should set the `startTime`, `stopTime`, `deltaT` and the `writeInterval` in the `controlDict`. Set `deltaT` to 0.005 s to satisfy the Courant number restriction and the `endTime` to 10 s.

2.1.8.2 Running the code

Execute `pisoFoam` by entering the case directory and typing “`pisoFoam`” in a terminal. In this case, where the viscosity is low, the boundary layer next to the moving lid is very thin and the cells next to the lid are comparatively large so the velocity at their centres are much less than the lid velocity. In fact, after ≈ 100 time steps it becomes apparent that the velocity in the cells adjacent to the lid reaches an upper limit of around 0.2 m s^{-1} hence the maximum Courant number does not rise much above 0.2. It is sensible to increase the solution time by increasing the time step to a level where the Courant number is much closer to 1. Therefore reset `deltaT` to 0.02 s and, on this occasion, set `startFrom` to `latestTime`. This instructs `pisoFoam` to read the start data from the latest time directory, *i.e.* `10.0`. The `endTime` should be set to 20 s since the run converges a lot slower than the laminar case. Restart the run as before and monitor the convergence of the solution. View the results at consecutive time steps as the solution progresses to see if the solution converges to a steady-state or perhaps reaches some periodically oscillating state. In the latter case, convergence may never occur but this does not mean the results are inaccurate.

2.1.9 Changing the case geometry

A user may wish to make changes to the geometry of a case and perform a new simulation. It may be useful to retain some or all of the original solution as the starting conditions for the new simulation. This is a little complex because the fields of the original solution are not consistent with the fields of the new case. However the `mapFields` utility can map fields that are inconsistent, either in terms of geometry or boundary types or both.

As an example, let us go to the `cavityClipped` case in the `icoFoam` directory which consists of the standard `cavity` geometry but with a square of length 0.04 m removed from the bottom right of the cavity, according to the `blockMeshDict` below:

```

17  convertToMeters 0.1;
18
19  vertices
20  (
21      (0 0 0)
22      (0.6 0 0)
23      (0 0.4 0)
24      (0.6 0.4 0)
25      (1 0.4 0)
26      (0 1 0)
27      (0.6 1 0)
28      (1 1 0)
29
30      (0 0 0.1)
31      (0.6 0 0.1)
32      (0 0.4 0.1)
33      (0.6 0.4 0.1)
34      (1 0.4 0.1)
35      (0 1 0.1)
36      (0.6 1 0.1)
37      (1 1 0.1)
38
39  );
40
41  blocks
42  (
43      hex (0 1 3 2 8 9 11 10) (12 8 1) simpleGrading (1 1 1)
44      hex (2 3 6 5 10 11 14 13) (12 12 1) simpleGrading (1 1 1)
45      hex (3 4 7 6 11 12 15 14) (8 12 1) simpleGrading (1 1 1)
46  );
47
48  edges
49  (
50  );
51
52  boundary
53  (
54      lid
55      {
56          type wall;
57          faces
58          (
59              (5 13 14 6)
60              (6 14 15 7)
61          );
62      }
63      fixedWalls
64      {
65          type wall;
66          faces
67          (
68              (0 8 10 2)
69              (2 10 13 5)
70              (7 15 12 4)
71              (4 12 11 3)
72              (3 11 9 1)
73              (1 9 8 0)
74          );
75      }
76      frontAndBack
77      {
78          type empty;
79          faces
80          (
81              (0 2 3 1)
82              (2 5 6 3)
83              (3 6 7 4)
84              (8 9 11 10)
85              (10 11 14 13)
86              (11 12 15 14)
87          );
88      }
89  );
90
91  mergePatchPairs
92  (
93  );
94
95  // ***** //

```

Generate the mesh with `blockMesh`. The patches are set accordingly as in previous cavity cases. For the sake of clarity in describing the field mapping process, the upper wall patch is renamed `lid`, previously the `movingWall` patch of the original `cavity`.

In an inconsistent mapping, there is no guarantee that all the field data can be mapped from the source case. The remaining data must come from field files in the target case itself. Therefore field data must exist in the time directory of the target case before mapping takes place. In the `cavityClipped` case the mapping is set to occur at time 0.5 s, since the `startTime` is set to 0.5 s in the `controlDict`. Therefore the user needs to copy initial field data to that directory, *e.g.* from time 0:

```
cd $FOAM_RUN/tutorials/incompressible/icoFoam/cavityClipped
cp -r 0 0.5
```

Before mapping the data, the user should view the geometry and fields at 0.5 s.

Now we wish to map the velocity and pressure fields from `cavity` onto the new fields of `cavityClipped`. Since the mapping is inconsistent, we need to edit the `mapFieldsDict` dictionary, located in the `system` directory. The dictionary contains 2 keyword entries: `patchMap` and `cuttingPatches`. The `patchMap` list contains a mapping of patches from the source fields to the target fields. It is used if the user wishes a patch in the target field to inherit values from a corresponding patch in the source field. In `cavityClipped`, we wish to inherit the boundary values on the `lid` patch from `movingWall` in `cavity` so we must set the `patchMap` as:

```
patchMap
(
    lid movingWall
);
```

The `cuttingPatches` list contains names of target patches whose values are to be mapped from the source internal field through which the target patch cuts. In this case we will include the `fixedWalls` to demonstrate the interpolation process.

```
cuttingPatches
(
    fixedWalls
);
```

Now the user should run `mapFields`, from within the `cavityClipped` directory:

```
mapFields ../cavity
```

The user can view the mapped field as shown in Figure 2.13. The boundary patches have inherited values from the source case as we expected. Having demonstrated this, however, we actually wish to reset the velocity on the `fixedWalls` patch to $(0,0,0)$. Edit the `U` field, go to the `fixedWalls` patch and change the field from `nonuniform` to `uniform (0,0,0)`. The `nonuniform` field is a list of values that requires deleting in its entirety. Now run the case with `icoFoam`.




Figure 2.13: cavity solution velocity field mapped onto cavityClipped.




Figure 2.14: cavityClipped solution for velocity field.

2.1.10 Post-processing the modified geometry

Velocity glyphs can be generated for the case as normal, first at time 0.5 s and later at time 0.6 s, to compare the initial and final solutions. In addition, we provide an outline of the geometry which requires some care to generate for a 2D case. The user should select **Extract Block** from the **Filter** menu and, in the **Parameter** panel, highlight the patches of interest, namely the **lid** and **fixedWalls**. On clicking **Apply**, these items of geometry can be displayed by selecting **Wireframe** in the **Display** panel. Figure 2.14 displays the patches in black and shows vortices forming in the bottom corners of the modified geometry.

2.2 Stress analysis of a plate with a hole

This tutorial describes how to pre-process, run and post-process a case involving linear-elastic, steady-state stress analysis on a square plate with a circular hole at its centre. The plate dimensions are: side length 4 m and radius $R = 0.5$ m. It is loaded with a uniform traction of $\sigma = 10$ kPa over its left and right faces as shown in Figure 2.15. Two symmetry planes can be identified for this geometry and therefore the solution domain need only cover a quarter of the geometry, shown by the shaded area in Figure 2.15.




Figure 2.15: Geometry of the plate with a hole.

The problem can be approximated as 2-dimensional since the load is applied in the plane of the plate. In a Cartesian coordinate system there are two possible assumptions to take in regard to the behaviour of the structure in the third dimension: (1) the plane stress condition, in which the stress components acting out of the 2D plane are assumed to be negligible; (2) the plane strain condition, in which the strain components out of the 2D plane are assumed negligible. The plane stress condition is appropriate for solids whose third dimension is thin as in this case; the plane strain condition is applicable for solids where the third dimension is thick.

An analytical solution exists for loading of an infinitely large, thin plate with a circular hole. The solution for the stress normal to the vertical plane of symmetry is

$$(\sigma_{xx})_{x=0} = \begin{cases} \sigma \left(1 + \frac{R^2}{2y^2} + \frac{3R^4}{2y^4} \right) & \text{for } |y| \geq R \\ 0 & \text{for } |y| < R \end{cases} \quad (2.14)$$

Results from the simulation will be compared with this solution. At the end of the tutorial, the user can: investigate the sensitivity of the solution to mesh resolution and mesh grading; and, increase the size of the plate in comparison to the hole to try to estimate the error in comparing the analytical solution for an infinite plate to the solution of this problem of a finite plate.

2.2.1 Mesh generation

The domain consists of four blocks, some of which have arc-shaped edges. The block structure for the part of the mesh in the $x-y$ plane is shown in Figure 2.16. As already mentioned in section 2.1.1.1, all geometries are generated in 3 dimensions in OpenFOAM even if the case is to be as a 2 dimensional problem. Therefore a dimension of the block in the z direction has to be chosen; here, 0.5 m is selected. It does not affect the solution since the traction boundary condition is specified as a stress rather than a force, thereby making the solution independent of the cross-sectional area.

The user should change into the `plateHole` case in the `$FOAM.RUN/tutorials/stress-Analysis/solidDisplacementFoam` directory and open the `blockMeshDict` file in an editor, as listed below

```

17  convertToMeters 1;
18
19  vertices
20  (
21      (0.5 0 0)
22      (1 0 0)
23      (2 0 0)
24      (2 0.707107 0)
25      (0.707107 0.707107 0)
26      (0.353553 0.353553 0)
27      (2 2 0)
28      (0.707107 2 0)
29      (0 2 0)
30      (0 1 0)
31      (0 0.5 0)
32      (0.5 0 0.5)
33      (1 0 0.5)
34      (2 0 0.5)
35      (2 0.707107 0.5)
36      (0.707107 0.707107 0.5)
37      (0.353553 0.353553 0.5)
38      (2 2 0.5)
39      (0.707107 2 0.5)
40      (0 2 0.5)
41      (0 1 0.5)
42      (0 0.5 0.5)
43  );
44
45  blocks
46  (
47      hex (5 4 9 10 16 15 20 21) (10 10 1) simpleGrading (1 1 1)
48      hex (0 1 4 5 11 12 15 16) (10 10 1) simpleGrading (1 1 1)
49      hex (1 2 3 4 12 13 14 15) (20 10 1) simpleGrading (1 1 1)
50      hex (4 3 6 7 15 14 17 18) (20 20 1) simpleGrading (1 1 1)
51      hex (9 4 7 8 20 15 18 19) (10 20 1) simpleGrading (1 1 1)
52  );
53
54  edges
```




Figure 2.16: Block structure of the mesh for the plate with a hole.

```

55 (
56   arc 0 5 (0.469846 0.17101 0)
57   arc 5 10 (0.17101 0.469846 0)
58   arc 1 4 (0.939693 0.34202 0)
59   arc 4 9 (0.34202 0.939693 0)
60   arc 11 16 (0.469846 0.17101 0.5)
61   arc 16 21 (0.17101 0.469846 0.5)
62   arc 12 15 (0.939693 0.34202 0.5)
63   arc 15 20 (0.34202 0.939693 0.5)
64 );
65
66 boundary
67 (
68   left
69   {
70     type symmetryPlane;
71     faces
72     (
73       (8 9 20 19)
74       (9 10 21 20)
75     );
76   }
77   right
78   {
79     type patch;
80     faces
81     (
82       (2 3 14 13)
83       (3 6 17 14)
84     );
85   }
86   down
87   {
88     type symmetryPlane;
89     faces

```

```

90     (
91         (0 1 12 11)
92         (1 2 13 12)
93     );
94 }
95 up
96 {
97     type patch;
98     faces
99     (
100         (7 8 19 18)
101         (6 7 18 17)
102     );
103 }
104 hole
105 {
106     type patch;
107     faces
108     (
109         (10 5 16 21)
110         (5 0 11 16)
111     );
112 }
113 frontAndBack
114 {
115     type empty;
116     faces
117     (
118         (10 9 4 5)
119         (5 4 1 0)
120         (1 4 3 2)
121         (4 7 6 3)
122         (4 9 8 7)
123         (21 16 15 20)
124         (16 11 12 15)
125         (12 13 14 15)
126         (15 14 17 18)
127         (15 18 19 20)
128     );
129 }
130 );
131
132 mergePatchPairs
133 (
134 );
135
136 // ***** //

```

Until now, we have only specified straight edges in the geometries of previous tutorials but here we need to specify curved edges. These are specified under the `edges` keyword entry which is a list of non-straight edges. The syntax of each list entry begins with the type of curve, including `arc`, `simpleSpline`, `polyLine` *etc.*, described further in section 5.3.1. In this example, all the edges are circular and so can be specified by the `arc` keyword entry. The following entries are the labels of the start and end vertices of the arc and a point vector through which the circular arc passes.

The blocks in this *blockMeshDict* do not all have the same orientation. As can be seen in Figure 2.16 the x_2 direction of block 0 is equivalent to the $-x_1$ direction for block 4. This means care must be taken when defining the number and distribution of cells in each block so that the cells match up at the block faces.

6 patches are defined: one for each side of the plate, one for the hole and one for the front and back planes. The `left` and `down` patches are both a symmetry plane. Since this is a *geometric* constraint, it is included in the definition of the *mesh*, rather than being purely a specification on the boundary condition of the fields. Therefore they are defined as such using a special `symmetryPlane` type as shown in the *blockMeshDict*.

The `frontAndBack` patch represents the plane which is ignored in a 2D case. Again this is a geometric constraint so is defined within the mesh, using the `empty` type as shown in the *blockMeshDict*. For further details of boundary types and geometric constraints, the user

should refer to section 5.2.1.

The remaining patches are of the regular `patch` type. The mesh should be generated using `blockMesh` and can be viewed in `paraFoam` as described in section 2.1.2. It should appear as in Figure 2.17.




Figure 2.17: Mesh of the hole in a plate problem.

2.2.1.1 Boundary and initial conditions

Once the mesh generation is complete, the initial field with boundary conditions must be set. For a stress analysis case without thermal stresses, only displacement `D` needs to be set. The `0/D` is as follows:

```

17 dimensions      [0 1 0 0 0 0 0];
18
19 internalField    uniform (0 0 0);
20
21 boundaryField
22 {
23     left
24     {
25         type      symmetryPlane;
26     }
27     right
28     {
29         type      tractionDisplacement;
30         traction   uniform (10000 0 0);
31         pressure   uniform 0;
32         value      uniform (0 0 0);
33     }
34     down
35     {
36         type      symmetryPlane;
37     }
38     up
39     {
40         type      tractionDisplacement;
41         traction   uniform (0 0 0);
42         pressure   uniform 0;
43         value      uniform (0 0 0);
44     }
45     hole
46     {
47         type      tractionDisplacement;
48         traction   uniform (0 0 0);

```

```

49         pressure      uniform 0;
50         value          uniform (0 0 0);
51     }
52     frontAndBack
53     {
54         type            empty;
55     }
56 }
57
58 // ***** //

```

Firstly, it can be seen that the displacement initial conditions are set to $(0, 0, 0)$ m. The **left** and **down** patches **must** be both of `symmetryPlane` type since they are specified as such in the mesh description in the `constant/polyMesh/boundary` file. Similarly the `frontAndBack` patch is declared `empty`.

The other patches are traction boundary conditions, set by a specialist `traction` boundary type. The traction boundary conditions are specified by a linear combination of: (1) a boundary traction vector under keyword `traction`; (2) a pressure that produces a traction normal to the boundary surface that is defined as negative when pointing out of the surface, under keyword `pressure`. The **up** and **hole** patches are zero traction so the boundary traction and pressure are set to zero. For the **right** patch the traction should be $(1e4, 0, 0)$ Pa and the pressure should be 0 Pa.

2.2.1.2 Mechanical properties

The physical properties for the case are set in the `mechanicalProperties` dictionary in the `constant` directory. For this problem, we need to specify the mechanical properties of steel given in Table 2.1. In the mechanical properties dictionary, the user must also set `planeStress` to `yes`.

| Property | Units | Keyword | Value |
|-----------------|--------------------|------------------|--------------------|
| Density | kg m^{-3} | <code>rho</code> | 7854 |
| Young's modulus | Pa | <code>E</code> | 2×10^{11} |
| Poisson's ratio | — | <code>nu</code> | 0.3 |

Table 2.1: Mechanical properties for steel

2.2.1.3 Thermal properties

The temperature field variable `T` is present in the `solidDisplacementFoam` solver since the user may opt to solve a thermal equation that is coupled with the momentum equation through the thermal stresses that are generated. The user specifies at run time whether OpenFOAM should solve the thermal equation by the `thermalStress` switch in the `thermalProperties` dictionary. This dictionary also sets the thermal properties for the case, *e.g.* for steel as listed in Table 2.2.

In this case we do not want to solve for the thermal equation. Therefore we must set the `thermalStress` keyword entry to `no` in the `thermalProperties` dictionary.

2.2.1.4 Control

As before, the information relating to the control of the solution procedure are read in from the `controlDict` dictionary. For this case, the `startTime` is 0 s. The time step is not

| Property | Units | Keyword | Value |
|--------------------------|--------------------------------|--------------|----------------------|
| Specific heat capacity | $\text{Jkg}^{-1}\text{K}^{-1}$ | C | 434 |
| Thermal conductivity | $\text{Wm}^{-1}\text{K}^{-1}$ | k | 60.5 |
| Thermal expansion coeff. | K^{-1} | alpha | 1.1×10^{-5} |

Table 2.2: Thermal properties for steel

important since this is a steady state case; in this situation it is best to set the time step `deltaT` to 1 so it simply acts as an iteration counter for the steady-state case. The `endTime`, set to 100, then acts as a limit on the number of iterations. The `writeInterval` can be set to 20.

The `controlDict` entries are as follows:

```

17
18 application      solidDisplacementFoam;
19
20 startFrom        startTime;
21
22 startTime        0;
23
24 stopAt           endTime;
25
26 endTime          100;
27
28 deltaT           1;
29
30 writeControl     timeStep;
31
32 writeInterval    20;
33
34 purgeWrite       0;
35
36 writeFormat      ascii;
37
38 writePrecision   6;
39
40 writeCompression off;
41
42 timeFormat       general;
43
44 timePrecision    6;
45
46 graphFormat      raw;
47
48 runTimeModifiable true;
49
50
51 // ***** //

```

2.2.1.5 Discretisation schemes and linear-solver control

Let us turn our attention to the `fvSchemes` dictionary. Firstly, the problem we are analysing is steady-state so the user should select `SteadyState` for the time derivatives in `timeScheme`. This essentially switches off the time derivative terms. Not all solvers, especially in fluid dynamics, work for both steady-state and transient problems but `solidDisplacementFoam` does work, since the base algorithm is the same for both types of simulation.

The momentum equation in linear-elastic stress analysis includes several explicit terms containing the gradient of displacement. The calculations benefit from accurate and smooth evaluation of the gradient. Normally, in the finite volume method the discretisation is based on Gauss's theorem. The Gauss method is sufficiently accurate for most purposes but, in this case, the least squares method will be used. The user should therefore open the `fvSchemes` dictionary in the `system` directory and ensure the `leastSquares` method is selected for the `grad(U)` gradient discretisation scheme in the `gradSchemes` sub-dictionary:

```

17
18 d2dt2Schemes
19 {
20     default          steadyState;
21 }
22
23 ddtSchemes
24 {
25     default          Euler;
26 }
27
28 gradSchemes
29 {
30     default          leastSquares;
31     grad(D)          leastSquares;
32     grad(T)          leastSquares;
33 }
34
35 divSchemes
36 {
37     default          none;
38     div(sigmaD)      Gauss linear;
39 }
40
41 laplacianSchemes
42 {
43     default          none;
44     laplacian(DD,D)  Gauss linear corrected;
45     laplacian(DT,T)  Gauss linear corrected;
46 }
47
48 interpolationSchemes
49 {
50     default          linear;
51 }
52
53 snGradSchemes
54 {
55     default          none;
56 }
57
58 // ***** //

```

The *fvSolution* dictionary in the *system* directory controls the linear equation solvers and algorithms used in the solution. The user should first look at the *solvers* sub-dictionary and notice that the choice of *solver* for D is **GAMG**. The solver *tolerance* should be set to 10^{-6} for this problem. The solver relative tolerance, denoted by *relTol*, sets the required reduction in the residuals within each iteration. It is uneconomical to set a tight (low) relative tolerance within each iteration since a lot of terms in each equation are explicit and are updated as part of the segregated iterative procedure. Therefore a reasonable value for the relative tolerance is 0.01, or possibly even higher, say 0.1, or in some cases even 0.9 (as in this case).

```

17
18 solvers
19 {
20     "(D|T)"
21     {
22         solver          GAMG;
23         tolerance       1e-06;
24         relTol          0.9;
25         smoother        GaussSeidel;
26         cacheAgglomeration true;
27         nCellsInCoarsestLevel 20;
28         agglomerator     faceAreaPair;
29         mergeLevels     1;
30     }
31 }
32
33 stressAnalysis
34 {
35     compactNormalStress yes;
36     nCorrectors        1;

```

```

37     D                1e-06;
38   }
39
40
41   // ***** //

```

The *fvSolution* dictionary contains a sub-dictionary, *stressAnalysis* that contains some control parameters specific to the application solver. Firstly there is `nCorrectors` which specifies the number of outer loops around the complete system of equations, including traction boundary conditions *within each time step*. Since this problem is steady-state, we are performing a set of iterations towards a converged solution with the 'time step' acting as an iteration counter. We can therefore set `nCorrectors` to 1.

The `D` keyword specifies a convergence tolerance for the outer iteration loop, *i.e.* sets a level of initial residual below which solving will cease. It should be set to the desired solver tolerance specified earlier, 10^{-6} for this problem.

2.2.2 Running the code

The user should run the code here in the background from the command line as specified below, so he/she can look at convergence information in the log file afterwards.

```

cd $FOAM_RUN/tutorials/stressAnalysis/solidDisplacementFoam/plateHole
solidDisplacementFoam > log &

```

The user should check the convergence information by viewing the generated *log* file which shows the number of iterations and the initial and final residuals of the displacement in each direction being solved. The final residual should always be less than 0.9 times the initial residual as this iteration tolerance set. Once both initial residuals have dropped below the convergence tolerance of 10^{-6} the run has converged and can be stopped by killing the batch job.

2.2.3 Post-processing

Post processing can be performed as in section 2.1.4. The `solidDisplacementFoam` solver outputs the stress field σ as a symmetric tensor field `sigma`. This is consistent with the way variables are usually represented in OpenFOAM solvers by the mathematical symbol by which they are represented; in the case of Greek symbols, the variable is named phonetically.

For post-processing individual scalar field components, σ_{xx} , σ_{xy} *etc.*, can be generated by running the `foamCalc` utility as before in section 2.1.5.7, this time on `sigma`:


```

foamCalc components sigma

```

Components named `sigmaxx`, `sigmaxy` *etc.* are written to time directories of the case. The σ_{xx} stresses can be viewed in `paraFoam` as shown in Figure 2.18.

We would like to compare the analytical solution of Equation 2.14 to our solution. We therefore must output a set of data of σ_{xx} along the left edge symmetry plane of our domain. The user may generate the required graph data using the `sample` utility. The utility uses a *sampleDict* dictionary located in the *system* directory, whose entries are summarised in Table 6.8. The sample line specified in `sets` is set between (0.0, 0.5, 0.25) and (0.0, 2.0, 0.25), and the fields are specified in the `fields` list:

Figure 2.18: σ_{xx} stress field in the plate with hole.

```

17
18 interpolationScheme cellPoint;
19
20 setFormat      raw;
21
22 sets
23 (
24     leftPatch
25     {
26         type      uniform;
27         axis      y;
28         start     (0 0.5 0.25);
29         end       (0 2 0.25);
30         nPoints   100;
31     }
32 );
33
34 fields          (sigmaEq);
35
36
37 // ***** //

```

The user should execute `sample` as normal. The `writeFormat` is `raw` 2 column format. The data is written into files within time subdirectories of a `postProcessing/sets` directory, *e.g.* the data at $t = 100$ s is found within the file `sets/100/leftPatch.sigmaxx.xy`. In an application such as `GnuPlot`, one could type the following at the command prompt would be sufficient to plot both the numerical data and analytical solution:

```


plot [0.5:2] [0:] 'postProcessing/sets/100/leftPatch sigmaxx.xy',
    1e4*(1+(0.125/(x**2))+(0.09375/(x**4)))

```

An example plot is shown in Figure 2.19.

2.2.4 Exercises

The user may wish to experiment with `solidDisplacementFoam` by trying the following exercises:



Numerical prediction \circ Analytical solution —

Figure 2.19: Normal stress along the vertical symmetry $(\sigma_{xx})_{x=0}$

2.2.4.1 Increasing mesh resolution

Increase the mesh resolution in each of the x and y directions. Use `mapFields` to map the final coarse mesh results from section 2.2.3 to the initial conditions for the fine mesh.

2.2.4.2 Introducing mesh grading

Grade the mesh so that the cells near the hole are finer than those away from the hole. Design the mesh so that the ratio of sizes between adjacent cells is no more than 1.1 and so that the ratio of cell sizes between blocks is similar to the ratios within blocks. Mesh grading is described in section 2.1.6. Again use `mapFields` to map the final coarse mesh results from section 2.2.3 to the initial conditions for the graded mesh. Compare the results with those from the analytical solution and previous calculations. Can this solution be improved upon using the same number of cells with a different solution?

2.2.4.3 Changing the plate size

The analytical solution is for an infinitely large plate with a finite sized hole in it. Therefore this solution is not completely accurate for a finite sized plate. To estimate the error, increase the plate size while maintaining the hole size at the same value.

2.3 Breaking of a dam

In this tutorial we shall solve a problem of simplified dam break in 2 dimensions using the `interFoam`. The feature of the problem is a transient flow of two fluids separated by a sharp interface, or free surface. The two-phase algorithm in `interFoam` is based on the volume of fluid (VOF) method in which a specie transport equation is used to determine the relative volume fraction of the two phases, or phase fraction α , in each computational cell. Physical properties are calculated as weighted averages based on this fraction. The nature of the VOF method means that an interface between the species is not explicitly computed, but

rather emerges as a property of the phase fraction field. Since the phase fraction can have any value between 0 and 1, the interface is never sharply defined, but occupies a volume around the region where a sharp interface should exist.

The test setup consists of a column of water at rest located behind a membrane on the left side of a tank. At time $t = 0$ s, the membrane is removed and the column of water collapses. During the collapse, the water impacts an obstacle at the bottom of the tank and creates a complicated flow structure, including several captured pockets of air. The geometry and the initial setup is shown in Figure 2.20.




Figure 2.20: Geometry of the dam break.

2.3.1 Mesh generation

The user should go to the *damBreak* case in their `$FOAM.RUN/tutorials/multiphase/interFoam/laminar` directory. Generate the mesh running `blockMesh` as described previously. The *damBreak* mesh consist of 5 blocks; the *blockMeshDict* entries are given below.

```

17  convertToMeters 0.146;
18
19  vertices
20  (
21      (0 0 0)
22      (2 0 0)
23      (2.16438 0 0)
24      (4 0 0)
25      (0 0.32876 0)
26      (2 0.32876 0)
27      (2.16438 0.32876 0)
28      (4 0.32876 0)
29      (0 4 0)
30      (2 4 0)
31      (2.16438 4 0)
32      (4 4 0)
33      (0 0 0.1)
34      (2 0 0.1)
35      (2.16438 0 0.1)

```

```

36     (4 0 0.1)
37     (0 0.32876 0.1)
38     (2 0.32876 0.1)
39     (2.16438 0.32876 0.1)
40     (4 0.32876 0.1)
41     (0 4 0.1)
42     (2 4 0.1)
43     (2.16438 4 0.1)
44     (4 4 0.1)
45 );
46
47 blocks
48 (
49     hex (0 1 5 4 12 13 17 16) (23 8 1) simpleGrading (1 1 1)
50     hex (2 3 7 6 14 15 19 18) (19 8 1) simpleGrading (1 1 1)
51     hex (4 5 9 8 16 17 21 20) (23 42 1) simpleGrading (1 1 1)
52     hex (5 6 10 9 17 18 22 21) (4 42 1) simpleGrading (1 1 1)
53     hex (6 7 11 10 18 19 23 22) (19 42 1) simpleGrading (1 1 1)
54 );
55
56 edges
57 (
58 );
59
60 boundary
61 (
62     leftWall
63     {
64         type wall;
65         faces
66         (
67             (0 12 16 4)
68             (4 16 20 8)
69         );
70     }
71     rightWall
72     {
73         type wall;
74         faces
75         (
76             (7 19 15 3)
77             (11 23 19 7)
78         );
79     }
80     lowerWall
81     {
82         type wall;
83         faces
84         (
85             (0 1 13 12)
86             (1 5 17 13)
87             (5 6 18 17)
88             (2 14 18 6)
89             (2 3 15 14)
90         );
91     }
92     atmosphere
93     {
94         type patch;
95         faces
96         (
97             (8 20 21 9)
98             (9 21 22 10)
99             (10 22 23 11)
100        );
101    }
102 );
103
104 mergePatchPairs
105 (
106 );
107
108 // ***** //

```

2.3.2 Boundary conditions

The user can examine the boundary geometry generated by `blockMesh` by viewing the *boundary* file in the *constant/polyMesh* directory. The file contains a list of 5 boundary patches: `leftWall`, `rightWall`, `lowerWall`, `atmosphere` and `defaultFaces`. The user should notice the **type** of the patches. The `atmosphere` is a standard **patch**, *i.e.* has no special attributes, merely an entity on which boundary conditions can be specified. The `defaultFaces` patch is **empty** since the patch normal is in the direction we will not solve in this 2D case. The `leftWall`, `rightWall` and `lowerWall` patches are each a **wall**. Like the plain **patch**, the **wall** type contains no geometric or topological information about the mesh and only differs from the plain **patch** in that it identifies the patch as a wall, should an application need to know, *e.g.* to apply special wall surface modelling.

A good example is that the `interFoam` solver includes modelling of surface tension at the contact point between the interface and wall surface. The models are applied by specifying the `alphaContactAngle` boundary condition on the `alpha` (α) field. With it, the user must specify the following: a static contact angle, `theta0` θ_0 ; leading and trailing edge dynamic contact angles, `thetaA` θ_A and `thetaR` θ_R respectively; and a velocity scaling function for dynamic contact angle, `uTheta`.

In this tutorial we would like to ignore surface tension effects between the wall and interface. We can do this by setting the static contact angle, $\theta_0 = 90^\circ$ and the velocity scaling function to 0. However, the simpler option which we shall choose here is to specify a `zeroGradient` type on `alpha`, rather than use the `alphaContactAngle` boundary condition.

The `top` boundary is free to the atmosphere so needs to permit both outflow and inflow according to the internal flow. We therefore use a combination of boundary conditions for pressure and velocity that does this while maintaining stability. They are:

- `totalPressure` which is a `fixedValue` condition calculated from specified total pressure p_0 and local velocity U ;
- `pressureInletOutletVelocity`, which applies `zeroGradient` on all components, except where there is inflow, in which case a `fixedValue` condition is applied to the *tangential* component;
- `inletOutlet`, which is a `zeroGradient` condition when flow outwards, `fixedValue` when flow is inwards.

At all wall boundaries, the `fixedFluxPressure` boundary condition is applied to the pressure field, which adjusts the pressure gradient so that the boundary flux matches the velocity boundary condition.

The `defaultFaces` patch representing the front and back planes of the 2D problem, is, as usual, an **empty** type.

2.3.3 Setting initial field

Unlike the previous cases, we shall now specify a non-uniform initial condition for the phase fraction α_{water} where

$$\alpha_{\text{water}} = \begin{cases} 1 & \text{for the water phase} \\ 0 & \text{for the air phase} \end{cases} \quad (2.15)$$

This will be done by running the `setFields` utility. It requires a `setFieldsDict` dictionary, located in the `system` directory, whose entries for this case are shown below.

```

17
18 defaultFieldValues
19 (
20     volScalarFieldValue alpha.water 0
21 );
22
23 regions
24 (
25     boxToCell
26     {
27         box (0 0 -1) (0.1461 0.292 1);
28         fieldValues
29         (
30             volScalarFieldValue alpha.water 1
31         );
32     }
33 );
34
35
36 // ***** //

```

The `defaultFieldValues` sets the default value of the fields, *i.e.* the value the field takes unless specified otherwise in the `regions` sub-dictionary. That sub-dictionary contains a list of subdictionaries containing `fieldValues` that override the defaults in a specified region. The region is expressed in terms of a `topoSetSource` that creates a set of points, cells or faces based on some topological constraint. Here, `boxToCell` creates a bounding box within a vector minimum and maximum to define the set of cells of the water region. The phase fraction α_{water} is defined as 1 in this region.

The `setFields` utility reads fields from file and, after re-calculating those fields, will write them back to file. Because the files are then overridden, it is recommended that a backup is made before `setFields` is executed. In the `damBreak` tutorial, the `alpha.water` field is initially stored as a backup *only*, named `alpha.water.org`. Before running `setFields`, the user first needs to copy `alpha.water.org` to `alpha.water`, *e.g.* by typing:

```
cp 0/alpha.water.org 0/alpha.water
```

The user should then execute `setFields` as any other utility is executed. Using `paraFoam`, check that the initial `alpha.water` field corresponds to the desired distribution as in Figure 2.21.

2.3.4 Fluid properties

Let us examine the `transportProperties` file in the `constant` directory. The dictionary contains the material properties for each fluid, separated into two dictionaries `water` and `air`. The transport model for each phase is selected by the `transportModel` keyword. The user should select `Newtonian` in which case the kinematic viscosity is single valued and specified under the keyword `nu`. The viscosity parameters for the other models, *e.g.* `CrossPowerLaw`, are specified within subdictionaries with the generic name `<model>Coeffs`, *i.e.* `CrossPowerLawCoeffs` in this example. The density is specified under the keyword `rho`.

The surface tension between the two phases is specified under the keyword `sigma`. The values used in this tutorial are listed in Table 2.3.

Gravitational acceleration is uniform across the domain and is specified in a file named `g` in the `constant` directory. Unlike a normal field file, *e.g.* `U` and `p`, `g` is a `uniformDimensionedVectorField` and so simply contains a set of `dimensions` and a value that represents $(0, 9.81, 0) \text{ m s}^{-2}$ for this tutorial:




Figure 2.21: Initial conditions for phase fraction `alpha.water`.

| water properties | | | |
|---------------------------|----------------------------|--------------------|-----------------------|
| Kinematic viscosity | $\text{m}^2 \text{s}^{-1}$ | <code>nu</code> | 1.0×10^{-6} |
| Density | kg m^{-3} | <code>rho</code> | 1.0×10^3 |
| air properties | | | |
| Kinematic viscosity | $\text{m}^2 \text{s}^{-1}$ | <code>nu</code> | 1.48×10^{-5} |
| Density | kg m^{-3} | <code>rho</code> | 1.0 |
| Properties of both phases | | | |
| Surface tension | N m^{-1} | <code>sigma</code> | 0.07 |

Table 2.3: Fluid properties for the `damBreak` tutorial

```

17
18 dimensions      [0 1 -2 0 0 0 0];
19 value           (0 -9.81 0);
20
21
22 // ***** //
    
```

2.3.5 Turbulence modelling

As in the cavity example, the choice of turbulence modelling method is selectable at run-time through the `simulationType` keyword in `turbulenceProperties` dictionary. In this example, we wish to run without turbulence modelling so we set `laminar`:

```

17
18 simulationType  laminar;
19
20
21 // ***** //
    
```

2.3.6 Time step control

Time step control is an important issue in free surface tracking since the surface-tracking algorithm is considerably more sensitive to the Courant number Co than in standard fluid flow calculations. Ideally, we should not exceed an upper limit $Co \approx 0.5$ in the region of the interface. In some cases, where the propagation velocity is easy to predict, the user should specify a fixed time-step to satisfy the Co criterion. For more complex cases, this is considerably more difficult. `interFoam` therefore offers automatic adjustment of the time step as standard in the `controlDict`. The user should specify `adjustTimeStep` to be on and the the maximum Co for the phase fields, `maxAlphaCo`, and other fields, `maxCo`, to be 1.0. The upper limit on time step `maxDeltaT` can be set to a value that will not be exceeded in this simulation, *e.g.* 1.0.

By using automatic time step control, the steps themselves are never rounded to a convenient value. Consequently if we request that OpenFOAM saves results at a fixed number of time step intervals, the times at which results are saved are somewhat arbitrary. However even with automatic time step adjustment, OpenFOAM allows the user to specify that results are written at fixed times; in this case OpenFOAM forces the automatic time stepping procedure to adjust time steps so that it ‘hits’ on the exact times specified for write output. The user selects this with the `adjustableRunTime` option for `writeControl` in the `controlDict` dictionary. The `controlDict` dictionary entries should be:

```

17
18 application      interFoam;
19
20 startFrom         startTime;
21
22 startTime         0;
23
24 stopAt           endTime;
25
26 endTime          1;
27
28 deltaT           0.001;
29
30 writeControl      adjustableRunTime;
31
32 writeInterval    0.05;
33
34 purgeWrite       0;
35
36 writeFormat      ascii;
37
38 writePrecision   6;
39
40 writeCompression uncompressed;
41
42 timeFormat       general;
43
44 timePrecision    6;
45
46 runTimeModifiable yes;
47
48 adjustTimeStep   yes;
49
50 maxCo            1;
51 maxAlphaCo       1;
52
53 maxDeltaT        1;
54
55 // ***** //
56
```

2.3.7 Discretisation schemes

The `interFoam` solver uses the multidimensional universal limiter for explicit solution (MULES) method, created by OpenCFD, to maintain boundedness of the phase fraction independent

of underlying numerical scheme, mesh structure, *etc.* The choice of schemes for convection are therefore not restricted to those that are strongly stable or bounded, *e.g.* upwind differencing.

The convection schemes settings are made in the *divSchemes* sub-dictionary of the *fvSchemes* dictionary. In this example, the convection term in the momentum equation ($\nabla \cdot (\rho \mathbf{U} \mathbf{U})$), denoted by the `div(rho*phi,U)` keyword, uses `Gauss linearUpwind grad(U)` to produce good accuracy. The limited linear schemes require a coefficient ϕ as described in section 4.4.1. Here, we have opted for best stability with $\phi = 1.0$. The $\nabla \cdot (\mathbf{U} \alpha_1)$ term, represented by the `div(phi,alpha)` keyword uses the `vanLeer` scheme. The $\nabla \cdot (\mathbf{U}_{rb} \alpha_1)$ term, represented by the `div(phirb,alpha)` keyword, can use second order `linear` (central) differencing as boundedness is assured by the MULES algorithm.

The other discretised terms use commonly employed schemes so that the *fvSchemes* dictionary entries should therefore be:

```

17
18 ddtSchemes
19 {
20     default          Euler;
21 }
22
23 gradSchemes
24 {
25     default          Gauss linear;
26 }
27
28 divSchemes
29 {
30     div(rhoPhi,U)   Gauss linearUpwind grad(U);
31     div(phi,alpha)  Gauss vanLeer;
32     div(phirb,alpha) Gauss linear;
33     div(((rho*nuEff)*dev2(T(grad(U)))))) Gauss linear;
34 }
35
36 laplacianSchemes
37 {
38     default          Gauss linear corrected;
39 }
40
41 interpolationSchemes
42 {
43     default          linear;
44 }
45
46 snGradSchemes
47 {
48     default          corrected;
49 }
50
51
52 // ***** //

```

2.3.8 Linear-solver control

In the *fvSolution*, the *PIMPLE* sub-dictionary contains elements that are specific to *interFoam*. There are the usual correctors to the momentum equation but also correctors to a PISO loop around the α phase equation. Of particular interest are the `nAlphaSubCycles` and `cAlpha` keywords. `nAlphaSubCycles` represents the number of sub-cycles within the α equation; sub-cycles are additional solutions to an equation within a given time step. It is used to enable the solution to be stable without reducing the time step and vastly increasing the solution time. Here we specify 2 sub-cycles, which means that the α equation is solved in $2 \times$ half length time steps within each actual time step.

The `cAlpha` keyword is a factor that controls the compression of the interface where: 0 corresponds to no compression; 1 corresponds to conservative compression; and, anything

larger than 1, relates to enhanced compression of the interface. We generally recommend a value of 1.0 which is employed in this example.

2.3.9 Running the code

Running of the code has been described in detail in previous tutorials. Try the following, that uses `tee`, a command that enables output to be written to both standard output and files:

```
cd $FOAM_RUN/tutorials/multiphase/interFoam/laminar/damBreak
interFoam | tee log
```

The code will now be run interactively, with a copy of output stored in the `log` file.

2.3.10 Post-processing

Post-processing of the results can now be done in the usual way. The user can monitor the development of the phase fraction `alpha.water` in time, *e.g.* see Figure 2.22.

2.3.11 Running in parallel

The results from the previous example are generated using a fairly coarse mesh. We now wish to increase the mesh resolution and re-run the case. The new case will typically take a few hours to run with a single processor so, should the user have access to multiple processors, we can demonstrate the parallel processing capability of OpenFOAM.

The user should first make a copy of the `damBreak` case, *e.g.* by

```
cd $FOAM_RUN/tutorials/multiphase/interFoam/laminar
mkdir damBreakFine
cp -r damBreak/0 damBreakFine
cp -r damBreak/system damBreakFine
cp -r damBreak/constant damBreakFine
```

Enter the new case directory and change the `blocks` description in the `blockMeshDict` dictionary to

```
blocks
(
    hex (0 1 5 4 12 13 17 16) (46 10 1) simpleGrading (1 1 1)
    hex (2 3 7 6 14 15 19 18) (40 10 1) simpleGrading (1 1 1)
    hex (4 5 9 8 16 17 21 20) (46 76 1) simpleGrading (1 2 1)
    hex (5 6 10 9 17 18 22 21) (4 76 1) simpleGrading (1 2 1)
    hex (6 7 11 10 18 19 23 22) (40 76 1) simpleGrading (1 2 1)
);
```

Here, the entry is presented as printed from the `blockMeshDict` file; in short the user must change the mesh densities, *e.g.* the `46 10 1` entry, and some of the mesh grading entries to `1 2 1`. Once the dictionary is correct, generate the mesh.




Figure 2.22: Snapshots of phase α .

As the mesh has now changed from the `damBreak` example, the user must re-initialise the phase field `alpha.water` in the `0` time directory since it contains a number of elements that is inconsistent with the new mesh. Note that there is no need to change the `U` and `p_rgh` fields since they are specified as `uniform` which is independent of the number of elements in the field. We wish to initialise the field with a sharp interface, *i.e.* it elements would have $\alpha = 1$ or $\alpha = 0$. Updating the field with `mapFields` may produce interpolated values $0 < \alpha < 1$ at the interface, so it is better to rerun the `setFields` utility. There is a backup copy of the initial uniform α field named `0/alpha.water.org` that the user should copy to `0/alpha.water` before running `setFields`:

```
cd $FOAM_RUN/tutorials/multiphase/interFoam/laminar/damBreakFine
cp -r 0/alpha.water.org 0/alpha.water
setFields
```

The method of parallel computing used by OpenFOAM is known as domain decomposition, in which the geometry and associated fields are broken into pieces and allocated to separate processors for solution. The first step required to run a parallel case is therefore to decompose the domain using the `decomposePar` utility. There is a dictionary associated with `decomposePar` named `decomposeParDict` which is located in the `system` directory of the tutorial case; also, like with many utilities, a default dictionary can be found in the directory of the source code of the specific utility, *i.e.* in `$FOAM_UTILITIES/parallelProcessing/decomposePar` for this case.

The first entry is `numberOfSubdomains` which specifies the number of subdomains into which the case will be decomposed, usually corresponding to the number of processors available for the case.

In this tutorial, the `method` of decomposition should be `simple` and the corresponding `simpleCoeffs` should be edited according to the following criteria. The domain is split into pieces, or subdomains, in the x , y and z directions, the number of subdomains in each direction being given by the vector `n`. As this geometry is 2 dimensional, the 3rd direction, z , cannot be split, hence n_z must equal 1. The n_x and n_y components of `n` split the domain in the x and y directions and must be specified so that the number of subdomains specified by n_x and n_y equals the specified `numberOfSubdomains`, *i.e.* $n_x n_y = \text{numberOfSubdomains}$. It is beneficial to keep the number of cell faces adjoining the subdomains to a minimum so, for a square geometry, it is best to keep the split between the x and y directions should be fairly even. The `delta` keyword should be set to 0.001.

For example, let us assume we wish to run on 4 processors. We would set `numberOfSubdomains` to 4 and `n = (2, 2, 1)`. When running `decomposePar`, we can see from the screen messages that the decomposition is distributed fairly even between the processors.

The user should consult section 3.4 for details of how to run a case in parallel; in this tutorial we merely present an example of running in parallel. We use the `openMPI` implementation of the standard message-passing interface (MPI). As a test here, the user can run in parallel on a single node, the local host only, by typing:

```
mpirun -np 4 interFoam -parallel > log &
```

The user may run on more nodes over a network by creating a file that lists the host names of the machines on which the case is to be run as described in section 3.4.2. The case should run in the background and the user can follow its progress by monitoring the `log` file as usual.




Figure 2.23: Mesh of processor 2 in parallel processed case.

2.3.12 Post-processing a case run in parallel

Once the case has completed running, the decomposed fields and mesh must be reassembled for post-processing using the `reconstructPar` utility. Simply execute it from the command line. The results from the fine mesh are shown in Figure 2.24. The user can see that the resolution of interface has improved significantly compared to the coarse mesh.

The user may also post-process a segment of the decomposed domain individually by simply treating the individual processor directory as a case in its own right. For example if the user starts `paraFoam` by

```
paraFoam -case processor1
```

then `processor1` will appear as a case module in `ParaView`. Figure 2.23 shows the mesh from processor 1 following the decomposition of the domain using the `simple` method.




Figure 2.24: Snapshots of phase α with refined mesh.

Chapter 3

Applications and libraries

We should reiterate from the outset that OpenFOAM is a C++ library used primarily to create executables, known as *applications*. OpenFOAM is distributed with a large set of precompiled applications but users also have the freedom to create their own or modify existing ones. Applications are split into two main categories:

solvers that are each designed to solve a specific problem in computational continuum mechanics;

utilities that perform simple pre-and post-processing tasks, mainly involving data manipulation and algebraic calculations.

OpenFOAM is divided into a set of precompiled libraries that are dynamically linked during compilation of the solvers and utilities. Libraries such as those for physical models are supplied as source code so that users may conveniently add their own models to the libraries. This chapter gives an overview of solvers, utilities and libraries, their creation, modification, compilation and execution.

3.1 The programming language of OpenFOAM

In order to understand the way in which the OpenFOAM library works, some background knowledge of C++, the base language of OpenFOAM, is required; the necessary information will be presented in this chapter. Before doing so, it is worthwhile addressing the concept of language in general terms to explain some of the ideas behind object-oriented programming and our choice of C++ as the main programming language of OpenFOAM.

3.1.1 Language in general

The success of verbal language and mathematics is based on efficiency, especially in expressing abstract concepts. For example, in fluid flow, we use the term “velocity field”, which has meaning without any reference to the nature of the flow or any specific velocity data. The term encapsulates the idea of movement with direction and magnitude and relates to other physical properties. In mathematics, we can represent velocity field by a single symbol, *e.g.* \mathbf{U} , and express certain concepts using symbols, *e.g.* “the field of velocity magnitude” by $|\mathbf{U}|$. The advantage of mathematics over verbal language is its greater efficiency, making it possible to express complex concepts with extreme clarity.

The problems that we wish to solve in continuum mechanics are not presented in terms of intrinsic entities, or types, known to a computer, *e.g.* bits, bytes, integers. They are usually presented first in verbal language, then as partial differential equations in 3 dimensions of space and time. The equations contain the following concepts: scalars, vectors, tensors, and fields thereof; tensor algebra; tensor calculus; dimensional units. The solution to these equations involves discretisation procedures, matrices, solvers, and solution algorithms.

3.1.2 Object-orientation and C++

Programming languages that are object-oriented, such as C++, provide the mechanism — *classes* — to declare types and associated operations that are part of the verbal and mathematical languages used in science and engineering. Our velocity field introduced earlier can be represented in programming code by the symbol `U` and “the field of velocity magnitude” can be `mag(U)`. The velocity is a vector field for which there should exist, in an object-oriented code, a `vectorField` class. The velocity field `U` would then be an instance, or *object*, of the `vectorField` class; hence the term object-oriented.

The clarity of having objects in programming that represent physical objects and abstract entities should not be underestimated. The class structure concentrates code development to contained regions of the code, *i.e.* the classes themselves, thereby making the code easier to manage. New classes can be derived or inherit properties from other classes, *e.g.* the `vectorField` can be derived from a `vector` class and a `Field` class. C++ provides the mechanism of *template classes* such that the template class `Field<Type>` can represent a field of any `<Type>`, *e.g.* `scalar`, `vector`, `tensor`. The general features of the template class are passed on to any class created from the template. Templating and inheritance reduce duplication of code and create class hierarchies that impose an overall structure on the code.

3.1.3 Equation representation

A central theme of the OpenFOAM design is that the solver applications, written using the OpenFOAM classes, have a syntax that closely resembles the partial differential equations being solved. For example the equation

$$\frac{\partial \rho \mathbf{U}}{\partial t} + \nabla \cdot \phi \mathbf{U} - \nabla \cdot \mu \nabla \mathbf{U} = -\nabla p$$

is represented by the code

```

solve
(
    fvm::ddt(rho, U)
  + fvm::div(phi, U)
  - fvm::laplacian(mu, U)
  ==
  - fvc::grad(p)
);

```

This and other requirements demand that the principal programming language of OpenFOAM has object-oriented features such as inheritance, template classes, virtual functions and operator overloading. These features are not available in many languages that purport

to be object-orientated but actually have very limited object-orientated capability, such as FORTRAN-90. C++, however, possesses all these features while having the additional advantage that it is widely used with a standard specification so that reliable compilers are available that produce efficient executables. It is therefore the primary language of OpenFOAM.

3.1.4 Solver codes

Solver codes are largely procedural since they are a close representation of solution algorithms and equations, which are themselves procedural in nature. Users do not need a deep knowledge of object-orientation and C++ programming to write a solver but should know the principles behind object-orientation and classes, and to have a basic knowledge of some C++ code syntax. An understanding of the underlying equations, models and solution method and algorithms is far more important.

There is often little need for a user to immerse themselves in the code of any of the OpenFOAM classes. The essence of object-orientation is that the user should not have to; merely the knowledge of the class' existence and its functionality are sufficient to use the class. A description of each class, its functions *etc.* is supplied with the OpenFOAM distribution in HTML documentation generated with Doxygen at `$WM_PROJECT_DIR/doc/Doxygen/html/index.html`.

3.2 Compiling applications and libraries

Compilation is an integral part of application development that requires careful management since every piece of code requires its own set instructions to access dependent components of the OpenFOAM library. In UNIX/Linux systems these instructions are often organised and delivered to the compiler using the standard UNIXmake utility. OpenFOAM, however, is supplied with the `wmake` compilation script that is based on `make` but is considerably more versatile and easier to use; `wmake` can, in fact, be used on any code, not simply the OpenFOAM library. To understand the compilation process, we first need to explain certain aspects of C++ and its file structure, shown schematically in Figure 3.1. A class is defined through a set of instructions such as object construction, data storage and class member functions. The file containing the class *definition* takes a `.C` extension, *e.g.* a class `nc` would be written in the file `nc.C`. This file can be compiled independently of other code into a binary executable library file known as a shared object library with the `.so` file extension, *i.e.* `nc.so`. When compiling a piece of code, say `newApp.C`, that uses the `nc` class, `nc.C` need not be recompiled, rather `newApp.C` calls `nc.so` at runtime. This is known as *dynamic linking*.

3.2.1 Header `.H` files

As a means of checking errors, the piece of code being compiled must know that the classes it uses and the operations they perform actually exist. Therefore each class requires a class *declaration*, contained in a header file with a `.H` file extension, *e.g.* `nc.H`, that includes the names of the class and its functions. This file is included at the beginning of any piece of code using the class, including the class declaration code itself. Any piece of `.C` code can resource any number of classes and must begin with all the `.H` files required to declare these classes. The classes in turn can resource other classes and begin with the relevant `.H`




Figure 3.1: Header files, source files, compilation and linking

files. By searching recursively down the class hierarchy we can produce a complete list of header files for all the classes on which the top level `.C` code ultimately depends; these `.H` files are known as the *dependencies*. With a dependency list, a compiler can check whether the source files have been updated since their last compilation and selectively compile only those that need to be.

Header files are included in the code using `# include` statements, *e.g.*

```
# include "otherHeader.H";
```

causes the compiler to suspend reading from the current file to read the file specified. Any self-contained piece of code can be put into a header file and included at the relevant location in the main code in order to improve code readability. For example, in most OpenFOAM applications the code for creating fields and reading field input data is included in a file `createFields.H` which is called at the beginning of the code. In this way, header files are not solely used as class declarations. It is `wmake` that performs the task of maintaining file dependency lists amongst other functions listed below.

- Automatic generation and maintenance of file dependency lists, *i.e.* lists of files which are included in the source files and hence on which they depend.
- Multi-platform compilation and linkage, handled through appropriate directory structure.
- Multi-language compilation and linkage, *e.g.* C, C++, Java.
- Multi-option compilation and linkage, *e.g.* debug, optimised, parallel and profiling.
- Support for source code generation programs, *e.g.* lex, yacc, IDL, MOC.
- Simple syntax for source file lists.
- Automatic creation of source file lists for new codes.

- Simple handling of multiple shared or static libraries.
- Extensible to new machine types.
- Extremely portable, works on any machine with: `make`; `sh`, `ksh` or `csh`; `lex`, `cc`.
- Has been tested on Apollo, SUN, SGI, HP (HPUX), Compaq (DEC), IBM (AIX), Cray, Ardent, Stardent, PC Linux, PPC Linux, NEC, SX4, Fujitsu VP1000.

3.2.2 Compiling with wmake

OpenFOAM applications are organised using a standard convention that the source code of each application is placed in a directory whose name is that of the application. The top level source file takes the application name with the `.C` extension. For example, the source code for an application called `newApp` would reside in a directory `newApp` and the top level file would be `newApp.C` as shown in Figure 3.2. The directory must also contain a `Make`




Figure 3.2: Directory structure for an application

subdirectory containing 2 files, `options` and `files`, that are described in the following sections.

3.2.2.1 Including headers

The compiler searches for the included header files in the following order, specified with the `-I` option in `wmake`:

1. the `$WM_PROJECT_DIR/src/OpenFOAM/InInclude` directory;
2. a local `InInclude` directory, *i.e.* `newApp/InInclude`;
3. the local directory, *i.e.* `newApp`;
4. platform dependent paths set in files in the `$WM_PROJECT_DIR/wmake/rules/$WM_ARCH/` directory, *e.g.* `/usr/X11/include` and `$(MPICH_ARCH_PATH)/include`;
5. other directories specified explicitly in the `Make/options` file with the `-I` option.

The `Make/options` file contains the full directory paths to locate header files using the syntax:

```

EXE_INC = \
    -I<directoryPath1> \
    -I<directoryPath2> \
    ... \
    -I<directoryPathN>

```

Notice first that the directory names are preceded by the `-I` flag and that the syntax uses the `\` to continue the `EXE_INC` across several lines, with no `\` after the final entry.

3.2.2.2 Linking to libraries

The compiler links to shared object library files in the following directory **paths**, specified with the `-L` option in `wmake`:

1. the `$FOAM_LIBBIN` directory;
2. platform dependent paths set in files in the `$WM_DIR/rules/$WM_ARCH/` directory, *e.g.* `/usr/X11/lib` and `$(MPICH_ARCH_PATH)/lib`;
3. other directories specified in the `Make/options` file.

The actual library **files** to be linked must be specified using the `-l` option and removing the `lib` prefix and `.so` extension from the library file name, *e.g.* `libnew.so` is included with the flag `-lnew`. By default, `wmake` loads the following libraries:

1. the `libOpenFOAM.so` library from the `$FOAM_LIBBIN` directory;
2. platform dependent libraries specified in set in files in the `$WM_DIR/rules/$WM_ARCH/` directory, *e.g.* `libm.so` from `/usr/X11/lib` and `liblam.so` from `$(LAM_ARCH_PATH)/lib`;
3. other libraries specified in the `Make/options` file.

The `Make/options` file contains the full directory paths and library names using the syntax:

```

EXE_LIBS = \
    -L<libraryPath1> \
    -L<libraryPath2> \
    ... \
    -L<libraryPathN> \
    -l<library1> \
    -l<library2> \
    ... \
    -l<libraryN>

```

Let us reiterate that the directory paths are preceded by the `-L` flag, the library names are preceded by the `-l` flag.

3.2.2.3 Source files to be compiled

The compiler requires a list of `.C` source files that must be compiled. The list must contain the main `.C` file but also any other source files that are created for the specific application but are not included in a class library. For example, users may create a new class or some new functionality to an existing class for a particular application. The full list of `.C` source files must be included in the `Make/files` file. As might be expected, for many applications the list only includes the name of the main `.C` file, *e.g.* `newApp.C` in the case of our earlier example.

The `Make/files` file also includes a full path and name of the compiled executable, specified by the `EXE =` syntax. Standard convention stipulates the name is that of the application, *i.e.* `newApp` in our example. The OpenFOAM release offers two useful choices for path: standard release applications are stored in `$FOAM_APPBIN`; applications developed by the user are stored in `$FOAM_USER_APPBIN`.

If the user is developing their own applications, we recommend they create an applications subdirectory in their `$WM_PROJECT_USER_DIR` directory containing the source code for personal OpenFOAM applications. As with standard applications, the source code for each OpenFOAM application should be stored within its own directory. The only difference between a user application and one from the standard release is that the `Make/files` file should specify that the user's executables are written into their `$FOAM_USER_APPBIN` directory. The `Make/files` file for our example would appear as follows:

```
newApp.C

EXE = $(FOAM_USER_APPBIN)/newApp
```

3.2.2.4 Running wmake

The `wmake` script is executed by typing:

```
wmake <optionalArguments> <optionalDirectory>
```

The `<optionalDirectory>` is the directory path of the application that is being compiled. Typically, `wmake` is executed from within the directory of the application being compiled, in which case `<optionalDirectory>` can be omitted.

If a user wishes to build an application executable, then no `<optionalArguments>` are required. However `<optionalArguments>` may be specified for building libraries *etc.* as described in Table 3.1.

| Argument | Type of compilation |
|--------------------|---|
| <code>lib</code> | Build a statically-linked library |
| <code>libso</code> | Build a dynamically-linked library |
| <code>libo</code> | Build a statically-linked object file library |
| <code>jar</code> | Build a JAVA archive |
| <code>exe</code> | Build an application independent of the specified project |

Table 3.1: Optional compilation arguments to `wmake`.

3.2.2.5 wmake environment variables

For information, the environment variable settings used by `wmake` are listed in Table 3.2.

| Main paths | |
|------------------------------------|---|
| <code>\$WM_PROJECT_INST_DIR</code> | Full path to installation directory, <i>e.g.</i> <code>\$HOME/OpenFOAM</code> |
| <code>\$WM_PROJECT</code> | Name of the project being compiled: <code>OpenFOAM</code> |
| <code>\$WM_PROJECT_VERSION</code> | Version of the project being compiled: <code>3.0.1</code> |
| <code>\$WM_PROJECT_DIR</code> | Full path to locate binary executables of OpenFOAM release, <i>e.g.</i> <code>\$HOME/OpenFOAM/OpenFOAM-3.0.1</code> |
| <code>\$WM_PROJECT_USER_DIR</code> | Full path to locate binary executables of the user <i>e.g.</i> <code>\$HOME/OpenFOAM/\${USER}-3.0.1</code> |
| Other paths/settings | |
| <code>\$WM_ARCH</code> | Machine architecture: <code>Linux</code> , <code>SunOS</code> |
| <code>\$WM_ARCH_OPTION</code> | 32 or 64 bit architecture |
| <code>\$WM_COMPILER</code> | Compiler being used: <code>Gcc43</code> - <code>gcc 4.5+</code> , <code>ICC</code> - <code>Intel</code> |
| <code>\$WM_COMPILER_DIR</code> | Compiler installation directory |
| <code>\$WM_COMPILER_BIN</code> | Compiler installation binaries <code>\$WM_COMPILER_BIN/bin</code> |
| <code>\$WM_COMPILER_LIB</code> | Compiler installation libraries <code>\$WM_COMPILER_BIN/lib</code> |
| <code>\$WM_COMPILE_OPTION</code> | Compilation option: <code>Debug</code> - <code>debugging</code> , <code>Opt</code> <code>optimisation</code> . |
| <code>\$WM_DIR</code> | Full path of the <code>wmake</code> directory |
| <code>\$WM_MPLIB</code> | Parallel communications library: <code>LAM</code> , <code>MPI</code> , <code>MPICH</code> , <code>PVM</code> |
| <code>\$WM_OPTIONS</code> | = <code>\$WM_ARCH\$WM_COMPILER...</code> <code>...\$WM_COMPILE_OPTION\$WM_MPLIB</code> <i>e.g.</i> <code>linuxGcc30ptMPICH</code> |
| <code>\$WM_PRECISION_OPTION</code> | Precision of the compiled binaries, <code>SP</code> , single precision or <code>DP</code> , double precision |

Table 3.2: Environment variable settings for `wmake`.

3.2.3 Removing dependency lists: `wclean` and `rmdepall`

On execution, `wmake` builds a dependency list file with a `.dep` file extension, *e.g.* `newApp.dep` in our example, and a list of files in a `Make/$WM_OPTIONS` directory. If the user wishes to remove these files, perhaps after making code changes, the user can run the `wclean` script by typing:

```
wclean <optionalArguments> <optionalDirectory>
```

Again, the `<optionalDirectory>` is a path to the directory of the application that is being compiled. Typically, `wclean` is executed from within the directory of the application, in which case the path can be omitted.

If a user wishes to remove the dependency files and files from the *Make* directory, then no `<optionalArguments>` are required. However if `lib` is specified in `<optionalArguments>` a local *InInclude* directory will be deleted also.

An additional script, `rmdepall` removes all dependency `.dep` files recursively down the directory tree from the point at which it is executed. This can be useful when updating OpenFOAM libraries.

3.2.4 Compilation example: the pisoFoam application

The source code for application `pisoFoam` is in the `$FOAM_APP/solvers/incompressible/pisoFoam` directory and the top level source file is named `pisoFoam.C`. The `pisoFoam.C` source code is:

```

1  /*-----*\
2  =====|
3  \ \      | F i e l d           | OpenFOAM: The Open Source CFD Toolbox
4  \ \      | O p e r a t i o n   |
5  \ \      | A n d               | Copyright (C) 2011-2015 OpenFOAM Foundation
6  \ \      | M a n i p u l a t i o n |
7  -----*/
8  License
9      This file is part of OpenFOAM.
10
11      OpenFOAM is free software: you can redistribute it and/or modify it
12      under the terms of the GNU General Public License as published by
13      the Free Software Foundation, either version 3 of the License, or
14      (at your option) any later version.
15
16      OpenFOAM is distributed in the hope that it will be useful, but WITHOUT
17      ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or
18      FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License
19      for more details.
20
21      You should have received a copy of the GNU General Public License
22      along with OpenFOAM. If not, see <http://www.gnu.org/licenses/>.
23
24  Application
25      pisoFoam
26
27  Description
28      Transient solver for incompressible flow.
29
30      Sub-models include:
31      - turbulence modelling, i.e. laminar, RAS or LES
32      - run-time selectable MRF and finite volume options, e.g. explicit porosity
33
34  \*-----*/
35
36  #include "fvCFD.H"
37  #include "singlePhaseTransportModel.H"
38  #include "turbulentTransportModel.H"
39  #include "pisoControl.H"
40  #include "fvIOoptionList.H"
41
42  // * * * * *
43
44  int main(int argc, char *argv[])
45  {
46      #include "setRootCase.H"
47      #include "createTime.H"
48      #include "createMesh.H"
49
50      pisoControl piso(mesh);
51
52      #include "createFields.H"
53      #include "createMRF.H"
54      #include "createFvOptions.H"
55      #include "initContinuityErrs.H"
56
57      // * * * * *
58
59      Info<< "\nStarting time loop\n" << endl;
60
61      while (runTime.loop())

```

```

62     {
63         Info<< "Time = " << runTime.timeName() << nl << endl;
64
65         #include "CourantNo.H"
66
67         // Pressure-velocity PISO corrector
68         {
69             #include "UEqn.H"
70
71             // --- PISO loop
72             while (piso.correct())
73             {
74                 #include "pEqn.H"
75             }
76         }
77
78         laminarTransport.correct();
79         turbulence->correct();
80
81         runTime.write();
82
83         Info<< "ExecutionTime = " << runTime.elapsedCpuTime() << " s"
84             << "   ClockTime = " << runTime.elapsedClockTime() << " s"
85             << nl << endl;
86     }
87
88     Info<< "End\n" << endl;
89
90     return 0;
91 }
92
93
94 // ***** //

```

The code begins with a brief description of the application contained within comments over 1 line (//) and multiple lines (/...*/). Following that, the code contains several # include statements, *e.g.* # include "fvCFD.H", which causes the compiler to suspend reading from the current file, *pisoFoam.C* to read the *fvCFD.H*.

pisoFoam resources the *incompressibleRASModels*, *incompressibleLESModels* and *incompressibleTransportModels* libraries and therefore requires the necessary header files, specified by the `EXE_INC = -I...` option, and links to the libraries with the `EXE_LIBS = -l...` option. The *Make/options* therefore contains the following:

```

1  EXE_INC = \
2      -I$(LIB_SRC)/TurbulenceModels/turbulenceModels/lnInclude \
3      -I$(LIB_SRC)/TurbulenceModels/incompressible/lnInclude \
4      -I$(LIB_SRC)/transportModels \
5      -I$(LIB_SRC)/transportModels/incompressible/singlePhaseTransportModel \
6      -I$(LIB_SRC)/finiteVolume/lnInclude \
7      -I$(LIB_SRC)/meshTools/lnInclude \
8      -I$(LIB_SRC)/fvOptions/lnInclude \
9      -I$(LIB_SRC)/sampling/lnInclude
10
11  EXE_LIBS = \
12      -lturbulenceModels \
13      -lincompressibleTurbulenceModels \
14      -lincompressibleTransportModels \
15      -lfiniteVolume \
16      -lmeshTools \
17      -lfvOptions \
18      -lsampling

```

pisoFoam contains only the *pisoFoam.C* source and the executable is written to the `$FOAM-APPBIN` directory as all standard applications are. The *Make/files* therefore contains:

```

1  pisoFoam.C
2
3  EXE = $(FOAM_APPBIN)/pisoFoam

```

Following the recommendations of section 3.2.2.3, the user can compile a separate version of *pisoFoam* into their local `$FOAM_USER_DIR` directory by the following:

- copying the `pisofFoam` source code to a local directory, e.g. `$FOAM_RUN`;

```
cd $FOAM_RUN
cp -r $FOAM_SOLVERS/incompressible/pisoFoam .
cd pisoFoam
```

- editing the `Make/files` file as follows;

```
1  pisoFoam.C
2
3  EXE = $(FOAM_USER_APPBIN)/pisoFoam
```

- executing `wmake`.

```
wmake
```

The code should compile and produce a message similar to the following

```
Making dependency list for source file pisoFoam.C

SOURCE_DIR=.
SOURCE=pisoFoam.C ;
g++ -DFOAM_EXCEPTION -Dlinux -DlinuxGccDPOpt
-DscalarMachine -DoptSolvers -DPARALLEL -DUSEMPI -Wall -O2 -DNoRepository
-ftemplate-depth-17 -I.../OpenFOAM/OpenFOAM-3.0.1/src/OpenFOAM/lnInclude
-IlnInclude
-I.
.....
-lmpich -L/usr/X11/lib -lm
-o ... platforms/bin/linuxGccDPOpt/pisoFoam
```

The user can now try recompiling and will receive a message similar to the following to say that the executable is up to date and compiling is not necessary:

```
make: Nothing to be done for `allFiles'.
make: `Make/linuxGccDPOpt/dependencies' is up to date.

make: `... platforms/linuxGccDPOpt/bin/pisoFoam'
is up to date.
```

The user can compile the application from scratch by removing the dependency list with

```
wclean
```

and running `wmake`.

3.2.5 Debug messaging and optimisation switches

OpenFOAM provides a system of messaging that is written during runtime, most of which are to help debugging problems encountered during running of a OpenFOAM case. The switches are listed in the `$WM_PROJECT_DIR/etc/controlDict` file; should the user wish to change the settings they should make a copy to their `$HOME` directory, i.e. `$HOME/.OpenFOAM/3.0.1/controlDict` file. The list of possible switches is extensive and can be

viewed by running the `foamDebugSwitches` application. Most of the switches correspond to a class or range of functionality and can be switched on by their inclusion in the `controlDict` file, and by being set to 1. For example, OpenFOAM can perform the checking of dimensional units in all calculations by setting the `dimensionSet` switch to 1. There are some switches that control messaging at a higher level than most, listed in Table 3.3.

In addition, there are some switches that control certain operational and optimisation issues. These switches are also listed in Table 3.3. Of particular importance is `fileModificationSkew`. OpenFOAM scans the write time of data files to check for modification. When running over a NFS with some disparity in the clock settings on different machines, field data files appear to be modified ahead of time. This can cause a problem if OpenFOAM views the files as newly modified and attempting to re-read this data. The `fileModificationSkew` keyword is the time in seconds that OpenFOAM will subtract from the file write time when assessing whether the file has been newly modified.

High level debugging switches - sub-dictionary *DebugSwitches*

| | |
|------------------------|---|
| <code>level</code> | Overall level of debugging messaging for OpenFOAM- - 3 levels 0, 1, 2 |
| <code>lduMatrix</code> | Messaging for solver convergence during a run - 3 levels 0, 1, 2 |

Optimisation switches - sub-dictionary *OptimisationSwitches*

| | |
|---------------------------------------|--|
| <code>fileModificationSkew</code> | A time in seconds that should be set higher than the maximum delay in NFS updates and clock difference for running OpenFOAM over a NFS. |
| <code>fileModificationChecking</code> | Method of checking whether files have been modified during a simulation, either reading the <code>timeStamp</code> or using <code>inotify</code> ; versions that read only master-node data exist, <code>timeStampMaster</code> , <code>inotifyMaster</code> . |
| <code>commsType</code> | Parallel communications type: <code>nonBlocking</code> , <code>scheduled</code> , <code>blocking</code> . |
| <code>floatTransfer</code> | If 1, will compact numbers to <code>float</code> precision before transfer; default is 0 |
| <code>nProcsSimpleSum</code> | Optimises global sum for parallel processing; sets number of processors above which hierarchical sum is performed rather than a linear sum (default 16) |

Table 3.3: Runtime message switches.

3.2.6 Linking new user-defined libraries to existing applications

The situation may arise that a user creates a new library, say `new`, and wishes the features within that library to be available across a range of applications. For example, the user may create a new boundary condition, compiled into `new`, that would need to be recognised by a range of solver applications, pre- and post-processing utilities, mesh tools, *etc.* Under normal circumstances, the user would need to recompile every application with the `new` linked to it.

Instead there is a simple mechanism to link one or more shared object libraries dynamically at run-time in OpenFOAM. Simply add the optional keyword entry `libs` to the

controlDict file for a case and enter the full names of the libraries within a list (as quoted string entries). For example, if a user wished to link the libraries `new1` and `new2` at run-time, they would simply need to add the following to the case *controlDict* file:

```
libs
(
    "libnew1.so"
    "libnew2.so"
);
```

3.3 Running applications

Each application is designed to be executed from a terminal command line, typically reading and writing a set of data files associated with a particular case. The data files for a case are stored in a directory named after the case as described in section 4.1; the directory name with full path is here given the generic name *<caseDir>*.

For any application, the form of the command line entry for any can be found by simply entering the application name at the command line with the `-help` option, *e.g.* typing

```
blockMesh -help
```

returns the usage

```
Usage: blockMesh [-region region name] [-case dir] [-blockTopology]
        [-help] [-doc] [-srcDoc]
```

The arguments in square brackets, [], are optional flags. If the application is executed from within a case directory, it will operate on that case. Alternatively, the `-case <caseDir>` option allows the case to be specified directly so that the application can be executed from anywhere in the filing system.

Like any UNIX/Linux executable, applications can be run as a background process, *i.e.* one which does not have to be completed before the user can give the shell additional commands. If the user wished to run the `blockMesh` example as a background process and output the case progress to a *log* file, they could enter:

```
blockMesh > log &
```

3.4 Running applications in parallel

This section describes how to run OpenFOAM in parallel on distributed processors. The method of parallel computing used by OpenFOAM is known as domain decomposition, in which the geometry and associated fields are broken into pieces and allocated to separate processors for solution. The process of parallel computation involves: decomposition of mesh and fields; running the application in parallel; and, post-processing the decomposed case as described in the following sections. The parallel running uses the public domain `openMPI` implementation of the standard message passing interface (MPI).

3.4.1 Decomposition of mesh and initial field data

The mesh and fields are decomposed using the `decomposePar` utility. The underlying aim is to break up the domain with minimal effort but in such a way to guarantee a fairly economic solution. The geometry and fields are broken up according to a set of parameters specified in a dictionary named `decomposeParDict` that must be located in the `system` directory of the case of interest. An example `decomposeParDict` dictionary can be copied from the `interFoam/damBreak` tutorial if the user requires one; the dictionary entries within it are reproduced below:

```

17
18  numberOfSubdomains 4;
19
20  method            simple;
21
22  simpleCoeffs
23  {
24      n                (2 2 1);
25      delta            0.001;
26  }
27
28  hierarchicalCoeffs
29  {
30      n                (1 1 1);
31      delta            0.001;
32      order            xyz;
33  }
34
35  manualCoeffs
36  {
37      dataFile         "";
38  }
39
40  distributed        no;
41
42  roots              ( );
43
44
45  // ***** //

```

The user has a choice of four methods of decomposition, specified by the `method` keyword as described below.

simple Simple geometric decomposition in which the domain is split into pieces by direction, *e.g.* 2 pieces in the x direction, 1 in y *etc.*

hierarchical Hierarchical geometric decomposition which is the same as **simple** except the user specifies the order in which the directional split is done, *e.g.* first in the y -direction, then the x -direction *etc.*

scotch Scotch decomposition which requires no geometric input from the user and attempts to minimise the number of processor boundaries. The user can specify a weighting for the decomposition between processors, through an optional `processorWeights` keyword which can be useful on machines with differing performance between processors. There is also an optional keyword entry `strategy` that controls the decomposition strategy through a complex string supplied to Scotch. For more information, see the source code file: `$FOAM_SRC/parallel/decomposescotchDecomp/scotchDecomp.C`

manual Manual decomposition, where the user directly specifies the allocation of each cell to a particular processor.

For each `method` there are a set of coefficients specified in a sub-dictionary of `decompositionDict`, named `<method>Coeffs` as shown in the dictionary listing. The full set of keyword entries in the `decomposeParDict` dictionary are explained in Table 3.4.

| Compulsory entries | | |
|--|--|---|
| numberOfSubdomains | Total number of subdomains | N |
| method | Method of decomposition | simple/ hierarchical/ scotch/ metis/ manual/ |
| simpleCoeffs entries | | |
| n | Number of subdomains in x, y, z | $(n_x \ n_y \ n_z)$ |
| delta | Cell skew factor | Typically, 10^{-3} |
| hierarchicalCoeffs entries | | |
| n | Number of subdomains in x, y, z | $(n_x \ n_y \ n_z)$ |
| delta | Cell skew factor | Typically, 10^{-3} |
| order | Order of decomposition | xyz/xzy/yzx... |
| scotchCoeffs entries | | |
| processorWeights (optional) | List of weighting factors for allocation of cells to processors; $\langle \text{wt1} \rangle$ is the weighting factor for processor 1, <i>etc.</i> ; weights are normalised so can take any range of values. | $(\langle \text{wt1} \rangle \dots \langle \text{wtN} \rangle)$ |
| strategy | Decomposition strategy: optional and complex | |
| manualCoeffs entries | | |
| dataFile | Name of file containing data of allocation of cells to processors | " $\langle \text{fileName} \rangle$ " |
| Distributed data entries (optional) — see section 3.4.3 | | |
| distributed | Is the data distributed across several disks? | yes/no |
| roots | Root paths to case directories; $\langle \text{rt1} \rangle$ is the root path for node 1, <i>etc.</i> | $(\langle \text{rt1} \rangle \dots \langle \text{rtN} \rangle)$ |

Table 3.4: Keywords in *decompositionDict* dictionary.

The `decomposePar` utility is executed in the normal manner by typing

```
decomposePar
```

On completion, a set of subdirectories will have been created, one for each processor, in the case directory. The directories are named *processorN* where $N = 0, 1, \dots$ represents a processor number and contains a time directory, containing the decomposed field descriptions, and a *constant/polyMesh* directory containing the decomposed mesh description.

3.4.2 Running a decomposed case

A decomposed OpenFOAM case is run in parallel using the `openMPI` implementation of MPI.

`openMPI` can be run on a local multiprocessor machine very simply but when running on machines across a network, a file must be created that contains the host names of the machines. The file can be given any name and located at any path. In the following description we shall refer to such a file by the generic name, including full path, `<machines>`.

The `<machines>` file contains the names of the machines listed one machine per line. The names must correspond to a fully resolved hostname in the `/etc/hosts` file of the machine on which the `openMPI` is run. The list must contain the name of the machine running the `openMPI`. Where a machine node contains more than one processor, the node name may be followed by the entry `cpu=n` where *n* is the number of processors `openMPI` should run on that node.

For example, let us imagine a user wishes to run `openMPI` from machine `aaa` on the following machines: `aaa`; `bbb`, which has 2 processors; and `ccc`. The `<machines>` would contain:

```
aaa
bbb cpu=2
ccc
```

An application is run in parallel using `mpirun`.

```
mpirun --hostfile <machines> -np <nProcs>
      <foamExec> <otherArgs> -parallel > log &
```

where: `<nProcs>` is the number of processors; `<foamExec>` is the executable, *e.g.* `icoFoam`; and, the output is redirected to a file named `log`. For example, if `icoFoam` is run on 4 nodes, specified in a file named `machines`, on the `cavity` tutorial in the `$FOAM_RUN/tutorials/incompressible/icoFoam` directory, then the following command should be executed:

```
mpirun --hostfile machines -np 4 icoFoam -parallel > log &
```

3.4.3 Distributing data across several disks

Data files may need to be distributed if, for example, if only local disks are used in order to improve performance. In this case, the user may find that the root path to the case directory may differ between machines. The paths must then be specified in the `decomposeParDict` dictionary using `distributed` and `roots` keywords. The `distributed` entry should read

```
distributed yes;
```

and the `roots` entry is a list of root paths, `<root0>`, `<root1>`, ..., for each node

```
roots
<nRoots>
(
```

```

    "<root0>"
    "<root1>"
    ...
);

```

where `<nRoots>` is the number of roots.

Each of the *processorN* directories should be placed in the case directory at each of the root paths specified in the *decomposeParDict* dictionary. The *system* directory and *files* within the *constant* directory must also be present in each case directory. Note: the files in the *constant* directory are needed, but the *polyMesh* directory is not.

3.4.4 Post-processing parallel processed cases

When post-processing cases that have been run in parallel the user has two options:

- reconstruction of the mesh and field data to recreate the complete domain and fields, which can be post-processed as normal;
- post-processing each segment of decomposed domain individually.

3.4.4.1 Reconstructing mesh and data

After a case has been run in parallel, it can be reconstructed for post-processing. The case is reconstructed by merging the sets of time directories from each *processorN* directory into a single set of time directories. The *reconstructPar* utility performs such a reconstruction by executing the command:

```
reconstructPar
```

When the data is distributed across several disks, it must be first copied to the local case directory for reconstruction.

3.4.4.2 Post-processing decomposed cases

The user may post-process decomposed cases using the *paraFoam* post-processor, described in section 6.1. The whole simulation can be post-processed by reconstructing the case or alternatively it is possible to post-process a segment of the decomposed domain individually by simply treating the individual processor directory as a case in its own right.

3.5 Standard solvers

The solvers with the OpenFOAM distribution are in the *\$FOAM_SOLVERS* directory, reached quickly by typing *sol* at the command line. This directory is further subdivided into several directories by category of continuum mechanics, *e.g.* incompressible flow, combustion and solid body stress analysis. Each solver is given a name that is reasonably descriptive, *e.g.* *icoFoam* solves incompressible, laminar flow. The current list of solvers distributed with OpenFOAM is given in Table 3.5.

‘Basic’ CFD codes

| | |
|---------------------|---|
| laplacianFoam | Solves a simple Laplace equation, e.g. for thermal diffusion in a solid |
| potentialFoam | Potential flow solver which solves for the velocity potential from which the flux-field is obtained and velocity field by reconstructing the flux |
| scalarTransportFoam | Solves a transport equation for a passive scalar |

Incompressible flow

| | |
|------------------------------|--|
| adjointShapeOptimizationFoam | Steady-state solver for incompressible, turbulent flow of non-Newtonian fluids with optimisation of duct shape by applying "blockage" in regions causing pressure loss as estimated using an adjoint formulation |
| boundaryFoam | Steady-state solver for incompressible, 1D turbulent flow, typically to generate boundary layer conditions at an inlet, for use in a simulation |
| icoFoam | Transient solver for incompressible, laminar flow of Newtonian fluids |
| nonNewtonianIcoFoam | Transient solver for incompressible, laminar flow of non-Newtonian fluids |
| pimpleFoam | Large time-step transient solver for incompressible, flow using the PIMPLE (merged PISO-SIMPLE) algorithm |
| pisoFoam | Transient solver for incompressible flow |
| shallowWaterFoam | Transient solver for inviscid shallow-water equations with rotation |
| simpleFoam | Steady-state solver for incompressible, turbulent flow |

Compressible flow

| | |
|---------------------|---|
| rhoCentralDyMFoam | Density-based compressible flow solver based on central-upwind schemes of Kurganov and Tadmor with moving mesh capability and turbulence modelling |
| rhoCentralFoam | Density-based compressible flow solver based on central-upwind schemes of Kurganov and Tadmor |
| rhoPimpleFoam | Transient solver for laminar or turbulent flow of compressible fluids for HVAC and similar applications |
| rhoPorousSimpleFoam | Steady-state solver for turbulent flow of compressible fluids with RANS turbulence modelling, implicit or explicit porosity treatment and run-time selectable finite volume sources |
| rhoSimplecFoam | Steady-state SIMPLEC solver for laminar or turbulent RANS flow of compressible fluids |
| rhoSimpleFoam | Steady-state SIMPLE solver for laminar or turbulent RANS flow of compressible fluids |
| sonicDyMFoam | Transient solver for trans-sonic/supersonic, laminar or turbulent flow of a compressible gas with mesh motion |

Continued on next page

Continued from previous page

| | |
|-----------------|--|
| sonicFoam | Transient solver for trans-sonic/supersonic, laminar or turbulent flow of a compressible gas |
| sonicLiquidFoam | Transient solver for trans-sonic/supersonic, laminar flow of a compressible liquid |

Multiphase flow

| | |
|---------------------------------|--|
| cavitatingDyMFoam | Transient cavitation code based on the homogeneous equilibrium model from which the compressibility of the liquid/vapour "mixture" is obtained, with optional mesh motion and mesh topology changes including adaptive re-meshing |
| cavitatingFoam | Transient cavitation code based on the homogeneous equilibrium model from which the compressibility of the liquid/vapour "mixture" is obtained |
| compressibleInterDyMFoam | Solver for 2 compressible, non-isothermal immiscible fluids using a VOF (volume of fluid) phase-fraction based interface capturing approach, with optional mesh motion and mesh topology changes including adaptive re-meshing |
| compressibleInterFoam | Solver for 2 compressible, non-isothermal immiscible fluids using a VOF (volume of fluid) phase-fraction based interface capturing approach |
| compressibleMultiphaseInterFoam | Solver for n compressible, non-isothermal immiscible fluids using a VOF (volume of fluid) phase-fraction based interface capturing approach |
| driftFluxFoam | Solver for 2 incompressible fluids using the mixture approach with the drift-flux approximation for relative motion of the phases |
| interFoam | Solver for 2 incompressible, isothermal immiscible fluids using a VOF (volume of fluid) phase-fraction based interface capturing approach |
| interMixingFoam | Solver for 3 incompressible fluids, two of which are miscible, using a VOF method to capture the interface |
| interPhaseChangeFoam | Solver for 2 incompressible, isothermal immiscible fluids with phase-change (e.g. cavitation). Uses a VOF (volume of fluid) phase-fraction based interface capturing approach |
| interPhaseChangeDyMFoam | Solver for 2 incompressible, isothermal immiscible fluids with phase-change (e.g. cavitation). Uses a VOF (volume of fluid) phase-fraction based interface capturing approach, with optional mesh motion and mesh topology changes including adaptive re-meshing |
| multiphaseEulerFoam | Solver for a system of many compressible fluid phases including heat-transfer |
| multiphaseInterFoam | Solver for n incompressible fluids which captures the interfaces and includes surface-tension and contact-angle effects for each phase |
| potentialFreeSurfaceFoam | Incompressible Navier-Stokes solver with inclusion of a wave height field to enable single-phase free-surface approximations |

Continued on next page

Continued from previous page

| | |
|---------------------|---|
| reactingEulerFoam | (Description not found) |
| twoLiquidMixingFoam | Solver for mixing 2 incompressible fluids |
| twoPhaseEulerFoam | Solver for a system of 2 compressible fluid phases with one phase dispersed, e.g. gas bubbles in a liquid including heat-transfer |

Direct numerical simulation (DNS)

| | |
|---------|--|
| dnsFoam | Direct numerical simulation solver for boxes of isotropic turbulence |
|---------|--|

Combustion

| | |
|------------------------|---|
| chemFoam | Solver for chemistry problems - designed for use on single cell cases to provide comparison against other chemistry solvers - single cell mesh created on-the-fly - fields created on the fly from the initial conditions |
| coldEngineFoam | Solver for cold-flow in internal combustion engines |
| engineFoam | Solver for internal combustion engines |
| fireFoam | Transient Solver for Fires and turbulent diffusion flames |
| PDRFoam | Solver for compressible premixed/partially-premixed combustion with turbulence modelling |
| reactingFoam | Solver for combustion with chemical reactions |
| rhoReactingBuoyantFoam | Solver for combustion with chemical reactions using density based thermodynamics package, using enhanced buoyancy treatment |
| rhoReactingFoam | Solver for combustion with chemical reactions using density based thermodynamics package |
| XiFoam | Solver for compressible premixed/partially-premixed combustion with turbulence modelling |

Heat transfer and buoyancy-driven flows

| | |
|-----------------------------|---|
| buoyantBoussinesqPimpleFoam | Transient solver for buoyant, turbulent flow of incompressible fluids |
| buoyantBoussinesqSimpleFoam | Steady-state solver for buoyant, turbulent flow of incompressible fluids |
| buoyantPimpleFoam | Transient solver for buoyant, turbulent flow of compressible fluids for ventilation and heat-transfer |
| buoyantSimpleFoam | Steady-state solver for buoyant, turbulent flow of compressible fluids, including radiation, for ventilation and heat-transfer |
| chtMultiRegionFoam | Combination of <code>heatConductionFoam</code> and <code>buoyantFoam</code> for conjugate heat transfer between a solid region and fluid region |
| chtMultiRegionSimpleFoam | Steady-state version of <code>chtMultiRegionFoam</code> |
| thermoFoam | Evolves the thermodynamics on a frozen flow field |

Continued on next page

Continued from previous page

Particle-tracking flows

| | |
|---------------------------------|---|
| coalChemistryFoam | Transient solver for: - compressible, - turbulent flow, with - coal and limestone parcel injections, - energy source, and - combustion |
| DPMFoam | Transient solver for the coupled transport of a single kinematic particle cloud including the effect of the volume fraction of particles on the continuous phase |
| icoUncoupledKinematicParcelFoam | Transient solver for the passive transport of a single kinematic particle cloud |
| reactingParcelFilmFoam | Transient PIMPLE solver for compressible, laminar or turbulent flow with reacting Lagrangian parcels, and surface film modelling |
| reactingParcelFoam | Transient PIMPLE solver for compressible, laminar or turbulent flow with reacting multiphase Lagrangian parcels, including run-time selectable finite volume options, e.g. sources, constraints |
| sprayFoam | Transient PIMPLE solver for compressible, laminar or turbulent flow with spray parcels |
| uncoupledKinematicParcelFoam | Transient solver for the passive transport of a single kinematic particle cloud |

Molecular dynamics methods

| | |
|---------------------|--|
| mdEquilibrationFoam | Equilibrates and/or preconditions molecular dynamics systems |
| mdFoam | Molecular dynamics solver for fluid dynamics |

Direct simulation Monte Carlo methods

| | |
|----------|--|
| dsmcFoam | Direct simulation Monte Carlo (DSMC) solver for 3D, transient, multi-species flows |
|----------|--|

Electromagnetics

| | |
|-------------------|---|
| electrostaticFoam | Solver for electrostatics |
| magneticFoam | Solver for the magnetic field generated by permanent magnets |
| mhdFoam | Solver for magnetohydrodynamics (MHD): incompressible, laminar flow of a conducting fluid under the influence of a magnetic field |

Stress analysis of solids

| | |
|----------------------------------|--|
| solidDisplacementFoam | Transient segregated finite-volume solver of linear-elastic, small-strain deformation of a solid body, with optional thermal diffusion and thermal stresses |
| solidEquilibriumDisplacementFoam | Steady-state segregated finite-volume solver of linear-elastic, small-strain deformation of a solid body, with optional thermal diffusion and thermal stresses |

Continued on next page

Continued from previous page

Finance

| | |
|---------------|--|
| financialFoam | Solves the Black-Scholes equation to price commodities |
|---------------|--|

Table 3.5: Standard library solvers.

3.6 Standard utilities

The utilities with the OpenFOAM distribution are in the `$FOAM_UTILITIES` directory, reached quickly by typing `util` at the command line. Again the names are reasonably descriptive, *e.g.* `ideasToFoam` converts mesh data from the format written by I-DEAS to the OpenFOAM format. The current list of utilities distributed with OpenFOAM is given in Table 3.6.

Pre-processing

| | |
|---|---|
| <code>applyBoundaryLayer</code> | Apply a simplified boundary-layer model to the velocity and turbulence fields based on the 1/7th power-law |
| <code>applyWallFunction-BoundaryConditions</code> | Updates OpenFOAM RAS cases to use the new (v1.6) wall function framework |
| <code>boxTurb</code> | Makes a box of turbulence which conforms to a given energy spectrum and is divergence free |
| <code>changeDictionary</code> | Utility to change dictionary entries, <i>e.g.</i> can be used to change the patch type in the field and polyMesh/boundary files |
| <code>createExternalCoupled-PatchGeometry</code> | Application to generate the patch geometry (points and faces) for use with the <code>externalCoupled</code> boundary condition |
| <code>dsmcInitialise</code> | Initialise a case for <code>dsmcFoam</code> by reading the initialisation dictionary <code>system/dsmcInitialise</code> |
| <code>engineSwirl</code> | Generates a swirling flow for engine calculations |
| <code>faceAgglomerate</code> | Agglomerate boundary faces for use with the view factor radiation model. Writes a map from the fine to the coarse grid. |
| <code>foamUpgradeCyclics</code> | Tool to upgrade mesh and fields for split cyclics |
| <code>foamUpgradeFvSolution</code> | Simple tool to upgrade the syntax of <code>system/fvSolution::solvers</code> |
| <code>mapFields</code> | Maps volume fields from one mesh to another, reading and interpolating all fields present in the time directory of both cases. Parallel and non-parallel cases are handled without the need to reconstruct them first |
| <code>mapFieldsPar</code> | Maps volume fields from one mesh to another, reading and interpolating all fields present in the time directory of both cases |
| <code>mdInitialise</code> | Initialises fields for a molecular dynamics (MD) simulation |
| <code>setFields</code> | Set values on a selected set of cells/patchfaces through a dictionary |
| <code>viewFactorsGen</code> | Calculates view factors based on agglomerated faces (<code>faceAgglomerat</code>) for view factor radiation model. |
| <code>wallFunctionTable</code> | Generates a table suitable for use by tabulated wall functions |

Continued on next page

Continued from previous page

Mesh generation

| | |
|-----------------------------|--|
| blockMesh | A multi-block mesh generator |
| extrudeMesh | Extrude mesh from existing patch (by default outwards facing normals; optional flips faces) or from patch read from file. |
| extrude2DMesh | Takes 2D mesh (all faces 2 points only, no front and back faces) and creates a 3D mesh by extruding with specified thickness |
| extrudeToRegionMesh | Extrude faceZones into separate mesh (as a different region), e.g. for creating liquid film regions |
| foamyHexMesh | Conformal Voronoi automatic mesh generator |
| foamyHexMeshBackgroundMesh | Writes out background mesh as constructed by foamyHexMesh and constructs distanceSurface |
| foamyHexMeshSurfaceSimplify | Simplifies surfaces by resampling |
| foamyQuadMesh | Conformal-Voronoi 2D extruding automatic mesher |
| snappyHexMesh | Automatic split hex mesher. Refines and snaps to surface |

Mesh conversion

| | |
|---------------------|--|
| ansysToFoam | Converts an ANSYS input mesh file, exported from I-DEAS, to OpenFOAM format |
| cfx4ToFoam | Converts a CFX 4 mesh to OpenFOAM format |
| datToFoam | Reads in a datToFoam mesh file and outputs a points file. Used in conjunction with blockMesh |
| fluent3DMeshToFoam | Converts a Fluent mesh to OpenFOAM format |
| fluentMeshToFoam | Converts a Fluent mesh to OpenFOAM format including multiple region and region boundary handling |
| foamMeshToFluent | Writes out the OpenFOAM mesh in Fluent mesh format |
| foamToStarMesh | Reads an OpenFOAM mesh and writes a PROSTAR (v4) bnd/cel/vrt format |
| foamToSurface | Reads an OpenFOAM mesh and writes the boundaries in a surface format |
| gambitToFoam | Converts a GAMBIT mesh to OpenFOAM format |
| gmshToFoam | Reads .msh file as written by Gmsh |
| ideasUnvToFoam | I-Deas unv format mesh conversion |
| kivaToFoam | Converts a KIVA grid to OpenFOAM format |
| mshToFoam | Converts .msh file generated by the Adventure system |
| netgenNeutralToFoam | Converts neutral file format as written by Netgen v4.4 |
| plot3dToFoam | Plot3d mesh (ascii/formatted format) converter |
| sammToFoam | Converts a STAR-CD (v3) SAMM mesh to OpenFOAM format |
| star3ToFoam | Converts a STAR-CD (v3) PROSTAR mesh into OpenFOAM format |
| star4ToFoam | Converts a STAR-CD (v4) PROSTAR mesh into OpenFOAM format |
| tetgenToFoam | Converts .ele and .node and .face files, written by tetgen |

Continued on next page

Continued from previous page

`vtkUnstructuredToFoam` Converts ascii `.vtk` (legacy format) file generated by `vtk/paraview`

`writeMeshObj` For mesh debugging: writes mesh as three separate OBJ files which can be viewed with e.g. `javaview`

Mesh manipulation

`attachMesh` Attach topologically detached mesh using prescribed mesh modifiers

`autoPatch` Divides external faces into patches based on (user supplied) feature angle

`checkMesh` Checks validity of a mesh

`createBaffles` Makes internal faces into boundary faces. Does not duplicate points, unlike `mergeOrSplitBaffles`

`createPatch` Utility to create patches out of selected boundary faces. Faces come either from existing patches or from a `faceSet`

`deformedGeom` Deforms a `polyMesh` using a displacement field U and a scaling factor supplied as an argument

`flattenMesh` Flattens the front and back planes of a 2D cartesian mesh

`insideCells` Picks up cells with cell centre 'inside' of surface. Requires surface to be closed and singly connected

`mergeMeshes` Merges two meshes

`mergeOrSplitBaffles` Detects faces that share points (baffles). Either merge them or duplicate the points

`mirrorMesh` Mirrors a mesh around a given plane

`moveDynamicMesh` Mesh motion and topological mesh changes utility

`moveEngineMesh` Solver for moving meshes for engine calculations

`moveMesh` Solver for moving meshes

`objToVTK` Read obj line (not surface!) file and convert into `vtk`

`orientFaceZone` Corrects orientation of `faceZone`

`polyDualMesh` Calculates the dual of a `polyMesh`. Adheres to all the feature and patch edges

`refineMesh` Utility to refine cells in multiple directions

`renumberMesh` Renumbers the cell list in order to reduce the bandwidth, reading and renumbering all fields from all the time directories

`rotateMesh` Rotates the mesh and fields from the direction n_1 to direction n_2

`setSet` Manipulate a cell/face/point/ set or zone interactively

`setsToZones` Add `pointZones/faceZones/cellZones` to the mesh from similar named `pointSets/faceSets/cellSets`

`singleCellMesh` Reads all fields and maps them to a mesh with all internal faces removed (`singleCellFvMesh`) which gets written to region "singleCell"

`splitMesh` Splits mesh by making internal faces external. Uses `attachDetach`

`splitMeshRegions` Splits mesh into multiple regions

`stitchMesh` 'Stitches' a mesh

Continued on next page

Continued from previous page

| | |
|-----------------|--|
| subsetMesh | Selects a section of mesh based on a <code>cellSet</code> |
| topoSet | Operates on <code>cellSets</code> / <code>faceSets</code> / <code>pointSets</code> through a dictionary |
| transformPoints | Transforms the mesh points in the <code>polyMesh</code> directory according to the <code>translate</code> , <code>rotate</code> and <code>scale</code> options |
| zipUpMesh | Reads in a mesh with hanging vertices and zips up the cells to guarantee that all polyhedral cells of valid shape are closed |

Other mesh tools

| | |
|-------------------|--|
| autoRefineMesh | Utility to refine cells near to a surface |
| collapseEdges | Collapses short edges and combines edges that are in line |
| combinePatchFaces | Checks for multiple patch faces on same cell and combines them. Multiple patch faces can result from e.g. removal of refined neighbouring cells, leaving 4 exposed faces with same owner |
| modifyMesh | Manipulates mesh elements |
| PDRMesh | Mesh and field preparation utility for PDR type simulations |
| refineHexMesh | Refines a hex mesh by 2x2x2 cell splitting |
| refinementLevel | Tries to figure out what the refinement level is on refined cartesian meshes. Run <i>before</i> snapping |
| refineWallLayer | Utility to refine cells next to patches |
| removeFaces | Utility to remove faces (combines cells on both sides) |
| selectCells | Select cells in relation to surface |
| splitCells | Utility to split cells with flat faces |

Post-processing graphics

| | |
|-------------------|--|
| ensightFoamReader | <code>EnSight</code> library module to read OpenFOAM data directly without translation |
|-------------------|--|

Post-processing data converters

| | |
|-------------------|---|
| foamDataToFluent | Translates OpenFOAM data to <code>Fluent</code> format |
| foamToEnight | Translates OpenFOAM data to <code>EnSight</code> format |
| foamToEnightParts | Translates OpenFOAM data to <code>EnSight</code> format. An <code>EnSight</code> part is created for each <code>cellZone</code> and patch |
| foamToGMV | Translates foam output to <code>GMV</code> readable files |
| foamToTecplot360 | <code>Tecplot</code> binary file format writer |
| foamToTetDualMesh | Converts <code>polyMesh</code> results to <code>tetDualMesh</code> |
| foamToVTK | Legacy <code>VTK</code> file format writer |
| smapToFoam | Translates a <code>STAR-CD</code> <code>SMAP</code> data file into OpenFOAM field format |

Post-processing velocity fields

| | |
|-----------|--|
| Co | Calculates and writes the Courant number obtained from field <code>phi</code> as a <code>volScalarField</code> . |
| enstrophy | Calculates and writes the enstrophy of the velocity field <code>U</code> |
| flowType | Calculates and writes the <code>flowType</code> of velocity field <code>U</code> |

Continued on next page

Continued from previous page

| | |
|----------------|--|
| Lambda2 | Calculates and writes the second largest eigenvalue of the sum of the square of the symmetrical and anti-symmetrical parts of the velocity gradient tensor |
| Mach | Calculates and optionally writes the local Mach number from the velocity field U at each time |
| Pe | Calculates the Peclet number Pe from the flux phi and writes the maximum value, the surfaceScalarField Pef and volScalarField Pe |
| Q | Calculates and writes the second invariant of the velocity gradient tensor |
| streamFunction | Calculates and writes the stream function of velocity field U at each time |
| uprime | Calculates and writes the scalar field of uprime ($\sqrt{2k/3}$) |
| vorticity | Calculates and writes the vorticity of velocity field U |

Post-processing stress fields

| | |
|------------------|---|
| stressComponents | Calculates and writes the scalar fields of the six components of the stress tensor sigma for each time |
|------------------|---|

Post-processing scalar fields

| | |
|---------|---|
| pPrime2 | Calculates and writes the scalar field of pPrime2 ($[p - \bar{p}]^2$) at each time |
|---------|---|

Post-processing at walls

| | |
|-----------------|---|
| wallGradU | Calculates and writes the gradient of U at the wall |
| wallHeatFlux | Calculates and writes the heat flux for all patches as the boundary field of a volScalarField and also prints the integrated flux for all wall patches |
| wallShearStress | Calculates and reports the turbulent wall shear stress for all patches, for the specified times |
| yPlus | Calculates and reports yPlus for the near-wall cells of all wall patches, for the specified times for laminar, LES and RAS |

Post-processing turbulence

| | |
|------------------------|--|
| createTurbulenceFields | Creates a full set of turbulence fields |
| R | Calculates and writes the Reynolds stress R for the current time step |

Post-processing patch data

| | |
|----------------|---|
| patchAverage | Calculates the average of the specified field over the specified patch |
| patchIntegrate | Calculates the integral of the specified field over the specified patch |

Post-processing Lagrangian simulation

Continued on next page

Continued from previous page

| | |
|----------------------|---|
| particleTracks | Generates a VTK file of particle tracks for cases that were computed using a tracked-parcel-type cloud |
| steadyParticleTracks | Generates a VTK file of particle tracks for cases that were computed using a steady-state cloud NOTE: case must be re-constructed (if running in parallel) before use |

Sampling post-processing

| | |
|----------------|--|
| probeLocations | Probe locations |
| sample | Sample field data with a choice of interpolation schemes, sampling options and write formats |

Miscellaneous post-processing

| | |
|-------------------------|---|
| dsmcFieldsCalc | Calculate intensive fields (U and T) from averaged extensive fields from a DSMC calculation |
| engineCompRatio | Calculate the geometric compression ratio. Note that if you have valves and/or extra volumes it will not work, since it calculates the volume at BDC and TCD |
| execFlowFunctionObjects | Execute the set of functionObjects specified in the selected dictionary (which defaults to <i>system/controlDict</i>) for the selected set of times. Alternative dictionaries should be placed in the <i>system/</i> directory |
| foamListTimes | List times using timeSelector |
| pdfPlot | Generates a graph of a probability distribution function |
| postChannel | Post-processes data from channel flow calculations |
| ptot | For each time: calculate the total pressure |
| temporalInterpolate | Interpolate fields between time-steps e.g. for animation |
| wdot | Calculates and writes wdot for each time |
| writeCellCentres | Write the three components of the cell centres as volScalarFields so they can be used in postprocessing in thresholding |

Surface mesh (e.g. STL) tools

| | |
|------------------------|--|
| surfaceAdd | Add two surfaces. Does geometric merge on points. Does not check for overlapping/intersecting triangles |
| surfaceAutoPatch | Patches surface according to feature angle. Like autoPatch |
| surfaceBooleanFeatures | Generates the extendedFeatureEdgeMesh for the interface between a boolean operation on two surfaces |
| surfaceCheck | Checking geometric and topological quality of a surface |
| surfaceClean | - removes baffles - collapses small edges, removing triangles. - converts sliver triangles into split edges by projecting point onto base of triangle |
| surfaceCoarsen | Surface coarsening using 'bunnylod'. |
| surfaceConvert | Converts from one surface mesh format to another |
| surfaceFeatureConvert | Convert between edgeMesh formats |
| surfaceFeatureExtract | Extracts and writes surface features to file |
| surfaceFind | Finds nearest face and vertex |
| surfaceHookUp | Find close open edges and stitches the surface along them |

Continued on next page

Continued from previous page

| | |
|----------------------------|---|
| surfaceInertia | Calculates the inertia tensor, principal axes and moments of a command line specified triSurface. Inertia can either be of the solid body or of a thin shell |
| surfaceLambdaMu-Smooth | Smooths a surface using lambda/mu smoothing. To get laplacian smoothing (previous surfaceSmooth behavior), set lambda to the relaxation factor and mu to zero |
| surfaceMeshConvert | Converts between surface formats with optional scaling or transformations (rotate/translate) on a coordinateSystem |
| surfaceMeshConvert-Testing | Converts from one surface mesh format to another, but primarily used for testing functionality |
| surfaceMeshExport | Export from surfMesh to various third-party surface formats with optional scaling or transformations (rotate/translate) on a coordinateSystem |
| surfaceMeshImport | Import from various third-party surface formats into surfMesh with optional scaling or transformations (rotate/translate) on a coordinateSystem |
| surfaceMeshInfo | Miscellaneous information about surface meshes |
| surfaceMeshTriangulate | Extracts triSurface from a polyMesh. Depending on output surface format triangulates faces. Region numbers on triangles are the patch numbers of the polyMesh. Optionally only triangulates named patches |
| surfaceOrient | Set normal consistent with respect to a user provided 'outside' point. If the -inside is used the point is considered inside. |
| surfacePointMerge | Merges points on surface if they are within absolute distance. Since absolute distance use with care! |
| surfaceRedistributePar | (Re)distribution of triSurface. Either takes an undecomposed surface or an already decomposed surface and redistributes it so that each processor has all triangles that overlap its mesh. |
| surfaceRefineRedGreen | Refine by splitting all three edges of triangle ('red' refinement). Neighbouring triangles (which are not marked for refinement get split in half ('green' refinement). (R. Verfuert, "A review of a posteriori error estimation and adaptive mesh refinement techniques", Wiley-Teubner, 1996) |
| surfaceSplitByPatch | Writes regions of triSurface to separate files |
| surfaceSplitByTopology | Strips any baffle parts of a surface |
| surfaceSplitNonManifolds | Takes multiply connected surface and tries to split surface at multiply connected edges by duplicating points. Introduces concept of - borderEdge. Edge with 4 faces connected to it. - borderPoint. Point connected to exactly 2 borderEdges. - borderLine. Connected list of borderEdges |
| surfaceSubset | A surface analysis tool which sub-sets the triSurface to choose only a part of interest. Based on subsetMesh |
| surfaceToPatch | Reads surface and applies surface regioning to a mesh. Uses boundaryMesh to do the hard work |
| surfaceTransformPoints | Transform (scale/rotate) a surface. Like transformPoints but for surfaces |

Continued on next page

Continued from previous page

Parallel processing

| | |
|--------------------|--|
| decomposePar | Automatically decomposes a mesh and fields of a case for parallel execution of OpenFOAM |
| reconstructPar | Reconstructs fields of a case that is decomposed for parallel execution of OpenFOAM |
| reconstructParMesh | Reconstructs a mesh using geometric information only |
| redistributePar | Redistributes existing decomposed mesh and fields according to the current settings in the decomposeParDict file |

Thermophysical-related utilities

| | |
|------------------------|--|
| adiabaticFlameT | Calculates the adiabatic flame temperature for a given fuel over a range of unburnt temperatures and equivalence ratios |
| chemkinToFoam | Converts CHEMKIN 3 thermodynamics and reaction data files into OpenFOAM format |
| equilibriumCO | Calculates the equilibrium level of carbon monoxide |
| equilibriumFlameT | Calculates the equilibrium flame temperature for a given fuel and pressure for a range of unburnt gas temperatures and equivalence ratios; the effects of dissociation on O ₂ , H ₂ O and CO ₂ are included |
| mixtureAdiabaticFlameT | Calculates the adiabatic flame temperature for a given mixture at a given temperature |

Miscellaneous utilities

| | |
|-------------------|---|
| expandDictionary | Read the dictionary provided as an argument, expand the macros etc. and write the resulting dictionary to standard output |
| foamDebugSwitches | Write out all library debug switches |
| foamFormatConvert | Converts all IObj _{ects} associated with a case into the format specified in the <i>controlDict</i> |
| foamHelp | Top level wrapper utility around foam help utilities |
| foamInfoExec | Interrogates a case and prints information to stdout |
| patchSummary | Writes fields and boundary condition info for each patch at each requested time instance |

Table 3.6: Standard library utilities.

3.7 Standard libraries

The libraries with the OpenFOAM distribution are in the *\$FOAM_LIB/\$WMM_OPTIONS* directory, reached quickly by typing `lib` at the command line. Again, the names are prefixed by `lib` and reasonably descriptive, *e.g.* `incompressibleTransportModels` contains the library of incompressible transport models. For ease of presentation, the libraries are separated into two types:

General libraries those that provide general classes and associated functions listed in Table 3.7;

Model libraries those that specify models used in computational continuum mechanics, listed in Table 3.8, Table 3.9 and Table 3.10.

Library of basic OpenFOAM tools — OpenFOAM

| | |
|------------------|--|
| algorithms | Algorithms |
| containers | Container classes |
| db | Database classes |
| dimensionedTypes | dimensioned<Type> class and derivatives |
| dimensionSet | dimensionSet class |
| fields | Field classes |
| global | Global settings |
| graph | graph class |
| interpolations | Interpolation schemes |
| matrices | Matrix classes |
| memory | Memory management tools |
| meshes | Mesh classes |
| primitives | Primitive classes |

Finite volume method library — finiteVolume

| | |
|---------------|---|
| cfdTools | CFD tools |
| fields | Volume, surface and patch field classes; includes boundary conditions |
| finiteVolume | Finite volume discretisation |
| fvMatrices | Matrices for finite volume solution |
| fvMesh | Meshes for finite volume discretisation |
| interpolation | Field interpolation and mapping |
| surfaceMesh | Mesh surface data for finite volume discretisation |
| volMesh | Mesh volume (cell) data for finite volume discretisation |

Post-processing libraries

| | |
|----------------------|---|
| cloudFunctionObjects | Function object outputs Lagrangian cloud information to a file |
| fieldFunctionObjects | Field function objects including field averaging, min/max, <i>etc.</i> |
| foamCalcFunctions | Functions for the foamCalc utility |
| forces | Tools for post-processing force/lift/drag data with function objects |
| FVFunctionObjects | Tools for calculating fvcDiv , fvcGrad etc with a function object |
| jobControl | Tools for controlling job running with a function object |
| postCalc | For using functionality of a function object as a post-processing activity |
| sampling | Tools for sampling field data at prescribed locations in a domain |

Continued on next page

Continued from previous page

| | |
|------------------------|--|
| systemCall | General function object for making system calls while running a case |
| utilityFunctionObjects | Utility function objects |

Solution and mesh manipulation libraries

| | |
|-------------------|--|
| autoMesh | Library of functionality for the <code>snappyHexMesh</code> utility |
| blockMesh | Library of functionality for the <code>blockMesh</code> utility |
| dynamicMesh | For solving systems with moving meshes |
| dynamicFvMesh | Library for a finite volume mesh that can move and undergo topological changes |
| edgeMesh | For handling edge-based mesh descriptions |
| fvMotionSolvers | Finite volume mesh motion solvers |
| ODE | Solvers for ordinary differential equations |
| meshTools | Tools for handling a OpenFOAM mesh |
| surfMesh | Library for handling surface meshes of different formats |
| triSurface | For handling standard triangulated surface-based mesh descriptions |
| topoChangerFvMesh | Topological changes functionality (largely redundant) |

Lagrangian particle tracking libraries

| | |
|------------------------|--|
| coalCombustion | Coal dust combustion modelling |
| distributionModels | Particle distribution function modelling |
| dsmc | Direct simulation Monte Carlo method modelling |
| lagrangian | Basic Lagrangian, or particle-tracking, solution scheme |
| lagrangianIntermediate | Particle-tracking kinematics, thermodynamics, multispecies reactions, particle forces, <i>etc.</i> |
| potential | Intermolecular potentials for molecular dynamics |
| molecule | Molecule classes for molecular dynamics |
| molecularMeasurements | For making measurements in molecular dynamics |
| solidParticle | Solid particle implementation |
| spray | Spray and injection modelling |
| turbulence | Particle dispersion and Brownian motion based on turbulence |

Miscellaneous libraries

| | |
|----------------------------|--|
| conversion | Tools for mesh and data conversions |
| decompositionMethods | Tools for domain decomposition |
| engine | Tools for engine calculations |
| fileFormats | Core routines for reading/writing data in some third-party formats |
| genericFvPatchField | A generic patch field |
| MGridGenGAMG-Agglomeration | Library for cell agglomeration using the MGridGen algorithm |
| pairPatchAgglomeration | Primitive pair patch agglomeration method |
| OSspecific | Operating system specific functions |
| randomProcesses | Tools for analysing and generating random processes |

Continued on next page

Continued from previous page

Parallel libraries

| | |
|---------------|--|
| decompose | General mesh/field decomposition library |
| distributed | Tools for searching and IO on distributed surfaces |
| metisDecomp | Metis domain decomposition library |
| reconstruct | Mesh/field reconstruction library |
| scotchDecomp | Scotch domain decomposition library |
| ptsotchDecomp | PTScotch domain decomposition library |

Table 3.7: Shared object libraries for general use.

Basic thermophysical models — basicThermophysicalModels

| | |
|-------------|--|
| hePsiThermo | General thermophysical model calculation based on compressibility ψ |
| heRhoThermo | General thermophysical model calculation based on density ρ |
| pureMixture | General thermophysical model calculation for passive gas mixtures |

Reaction models — reactionThermophysicalModels

| | |
|----------------------------|--|
| psiReactionThermo | Calculates enthalpy for combustion mixture based on ψ |
| psiuReactionThermo | Calculates enthalpy for combustion mixture based on ψ_u |
| rhoReactionThermo | Calculates enthalpy for combustion mixture based on ρ |
| heheuPsiThermo | Calculates enthalpy for unburnt gas and combustion mixture |
| homogeneousMixture | Combustion mixture based on normalised fuel mass fraction b |
| inhomogeneousMixture | Combustion mixture based on b and total fuel mass fraction f_t |
| veryInhomogeneousMixture | Combustion mixture based on b , f_t and unburnt fuel mass fraction f_u |
| basicMultiComponentMixture | Basic mixture based on multiple components |
| multiComponentMixture | Derived mixture based on multiple components |
| reactingMixture | Combustion mixture using thermodynamics and reaction schemes |
| egrMixture | Exhaust gas recirculation mixture |
| singleStepReactingMixture | Single step reacting mixture |

Radiation models — radiationModels

Continued on next page

Continued from previous page

| | |
|-------------|--|
| P1 | P1 model |
| fvDOM | Finite volume discrete ordinate method |
| opaqueSolid | Radiation for solid opaque solids; does nothing to energy equation source terms (returns zeros) but creates absorptionEmissionModel and scatterModel |
| viewFactor | View factor radiation model |

Laminar flame speed models — laminarFlameSpeedModels

| | |
|-------------------------------|---|
| constant | Constant laminar flame speed |
| GuldersLaminarFlameSpeed | Gulder's laminar flame speed model |
| GuldersEGR Laminar-FlameSpeed | Gulder's laminar flame speed model with exhaust gas recirculation modelling |
| RaviPetersen | Laminar flame speed obtained from Ravi and Petersen's correlation |

Barotropic compressibility models — barotropicCompressibilityModels

| | |
|--------|------------------------------|
| linear | Linear compressibility model |
| Chung | Chung compressibility model |
| Wallis | Wallis compressibility model |

Thermophysical properties of gaseous species — specie

| | |
|--------------------------|--|
| adiabaticPerfectFluid | Adiabatic perfect gas equation of state |
| icoPolynomial | Incompressible polynomial equation of state, <i>e.g.</i> for liquids |
| perfectFluid | Perfect gas equation of state |
| incompressiblePerfectGas | Incompressible gas equation of state using a constant reference pressure. Density only varies with temperature and composition |
| rhoConst | Constant density equation of state |
| eConstThermo | Constant specific heat c_p model with evaluation of internal energy e and entropy s |
| hConstThermo | Constant specific heat c_p model with evaluation of enthalpy h and entropy s |
| hPolynomialThermo | c_p evaluated by a function with coefficients from polynomials, from which h , s are evaluated |
| janafThermo | c_p evaluated by a function with coefficients from JANAF thermodynamic tables, from which h , s are evaluated |
| specieThermo | Thermophysical properties of species, derived from c_p , h and/or s |
| constTransport | Constant transport properties |
| polynomialTransport | Polynomial based temperature-dependent transport properties |
| sutherlandTransport | Sutherland's formula for temperature-dependent transport properties |

Functions/tables of thermophysical properties — thermophysicalFunctions

Continued on next page

Continued from previous page

| | |
|----------------|--|
| NSRDSfunctions | National Standard Reference Data System (NSRDS) - American Institute of Chemical Engineers (AIChE) data compilation tables |
| APIfunctions | American Petroleum Institute (API) function for vapour mass diffusivity |

Chemistry model — chemistryModel

| | |
|-----------------|--------------------------|
| chemistryModel | Chemical reaction model |
| chemistrySolver | Chemical reaction solver |

Other libraries

| | |
|-------------------------|---|
| liquidProperties | Thermophysical properties of liquids |
| liquidMixtureProperties | Thermophysical properties of liquid mixtures |
| basicSolidThermo | Thermophysical models of solids |
| hExponentialThermo | Exponential properties thermodynamics package templated into the <code>equationOfState</code> |
| SLGThermo | Thermodynamic package for solids, liquids and gases |
| solidChemistryModel | Thermodynamic model of solid chemistry including pyrolysis |
| solidProperties | Thermophysical properties of solids |
| solidMixtureProperties | Thermophysical properties of solid mixtures |
| solidSpecie | Solid reaction rates and transport models |
| solidThermo | Solid energy modelling |

Table 3.8: Libraries of thermophysical models.

RAS turbulence models for incompressible fluids — incompressibleRASModels

| | |
|---------------------|--|
| laminar | Dummy turbulence model for laminar flow |
| kEpsilon | Standard high- Re $k - \epsilon$ model |
| kOmega | Standard high- Re $k - \omega$ model |
| kOmegaSST | $k - \omega$ -SST model |
| RNGkEpsilon | RNG $k - \epsilon$ model |
| NonlinearKEShih | Non-linear Shih $k - \epsilon$ model |
| LienCubicKE | Lien cubic $k - \epsilon$ model |
| qZeta | $q - \zeta$ model |
| kkLOmega | Low Reynolds-number k- ω -omega turbulence model for incompressible flows |
| LaunderSharmaKE | Launder-Sharma low- Re $k - \epsilon$ model |
| LamBremhorstKE | Lam-Bremhorst low- Re $k - \epsilon$ model |
| LienCubicKELowRe | Lien cubic low- Re $k - \epsilon$ model |
| LienLeschzinerLowRe | Lien-Leschziner low- Re $k - \epsilon$ model |
| LRR | Launder-Reece-Rodi RSTM |
| LaunderGibsonRSTM | Launder-Gibson RSTM with wall-reflection terms |
| realizableKE | Realizable $k - \epsilon$ model |
| SpalartAllmaras | Spalart-Allmaras 1-eqn mixing-length model |

Continued on next page

Continued from previous page

v2f Lien and Kalitzin's v2-f turbulence model for incompressible flows

RAS turbulence models for compressible fluids — compressibleRASModels

| | |
|-------------------|--|
| laminar | Dummy turbulence model for laminar flow |
| kEpsilon | Standard $k - \varepsilon$ model |
| kOmegaSST | $k - \omega - SST$ model |
| RNGkEpsilon | RNG $k - \varepsilon$ model |
| LaunderSharmaKE | Launder-Sharma low- Re $k - \varepsilon$ model |
| LRR | Launder-Reece-Rodi RSTM |
| LaunderGibsonRSTM | Launder-Gibson RSTM |
| realizableKE | Realizable $k - \varepsilon$ model |
| SpalartAllmaras | Spalart-Allmaras 1-eqn mixing-length model |
| v2f | Lien and Kalitzin's v2-f turbulence model for incompressible flows |

Large-eddy simulation (LES) filters — LESfilters

| | |
|-------------------|--------------------|
| laplaceFilter | Laplace filters |
| simpleFilter | Simple filter |
| anisotropicFilter | Anisotropic filter |

Large-eddy simulation deltas — LESdeltas

| | |
|------------------|--|
| PrandtlDelta | Prandtl delta |
| cubeRootVolDelta | Cube root of cell volume delta |
| maxDeltaxyz | Maximum of x, y and z; for structured hex cells only |
| smoothDelta | Smoothing of delta |

Incompressible LES turbulence models — incompressibleLESModels

| | |
|--------------------------|--|
| Smagorinsky | Smagorinsky model |
| Smagorinsky2 | Smagorinsky model with 3-D filter |
| homogenousDynSmagorinsky | Homogeneous dynamic Smagorinsky model |
| dynLagrangian | Lagrangian two equation eddy-viscosity model |
| scaleSimilarity | Scale similarity model |
| mixedSmagorinsky | Mixed Smagorinsky/scale similarity model |
| homogenousDynOneEqEddy | One Equation Eddy Viscosity Model for incompressible flows |
| laminar | Simply returns laminar properties |
| kOmegaSSTSAS | $k - \omega$ -SST scale adaptive simulation (SAS) model |
| oneEqEddy | k -equation eddy-viscosity model |
| dynOneEqEddy | Dynamic k -equation eddy-viscosity model |
| spectEddyVisc | Spectral eddy viscosity model |
| LRDDiffStress | LRR differential stress model |
| DeardorffDiffStress | Deardorff differential stress model |
| SpalartAllmaras | Spalart-Allmaras model |

Continued on next page

Continued from previous page

| | |
|----------------------|---|
| SpalartAllmarasDDES | Spalart-Allmaras delayed detached eddy simulation (DDES) model |
| SpalartAllmarasIDDES | Spalart-Allmaras improved DDES (IDDES) model |
| vanDriestDelta | Simple cube-root of cell volume delta used in incompressible LES models |

Compressible LES turbulence models — compressibleLESModels

| | |
|------------------------|---|
| Smagorinsky | Smagorinsky model |
| oneEqEddy | k -equation eddy-viscosity model |
| lowReOneEqEddy | Low- Re k -equation eddy-viscosity model |
| homogenousDynOneEqEddy | One Equation Eddy Viscosity Model for incompressible flows |
| DeardorffDiffStress | Deardorff differential stress model |
| SpalartAllmaras | Spalart-Allmaras 1-eqn mixing-length model |
| vanDriestDelta | Simple cube-root of cell volume delta used in incompressible LES models |

Table 3.9: Libraries of RAS and LES turbulence models.

Transport models for incompressible fluids — incompressibleTransportModels

| | |
|---------------------|--|
| Newtonian | Linear viscous fluid model |
| CrossPowerLaw | Cross Power law nonlinear viscous model |
| BirdCarreau | Bird-Carreau nonlinear viscous model |
| HerschelBulkley | Herschel-Bulkley nonlinear viscous model |
| powerLaw | Power-law nonlinear viscous model |
| interfaceProperties | Models for the interface, <i>e.g.</i> contact angle, in multiphase simulations |

Miscellaneous transport modelling libraries

| | |
|---------------------|--|
| interfaceProperties | Calculation of interface properties |
| twoPhaseProperties | Two phase properties models, including boundary conditions |
| surfaceFilmModels | Surface film models |

Table 3.10: Shared object libraries of transport models.

Chapter 4

OpenFOAM cases

This chapter deals with the file structure and organisation of OpenFOAM cases. Normally, a user would assign a name to a case, *e.g.* the tutorial case of flow in a cavity is simply named `cavity`. This name becomes the name of a directory in which all the case files and subdirectories are stored. The case directories themselves can be located anywhere but we recommend they are within a `run` subdirectory of the user's project directory, *i.e.* `$HOME/OpenFOAM/${USER}-3.0.1` as described at the beginning of chapter 2. One advantage of this is that the `$FOAM_RUN` environment variable is set to `$HOME/OpenFOAM/${USER}-3.0.1/run` by default; the user can quickly move to that directory by executing a preset alias, `run`, at the command line.

The tutorial cases that accompany the OpenFOAM distribution provide useful examples of the case directory structures. The tutorials are located in the `$FOAM_TUTORIALS` directory, reached quickly by executing the `tut` alias at the command line. Users can view tutorial examples at their leisure while reading this chapter.

4.1 File structure of OpenFOAM cases

The basic directory structure for a OpenFOAM case, that contains the minimum set of files required to run an application, is shown in Figure 4.1 and described as follows:

A *constant* directory that contains a full description of the case mesh in a subdirectory `polyMesh` and files specifying physical properties for the application concerned, *e.g.* `transportProperties`.

A *system* directory for setting parameters associated with the solution procedure itself. It contains *at least* the following 3 files: `controlDict` where run control parameters are set including start/end time, time step and parameters for data output; `fvSchemes` where discretisation schemes used in the solution may be selected at run-time; and, `fvSolution` where the equation solvers, tolerances and other algorithm controls are set for the run.

The ‘time’ directories containing individual files of data for particular fields. The data can be: either, initial values and boundary conditions that the user must specify to define the problem; or, results written to file by OpenFOAM. Note that the OpenFOAM fields must always be initialised, even when the solution does not strictly require it, as in steady-state problems. The name of each time directory is based on the simulated




Figure 4.1: Case directory structure

time at which the data is written and is described fully in section 4.3. It is sufficient to say now that since we usually start our simulations at time $t = 0$, the initial conditions are usually stored in a directory named 0 or $0.000000e+00$, depending on the name format specified. For example, in the `cavity` tutorial, the velocity field \mathbf{U} and pressure field p are initialised from files $0/U$ and $0/p$ respectively.

4.2 Basic input/output file format

OpenFOAM needs to read a range of data structures such as strings, scalars, vectors, tensors, lists and fields. The input/output (I/O) format of files is designed to be extremely flexible to enable the user to modify the I/O in OpenFOAM applications as easily as possible. The I/O follows a simple set of rules that make the files extremely easy to understand, in contrast to many software packages whose file format may not only be difficult to understand intuitively but also not be published anywhere. The OpenFOAM file format is described in the following sections.

4.2.1 General syntax rules

The format follows some general principles of C++ source code.

- Files have free form, with no particular meaning assigned to any column and no need to indicate continuation across lines.
- Lines have no particular meaning except to a `//` comment delimiter which makes OpenFOAM ignore any text that follows it until the end of line.
- A comment over multiple lines is done by enclosing the text between `/*` and `*/` delimiters.

4.2.2 Dictionaries

OpenFOAM uses *dictionaries* as the most common means of specifying data. A dictionary is an entity that contains data entries that can be retrieved by the I/O by means of *keywords*. The keyword entries follow the general format

```
<keyword> <dataEntry1> ... <dataEntryN>;
```

Most entries are single data entries of the form:

```
<keyword> <dataEntry>;
```

Most OpenFOAM data files are themselves dictionaries containing a set of keyword entries. Dictionaries provide the means for organising entries into logical categories and can be specified hierarchically so that any dictionary can itself contain one or more dictionary entries. The format for a dictionary is to specify the dictionary name followed by keyword entries enclosed in curly braces `{}` as follows

```
<dictionaryName>
{
    ... keyword entries ...
}
```

4.2.3 The data file header

All data files that are read and written by OpenFOAM begin with a dictionary named `FoamFile` containing a standard set of keyword entries, listed in Table 4.1. The table

| Keyword | Description | Entry |
|-----------------------|---|--|
| <code>version</code> | I/O format version | 2.0 |
| <code>format</code> | Data format | ascii / binary |
| <code>location</code> | Path to the file, in "..." | (optional) |
| <code>class</code> | OpenFOAM class constructed from the data file concerned | typically dictionary or a field, <i>e.g.</i> <code>volVectorField</code> |
| <code>object</code> | Filename | <i>e.g.</i> <code>controlDict</code> |

Table 4.1: Header keywords entries for data files.

provides brief descriptions of each entry, which is probably sufficient for most entries with the notable exception of `class`. The `class` entry is the name of the C++ class in the OpenFOAM library that will be constructed from the data in the file. Without knowledge of the underlying code which calls the file to be read, and knowledge of the OpenFOAM classes, the user will probably be unable to surmise the `class` entry correctly. However, most data files with simple keyword entries are read into an internal `dictionary` class and therefore the `class` entry is `dictionary` in those cases.

The following example shows the use of keywords to provide data for a case using the types of entry described so far. The extract, from an *fvSolution* dictionary file, contains 2 dictionaries, *solvers* and *PISO*. The *solvers* dictionary contains multiple data entries for

solver and tolerances for each of the pressure and velocity equations, represented by the p and U keywords respectively; the *PISO* dictionary contains algorithm controls.

```

17
18 solvers
19 {
20     p
21     {
22         solver          PCG;
23         preconditioner  DIC;
24         tolerance       1e-06;
25         relTol          0;
26     }
27
28     U
29     {
30         solver          smoothSolver;
31         smoother        symGaussSeidel;
32         tolerance       1e-05;
33         relTol          0;
34     }
35 }
36
37 PISO
38 {
39     nCorrectors          2;
40     nNonOrthogonalCorrectors 0;
41     pRefCell             0;
42     pRefValue            0;
43 }
44
45 // ***** //
46

```

4.2.4 Lists

OpenFOAM applications contain lists, *e.g.* a list of vertex coordinates for a mesh description. Lists are commonly found in I/O and have a format of their own in which the entries are contained within round braces (). There is also a choice of format preceding the round braces:

simple the keyword is followed immediately by round braces

```

<listName>
(
    ... entries ...
);

```

numbered the keyword is followed by the number of elements <n> in the list

```

<listName>
<n>
(
    ... entries ...
);

```

token identifier the keyword is followed by a class name identifier `Label<Type>` where <Type> states what the list contains, *e.g.* for a list of scalar elements is

```

<listName>
List<scalar>

```

```

    <n>          // optional
    (
        ... entries ...
    );

```

Note that `<scalar>` in `List<scalar>` is not a generic name but the actual text that should be entered.

The simple format is a convenient way of writing a list. The other formats allow the code to read the data faster since the size of the list can be allocated to memory in advance of reading the data. The simple format is therefore preferred for short lists, where read time is minimal, and the other formats are preferred for long lists.

4.2.5 Scalars, vectors and tensors

A scalar is a single number represented as such in a data file. A vector is a `VectorSpace` of rank 1 and dimension 3, and since the number of elements is always fixed to 3, the simple List format is used. Therefore a vector (1.0, 1.1, 1.2) is written:

```
(1.0 1.1 1.2)
```

In OpenFOAM, a tensor is a `VectorSpace` of rank 2 and dimension 3 and therefore the data entries are always fixed to 9 real numbers. Therefore the identity tensor can be written:

```
(
    1 0 0
    0 1 0
    0 0 1
)
```

This example demonstrates the way in which OpenFOAM ignores the line return is so that the entry can be written over multiple lines. It is treated no differently to listing the numbers on a single line:

```
( 1 0 0 0 1 0 0 0 1 )
```

4.2.6 Dimensional units

In continuum mechanics, properties are represented in some chosen units, *e.g.* mass in kilograms (kg), volume in cubic metres (m³), pressure in Pascals (kg m⁻¹ s⁻²). Algebraic operations must be performed on these properties using consistent units of measurement; in particular, addition, subtraction and equality are only physically meaningful for properties of the same dimensional units. As a safeguard against implementing a meaningless operation, OpenFOAM attaches dimensions to field data and physical properties and performs dimension checking on any tensor operation.

The I/O format for a `dimensionSet` is 7 scalars delimited by square brackets, *e.g.*

```
[0 2 -1 0 0 0 0]
```

| No. | Property | SI unit | USCS unit |
|-----|--------------------|---------------|----------------------|
| 1 | Mass | kilogram (kg) | pound-mass (lbm) |
| 2 | Length | metre (m) | foot (ft) |
| 3 | Time | — — — — | second (s) — — — — |
| 4 | Temperature | Kelvin (K) | degree Rankine (°R) |
| 5 | Quantity | — — — — | mole (mol) — — — — |
| 6 | Current | — — — — | ampere (A) — — — — |
| 7 | Luminous intensity | — — — — | candela (cd) — — — — |

Table 4.2: Base units for SI and USCS

where each of the values corresponds to the power of each of the base units of measurement listed in Table 4.2. The table gives the base units for the *Système International* (SI) and the *United States Customary System* (USCS) but OpenFOAM can be used with any system of units. All that is required is that the *input data is correct for the chosen set of units*. It is particularly important to recognise that OpenFOAM requires some dimensioned physical constants, *e.g.* the Universal Gas Constant R , for certain calculations, *e.g.* thermophysical modelling. These dimensioned constants are specified in a *DimensionedConstant* sub-dictionary of main *controlDict* file of the OpenFOAM installation ($\$WM_PROJECT_DIR/etc/controlDict$). By default these constants are set in SI units. Those wishing to use the USCS or any other system of units should modify these constants to their chosen set of units accordingly.

4.2.7 Dimensioned types

Physical properties are typically specified with their associated dimensions. These entries have the format that the following example of a `dimensionedScalar` demonstrates:

```
nu          nu  [0 2 -1 0 0 0 0]  1;
```

The first `nu` is the keyword; the second `nu` is the word name stored in class `word`, usually chosen to be the same as the keyword; the next entry is the `dimensionSet` and the final entry is the `scalar` value.

4.2.8 Fields

Much of the I/O data in OpenFOAM are tensor fields, *e.g.* velocity, pressure data, that are read from and written into the time directories. OpenFOAM writes field data using keyword entries as described in Table 4.3.

| Keyword | Description | Example |
|----------------------------|-------------------------|-----------------------------------|
| <code>dimensions</code> | Dimensions of field | <code>[1 1 -2 0 0 0 0]</code> |
| <code>internalField</code> | Value of internal field | <code>uniform (1 0 0)</code> |
| <code>boundaryField</code> | Boundary field | see file listing in section 4.2.8 |

Table 4.3: Main keywords used in field dictionaries.

The data begins with an entry for its `dimensions`. Following that, is the `internalField`, described in one of the following ways.

Uniform field a single value is assigned to all elements within the field, taking the form:

```
internalField uniform <entry>;
```

Nonuniform field each field element is assigned a unique value from a list, taking the following form where the token identifier form of list is recommended:

```
internalField nonuniform <List>;
```

The `boundaryField` is a dictionary containing a set of entries whose names correspond to each of the names of the boundary patches listed in the *boundary* file in the *polyMesh* directory. Each patch entry is itself a dictionary containing a list of keyword entries. The compulsory entry, `type`, describes the patch field condition specified for the field. The remaining entries correspond to the type of patch field condition selected and can typically include field data specifying initial conditions on patch faces. A selection of patch field conditions available in OpenFOAM are listed in Table 5.3 and Table 5.4 with a description and the data that must be specified with it. Example field dictionary entries for velocity `U` are shown below:

```

17  dimensions      [0 1 -1 0 0 0];
18
19  internalField   uniform (0 0 0);
20
21  boundaryField
22  {
23      movingWall
24      {
25          type      fixedValue;
26          value     uniform (1 0 0);
27      }
28
29      fixedWalls
30      {
31          type      fixedValue;
32          value     uniform (0 0 0);
33      }
34
35      frontAndBack
36      {
37          type      empty;
38      }
39  }
40
41  // ***** //
```

4.2.9 Directives and macro substitutions

There is additional file syntax that offers great flexibility for the setting up of OpenFOAM case files, namely directives and macro substitutions. Directives are commands that can be contained within case files that begin with the hash (`#`) symbol. Macro substitutions begin with the dollar (`$`) symbol.

At present there are 4 directive commands available in OpenFOAM:

```
#include "<fileName>" (or #includeIfPresent "<fileName>" reads the file of name
<fileName>;
```

```
#inputMode has two options: merge, which merges keyword entries in successive dictio-
naries, so that a keyword entry specified in one place will be overridden by a later
specification of the same keyword entry; overwrite, which overwrites the contents of
an entire dictionary; generally, use merge;
```

`#remove <keywordEntry>` removes any included keyword entry; can take a word or regular expression;

`#codeStream` followed by verbatim C++ code, compiles, loads and executes the code on-the-fly to generate the entry.

4.2.10 The `#include` and `#inputMode` directives

For example, let us say a user wishes to set an initial value of pressure once to be used as the internal field and initial value at a boundary. We could create a file, *e.g.* named *initialConditions*, which contains the following entries:

```
pressure 1e+05;


```

In order to use this pressure for both the internal and initial boundary fields, the user would simply include the following macro substitutions in the pressure field file *p*:

```
#include "initialConditions"
internalField uniform $pressure;
boundaryField
{
    patch1
    {
        type fixedValue;
        value $internalField;
    }
}
```

This is a fairly trivial example that simply demonstrates how this functionality works. However, the functionality can be used in many, more powerful ways particularly as a means of generalising case data to suit the user's needs. For example, if a user has a set of cases that require the same turbulence model settings, a single file can be created with those settings which is simply included in the *turbulenceProperties* file of each case. Macro substitutions can extend well beyond a single value so that, for example, sets of boundary conditions can be predefined and called by a single macro. The extent to which such functionality can be used is almost endless.

4.2.11 The `#codeStream` directive

The `#codeStream` directive takes C++ code which is compiled and executed to deliver the dictionary entry. The code and compilation instructions are specified through the following keywords.

- `code`: specifies the code, called with arguments `OStream& os` and `const dictionary& dict` which the user can use in the code, *e.g.* to lookup keyword entries from within the current case dictionary (file).

- `codeInclude` (optional): specifies additional C++ `#include` statements to include OpenFOAM files.
- `codeOptions` (optional): specifies any extra compilation flags to be added to `EXE_INC` in `Make/options`.
- `codeLibs` (optional): specifies any extra compilation flags to be added to `LIB_LIBS` in `Make/options`.

Code, like any string, can be written across multiple lines by enclosing it within hash-bracket delimiters, *i.e.* `#{...#}`. Anything in between these two delimiters becomes a string with all newlines, quotes, *etc.* preserved.

An example of `#codeStream` is given below. The code in the `controlDict` file looks up dictionary entries and does a simple calculation for the write interval:

```

startTime      0;
endTime        100;
...
writeInterval  #codeStream
{
    code
    #{
        scalar start = readScalar(dict.lookup("startTime"));
        scalar end   = readScalar(dict.lookup("endTime"));
        label nDumps = 5;
        os << ((end - start)/nDumps);
    #};
};

```

4.3 Time and data input/output control

The OpenFOAM solvers begin all runs by setting up a database. The database controls I/O and, since output of data is usually requested at intervals of time during the run, time is an inextricable part of the database. The `controlDict` dictionary sets input parameters *essential* for the creation of the database. The keyword entries in `controlDict` are listed in Table 4.4. Only the time control and `writeInterval` entries are truly compulsory, with the database taking default values indicated by † in Table 4.4 for any of the optional entries that are omitted.

Time control

| | |
|---------------------------|---|
| <code>startFrom</code> | Controls the start time of the simulation. |
| - <code>firstTime</code> | Earliest time step from the set of time directories. |
| - <code>startTime</code> | Time specified by the <code>startTime</code> keyword entry. |
| - <code>latestTime</code> | Most recent time step from the set of time directories. |
| <code>startTime</code> | Start time for the simulation with <code>startFrom startTime</code> ; |
| <code>stopAt</code> | Controls the end time of the simulation. |
| - <code>endTime</code> | Time specified by the <code>endTime</code> keyword entry. |
| - <code>writeNow</code> | Stops simulation on completion of current time step and writes data. |

Continued on next page

Continued from previous page

| | |
|--------------|---|
| - noWriteNow | Stops simulation on completion of current time step and does not write out data. |
| - nextWrite | Stops simulation on completion of next scheduled write time, specified by <code>writeControl</code> . |
| endTime | End time for the simulation when <code>stopAt endTime</code> ; is specified. |
| deltaT | Time step of the simulation. |

Data writing

| | |
|---------------------|--|
| writeControl | Controls the timing of write output to file. |
| - timeStep† | Writes data every <code>writeInterval</code> time steps. |
| - runTime | Writes data every <code>writeInterval</code> seconds of simulated time. |
| - adjustableRunTime | Writes data every <code>writeInterval</code> seconds of simulated time, adjusting the time steps to coincide with the <code>writeInterval</code> if necessary — used in cases with automatic time step adjustment. |
| - cpuTime | Writes data every <code>writeInterval</code> seconds of CPU time. |
| - clockTime | Writes data out every <code>writeInterval</code> seconds of real time. |
| writeInterval | Scalar used in conjunction with <code>writeControl</code> described above. |
| purgeWrite | Integer representing a limit on the number of time directories that are stored by overwriting time directories on a cyclic basis. Example of $t_0 = 5\text{s}$, $\Delta t = 1\text{s}$ and <code>purgeWrite 2</code> ;: data written into 2 directories, 6 and 7 , before returning to write the data at 8 s in 6 , data at 9 s into 7 , <i>etc.</i> <i>To disable the time directory limit, specify <code>purgeWrite 0</code>;†</i> For steady-state solutions, results from previous iterations can be continuously overwritten by specifying <code>purgeWrite 1</code> ; |
| writeFormat | Specifies the format of the data files. |
| - ascii† | ASCII format, written to <code>writePrecision</code> significant figures. |
| - binary | Binary format. |
| writePrecision | Integer used in conjunction with <code>writeFormat</code> described above, 6^\dagger by default |
| writeCompression | Specifies the compression of the data files. |
| - uncompressed | No compression.† |
| - compressed | gzip compression. |
| timeFormat | Choice of format of the naming of the time directories. |
| - fixed | $\pm m.d\text{d}\text{d}\text{d}\text{d}$ where the number of <i>ds</i> is set by <code>timePrecision</code> . |
| - scientific | $\pm m.d\text{d}\text{d}\text{d}\text{d}e\pm xx$ where the number of <i>ds</i> is set by <code>timePrecision</code> . |
| - general† | Specifies <code>scientific</code> format if the exponent is less than -4 or greater than or equal to that specified by <code>timePrecision</code> . |

Continued on next page

Continued from previous page

| | |
|----------------------------|--|
| <code>timePrecision</code> | Integer used in conjunction with <code>timeFormat</code> described above, 6† by default |
| <code>graphFormat</code> | Format for graph data written by an application. |
| - <code>raw</code> † | Raw ASCII format in columns. |
| - <code>gnuplot</code> | Data in <code>gnuplot</code> format. |
| - <code>xmgr</code> | Data in <code>Grace/xmgr</code> format. |
| - <code>jplot</code> | Data in <code>jPlot</code> format. |

Adjustable time step

| | |
|-----------------------------|---|
| <code>adjustTimeStep</code> | <code>yes</code> †/no switch for OpenFOAM to adjust the time step during the simulation, usually according to... |
| <code>maxCo</code> | Maximum Courant number, <i>e.g.</i> 0.5 |

Data reading

| | |
|--------------------------------|---|
| <code>runTimeModifiable</code> | <code>yes</code> †/no switch for whether dictionaries, <i>e.g.</i> <code>controlDict</code> , are re- read by OpenFOAM at the beginning of each time step. |
|--------------------------------|---|

Run-time loadable functionality

| | |
|------------------------|---|
| <code>libs</code> | List of additional libraries (on <code>\$LD_LIBRARY_PATH</code>) to be loaded at run-time, <i>e.g.</i> (<code>"libUser1.so" "libUser2.so"</code>) |
| <code>functions</code> | List of functions, <i>e.g.</i> <code>probes</code> to be loaded at run-time; see examples in <code>\$FOAM_TUTORIALS</code> |

† denotes default entry if associated keyword is omitted.

Table 4.4: Keyword entries in the *controlDict* dictionary.

Example entries from a *controlDict* dictionary are given below:

```

17 application      icoFoam;
18
19 startFrom        startTime;
20
21 startTime        0;
22
23 stopAt           endTime;
24
25 endTime          0.5;
26
27 deltaT           0.005;
28
29 writeControl     timeStep;
30
31 writeInterval    20;
32
33 purgeWrite       0;
34
35 writeFormat      ascii;
36
37 writePrecision   6;
38
39 writeCompression off;
40
41 timeFormat       general;
42

```

```

43
44   timePrecision    6;
45
46   runtimeModifiable true;
47
48   // *****
49

```

4.4 Numerical schemes

The *fvSchemes* dictionary in the *system* directory sets the numerical schemes for terms, such as derivatives in equations, that appear in applications being run. This section describes how to specify the schemes in the *fvSchemes* dictionary.

The terms that must typically be assigned a numerical scheme in *fvSchemes* range from derivatives, *e.g.* gradient ∇ , and interpolations of values from one set of points to another. The aim in OpenFOAM is to offer an unrestricted choice to the user. For example, while linear interpolation is effective in many cases, OpenFOAM offers complete freedom to choose from a wide selection of interpolation schemes for all interpolation terms.

The derivative terms further exemplify this freedom of choice. The user first has a choice of discretisation practice where standard Gaussian finite volume integration is the common choice. Gaussian integration is based on summing values on cell faces, which must be interpolated from cell centres. The user again has a completely free choice of interpolation scheme, with certain schemes being specifically designed for particular derivative terms, especially the convection divergence $\nabla \cdot$ terms.

The set of terms, for which numerical schemes must be specified, are subdivided within the *fvSchemes* dictionary into the categories listed in Table 4.5. Each keyword in Table 4.5 is the name of a sub-dictionary which contains terms of a particular type, *e.g.* *gradSchemes* contains all the gradient derivative terms such as *grad(p)* (which represents ∇p). Further examples can be seen in the extract from an *fvSchemes* dictionary below:

| Keyword | Category of mathematical terms |
|-----------------------------|--|
| <i>interpolationSchemes</i> | Point-to-point interpolations of values |
| <i>snGradSchemes</i> | Component of gradient normal to a cell face |
| <i>gradSchemes</i> | Gradient ∇ |
| <i>divSchemes</i> | Divergence $\nabla \cdot$ |
| <i>laplacianSchemes</i> | Laplacian ∇^2 |
| <i>timeScheme</i> | First and second time derivatives $\partial/\partial t, \partial^2/\partial^2 t$ |
| <i>fluxRequired</i> | Fields which require the generation of a flux |

Table 4.5: Main keywords used in *fvSchemes*.

```

17
18   ddtSchemes
19   {
20     default      Euler;
21   }
22
23   gradSchemes
24   {
25     default      Gauss linear;
26     grad(p)      Gauss linear;
27   }
28
29   divSchemes

```

```

30 {
31     default          none;
32     div(phi,U)      Gauss linear;
33 }
34
35 laplacianSchemes
36 {
37     default          Gauss linear orthogonal;
38 }
39
40 interpolationSchemes
41 {
42     default          linear;
43 }
44
45 snGradSchemes
46 {
47     default          orthogonal;
48 }
49
50 // *****
51 // ***** //

```

The example shows that the *fvSchemes* dictionary contains the following:

- 6... *Schemes* subdictionaries containing keyword entries for each term specified within including: a **default** entry; other entries whose names correspond to a **word** identifier for the particular term specified, *e.g.* `grad(p)` for ∇p
- a *fluxRequired* sub-dictionary containing fields for which the flux is generated in the application, *e.g.* `p` in the example.

If a **default** scheme is specified in a particular ... *Schemes* sub-dictionary, it is assigned to all of the terms to which the sub-dictionary refers, *e.g.* specifying a **default** in *gradSchemes* sets the scheme for all gradient terms in the application, *e.g.* ∇p , $\nabla \mathbf{U}$. When a **default** is specified, it is not necessary to specify each specific term itself in that sub-dictionary, *i.e.* the entries for `grad(p)`, `grad(U)` in this example. However, if any of these terms are included, the specified scheme overrides the **default** scheme for that term.

Alternatively the user may insist on no **default** scheme by the **none** entry. In this instance the user is obliged to specify all terms in that sub-dictionary individually. Setting **default** to **none** may appear superfluous since **default** can be overridden. However, specifying **none** forces the user to specify all terms individually which can be useful to remind the user which terms are actually present in the application.

The following sections describe the choice of schemes for each of the categories of terms in Table 4.5.

4.4.1 Interpolation schemes

The *interpolationSchemes* sub-dictionary contains terms that are interpolations of values typically from cell centres to face centres. A *selection* of interpolation schemes in OpenFOAM are listed in Table 4.6, being divided into 4 categories: 1 category of general schemes; and, 3 categories of schemes used primarily in conjunction with Gaussian discretisation of convection (divergence) terms in fluid flow, described in section 4.4.5. It is *highly unlikely* that the user would adopt any of the convection-specific schemes for general field interpolations in the *interpolationSchemes* sub-dictionary, but, as valid interpolation schemes, they are described here rather than in section 4.4.5. Note that additional schemes such as **UMIST** are available in OpenFOAM but only those schemes that are generally recommended are listed in Table 4.6.

A general scheme is simply specified by quoting the keyword and entry, *e.g.* a `linear` scheme is specified as `default` by:

```
default linear;
```

The convection-specific schemes calculate the interpolation based on the flux of the flow velocity. The specification of these schemes requires the name of the flux field on which the interpolation is based; in most OpenFOAM applications this is `phi`, the name commonly adopted for the `surfaceScalarField` velocity flux ϕ . The 3 categories of convection-specific schemes are referred to in this text as: general convection; normalised variable (NV); and, total variation diminishing (TVD). With the exception of the `blended` scheme, the general convection and TVD schemes are specified by the scheme and flux, *e.g.* an `upwind` scheme based on a flux `phi` is specified as `default` by:

```
default upwind phi;
```

Some TVD/NVD schemes require a coefficient ψ , $0 \leq \psi \leq 1$ where $\psi = 1$ corresponds to TVD conformance, usually giving best convergence and $\psi = 0$ corresponds to best accuracy. Running with $\psi = 1$ is generally recommended. A `limitedLinear` scheme based on a flux `phi` with $\psi = 1.0$ is specified as `default` by:

```
default limitedLinear phi 1.0;
```

4.4.1.1 Schemes for strictly bounded scalar fields

There are enhanced versions of some of the limited schemes for scalars that need to be strictly bounded. To bound between user-specified limits, the scheme name should be preceded by the word `limited` and followed by the lower and upper limits respectively. For example, to bound the `vanLeer` scheme strictly between -2 and 3, the user would specify:

```
default limitedVanLeer -2.0 3.0;
```

There are specialised versions of these schemes for scalar fields that are commonly bounded between 0 and 1. These are selected by adding `01` to the name of the scheme. For example, to bound the `vanLeer` scheme strictly between 0 and 1, the user would specify:

```
default vanLeer01;
```

Strictly bounded versions are available for the following schemes: `limitedLinear`, `vanLeer`, `Gamma`, `limitedCubic`, `MUSCL` and `SuperBee`.

4.4.1.2 Schemes for vector fields

There are improved versions of some of the limited schemes for vector fields in which the limiter is formulated to take into account the direction of the field. These schemes are selected by adding `V` to the name of the general scheme, *e.g.* `limitedLinearV` for `limitedLinear`. 'V' versions are available for the following schemes: `limitedLinearV`, `vanLeerV`, `GammaV`, `limitedCubicV` and `SFCDV`.

| | |
|--------------------------------------|--|
| Centred schemes | |
| <code>linear</code> | Linear interpolation (central differencing) |
| <code>cubicCorrection</code> | Cubic scheme |
| <code>midPoint</code> | Linear interpolation with symmetric weighting |
| Upwinded convection schemes | |
| <code>upwind</code> | Upwind differencing |
| <code>linearUpwind</code> | Linear upwind differencing |
| <code>skewLinear</code> | Linear with skewness correction |
| <code>filteredLinear2</code> | Linear with filtering for high-frequency ringing |
| TVD schemes | |
| <code>limitedLinear</code> | limited linear differencing |
| <code>vanLeer</code> | van Leer limiter |
| <code>MUSCL</code> | MUSCL limiter |
| <code>limitedCubic</code> | Cubic limiter |
| NVD schemes | |
| <code>SFCD</code> | Self-filtered central differencing |
| <code>Gamma ψ</code> | Gamma differencing |

Table 4.6: Interpolation schemes.

4.4.2 Surface normal gradient schemes

The `snGradSchemes` sub-dictionary contains surface normal gradient terms. A surface normal gradient is evaluated at a cell face; it is the component, normal to the face, of the gradient of values at the centres of the 2 cells that the face connects. A surface normal gradient may be specified in its own right and is also required to evaluate a Laplacian term using Gaussian integration.

The available schemes are listed in Table 4.7 and are specified by simply quoting the keyword and entry, with the exception of `limited` which requires a coefficient ψ , $0 \leq \psi \leq 1$ where

$$\psi = \begin{cases} 0 & \text{corresponds to } \text{uncorrected}, \\ 0.333 & \text{non-orthogonal correction} \leq 0.5 \times \text{orthogonal part}, \\ 0.5 & \text{non-orthogonal correction} \leq \text{orthogonal part}, \\ 1 & \text{corresponds to } \text{corrected}. \end{cases} \quad (4.1)$$

A `limited` scheme with $\psi = 0.5$ is therefore specified as `default` by:

```
default limited 0.5;
```

| Scheme | Description |
|--|---|
| <code>corrected</code> | Explicit non-orthogonal correction |
| <code>uncorrected</code> | No non-orthogonal correction |
| <code>limited ψ</code> | Limited non-orthogonal correction |
| <code>bounded</code> | Bounded correction for positive scalars |
| <code>fourth</code> | Fourth order |

Table 4.7: Surface normal gradient schemes.

4.4.3 Gradient schemes

The *gradSchemes* sub-dictionary contains gradient terms. The discretisation scheme for each term can be selected from those listed in Table 4.8.

| Discretisation scheme | Description |
|--|--|
| <code>Gauss <interpolationScheme></code> | Second order, Gaussian integration |
| <code>leastSquares</code> | Second order, least squares |
| <code>fourth</code> | Fourth order, least squares |
| <code>cellLimited <gradScheme></code> | Cell limited version of one of the above schemes |
| <code>faceLimited <gradScheme></code> | Face limited version of one of the above schemes |

Table 4.8: Discretisation schemes available in *gradSchemes*.

The discretisation scheme is sufficient to specify the scheme completely in the cases of `leastSquares` and `fourth`, *e.g.*

```
grad(p) leastSquares;
```

The `Gauss` keyword specifies the standard finite volume discretisation of Gaussian integration which requires the interpolation of values from cell centres to face centres. Therefore, the `Gauss` entry must be followed by the choice of interpolation scheme from Table 4.6. It would be extremely unusual to select anything other than general interpolation schemes and in most cases the `linear` scheme is an effective choice, *e.g.*

```
grad(p) Gauss linear;
```

Limited versions of any of the 3 base gradient schemes — `Gauss`, `leastSquares` and `fourth` — can be selected by preceding the discretisation scheme by `cellLimited` (or `faceLimited`), *e.g.* a cell limited Gauss scheme

```
grad(p) cellLimited Gauss linear 1;
```

4.4.4 Laplacian schemes

The *laplacianSchemes* sub-dictionary contains Laplacian terms. Let us discuss the syntax of the entry in reference to a typical Laplacian term found in fluid dynamics, $\nabla \cdot (\nu \nabla \mathbf{U})$, given the word identifier `laplacian(nu,U)`. The `Gauss` scheme is the only choice of discretisation

and requires a selection of both an interpolation scheme for the diffusion coefficient, *i.e.* ν in our example, and a surface normal gradient scheme, *i.e.* $\nabla\mathbf{U}$. To summarise, the entries required are:

```
Gauss <interpolationScheme> <snGradScheme>
```

The interpolation scheme is selected from Table 4.6, the typical choices being from the general schemes and, in most cases, **linear**. The surface normal gradient scheme is selected from Table 4.7; the choice of scheme determines numerical behaviour as described in Table 4.9. A typical entry for our example Laplacian term would be:

```
laplacian(nu,U) Gauss linear corrected;
```

| Scheme | Numerical behaviour |
|----------------------------------|--|
| corrected | Unbounded, second order, conservative |
| uncorrected | Bounded, first order, non-conservative |
| limited ψ | Blend of corrected and uncorrected |
| bounded | First order for bounded scalars |
| fourth | Unbounded, fourth order, conservative |

Table 4.9: Behaviour of surface normal schemes used in *laplacianSchemes*.

4.4.5 Divergence schemes

The *divSchemes* sub-dictionary contains divergence terms. Let us discuss the syntax of the entry in reference to a typical convection term found in fluid dynamics $\nabla \cdot (\rho\mathbf{U}\mathbf{U})$, which in OpenFOAM applications is commonly given the identifier `div(phi,U)`, where `phi` refers to the flux $\phi = \rho\mathbf{U}$.

The **Gauss** scheme is the only choice of discretisation and requires a selection of the interpolation scheme for the dependent field, *i.e.* \mathbf{U} in our example. To summarise, the entries required are:

```
Gauss <interpolationScheme>
```

The interpolation scheme is selected from the full range of schemes in Table 4.6, both general and convection-specific. The choice critically determines numerical behaviour as described in Table 4.10. The syntax here for specifying convection-specific interpolation schemes *does not include the flux* as it is already known for the particular term, *i.e.* for `div(phi,U)`, we know the flux is `phi` so specifying it in the interpolation scheme would only invite an inconsistency. Specification of upwind interpolation in our example would therefore be:

```
div(phi,U) Gauss upwind;
```

| Scheme | Numerical behaviour |
|-----------------------------|---|
| <code>linear</code> | Second order, unbounded |
| <code>skewLinear</code> | Second order, (more) unbounded, skewness correction |
| <code>cubicCorrected</code> | Fourth order, unbounded |
| <code>upwind</code> | First order, bounded |
| <code>linearUpwind</code> | First/second order, bounded |
| <code>QUICK</code> | First/second order, bounded |
| TVD schemes | First/second order, bounded |
| <code>SFCD</code> | Second order, bounded |
| NVD schemes | First/second order, bounded |

Table 4.10: Behaviour of interpolation schemes used in *divSchemes*.

4.4.6 Time schemes

The first time derivative ($\partial/\partial t$) terms are specified in the *ddtSchemes* sub-dictionary. The discretisation scheme for each term can be selected from those listed in Table 4.11.

There is an off-centering coefficient ψ with the `CrankNicolson` scheme that blends it with the `Euler` scheme. A coefficient of $\psi = 1$ corresponds to pure `CrankNicolson` and $\psi = 0$ corresponds to pure `Euler`. The blending coefficient can help to improve stability in cases where pure `CrankNicolson` are unstable.

| Scheme | Description |
|-----------------------------------|---|
| <code>Euler</code> | First order, bounded, implicit |
| <code>localEuler</code> | Local-time step, first order, bounded, implicit |
| <code>CrankNicolson</code> ψ | Second order, bounded, implicit |
| <code>backward</code> | Second order, implicit |
| <code>steadyState</code> | Does not solve for time derivatives |

Table 4.11: Discretisation schemes available in *ddtSchemes*.

When specifying a time scheme it must be noted that an application designed for transient problems will not necessarily run as steady-state and visa versa. For example the solution will not converge if `steadyState` is specified when running `icoFoam`, the transient, laminar incompressible flow code; rather, `simpleFoam` should be used for steady-state, incompressible flow.

Any second time derivative ($\partial^2/\partial t^2$) terms are specified in the *d2dt2Schemes* sub-dictionary. Only the `Euler` scheme is available for *d2dt2Schemes*.

4.4.7 Flux calculation

The *fluxRequired* sub-dictionary lists the fields for which the flux is generated in the application. For example, in many fluid dynamics applications the flux is generated after solving a pressure equation, in which case the *fluxRequired* sub-dictionary would simply be entered as follows, `p` being the word identifier for pressure:

```
fluxRequired
{
```

```

    p;
}

```

4.5 Solution and algorithm control

The equation solvers, tolerances and algorithms are controlled from the *fvSolution* dictionary in the *system* directory. Below is an example set of entries from the *fvSolution* dictionary required for the *icoFoam* solver.

```

17
18 solvers
19 {
20     p
21     {
22         solver          PCG;
23         preconditioner  DIC;
24         tolerance       1e-06;
25         relTol          0;
26     }
27     U
28     {
29         solver          smoothSolver;
30         smoother        symGaussSeidel;
31         tolerance       1e-05;
32         relTol          0;
33     }
34 }
35
36 PISO
37 {
38     nCorrectors          2;
39     nNonOrthogonalCorrectors 0;
40     pRefCell             0;
41     pRefValue            0;
42 }
43
44
45
46 // ***** //

```

fvSolution contains a set of subdictionaries that are specific to the solver being run. However, there is a small set of standard subdictionaries that cover most of those used by the standard solvers. These subdictionaries include *solvers*, *relaxationFactors*, *PISO* and *SIMPLE* which are described in the remainder of this section.

4.5.1 Linear solver control

The first sub-dictionary in our example, and one that appears in all solver applications, is *solvers*. It specifies each linear-solver that is used for each discretised equation; it is emphasised that the term *linear*-solver refers to the method of number-crunching to solve the set of linear equations, as opposed to *application* solver which describes the set of equations and algorithms to solve a particular problem. The term ‘linear-solver’ is abbreviated to ‘solver’ in much of the following discussion; we hope the context of the term avoids any ambiguity.

The syntax for each entry within *solvers* uses a keyword that is the word relating to the variable being solved in the particular equation. For example, *icoFoam* solves equations for velocity **U** and pressure *p*, hence the entries for **U** and **p**. The keyword is followed by a dictionary containing the type of solver and the parameters that the solver uses. The solver is selected through the *solver* keyword from the choice in OpenFOAM, listed

in Table 4.12. The parameters, including `tolerance`, `relTol`, `preconditioner`, *etc.* are described in following sections.

| Solver | Keyword |
|--|--------------|
| Preconditioned (bi-)conjugate gradient | PCG/PBiCG† |
| Solver using a smoother | smoothSolver |
| Generalised geometric-algebraic multi-grid | GAMG |
| Diagonal solver for explicit systems | diagonal |

†PCG for symmetric matrices, PBiCG for asymmetric

Table 4.12: Linear solvers.

The solvers distinguish between symmetric matrices and asymmetric matrices. The symmetry of the matrix depends on the structure of the equation being solved and, while the user may be able to determine this, it is not essential since OpenFOAM will produce an error message to advise the user if an inappropriate solver has been selected, *e.g.*

```
--> FOAM FATAL IO ERROR : Unknown asymmetric matrix solver PCG
Valid asymmetric matrix solvers are :
3
(
PBiCG
smoothSolver
GAMG
)
```

4.5.1.1 Solution tolerances

The sparse matrix solvers are iterative, *i.e.* they are based on reducing the equation residual over a succession of solutions. The residual is ostensibly a measure of the error in the solution so that the smaller it is, the more accurate the solution. More precisely, the residual is evaluated by substituting the current solution into the equation and taking the magnitude of the difference between the left and right hand sides; it is also normalised to make it independent of the scale of the problem being analysed.

Before solving an equation for a particular field, the initial residual is evaluated based on the current values of the field. After each solver iteration the residual is re-evaluated. The solver stops if *either* of the following conditions are reached:

- the residual falls below the *solver tolerance*, `tolerance`;
- the ratio of current to initial residuals falls below the *solver relative tolerance*, `relTol`;
- the number of iterations exceeds a *maximum number of iterations*, `maxIter`;

The solver tolerance should represent the level at which the residual is small enough that the solution can be deemed sufficiently accurate. The solver relative tolerance limits the relative improvement from initial to final solution. In transient simulations, it is usual to set the solver relative tolerance to 0 to force the solution to converge to the solver tolerance in each time step. The tolerances, `tolerance` and `relTol` must be specified in the dictionaries for all solvers; `maxIter` is optional.

4.5.1.2 Preconditioned conjugate gradient solvers

There are a range of options for preconditioning of matrices in the conjugate gradient solvers, represented by the `preconditioner` keyword in the solver dictionary. The preconditioners are listed in Table 4.13.

| Preconditioner | Keyword |
|--|----------|
| Diagonal incomplete-Cholesky (symmetric) | DIC |
| Faster diagonal incomplete-Cholesky (DIC with caching) | FDIC |
| Diagonal incomplete-LU (asymmetric) | DILU |
| Diagonal | diagonal |
| Geometric-algebraic multi-grid | GAMG |
| No preconditioning | none |

Table 4.13: Preconditioner options.

4.5.1.3 Smooth solvers

The solvers that use a smoother require the smoother to be specified. The smoother options are listed in Table 4.14. Generally `GaussSeidel` is the most reliable option, but for bad matrices `DIC` can offer better convergence. In some cases, additional post-smoothing using `GaussSeidel` is further beneficial, *i.e.* the method denoted as `DICGaussSeidel`

| Smoother | Keyword |
|--|----------------|
| Gauss-Seidel | GaussSeidel |
| Diagonal incomplete-Cholesky (symmetric) | DIC |
| Diagonal incomplete-Cholesky with Gauss-Seidel (symmetric) | DICGaussSeidel |

Table 4.14: Smoother options.

The user must also specify the number of sweeps, by the `nSweeps` keyword, before the residual is recalculated, following the tolerance parameters.

4.5.1.4 Geometric-algebraic multi-grid solvers

The generalised method of geometric-algebraic multi-grid (GAMG) uses the principle of: generating a quick solution on a mesh with a small number of cells; mapping this solution onto a finer mesh; using it as an initial guess to obtain an accurate solution on the fine mesh. GAMG is faster than standard methods when the increase in speed by solving first on coarser meshes outweighs the additional costs of mesh refinement and mapping of field data. In practice, GAMG starts with the mesh specified by the user and coarsens/refines the mesh in stages. The user is only required to specify an approximate mesh size at the most coarse level in terms of the number of cells `nCoarsestCells`.

The agglomeration of cells is performed by the algorithm specified by the `agglomerator` keyword. Presently we recommend the `faceAreaPair` method. It is worth noting there is an `MGridGen` option that requires an additional entry specifying the shared object library for `MGridGen`:

```
geometricGangAgglomerationLibs ("libMGridGenGangAgglomeration.so");
```

In the experience of OpenCFD, the `MGridGen` method offers no obvious benefit over the `faceAreaPair` method. For all methods, agglomeration can be optionally cached by the `cacheAgglomeration` switch.

Smoothing is specified by the `smoother` as described in section 4.5.1.3. The number of sweeps used by the smoother at different levels of mesh density are specified by the `nPreSweeps`, `nPostSweeps` and `nFinestSweeps` keywords. The `nPreSweeps` entry is used as the algorithm is coarsening the mesh, `nPostSweeps` is used as the algorithm is refining, and `nFinestSweeps` is used when the solution is at its finest level.

The `mergeLevels` keyword controls the speed at which coarsening or refinement levels is performed. It is often best to do so only at one level at a time, *i.e.* set `mergeLevels` 1. In some cases, particularly for simple meshes, the solution can be safely speeded up by coarsening/refining two levels at a time, *i.e.* setting `mergeLevels` 2.

4.5.2 Solution under-relaxation

A second sub-dictionary of `fvSolution` that is often used in OpenFOAM is `relaxationFactors` which controls under-relaxation, a technique used for improving stability of a computation, particularly in solving steady-state problems. Under-relaxation works by limiting the amount which a variable changes from one iteration to the next, either by modifying the solution matrix and source prior to solving for a field or by modifying the field directly. An under-relaxation factor α , $0 < \alpha \leq 1$ specifies the amount of under-relaxation, as described below.

- No specified α : no under-relaxation.
- $\alpha = 1$: guaranteed matrix diagonal equality/dominance.
- α decreases, under-relaxation increases.
- $\alpha = 0$: solution does not change with successive iterations.

An optimum choice of α is one that is small enough to ensure stable computation but large enough to move the iterative process forward quickly; values of α as high as 0.9 can ensure stability in some cases and anything much below, say, 0.2 are prohibitively restrictive in slowing the iterative process.

The user can specify the relaxation factor for a particular field by specifying first the word associated with the field, then the factor. The user can view the relaxation factors used in a tutorial example of `simpleFoam` for incompressible, laminar, steady-state flows.

```

17
18 solvers
19 {
20     p
21     {
22         solver          GAMG;
23         tolerance       1e-06;
24         relTol          0.1;
25         smoother        GaussSeidel;
26         nPreSweeps      0;
27         nPostSweeps     2;
28         cacheAgglomeration on;
29         agglomerator    faceAreaPair;

```

```

30         nCellsInCoarsestLevel 10;
31         mergeLevels      1;
32     }
33
34     "(U|k|epsilon|omega|f|v2)"
35     {
36         solver      smoothSolver;
37         smoother    symGaussSeidel;
38         tolerance   1e-05;
39         relTol      0.1;
40     }
41 }
42
43 SIMPLE
44 {
45     nNonOrthogonalCorrectors 0;
46     consistent      yes;
47
48     residualControl
49     {
50         p          1e-2;
51         U          1e-3;
52         "(k|epsilon|omega|f|v2)" 1e-3;
53     }
54 }
55
56 relaxationFactors
57 {
58     equations
59     {
60         U          0.9; // 0.9 is more stable but 0.95 more convergent
61         ".*"      0.9; // 0.9 is more stable but 0.95 more convergent
62     }
63 }
64
65
66 // ***** //

```

4.5.3 PISO and SIMPLE algorithms

Most fluid dynamics solver applications in OpenFOAM use the pressure-implicit split-operator (PISO) or semi-implicit method for pressure-linked equations (SIMPLE) algorithms. These algorithms are iterative procedures for solving equations for velocity and pressure, PISO being used for transient problems and SIMPLE for steady-state.

Both algorithms are based on evaluating some initial solutions and then correcting them. SIMPLE only makes 1 correction whereas PISO requires more than 1, but typically not more than 4. The user must therefore specify the number of correctors in the PISO dictionary by the `nCorrectors` keyword as shown in the example on page U-123.

An additional correction to account for mesh non-orthogonality is available in both SIMPLE and PISO in the standard OpenFOAM solver applications. A mesh is orthogonal if, for each face within it, the face normal is parallel to the vector between the centres of the cells that the face connects, *e.g.* a mesh of hexahedral cells whose faces are aligned with a Cartesian coordinate system. The number of non-orthogonal correctors is specified by the `nNonOrthogonalCorrectors` keyword as shown in the examples above and on page U-123. The number of non-orthogonal correctors should correspond to the mesh for the case being solved, *i.e.* 0 for an orthogonal mesh and increasing with the degree of non-orthogonality up to, say, 20 for the most non-orthogonal meshes.

4.5.3.1 Pressure referencing

In a closed incompressible system, pressure is relative: it is the pressure range that matters not the absolute values. In these cases, the solver sets a reference level of `pRefValue` in cell

`pRefCell` where `p` is the name of the pressure solution variable. Where the pressure is `p_rgh`, the names are `p_rghRefValue` and `p_rghRefCell` respectively. These entries are generally stored in the *PISO/SIMPLE* sub-dictionary and are used by those solvers that require them when the case demands it. If omitted, the solver will not run, but give a message to alert the user to the problem.

4.5.4 Other parameters

The *fvSolutions* dictionaries in the majority of standard OpenFOAM solver applications contain no other entries than those described so far in this section. However, in general the *fvSolution* dictionary may contain any parameters to control the solvers, algorithms, or in fact anything. For a given solver, the user can look at the source code to find the parameters required. Ultimately, if any parameter or sub-dictionary is missing when an solver is run, it will terminate, printing a detailed error message. The user can then add missing parameters accordingly.

Chapter 5

Mesh generation and conversion

This chapter describes all topics relating to the creation of meshes in OpenFOAM: section 5.1 gives an overview of the ways a mesh may be described in OpenFOAM; section 5.3 covers the `blockMesh` utility for generating simple meshes of blocks of hexahedral cells; section 5.4 covers the `snappyHexMesh` utility for generating complex meshes of hexahedral and split-hexahedral cells automatically from triangulated surface geometries; section 5.5 describes the options available for conversion of a mesh that has been generated by a third-party product into a format that OpenFOAM can read.

5.1 Mesh description

This section provides a specification of the way the OpenFOAM C++ classes handle a mesh. The mesh is an integral part of the numerical solution and must satisfy certain criteria to ensure a valid, and hence accurate, solution. During any run, OpenFOAM checks that the mesh satisfies a fairly stringent set of validity constraints and will cease running if the constraints are not satisfied. The consequence is that a user may experience some frustration in ‘correcting’ a large mesh generated by third-party mesh generators before OpenFOAM will run using it. This is unfortunate but we make no apology for OpenFOAM simply adopting good practice to ensure the mesh is valid; otherwise, the solution is flawed before the run has even begun.

By default OpenFOAM defines a mesh of arbitrary polyhedral cells in 3-D, bounded by arbitrary polygonal faces, *i.e.* the cells can have an unlimited number of faces where, for each face, there is no limit on the number of edges nor any restriction on its alignment. A mesh with this general structure is known in OpenFOAM as a `polyMesh`. This type of mesh offers great freedom in mesh generation and manipulation in particular when the geometry of the domain is complex or changes over time. The price of absolute mesh generality is, however, that it can be difficult to convert meshes generated using conventional tools. The OpenFOAM library therefore provides `cellShape` tools to manage conventional mesh formats based on sets of pre-defined cell shapes.

5.1.1 Mesh specification and validity constraints

Before describing the OpenFOAM mesh format, `polyMesh`, and the `cellShape` tools, we will first set out the validity constraints used in OpenFOAM. The conditions that a mesh must satisfy are:

5.1.1.1 Points

A point is a location in 3-D space, defined by a vector in units of metres (m). The points are compiled into a list and each point is referred to by a label, which represents its position in the list, starting from zero. *The point list cannot contain two different points at an exactly identical position nor any point that is not part at least one face.*

5.1.1.2 Faces

A face is an ordered list of points, where a point is referred to by its label. The ordering of point labels in a face is such that each two neighbouring points are connected by an edge, *i.e.* you follow points as you travel around the circumference of the face. Faces are compiled into a list and each face is referred to by its label, representing its position in the list. The direction of the face normal vector is defined by the right-hand rule, *i.e.* looking towards a face, if the numbering of the points follows an anti-clockwise path, the normal vector points towards you, as shown in Figure 5.1.




Figure 5.1: Face area vector from point numbering on the face

There are two types of face:

Internal faces Those faces that connect two cells (and it can never be more than two).

For each internal face, the ordering of the point labels is such that the face normal points into the cell with the larger label, *i.e.* for cells 2 and 5, the normal points into 5;

Boundary faces Those belonging to one cell since they coincide with the boundary of the domain. A boundary face is therefore addressed by one cell(only) and a boundary patch. The ordering of the point labels is such that the face normal points outside of the computational domain.

Faces are generally expected to be convex; at the very least the face centre needs to be inside the face. Faces are allowed to be warped, *i.e.* not all points of the face need to be coplanar.

5.1.1.3 Cells

A cell is a list of faces in arbitrary order. Cells must have the properties listed below.

Contiguous The cells must completely cover the computational domain and must not overlap one another.

Convex Every cell must be convex and its cell centre inside the cell.

Closed Every cell must be *closed*, both geometrically and topologically where:

- geometrical closedness requires that when all face area vectors are oriented to point outwards of the cell, their sum should equal the zero vector to machine accuracy;
- topological closedness requires that all the edges in a cell are used by exactly two faces of the cell in question.

Orthogonality For all internal faces of the mesh, we define the centre-to-centre vector as that connecting the centres of the 2 cells that it adjoins oriented from the centre of the cell with smaller label to the centre of the cell with larger label. The orthogonality constraint requires that for each internal face, the angle between the face area vector, oriented as described above, and the centre-to-centre vector must always be less than 90° .

5.1.1.4 Boundary

A boundary is a list of patches, each of which is associated with a boundary condition. A patch is a list of face labels which clearly must contain only boundary faces and no internal faces. The boundary is required to be closed, *i.e.* the sum all boundary face area vectors equates to zero to machine tolerance.

5.1.2 The polyMesh description

The *constant* directory contains a full description of the case `polyMesh` in a subdirectory `polyMesh`. The `polyMesh` description is based around faces and, as already discussed, internal faces connect 2 cells and boundary faces address a cell and a boundary patch. Each face is therefore assigned an ‘owner’ cell and ‘neighbour’ cell so that the connectivity across a given face can simply be described by the owner and neighbour cell labels. In the case of boundaries, the connected cell is the owner and the neighbour is assigned the label ‘-1’. With this in mind, the I/O specification consists of the following files:

points a list of vectors describing the cell vertices, where the first vector in the list represents vertex 0, the second vector represents vertex 1, *etc.*;

faces a list of faces, each face being a list of indices to vertices in the points list, where again, the first entry in the list represents face 0, *etc.*;

owner a list of owner cell labels, the index of entry relating directly to the index of the face, so that the first entry in the list is the owner label for face 0, the second entry is the owner label for face 1, *etc.*;

neighbour a list of neighbour cell labels;

boundary a list of patches, containing a dictionary entry for each patch, declared using the patch name, *e.g.*

```
movingWall
{
    type patch;
    nFaces 20;
    startFace 760;
}
```

The `startFace` is the index into the face list of the first face in the patch, and `nFaces` is the number of faces in the patch.

Note that if the user wishes to know how many cells are in their domain, there is a note in the FoamFile header of the owner file that contains an entry for nCells.

5.1.3 The cellShape tools

We shall describe the alternative `cellShape` tools that may be used particularly when converting some standard (simpler) mesh formats for the use with OpenFOAM library.

The vast majority of mesh generators and post-processing systems support only a fraction of the possible polyhedral cell shapes in existence. They define a mesh in terms of a limited set of 3D cell geometries, referred to as *cell shapes*. The OpenFOAM library contains definitions of these standard shapes, to enable a conversion of such a mesh into the `polyMesh` format described in the previous section.

The `cellShape` models supported by OpenFOAM are shown in Table 5.1. The shape is defined by the ordering of point labels in accordance with the numbering scheme contained in the shape model. The ordering schemes for points, faces and edges are shown in Table 5.1. The numbering of the points must not be such that the shape becomes twisted or degenerate into other geometries, *i.e.* the same point label cannot be used more than once in a single shape. Moreover it is unnecessary to use duplicate points in OpenFOAM since the available shapes in OpenFOAM cover the full set of degenerate hexahedra.

The cell description consists of two parts: the name of a cell model and the ordered list of labels. Thus, using the following list of points

```
8
(
    (0 0 0)
    (1 0 0)
    (1 1 0)
    (0 1 0)
    (0 0 0.5)
    (1 0 0.5)
    (1 1 0.5)
    (0 1 0.5)
)
```

A hexahedral cell would be written as:

```
(hex 8(0 1 2 3 4 5 6 7))
```

Here the hexahedral cell shape is declared using the keyword `hex`. Other shapes are described by the keywords listed in Table 5.1.

5.1.4 1- and 2-dimensional and axi-symmetric problems

OpenFOAM is designed as a code for 3-dimensional space and defines all meshes as such. However, 1- and 2- dimensional and axi-symmetric problems can be simulated in OpenFOAM by generating a mesh in 3 dimensions and applying special boundary conditions on any patch in the plane(s) normal to the direction(s) of interest. More specifically, 1- and 2-dimensional problems use the `empty` patch type and axi-symmetric problems use the `wedge` type. The use of both are described in section 5.2.2 and the generation of wedge geometries for axi-symmetric problems is discussed in section 5.3.3.

5.2 Boundaries

In this section we discuss the way in which boundaries are treated in OpenFOAM. The subject of boundaries is a little involved because their role in modelling is not simply that of a geometric entity but an integral part of the solution and numerics through boundary conditions or inter-boundary ‘connections’. A discussion of boundaries sits uncomfortably between a discussion on meshes, fields, discretisation, computational processing *etc.* Its placement in this Chapter on meshes is a choice of convenience.

We first need to consider that, for the purpose of applying boundary conditions, a boundary is generally broken up into a set of *patches*. One patch may include one or more enclosed areas of the boundary surface which do not necessarily need to be physically connected.




Figure 5.2: Patch attributes



















| Cell type | Keyword | Vertex numbering | Face numbering | Edge numbering |
|-------------|----------|---|--|---|
| Hexahedron | hex |  |  |  |
| | |  |  |  |
| Wedge | wedge |  |  |  |
| | |  |  |  |
| Prism | prism |  |  |  |
| | |  |  |  |
| Pyramid | pyr |  |  |  |
| | |  |  |  |
| Tetrahedron | tet | | | |
| | | | | |
| Tet-wedge | tetWedge | | | |
| | | | | |

Table 5.1: Vertex, face and edge numbering for cellShapes.

There are three attributes associated with a patch that are described below in their natural hierarchy and Figure 5.2 shows the names of different patch types introduced at each level of the hierarchy. The hierarchy described below is very similar, but not identical, to the class hierarchy used in the OpenFOAM library.

Base type The type of patch described purely in terms of geometry or a data ‘communication link’.

Primitive type The base numerical patch condition assigned to a field variable on the patch.

Derived type A complex patch condition, derived from the primitive type, assigned to a field variable on the patch.

5.2.1 Specification of patch types in OpenFOAM

The patch types are specified in the mesh and field files of a OpenFOAM case. More precisely:

- the base type is specified under the `type` keyword for each patch in the *boundary* file, located in the *constant/polyMesh* directory;
- the numerical patch type, be it a primitive or derived type, is specified under the `type` keyword for each patch in a field file.

An example *boundary* file is shown below for a *sonicFoam* case, followed by a pressure field file, *p*, for the same case:

```

17
18 6
19 (
20     inlet
21     {
22         type           patch;
23         nFaces         50;
24         startFace     10325;
25     }
26     outlet
27     {
28         type           patch;
29         nFaces         40;
30         startFace     10375;
31     }
32     bottom
33     {
34         type           symmetryPlane;
35         inGroups       1(symmetryPlane);
36         nFaces         25;
37         startFace     10415;
38     }
39     top
40     {
41         type           symmetryPlane;
42         inGroups       1(symmetryPlane);
43         nFaces         125;
44         startFace     10440;
45     }
46     obstacle
47     {
48         type           patch;
49         nFaces         110;
50         startFace     10565;
51     }
52     defaultFaces
53     {
54         type           empty;

```

```

55         inGroups      1(empty);
56         nFaces        10500;
57         startFace     10675;
58     }
59 )
60
61 // ***** //

17 dimensions      [1 -1 -2 0 0 0 0];
18
19 internalField   uniform 1;
20
21 boundaryField
22 {
23     inlet
24     {
25         type          fixedValue;
26         value         uniform 1;
27     }
28
29     outlet
30     {
31         type          waveTransmissive;
32         field         p;
33         phi           phi;
34         rho           rho;
35         psi           thermo:psi;
36         gamma        1.4;
37         fieldInf     1;
38         lInf         3;
39         value         uniform 1;
40     }
41
42     bottom
43     {
44         type          symmetryPlane;
45     }
46
47     top
48     {
49         type          symmetryPlane;
50     }
51
52     obstacle
53     {
54         type          zeroGradient;
55     }
56
57     defaultFaces
58     {
59         type          empty;
60     }
61 }
62
63 // ***** //

```

The `type` in the boundary file is `patch` for all patches except those that have some geometrical constraint applied to them, *i.e.* the `symmetryPlane` and `empty` patches. The `p` file includes primitive types applied to the `inlet` and `bottom` faces, and a more complex derived type applied to the `outlet`. Comparison of the two files shows that the base and numerical types are consistent where the base type is not a simple `patch`, *i.e.* for the `symmetryPlane` and `empty` patches.

5.2.2 Base types

The base and geometric types are described below; the keywords used for specifying these types in OpenFOAM are summarised in Table 5.2.

`patch` The basic patch type for a patch condition that contains no geometric or topological information about the mesh (with the exception of `wall`), *e.g.* an inlet or an outlet.




Figure 5.3: Axi-symmetric geometry using the `wedge` patch type.

| Selection Key | Description |
|----------------------------|--|
| <code>patch</code> | generic patch |
| <code>symmetryPlane</code> | plane of symmetry |
| <code>empty</code> | front and back planes of a 2D geometry |
| <code>wedge</code> | wedge front and back for an axi-symmetric geometry |
| <code>cyclic</code> | cyclic plane |
| <code>wall</code> | wall — used for wall functions in turbulent flows |
| <code>processor</code> | inter-processor boundary |

Table 5.2: Basic patch types.

wall There are instances where a patch that coincides with a wall needs to be identifiable as such, particularly where specialist modelling is applied at wall boundaries. A good example is wall turbulence modelling where a wall must be specified with a `wall` patch type, so that the distance from the wall to the cell centres next to the wall are stored as part of the patch.

symmetryPlane For a symmetry plane.

empty While OpenFOAM always generates geometries in 3 dimensions, it can be instructed to solve in 2 (or 1) dimensions by specifying a special `empty` condition on each patch whose plane is normal to the 3rd (and 2nd) dimension for which no solution is required.

wedge For 2 dimensional axi-symmetric cases, *e.g.* a cylinder, the geometry is specified as a wedge of small angle (*e.g.* $< 5^\circ$) and 1 cell thick running along the plane of symmetry, straddling one of the coordinate planes, as shown in Figure 5.3. The axi-symmetric wedge planes must be specified as separate patches of `wedge` type. The details of generating wedge-shaped geometries using `blockMesh` are described in section 5.3.3.

cyclic Enables two patches to be treated as if they are physically connected; used for repeated geometries, *e.g.* heat exchanger tube bundles. One `cyclic` patch is linked to another

through a `neighbourPatch` keyword in the *boundary* file. Each pair of connecting faces must have similar area to within a tolerance given by the `matchTolerance` keyword in the *boundary* file. Faces do not need to be of the same orientation.

processor If a code is being run in parallel, on a number of processors, then the mesh must be divided up so that each processor computes on roughly the same number of cells. The boundaries between the different parts of the mesh are called **processor boundaries**.

5.2.3 Primitive types

The primitive types are listed in Table 5.3.

| Type | Description of condition for patch field ϕ | Data to specify |
|-----------------------------|--|---|
| <code>fixedValue</code> | Value of ϕ is specified | <code>value</code> |
| <code>fixedGradient</code> | Normal gradient of ϕ is specified | <code>gradient</code> |
| <code>zeroGradient</code> | Normal gradient of ϕ is zero | — |
| <code>calculated</code> | Boundary field ϕ derived from other fields | — |
| <code>mixed</code> | Mixed <code>fixedValue</code> / <code>fixedGradient</code> condition depending on the value in <code>valueFraction</code> | <code>refValue</code> , <code>refGradient</code> , <code>valueFraction</code> , <code>value</code> |
| <code>directionMixed</code> | A mixed condition with tensorial <code>valueFraction</code> , <i>e.g.</i> for different levels of mixing in normal and tangential directions | <code>refValue</code> , <code>refGradient</code> , <code>valueFraction</code> , <code>value</code> |

Table 5.3: Primitive patch field types.

5.2.4 Derived types

There are numerous derived types of boundary conditions in OpenFOAM, too many to list here. Instead a small selection is listed in Table 5.4. If the user wishes to obtain a list of all available models, they should consult the OpenFOAM source code. Derived boundary condition source code can be found at the following locations:

- in `$FOAM_SRC/finiteVolume/fields/fvPatchFields/derived`
- within certain model libraries, that can be located by typing the following command in a terminal window

```
find $FOAM_SRC -name "*derivedFvPatch*"
```

- within certain solvers, that can be located by typing the following command in a terminal window

```
find $FOAM_SOLVERS -name "*fvPatch*"
```

| Types derived from fixedValue | | Data to specify |
|---|--|-------------------------------------|
| movingWallVelocity | Replaces the normal of the patch <code>value</code> so the flux across the patch is zero | value |
| pressureInletVelocity | When p is known at inlet, \mathbf{U} is evaluated from the flux, normal to the patch | value |
| pressureDirectedInletVelocity | When p is known at inlet, \mathbf{U} is calculated from the flux in the <code>inletDirection</code> | value, inletDirection |
| surfaceNormalFixedValue | Specifies a vector boundary condition, normal to the patch, by its magnitude; +ve for vectors pointing out of the domain | value |
| totalPressure | Total pressure $p_0 = p + \frac{1}{2}\rho \mathbf{U} ^2$ is fixed; when \mathbf{U} changes, p is adjusted accordingly | p0 |
| turbulentInlet | Calculates a fluctuating variable based on a scale of a mean value | referenceField, fluctuationScale |
| Types derived from fixedGradient/zeroGradient | | |
| fluxCorrectedVelocity | Calculates normal component of \mathbf{U} at inlet from flux | value |
| buoyantPressure | Sets <code>fixedGradient</code> pressure based on the atmospheric pressure gradient | — |
| Types derived from mixed | | |
| inletOutlet | Switches \mathbf{U} and p between <code>fixedValue</code> and <code>zeroGradient</code> depending on direction of \mathbf{U} | inletValue, value |
| outletInlet | Switches \mathbf{U} and p between <code>fixedValue</code> and <code>zeroGradient</code> depending on direction of \mathbf{U} | outletValue, value |
| pressureInletOutletVelocity | Combination of <code>pressureInletVelocity</code> and <code>inletOutlet</code> | value |
| pressureDirected- InletOutletVelocity | Combination of <code>pressureDirectedInletVelocity</code> and <code>inletOutlet</code> | value, inletDirection |
| pressureTransmissive | Transmits supersonic pressure waves to surrounding pressure p_∞ | pInf |
| supersonicFreeStream | Transmits oblique shocks to surroundings at $p_\infty, T_\infty, \mathbf{U}_\infty$ | pInf, TInf, UInf |
| Other types | | |
| slip | <code>zeroGradient</code> if ϕ is a scalar; if ϕ is a vector, normal component is <code>fixedValue zero</code> , tangential components are <code>zeroGradient</code> | — |
| partialSlip | Mixed <code>zeroGradient</code> / <code>slip</code> condition depending on the <code>valueFraction</code> ; = 0 for <code>slip</code> | valueFraction |

Note: p is pressure, \mathbf{U} is velocity

Table 5.4: Derived patch field types.

5.3 Mesh generation with the blockMesh utility

This section describes the mesh generation utility, `blockMesh`, supplied with OpenFOAM. The `blockMesh` utility creates parametric meshes with grading and curved edges.

The mesh is generated from a dictionary file named `blockMeshDict` located in the `system` (or `constant/polyMesh`) directory of a case. `blockMesh` reads this dictionary, generates the mesh and writes out the mesh data to `points` and `faces`, `cells` and `boundary` files in the same directory.

The principle behind `blockMesh` is to decompose the domain geometry into a set of 1 or more three dimensional, hexahedral blocks. Edges of the blocks can be straight lines, arcs or splines. The mesh is ostensibly specified as a number of cells in each direction of the block, sufficient information for `blockMesh` to generate the mesh data.

Each block of the geometry is defined by 8 vertices, one at each corner of a hexahedron. The vertices are written in a list so that each vertex can be accessed using its label, remembering that OpenFOAM always uses the C++ convention that the first element of the list has label '0'. An example block is shown in Figure 5.4 with each vertex numbered according to the list. The edge connecting vertices 1 and 5 is curved to remind the reader that curved edges can be specified in `blockMesh`.

It is possible to generate blocks with less than 8 vertices by collapsing one or more pairs of vertices on top of each other, as described in section 5.3.3.

Each block has a local coordinate system (x_1, x_2, x_3) that must be right-handed. A right-handed set of axes is defined such that to an observer looking down the Oz axis, with O nearest them, the arc from a point on the Ox axis to a point on the Oy axis is in a clockwise sense.

The local coordinate system is defined by the order in which the vertices are presented in the block definition according to:

- the axis origin is the first entry in the block definition, vertex 0 in our example;
- the x_1 direction is described by moving from vertex 0 to vertex 1;
- the x_2 direction is described by moving from vertex 1 to vertex 2;
- vertices 0, 1, 2, 3 define the plane $x_3 = 0$;
- vertex 4 is found by moving from vertex 0 in the x_3 direction;
- vertices 5,6 and 7 are similarly found by moving in the x_3 direction from vertices 1,2 and 3 respectively.

5.3.1 Writing a `blockMeshDict` file

The `blockMeshDict` file is a dictionary using keywords described in Table 5.5. The `convertToMeters` keyword specifies a scaling factor by which all vertex coordinates in the mesh description are multiplied. For example,

```
convertToMeters    0.001;
```

means that all coordinates are multiplied by 0.001, *i.e.* the values quoted in the `blockMeshDict` file are in mm.




Figure 5.4: A single block

| Keyword | Description | Example/selection |
|------------------------------|---|--|
| <code>convertToMeters</code> | Scaling factor for the vertex coordinates | 0.001 scales to mm |
| <code>vertices</code> | List of vertex coordinates | (0 0 0) |
| <code>edges</code> | Used to describe arc or spline edges | arc 1 4 (0.939 0.342 -0.5) |
| <code>block</code> | Ordered list of vertex labels and mesh size | hex (0 1 2 3 4 5 6 7) (10 10 1) |
| <code>patches</code> | List of patches | simpleGrading (1.0 1.0 1.0) symmetryPlane base ((0 1 2 3)) |
| <code>mergePatchPairs</code> | List of patches to be merged | see section 5.3.2 |

Table 5.5: Keywords used in *blockMeshDict*.

5.3.1.1 The vertices

The vertices of the blocks of the mesh are given next as a standard list named `vertices`, e.g. for our example block in Figure 5.4, the vertices are:

```
vertices
(
  ( 0 0 0 ) // vertex number 0
  ( 1 0 0.1) // vertex number 1
  ( 1.1 1 0.1) // vertex number 2
  ( 0 1 0.1) // vertex number 3
  (-0.1 -0.1 1 ) // vertex number 4
  ( 1.3 0 1.2) // vertex number 5
  ( 1.4 1.1 1.3) // vertex number 6
  ( 0 1 1.1) // vertex number 7
);
```

5.3.1.2 The edges

Each edge joining 2 vertex points is assumed to be straight by default. However any edge may be specified to be curved by entries in a list named `edges`. The list is optional; if the geometry contains no curved edges, it may be omitted.

Each entry for a curved edge begins with a keyword specifying the type of curve from those listed in Table 5.6.

| Keyword selection | Description | Additional entries |
|-----------------------|----------------|------------------------------|
| <code>arc</code> | Circular arc | Single interpolation point |
| <code>spline</code> | Spline curve | List of interpolation points |
| <code>polyLine</code> | Set of lines | List of interpolation points |
| <code>BSpline</code> | B-spline curve | List of interpolation points |
| <code>line</code> | Straight line | — |

Table 5.6: Edge types available in the *blockMeshDict* dictionary.

The keyword is then followed by the labels of the 2 vertices that the edge connects. Following that, interpolation points must be specified through which the edge passes. For a `arc`, a single interpolation point is required, which the circular arc will intersect. For `spline`, `polyLine` and `BSpline`, a list of interpolation points is required. The `line` edge is directly equivalent to the option executed by default, and requires no interpolation points. Note that there is no need to use the `line` edge but it is included for completeness. For our example block in Figure 5.4 we specify an `arc` edge connecting vertices 1 and 5 as follows through the interpolation point (1.1, 0.0, 0.5):

```
edges
(
    arc 1 5 (1.1 0.0 0.5)
);
```

5.3.1.3 The blocks

The block definitions are contained in a list named `blocks`. Each block definition is a compound entry consisting of a list of vertex labels whose order is described in section 5.3, a vector giving the number of cells required in each direction, the type and list of cell expansion ratio in each direction.

Then the blocks are defined as follows:

```
blocks
(
    hex (0 1 2 3 4 5 6 7) // vertex numbers
    (10 10 10) // numbers of cells in each direction
    simpleGrading (1 2 3) // cell expansion ratios
);
```

The definition of each block is as follows:

Vertex numbering The first entry is the shape identifier of the block, as defined in the `.OpenFOAM-3.0.1/cellModels` file. The shape is always `hex` since the blocks are always hexahedra. There follows a list of vertex numbers, ordered in the manner described on page U-140.

Number of cells The second entry gives the number of cells in each of the x_1 x_2 and x_3 directions for that block.

Cell expansion ratios The third entry gives the cell expansion ratios for each direction in the block. The expansion ratio enables the mesh to be graded, or refined, in specified directions. The ratio is that of the width of the end cell δ_e along one edge of a block to the width of the start cell δ_s along that edge, as shown in Figure 5.5. Each of the following keywords specify one of two types of grading specification available in blockMesh.

simpleGrading The simple description specifies uniform expansions in the local x_1 , x_2 and x_3 directions respectively with only 3 expansion ratios, *e.g.*

```
simpleGrading (1 2 3)
```

edgeGrading The full cell expansion description gives a ratio for each edge of the block, numbered according to the scheme shown in Figure 5.4 with the arrows representing the direction ‘from first cell... to last cell’ *e.g.* something like

```
edgeGrading (1 1 1 1 2 2 2 2 3 3 3 3)
```

This means the ratio of cell widths along edges 0-3 is 1, along edges 4-7 is 2 and along 8-11 is 3 and is directly equivalent to the `simpleGrading` example given above.




Figure 5.5: Mesh grading along a block edge

5.3.1.4 Multi-grading of a block

Using a single expansion ratio to describe mesh grading permits only “one-way” grading within a mesh block. In some cases, it reduces complexity and effort to be able to control grading within separate divisions of a single block, rather than have to define several blocks with one grading per block. For example, to mesh a channel with two opposing walls and grade the mesh towards the walls requires three regions: two with grading to the wall with one in the middle without grading.

OpenFOAM v2.4+ includes multi-grading functionality that can divide a block in an given direction and apply different grading within each division. This multi-grading is specified by replacing any single value expansion ratio in the grading specification of the block, *e.g.* “1”, “2”, “3” in

```
blocks
(
  hex (0 1 2 3 4 5 6 7) (100 300 100)
  simpleGrading (1 2 3);
);
```

We will present multi-grading for the following example:

- split the block into 3 divisions in the y -direction, representing 20%, 60% and 20% of the block length;
- include 30% of the total cells in the y -direction (300) in *each* divisions 1 and 3 and the remaining 40% in division 2;
- apply 1:4 expansion in divisions 1 and 3, and zero expansion in division 2.

We can specify this by replacing the y -direction expansion ratio “2” in the example above with the following:

```
blocks
(
  hex (0 1 2 3 4 5 6 7) (100 300 100)
  simpleGrading
  (
    1 // x-direction expansion ratio
    (
      (0.2 0.3 4) // 20% y-dir, 30% cells, expansion = 4
      (0.6 0.4 1) // 60% y-dir, 40% cells, expansion = 1
      (0.2 0.3 0.25) // 20% y-dir, 30% cells, expansion = 0.25 (1/4)
    )
    3 // z-direction expansion ratio
  )
);
```

Both the fraction of the block and the fraction of the cells are normalized automatically. They can be specified as percentages, fractions, absolute lengths, *etc.* and do not need to sum to 100, 1, *etc.* The example above can be specified using percentages, *e.g.*

```
blocks
(
  hex (0 1 2 3 4 5 6 7) (100 300 100)
  simpleGrading
  (
    1
    (
      (20 30 4) // 20%, 30%...
      (60 40 1)
      (20 30 0.25)
    )
  )
);
```

```

        )
    3
)
);

```

5.3.1.5 The boundary

The boundary of the mesh is given in a list named **boundary**. The boundary is broken into patches (regions), where each patch in the list has its name as the keyword, which is the choice of the user, although we recommend something that conveniently identifies the patch, *e.g.* **inlet**; the name is used as an identifier for setting boundary conditions in the field data files. The patch information is then contained in sub-dictionary with:

- **type**: the patch type, either a generic **patch** on which some boundary conditions are applied or a particular geometric condition, as listed in Table 5.2 and described in section 5.2.2;
- **faces**: a list of block faces that make up the patch and whose name is the choice of the user, although we recommend something that conveniently identifies the patch, *e.g.* **inlet**; the name is used as an identifier for setting boundary conditions in the field data files.

blockMesh collects faces from any boundary patch that is omitted from the **boundary** list and assigns them to a default patch named **defaultFaces** of type **empty**. This means that for a 2 dimensional geometry, the user has the option to omit block faces lying in the 2D plane, knowing that they will be collected into an **empty** patch as required.

Returning to the example block in Figure 5.4, if it has an inlet on the left face, an output on the right face and the four other faces are walls then the patches could be defined as follows:

```

boundary          // keyword
(
  inlet           // patch name
  {
    type patch;   // patch type for patch 0
    faces
    (
      (0 4 7 3) // block face in this patch
    );
  }              // end of 0th patch definition

  outlet         // patch name
  {
    type patch;   // patch type for patch 1
    faces
    (
      (1 2 6 5)
    );
  }

```

```

    walls
    {
        type wall;
        faces
        (
            (0 1 5 4)
            (0 3 2 1)
            (3 7 6 2)
            (4 5 6 7)
        );
    }
);

```

Each block face is defined by a list of 4 vertex numbers. The order in which the vertices are given **must** be such that, looking from inside the block and starting with any vertex, the face must be traversed in a clockwise direction to define the other vertices.

When specifying a cyclic patch in `blockMesh`, the user must specify the name of the related cyclic patch through the `neighbourPatch` keyword. For example, a pair of cyclic patches might be specified as follows:

```

left
{
    type          cyclic;
    neighbourPatch right;
    faces         ((0 4 7 3));
}
right
{
    type          cyclic;
    neighbourPatch left;
    faces         ((1 5 6 2));
}

```

5.3.2 Multiple blocks

A mesh can be created using more than 1 block. In such circumstances, the mesh is created as has been described in the preceding text; the only additional issue is the connection between blocks, in which there are two distinct possibilities:

face matching the set of faces that comprise a patch from one block are formed from *the same set of vertices* as a set of faces patch that comprise a patch from another block;

face merging a group of faces from a patch from one block are connected to another group of faces from a patch from another block, to create a new set of internal faces connecting the two blocks.

To connect two blocks with **face matching**, the two patches that form the connection should simply be ignored from the `patches` list. `blockMesh` then identifies that the faces

do not form an external boundary and combines each collocated pair into a single internal faces that connects cells from the two blocks.

The alternative, **face merging**, requires that the block patches to be merged are first defined in the `patches` list. Each pair of patches whose faces are to be merged must then be included in an optional list named `mergePatchPairs`. The format of `mergePatchPairs` is:

```
mergePatchPairs
(
    ( <masterPatch> <slavePatch> ) // merge patch pair 0
    ( <masterPatch> <slavePatch> ) // merge patch pair 1
    ...
)
```

The pairs of patches are interpreted such that the first patch becomes the *master* and the second becomes the *slave*. The rules for merging are as follows:

- the faces of the master patch remain as originally defined, with all vertices in their original location;
- the faces of the slave patch are projected onto the master patch where there is some separation between slave and master patch;
- the location of any vertex of a slave face might be adjusted by `blockMesh` to eliminate any face edge that is shorter than a minimum tolerance;
- if patches overlap as shown in Figure 5.6, each face that does not merge remains as an external face of the original patch, on which boundary conditions must then be applied;
- if all the faces of a patch are merged, then the patch itself will contain no faces and is removed.

The consequence is that the original geometry of the slave patch will not necessarily be completely preserved during merging. Therefore in a case, say, where a cylindrical block is being connected to a larger block, it would be wise to the assign the master patch to the cylinder, so that its cylindrical shape is correctly preserved. There are some additional recommendations to ensure successful merge procedures:

- in 2 dimensional geometries, the size of the cells in the third dimension, *i.e.* out of the 2D plane, should be similar to the width/height of cells in the 2D plane;
- it is inadvisable to merge a patch twice, *i.e.* include it twice in `mergePatchPairs`;
- where a patch to be merged shares a common edge with another patch to be merged, both should be declared as a master patch.




Figure 5.6: Merging overlapping patches

5.3.3 Creating blocks with fewer than 8 vertices

It is possible to collapse one or more pair(s) of vertex(es) onto each other in order to create a block with fewer than 8 vertices. The most common example of collapsing vertices is when creating a 6-sided wedge shaped block for 2-dimensional axi-symmetric cases that use the `wedge` patch type described in section 5.2.2. The process is best illustrated by using a simplified version of our example block shown in Figure 5.7. Let us say we wished to create a wedge shaped block by collapsing vertex 7 onto 4 and 6 onto 5. This is simply done by exchanging the vertex number 7 by 4 and 6 by 5 respectively so that the block numbering would become:

```
hex (0 1 2 3 4 5 5 4)
```




Figure 5.7: Creating a wedge shaped block with 6 vertices

The same applies to the patches with the main consideration that the block face containing the collapsed vertices, previously (4 5 6 7) now becomes (4 5 5 4). This is a block face of zero area which creates a patch with no faces in the `polyMesh`, as the user can see in a `boundary` file for such a case. The patch should be specified as `empty` in the `blockMeshDict` and the boundary condition for any fields should consequently be `empty` also.

5.3.4 Running `blockMesh`

As described in section 3.3, the following can be executed at the command line to run `blockMesh` for a case in the `<case>` directory:

```
blockMesh -case <case>
```

The `blockMeshDict` file must exist in the `system` (or `constant/polyMesh`) directory.

5.4 Mesh generation with the `snappyHexMesh` utility

This section describes the mesh generation utility, `snappyHexMesh`, supplied with OpenFOAM. The `snappyHexMesh` utility generates 3-dimensional meshes containing hexahedra (hex) and split-hexahedra (split-hex) automatically from triangulated surface geometries, or tri-surfaces, in Stereolithography (STL) or Wavefront Object (OBJ) format. The mesh approximately conforms to the surface by iteratively refining a starting mesh and morphing the resulting split-hex mesh to the surface. An optional phase will shrink back the resulting mesh and insert cell layers. The specification of mesh refinement level is very flexible and the surface handling is robust with a pre-specified final mesh quality. It runs in parallel with a load balancing step every iteration.




Figure 5.8: Schematic 2D meshing problem for `snappyHexMesh`

5.4.1 The mesh generation process of `snappyHexMesh`

The process of generating a mesh using `snappyHexMesh` will be described using the schematic in Figure 5.8. The objective is to mesh a rectangular shaped region (shaded grey in the

figure) surrounding an object described by a tri-surface, *e.g.* typical for an external aerodynamics simulation. Note that the schematic is 2-dimensional to make it easier to understand, even though the `snappyHexMesh` is a 3D meshing tool.

In order to run `snappyHexMesh`, the user requires the following:

- one or more tri-surface files located in a *constant/triSurface* sub-directory of the case directory;
- a background hex mesh which defines the extent of the computational domain and a base level mesh density; typically generated using `blockMesh`, discussed in section 5.4.2.
- a *snappyHexMeshDict* dictionary, with appropriate entries, located in the *system* sub-directory of the case.

The *snappyHexMeshDict* dictionary includes: switches at the top level that control the various stages of the meshing process; and, individual sub-directories for each process. The entries are listed in Table 5.7.

| Keyword | Description | Example |
|--------------------------------------|---|--------------------|
| <code>castellatedMesh</code> | Create the castellated mesh? | <code>true</code> |
| <code>snap</code> | Do the surface snapping stage? | <code>true</code> |
| <code>doLayers</code> | Add surface layers? | <code>true</code> |
| <code>mergeTolerance</code> | Merge tolerance as fraction of bounding box of initial mesh | <code>1e-06</code> |
| <code>debug</code> | Controls writing of intermediate meshes and screen printing | |
| | — Write final mesh only | 0 |
| | — Write intermediate meshes | 1 |
| | — Write <code>volScalarField</code> with <code>cellLevel</code> for post-processing | 2 |
| | — Write current intersections as <i>.obj</i> files | 4 |
| <code>geometry</code> | Sub-dictionary of all surface geometry used | |
| <code>castellatedMeshControls</code> | Sub-dictionary of controls for castellated mesh | |
| <code>snapControls</code> | Sub-dictionary of controls for surface snapping | |
| <code>addLayersControls</code> | Sub-dictionary of controls for layer addition | |
| <code>meshQualityControls</code> | Sub-dictionary of controls for mesh quality | |

Table 5.7: Keywords at the top level of *snappyHexMeshDict*.

All the geometry used by `snappyHexMesh` is specified in a *geometry* sub-dictionary in the *snappyHexMeshDict* dictionary. The geometry can be specified through a tri-surface or bounding geometry entities in OpenFOAM. An example is given below:

```

geometry
{
    sphere.stl // STL filename
    {
        type triSurfaceMesh;
        regions
        {
            secondSolid // Named region in the STL file
            {

```

```

        name mySecondPatch; // User-defined patch name
    }
}

box1x1x1 // User defined region name
{
    type    searchableBox;    // region defined by bounding box
    min     (1.5 1 -0.5);
    max     (3.5 2 0.5);
}

sphere2 // User defined region name
{
    type    searchableSphere; // region defined by bounding sphere
    centre  (1.5 1.5 1.5);
    radius  1.03;
}
};

```

5.4.2 Creating the background hex mesh

Before `snappyHexMesh` is executed the user must create a background mesh of hexahedral cells that fills the entire region within by the external boundary as shown in Figure 5.9. This can be done simply using `blockMesh`. The following criteria must be observed when




Figure 5.9: Initial mesh generation in `snappyHexMesh` meshing process

creating the background mesh:

- the mesh must consist purely of hexes;
- the cell aspect ratio should be approximately 1, at least near surfaces at which the subsequent snapping procedure is applied, otherwise the convergence of the snapping procedure is slow, possibly to the point of failure;
- there must be at least one intersection of a cell edge with the tri-surface, *i.e.* a mesh of one cell will not work.




Figure 5.10: Cell splitting by feature edge in `snappyHexMesh` meshing process

5.4.3 Cell splitting at feature edges and surfaces

Cell splitting is performed according to the specification supplied by the user in the `castellatedMeshControls` sub-dictionary in the `snappyHexMeshDict`. The entries for `castellatedMeshControls` are presented in Table 5.8.

| Keyword | Description | Example |
|----------------------------------|--|---------|
| <code>locationInMesh</code> | Location vector inside the region to be meshed <i>N.B.</i> vector must not coincide with a cell face either before or during refinement | (5 0 0) |
| <code>maxLocalCells</code> | Max number of cells per processor during refinement | 1e+06 |
| <code>maxGlobalCells</code> | Overall cell limit during refinement (<i>i.e.</i> before removal) | 2e+06 |
| <code>minRefinementCells</code> | If \geq number of cells to be refined, surface refinement stops | 0 |
| <code>nCellsBetweenLevels</code> | Number of buffer layers of cells between different levels of refinement | 1 |
| <code>resolveFeatureAngle</code> | Applies maximum level of refinement to cells that can see intersections whose angle exceeds this | 30 |
| <code>features</code> | List of features for refinement | |
| <code>refinementSurfaces</code> | Dictionary of surfaces for refinement | |
| <code>refinementRegions</code> | Dictionary of regions for refinement | |

Table 5.8: Keywords in the `castellatedMeshControls` sub-dictionary of `snappyHexMeshDict`.

The splitting process begins with cells being selected according to specified edge features first within the domain as illustrated in Figure 5.10. The `features` list in the `castellatedMeshControls` sub-dictionary permits dictionary entries containing a name of an `edgeMesh` file and the `level` of refinement, *e.g.*:

```
features
(
```

```

    {
        file "features.eMesh"; // file containing edge mesh
        level 2;                // level of refinement
    }
};

```

The `edgeMesh` containing the features can be extracted from the tri-surface file using `surfaceFeatureExtract` which specifies the tri-surface and controls such as included angle through a `surfaceFeatureExtractDict` configuration file, examples of which can be found in several tutorials and the `$FOAM_UTILITIES/surface/surfaceFeatureExtract` directory in the OpenFOAM installation. The utility is simply run by executing the following in a terminal

```
surfaceFeatureExtract
```

Following feature refinement, cells are selected for splitting in the locality of specified surfaces as illustrated in Figure 5.11. The `refinementSurfaces` dictionary in `castellatedMeshControls` requires dictionary entries for each STL surface and a default `level` specification of the minimum and maximum refinement in the form (`<min> <max>`). The minimum level is applied generally across the surface; the maximum level is applied to cells that can see intersections that form an angle in excess of that specified by `resolveFeatureAngle`.

The refinement can optionally be overridden on one or more specific region of an STL surface. The region entries are collected in a `regions` sub-dictionary. The keyword for each region entry is the name of the region itself and the refinement level is contained within a further sub-dictionary. An example is given below:

```

refinementSurfaces
{
    sphere.stl
    {
        level (2 2); // default (min max) refinement for whole surface
        regions
        {
            secondSolid
            {
                level (3 3); // optional refinement for secondSolid region
            }
        }
    }
}

```




Figure 5.11: Cell splitting by surface in `snappyHexMesh` meshing process

5.4.4 Cell removal

Once the feature and surface splitting is complete a process of cell removal begins. Cell removal requires one or more regions enclosed entirely by a bounding surface within the domain. The region in which cells are retained are simply identified by a location vector within that region, specified by the `locationInMesh` keyword in `castellatedMeshControls`. Cells are retained if, approximately speaking, 50% or more of their volume lies within the region. The remaining cells are removed accordingly as illustrated in Figure 5.12.




Figure 5.12: Cell removal in `snappyHexMesh` meshing process

5.4.5 Cell splitting in specified regions

Those cells that lie within one or more specified volume regions can be further split as illustrated in Figure 5.13 by a rectangular region shown by dark shading. The `refinementRegions` sub-dictionary in `castellatedMeshControls` contains entries for refinement of the volume regions specified in the `geometry` sub-dictionary. A refinement mode is applied to each region which can be:

- `inside` refines inside the volume region;
- `outside` refines outside the volume region
- `distance` refines according to distance to the surface; and can accommodate different levels at multiple distances with the `levels` keyword.

For the `refinementRegions`, the refinement level is specified by the `levels` list of entries with the format(`<distance>` `<level>`). In the case of `inside` and `outside` refinement, the `<distance>` is not required so is ignored (but it must be specified). Examples are shown below:

```
refinementRegions
{
    box1x1x1
    {
        mode inside;
        levels ((1.0 4));           // refinement level 4 (1.0 entry ignored)
    }
}
```

```

sphere.stl
{
    // refinement level 5 within 1.0 m
    mode distance; // refinement level 3 within 2.0 m
    levels ((1.0 5) (2.0 3)); // levels must be ordered nearest first
}
}

```

5.4.6 Snapping to surfaces

The next stage of the meshing process involves moving cell vertex points onto surface geometry to remove the jagged castellated surface from the mesh. The process is:

1. displace the vertices in the castellated boundary onto the STL surface;
2. solve for relaxation of the internal mesh with the latest displaced boundary vertices;
3. find the vertices that cause mesh quality parameters to be violated;
4. reduce the displacement of those vertices from their initial value (at 1) and repeat from 2 until mesh quality is satisfied.

The method uses the settings in the `snapControls` sub-dictionary in `snappyHexMeshDict`, listed in Table 5.9. An example is illustrated in the schematic in Figure 5.14 (albeit with

| Keyword | Description | Example |
|---------------------------|---|---------|
| <code>nSmoothPatch</code> | Number of patch smoothing iterations before finding correspondence to surface | 3 |
| <code>tolerance</code> | Ratio of distance for points to be attracted by surface feature point or edge, to local maximum edge length | 4.0 |
| <code>nSolveIter</code> | Number of mesh displacement relaxation iterations | 30 |
| <code>nRelaxIter</code> | Maximum number of snapping relaxation iterations | 5 |

Table 5.9: Keywords in the `snapControls` dictionary of `snappyHexMeshDict`.

mesh motion that looks slightly unrealistic).

5.4.7 Mesh layers

The mesh output from the snapping stage may be suitable for the purpose, although it can produce some irregular cells along boundary surfaces. There is an optional stage of the meshing process which introduces additional layers of hexahedral cells aligned to the boundary surface as illustrated by the dark shaded cells in Figure 5.15.

The process of mesh layer addition involves shrinking the existing mesh from the boundary and inserting layers of cells, broadly as follows:

1. the mesh is projected back from the surface by a specified thickness in the direction normal to the surface;
2. solve for relaxation of the internal mesh with the latest projected boundary vertices;




Figure 5.13: Cell splitting by region in `snappyHexMesh` meshing process




Figure 5.14: Surface snapping in `snappyHexMesh` meshing process




Figure 5.15: Layer addition in `snappyHexMesh` meshing process

3. check if validation criteria are satisfied otherwise reduce the projected thickness and return to 2; if validation cannot be satisfied for any thickness, do not insert layers;
4. if the validation criteria can be satisfied, insert mesh layers;
5. the mesh is checked again; if the checks fail, layers are removed and we return to 2.

The layer addition procedure uses the settings in the `addLayersControls` sub-dictionary in `snappyHexMeshDict`; entries are listed in Table 5.10. The `layers` sub-dictionary contains

| Keyword | Description | Example |
|---|--|-------------------------|
| <code>layers</code> | Dictionary of layers | |
| <code>relativeSizes</code> | Are layer thicknesses relative to undistorted cell size outside layer or absolute? | <code>true/false</code> |
| <code>expansionRatio</code> | Expansion factor for layer mesh | 1.0 |
| <code>finalLayerThickness</code> | Thickness of layer furthest from the wall, either relative or absolute according to the <code>relativeSizes</code> entry | 0.3 |
| <code>minThickness</code> | Minimum thickness of cell layer, either relative or absolute (as above) | 0.25 |
| <code>nGrow</code> | Number of layers of connected faces that are not grown if points get not extruded; helps convergence of layer addition close to features | 1 |
| <code>featureAngle</code> | Angle above which surface is not extruded | 60 |
| <code>nRelaxIter</code> | Maximum number of snapping relaxation iterations | 5 |
| <code>nSmoothSurfaceNormals</code> | Number of smoothing iterations of surface normals | 1 |
| <code>nSmoothNormals</code> | Number of smoothing iterations of interior mesh movement direction | 3 |
| <code>nSmoothThickness</code> | Smooth layer thickness over surface patches | 10 |
| <code>maxFaceThicknessRatio</code> | Stop layer growth on highly warped cells | 0.5 |
| <code>maxThicknessTo-MedialRatio</code> | Reduce layer growth where ratio thickness to medial distance is large | 0.3 |
| <code>minMedianAxisAngle</code> | Angle used to pick up medial axis points | 130 |
| <code>nBufferCellsNoExtrude</code> | Create buffer region for new layer terminations | 0 |
| <code>nLayerIter</code> | Overall max number of layer addition iterations | 50 |
| <code>nRelaxedIter</code> | Max number of iterations after which the controls in the <code>relaxed</code> sub dictionary of <code>meshQuality</code> are used | 20 |

Table 5.10: Keywords in the `addLayersControls` sub-dictionary of `snappyHexMeshDict`.

entries for each *patch* on which the layers are to be applied and the number of surface layers required. The patch name is used because the layers addition relates to the existing mesh, not the surface geometry; hence applied to a patch, not a surface region. An example `layers` entry is as follows:

```

layers
{
  sphere.stl_firstSolid
  {
    nSurfaceLayers 1;
  }
  maxY
  {
    nSurfaceLayers 1;
  }
}

```

| Keyword | Description | Example |
|----------------------------------|---|---------------------------------------|
| <code>maxNonOrtho</code> | Maximum non-orthogonality allowed; 180 disables | 65 |
| <code>maxBoundarySkewness</code> | Max boundary face skewness allowed; <0 disables | 20 |
| <code>maxInternalSkewness</code> | Max internal face skewness allowed; <0 disables | 4 |
| <code>maxConcave</code> | Max concaveness allowed; 180 disables | 80 |
| <code>minFlatness</code> | Ratio of minimum projected area to actual area; -1 disables | 0.5 |
| <code>minVol</code> | Minimum pyramid volume; large negative number, <i>e.g.</i> -1e30 disables | 1e-13 |
| <code>minArea</code> | Minimum face area; <0 disables | -1 |
| <code>minTwist</code> | Minimum face twist; <-1 disables | 0.05 |
| <code>minDeterminant</code> | Minimum normalised cell determinant; 1 = hex; ≤ 0 illegal cell | 0.001 |
| <code>minFaceWeight</code> | 0→0.5 | 0.05 |
| <code>minVolRatio</code> | 0→1.0 | 0.01 |
| <code>minTriangleTwist</code> | >0 for Fluent compatability | -1 |
| <code>nSmoothScale</code> | Number of error distribution iterations | 4 |
| <code>errorReduction</code> | Amount to scale back displacement at error points | 0.75 |
| <code>relaxed</code> | Sub-dictionary that can include modified values for the above keyword entries to be used when <code>nRelaxedIter</code> is exceeded in the layer addition process | <code>relaxed</code> { ... } |

Table 5.11: Keywords in the *meshQualityControls* sub-dictionary of *snappyHexMeshDict*.

5.4.8 Mesh quality controls

The mesh quality is controlled by the entries in the *meshQualityControls* sub-dictionary in *snappyHexMeshDict*; entries are listed in Table 5.11.

5.5 Mesh conversion

The user can generate meshes using other packages and convert them into the format that OpenFOAM uses. There are numerous mesh conversion utilities listed in Table 3.6. Some of

the more popular mesh converters are listed below and their use is presented in this section.

`fluentMeshToFoam` reads a `Fluent.msh` mesh file, working for both 2-D and 3-D cases;

`starToFoam` reads STAR-CD/PROSTAR mesh files.

`gambitToFoam` reads a GAMBIT `.neu` neutral file;

`ideasToFoam` reads an I-DEAS mesh written in ANSYS `.ans` format;

`cfx4ToFoam` reads a CFX mesh written in `.geo` format;

5.5.1 `fluentMeshToFoam`

Fluent writes mesh data to a single file with a `.msh` extension. The file must be written in ASCII format, which is not the default option in `Fluent`. It is possible to convert single-stream `Fluent` meshes, including the 2 dimensional geometries. In `OpenFOAM`, 2 dimensional geometries are currently treated by defining a mesh in 3 dimensions, where the front and back plane are defined as the `empty` boundary patch type. When reading a 2 dimensional `Fluent` mesh, the converter automatically extrudes the mesh in the third direction and adds the empty patch, naming it `frontAndBackPlanes`.

The following features should also be observed.

- The `OpenFOAM` converter will attempt to capture the `Fluent` boundary condition definition as much as possible; however, since there is no clear, direct correspondence between the `OpenFOAM` and `Fluent` boundary conditions, the user should check the boundary conditions before running a case.
- Creation of axi-symmetric meshes from a 2 dimensional mesh is currently not supported but can be implemented on request.
- Multiple material meshes are not permitted. If multiple fluid materials exist, they will be converted into a single `OpenFOAM` mesh; if a solid region is detected, the converter will attempt to filter it out.
- `Fluent` allows the user to define a patch which is internal to the mesh, *i.e.* consists of the faces with cells on both sides. Such patches are not allowed in `OpenFOAM` and the converter will attempt to filter them out.
- There is currently no support for embedded interfaces and refinement trees.

The procedure of converting a `Fluent.msh` file is first to create a new `OpenFOAM` case by creating the necessary directories/files: the case directory containing a `controlDict` file in a `system` subdirectory. Then at a command prompt the user should execute:

```
fluentMeshToFoam <meshFile>
```

where `<meshFile>` is the name of the `.msh` file, including the full or relative path.

5.5.2 starToFoam

This section describes how to convert a mesh generated on the STAR-CD code into a form that can be read by OpenFOAM mesh classes. The mesh can be generated by any of the packages supplied with STAR-CD, *i.e.* PROSTAR, SAMM, ProAM and their derivatives. The converter accepts any single-stream mesh including integral and arbitrary couple matching and all cell types are supported. The features that the converter does not support are:

- multi-stream mesh specification;
- baffles, *i.e.* zero-thickness walls inserted into the domain;
- partial boundaries, where an uncovered part of a couple match is considered to be a boundary face;
- sliding interfaces.

For multi-stream meshes, mesh conversion can be achieved by writing each individual stream as a separate mesh and reassemble them in OpenFOAM.

OpenFOAM adopts a policy of only accepting input meshes that conform to the fairly stringent validity criteria specified in section 5.1. It will simply not run using invalid meshes and cannot convert a mesh that is itself invalid. The following sections describe steps that must be taken when generating a mesh using a mesh generating package supplied with STAR-CD to ensure that it can be converted to OpenFOAM format. To avoid repetition in the remainder of the section, the mesh generation tools supplied with STAR-CD will be referred to by the collective name STAR-CD.

5.5.2.1 General advice on conversion

We strongly recommend that the user run the STAR-CD mesh checking tools before attempting a `starToFoam` conversion and, after conversion, the `checkMesh` utility should be run on the newly converted mesh. Alternatively, `starToFoam` may itself issue warnings containing PROSTAR commands that will enable the user to take a closer look at cells with problems. Problematic cells and matches should be checked and fixed before attempting to use the mesh with OpenFOAM. Remember that an invalid mesh will not run with OpenFOAM, but it may run in another environment that does not impose the validity criteria.

Some problems of tolerance matching can be overcome by the use of a matching tolerance in the converter. However, there is a limit to its effectiveness and an apparent need to increase the matching tolerance from its default level indicates that the original mesh suffers from inaccuracies.

5.5.2.2 Eliminating extraneous data

When mesh generation is completed, remove any extraneous vertices and compress the cells boundary and vertex numbering, assuming that fluid cells have been created and all other cells are discarded. This is done with the following PROSTAR commands:

```
CSET NEWS FLUID
CSET INVE
```

The CSET should be empty. If this is not the case, examine the cells in CSET and adjust the model. If the cells are genuinely not desired, they can be removed using the PROSTAR command:

```
CDEL CSET
```

Similarly, vertices will need to be discarded as well:

```
CSET NEWS FLUID
VSET NEWS CSET
VSET INVE
```

Before discarding these unwanted vertices, the unwanted boundary faces have to be collected before purging:

```
CSET NEWS FLUID
VSET NEWS CSET
BSET NEWS VSET ALL
BSET INVE
```

If the BSET is not empty, the unwanted boundary faces can be deleted using:

```
BDEL BSET
```

At this time, the model should contain only the fluid cells and the supporting vertices, as well as the defined boundary faces. All boundary faces should be fully supported by the vertices of the cells, if this is not the case, carry on cleaning the geometry until everything is clean.

5.5.2.3 Removing default boundary conditions

By default, STAR-CD assigns wall boundaries to any boundary faces not explicitly associated with a boundary region. The remaining boundary faces are collected into a **default** boundary region, with the assigned boundary type 0. OpenFOAM deliberately does not have a concept of a **default** boundary condition for undefined boundary faces since it invites human error, *e.g.* there is no means of checking that we meant to give all the unassociated faces the default condition.

Therefore **all** boundaries for each OpenFOAM mesh must be specified for a mesh to be successfully converted. The **default** boundary needs to be transformed into a real one using the procedure described below:

1. Plot the geometry with **Wire Surface** option.
2. Define an extra boundary region with the same parameters as the **default** region 0 and add all visible faces into the new region, say 10, by selecting a zone option in the boundary tool and drawing a polygon around the entire screen draw of the model. This can be done by issuing the following commands in PROSTAR:

```
RDEF 10 WALL
BZON 10 ALL
```

3. We shall remove all previously defined boundary types from the set. Go through the boundary regions:

```
BSET NEWS REGI 1
BSET NEWS REGI 2
... 3, 4, ...
```

Collect the vertices associated with the boundary set and then the boundary faces associated with the vertices (there will be twice as many of them as in the original set).

```
BSET NEWS REGI 1
VSET NEWS BSET
BSET NEWS VSET ALL
BSET DELE REGI 1
REPL
```

This should give the faces of boundary Region 10 which have been defined on top of boundary Region 1. Delete them with `BDEL BSET`. Repeat these for all regions.

5.5.2.4 Renumbering the model

Renumber and check the model using the commands:

```
CSET NEW FLUID
CCOM CSET

VSET NEWS CSET
VSET INVE (Should be empty!)
VSET INVE
VCOM VSET

BSET NEWS VSET ALL
BSET INVE (Should be empty also!)
BSET INVE
BCOM BSET

CHECK ALL
GEOM
```

Internal PROSTAR checking is performed by the last two commands, which may reveal some other unforeseeable error(s). Also, take note of the scaling factor because PROSTAR only applies the factor for STAR-CD and not the geometry. If the factor is not 1, use the `scalePoints` utility in OpenFOAM.

5.5.2.5 Writing out the mesh data

Once the mesh is completed, place all the integral matches of the model into the couple type 1. All other types will be used to indicate arbitrary matches.

```
CPSET NEWS TYPE INTEGRAL
CPMOD CPSET 1
```

The components of the computational grid must then be written to their own files. This is done using PROSTAR for boundaries by issuing the command

```
BWRITE
```

by default, this writes to a `.23` file (versions prior to 3.0) or a `.bnd` file (versions 3.0 and higher). For cells, the command

```
CWRITE
```

outputs the cells to a `.14` or `.cel` file and for vertices, the command

```
VWRITE
```

outputs to file a `.15` or `.vrt` file. The current default setting writes the files in ASCII format. If couples are present, an additional couple file with the extension `.cpl` needs to be written out by typing:

```
CPWRITE
```

After outputting to the three files, exit PROSTAR or close the files. Look through the panels and take note of all STAR-CD sub-models, material and fluid properties used – the material properties and mathematical model will need to be set up by creating and editing OpenFOAM dictionary files.

The procedure of converting the PROSTAR files is first to create a new OpenFOAM case by creating the necessary directories. The PROSTAR files must be stored within the same directory and the user must change the file extensions: from `.23`, `.14` and `.15` (below STAR-CD version 3.0), or `.pcs`, `.cls` and `.vtx` (STAR-CD version 3.0 and above); to `.bnd`, `.cel` and `.vrt` respectively.

5.5.2.6 Problems with the `.vrt` file

The `.vrt` file is written in columns of data of specified width, rather than free format. A typical line of data might be as follows, giving a vertex number followed by the coordinates:

```
19422      -0.105988957      -0.413711881E-02  0.000000000E+00
```

If the ordinates are written in scientific notation and are negative, there may be no space between values, *e.g.*:

```
19423      -0.953953117E-01-0.338810333E-02  0.000000000E+00
```

The `starToFoam` converter reads the data using spaces to delimit the ordinate values and will therefore object when reading the previous example. Therefore, OpenFOAM includes a simple script, `foamCorrectVrt` to insert a space between values where necessary, *i.e.* it would convert the previous example to:

```
19423      -0.953953117E-01 -0.338810333E-02 0.000000000E+00
```

The `foamCorrectVrt` script should therefore be executed if necessary before running the `starToFoam` converter, by typing:

```
foamCorrectVrt <file>.vrt
```

5.5.2.7 Converting the mesh to OpenFOAM format

The translator utility `starToFoam` can now be run to create the boundaries, cells and points files necessary for a OpenFOAM run:

```
starToFoam <meshFilePrefix>
```

where `<meshFilePrefix>` is the name of the the prefix of the mesh files, including the full or relative path. After the utility has finished running, OpenFOAM boundary types should be specified by editing the *boundary* file by hand.

5.5.3 gambitToFoam

GAMBIT writes mesh data to a single file with a *.neu* extension. The procedure of converting a GAMBIT *.neu* file is first to create a new OpenFOAM case, then at a command prompt, the user should execute:

```
gambitToFoam <meshFile>
```

where `<meshFile>` is the name of the *.neu* file, including the full or relative path.

The GAMBIT file format does not provide information about type of the boundary patch, *e.g.* wall, symmetry plane, cyclic. Therefore all the patches have been created as type patch. Please reset after mesh conversion as necessary.

5.5.4 ideasToFoam

OpenFOAM can convert a mesh generated by I-DEAS but written out in ANSYS format as a *.ans* file. The procedure of converting the *.ans* file is first to create a new OpenFOAM case, then at a command prompt, the user should execute:

```
ideasToFoam <meshFile>
```

where `<meshFile>` is the name of the *.ans* file, including the full or relative path.

5.5.5 cfx4ToFoam

CFX writes mesh data to a single file with a `.geo` extension. The mesh format in CFX is block-structured, *i.e.* the mesh is specified as a set of blocks with glueing information and the vertex locations. OpenFOAM will convert the mesh and capture the CFX boundary condition as best as possible. The 3 dimensional ‘patch’ definition in CFX, containing information about the porous, solid regions *etc.* is ignored with all regions being converted into a single OpenFOAM mesh. CFX supports the concept of a ‘default’ patch, where each external face without a defined boundary condition is treated as a `wall`. These faces are collected by the converter and put into a `defaultFaces` patch in the OpenFOAM mesh and given the type `wall`; of course, the patch type can be subsequently changed.

Like, OpenFOAM 2 dimensional geometries in CFX are created as 3 dimensional meshes of 1 cell thickness. If a user wishes to run a 2 dimensional case on a mesh created by CFX, the boundary condition on the front and back planes should be set to `empty`; the user should ensure that the boundary conditions on all other faces in the plane of the calculation are set correctly. Currently there is no facility for creating an axi-symmetric geometry from a 2 dimensional CFX mesh.

The procedure of converting a CFX.`geo` file is first to create a new OpenFOAM case, then at a command prompt, the user should execute:

```
cfx4ToFoam <meshFile>
```

where `<meshFile>` is the name of the `.geo` file, including the full or relative path.

5.6 Mapping fields between different geometries

The `mapFields` utility maps one or more fields relating to a given geometry onto the corresponding fields for another geometry. It is completely generalised in so much as there does not need to be any similarity between the geometries to which the fields relate. However, for cases where the geometries are consistent, `mapFields` can be executed with a special option that simplifies the mapping process.

For our discussion of `mapFields` we need to define a few terms. First, we say that the data is mapped from the *source* to the *target*. The fields are deemed *consistent* if the geometry *and* boundary types, or conditions, of both source and target fields are identical. The field data that `mapFields` maps are those fields within the time directory specified by `startFrom/startTime` in the *controlDict* of the target case. The data is read from the equivalent time directory of the source case and mapped onto the equivalent time directory of the target case.

5.6.1 Mapping consistent fields

A mapping of consistent fields is simply performed by executing `mapFields` on the (target) case using the `-consistent` command line option as follows:

```
mapFields <source dir> -consistent
```

5.6.2 Mapping inconsistent fields

When the fields are not consistent, as shown in Figure 5.16, `mapFields` requires a `mapFieldsDict` dictionary in the `system` directory of the target case. The following rules apply to the mapping:

- the field data is mapped from source to target wherever possible, *i.e.* in our example all the field data within the target geometry is mapped from the source, except those in the shaded region which remain unaltered;
- the patch field data is left unaltered unless specified otherwise in the `mapFieldsDict` dictionary.

The `mapFieldsDict` dictionary contain two lists that specify mapping of patch data. The first list is `patchMap` that specifies mapping of data between pairs of source and target patches that are geometrically coincident, as shown in Figure 5.16. The list contains each pair of names of source and target patch. The second list is `cuttingPatches` that contains names of target patches whose values are to be mapped from the source internal field through which the target patch cuts. In the situation where the target patch only cuts through part of the source internal field, *e.g.* bottom left target patch in our example, those values within the internal field are mapped and those outside remain unchanged. An example `mapFieldsDict`




Figure 5.16: Mapping inconsistent fields

dictionary is shown below:

```

17 patchMap      ( lid movingWall );
18
19 cuttingPatches ( fixedWalls );
20
21
22 // *****
23 // *****

```

```
mapFields <source dir>
```

5.6.3 Mapping parallel cases

If either or both of the source and target cases are decomposed for running in parallel, additional options must be supplied when executing `mapFields`:

- parallelSource if the source case is decomposed for parallel running;
- parallelTarget if the target case is decomposed for parallel running.

Chapter 6

Post-processing

This chapter describes options for post-processing with OpenFOAM. OpenFOAM is supplied with a post-processing utility `paraFoam` that uses `ParaView`, an open source visualisation application described in section 6.1.

Other methods of post-processing using third party products are offered, including `EnSight`, `Fieldview` and the post-processing supplied with `Fluent`.

6.1 `paraFoam`

The main post-processing tool provided with OpenFOAM is a reader module to run with `ParaView`, an open-source, visualization application. The module is compiled into 2 libraries, `PV4FoamReader` and `vtkPV4Foam` using version 4.4.0 of `ParaView` supplied with the OpenFOAM release. It is recommended that this version of `ParaView` is used, although it is possible that the latest binary release of the software will run adequately. Further details about `ParaView` can be found at <http://www.paraview.org>.

`ParaView` uses the Visualisation Toolkit (VTK) as its data processing and rendering engine and can therefore read any data in VTK format. OpenFOAM includes the `foamToVTK` utility to convert data from its native format to VTK format, which means that any VTK-based graphics tools can be used to post-process OpenFOAM cases. This provides an alternative means for using `ParaView` with OpenFOAM.

In summary, we recommend the reader module for `ParaView` as the primary post-processing tool for OpenFOAM. Alternatively OpenFOAM data can be converted into VTK format to be read by `ParaView` or any other VTK -based graphics tools.

6.1.1 Overview of `paraFoam`

`paraFoam` is strictly a script that launches `ParaView` using the reader module supplied with OpenFOAM. It is executed like any of the OpenFOAM utilities either by the single command from within the case directory or with the `-case` option with the case path as an argument, *e.g.*:

```
paraFoam -case <caseDir>
```

`ParaView` is launched and opens the window shown in Figure 6.1. The case is controlled from the left panel, which contains the following:




Figure 6.1: The paraFoam window

Pipeline Browser lists the *modules* opened in ParaView, where the selected modules are highlighted in blue and the graphics for the given module can be enabled/disabled by clicking the eye button alongside;

Properties panel contains the input selections for the case, such as times, regions and fields; it includes the **Display** panel that controls the visual representation of the selected module, *e.g.* colours;

Other panels can be selected from the **View** menu, including the **Information** panel which gives case statistics such as mesh geometry and size.

ParaView operates a tree-based structure in which data can be filtered from the top-level case module to create sets of sub-modules. For example, a contour plot of, say, pressure could be a sub-module of the case module which contains all the pressure data. The strength of ParaView is that the user can create a number of sub-modules and display whichever ones they feel to create the desired image or animation. For example, they may add some solid geometry, mesh and velocity vectors, to a contour plot of pressure, switching any of the items on and off as necessary.

The general operation of the system is based on the user making a selection and then clicking the green **Apply** button in the **Properties** panel. The additional buttons are: the **Reset** button which can be used to reset the GUI if necessary; and, the **Delete** button that will delete the active module.

6.1.2 The Parameters panel

The Properties window for the case module includes the Parameters panel that contains the settings for mesh, fields and global controls. The controls are described in Figure 6.2. The




Figure 6.2: The Properties panel for the case module

user can select mesh and field data which is loaded for all time directories into **ParaView**. The buttons in the **Current Time Controls** and **VCR Controls** toolbars then select the time data to be displayed, as shown in section 6.1.4.

As with any operation in **paraFoam**, the user must click **Apply** after making any changes to any selections. The **Apply** button is highlighted in green to alert the user if changes have been made but not accepted. This method of operation has the advantage of allowing the user to make a number of selections before accepting them, which is particularly useful in large cases where data processing is best kept to a minimum.

If new data is written to time directories while the user is running **ParaView**, the user must load the additional time directories by checking the **Refresh Times** button. Where there are occasions when the case data changes on file and **ParaView** needs to load the changes, the user can also check the **Update GUI** button in the **Parameters** panel and apply the changes.




Figure 6.3: The Display panel

6.1.3 The Display panel

The Properties window contains the Display panel that includes the settings for visualising the data for a given case module. The following points are particularly important:

- the data range may not be automatically updated to the max/min limits of a field, so the user should take care to select **Rescale** at appropriate intervals, in particular after loading the initial case module;
- clicking the **Edit Color Map** button, brings up a window in which there are two panels:

1. The **Color Scale** panel in which the colours within the scale can be chosen. The standard blue to red colour scale for CFD can be selected by clicking **Choose Preset** and selecting **Blue to Red Rainbow HSV**.
 2. The **Color Legend** panel has a toggle switch for a colour bar legend and contains settings for the layout of the legend, *e.g.* font.
- the underlying mesh can be represented by selecting **Wireframe** in the **Representation** menu of the **Style** panel;
 - the geometry, *e.g.* a mesh (if **Wireframe** is selected), can be visualised as a single colour by selecting **Solid Color** from the **Color By** menu and specifying the colour in the **Set Ambient Color** window;
 - the image can be made translucent by editing the value in the **Opacity** text box (1 = solid, 0 = invisible) in the **Style** panel.

6.1.4 The button toolbars

ParaView duplicates functionality from pull-down menus at the top of the main window and the major panels, within the toolbars below the main pull-down menus. The displayed toolbars can be selected from **Toolbars** in the main **View** menu. The default layout with all toolbars is shown in Figure 6.4 with each toolbar labelled. The function of many of the buttons is clear from their icon and, with tooltips enabled in the **Help** menu, the user is given a concise description of the function of any button.




Figure 6.4: Toolbars in ParaView

6.1.5 Manipulating the view

This section describes operations for setting and manipulating the view of objects in **paraFoam**.

6.1.5.1 View settings

The **View Settings** are available in the **Render View** panel below the **Display** panel in the **Properties** window. Settings that are generally important only appear when the user checks the gearwheel button at the top of the **Properties** window, next to the search bar. These *advanced properties* include setting the background colour, where white is often a preferred choice for creating images for printed and website material.

The **Lights** button opens detailed lighting controls within the **Light Kit** panel. A separate **Headlight** panel controls the direct lighting of the image. Checking the **Headlight** button with white light colour of strength 1 seems to help produce images with strong bright colours, e.g. with an isosurface.

The **Camera Parallel Projection** is the usual choice for CFD, especially for 2D cases, and so should generally be checked. Other settings include **Cube Axes** which displays axes on the selected object to show its orientation and geometric dimensions.

6.1.5.2 General settings

The general **Settings** are selected from the **Edit** menu, which opens a general **Options** window with **General**, **Colors**, **Animations**, **Charts** and **Render View** menu items.

The **General** panel controls some default behaviour of **ParaView**. In particular, there is an **Auto Accept** button that enables **ParaView** to accept changes automatically without clicking the green **Apply** button in the **Properties** window. For larger cases, this option is generally not recommended: the user does not generally want the image to be re-rendered between each of a number of changes he/she selects, but be able to apply a number of changes to be re-rendered in their entirety once.

The **Render View** panel contains 3 sub-items: **General**, **Camera** and **Server**. The **General** panel includes the level of detail (LOD) which controls the rendering of the image while it is being manipulated, e.g. translated, resized, rotated; lowering the levels set by the sliders, allows cases with large numbers of cells to be re-rendered quickly during manipulation.

The **Camera** panel includes control settings for 3D and 2D movements. This presents the user with a map of rotation, translate and zoom controls using the mouse in combination with Shift- and Control-keys. The map can be edited to suit by the user.

6.1.6 Contour plots

A contour plot is created by selecting **Contour** from the **Filter** menu at the top menu bar. The filter acts on a given module so that, if the module is the 3D case module itself, the contours will be a set of 2D surfaces that represent a constant value, *i.e.* isosurfaces. The **Properties** panel for contours contains an **Isosurfaces** list that the user can edit, most conveniently by the **New Range** window. The chosen scalar field is selected from a pull down menu.

6.1.6.1 Introducing a cutting plane

Very often a user will wish to create a contour plot across a plane rather than producing isosurfaces. To do so, the user must first use the **Slice** filter to create the cutting plane, on which the contours can be plotted. The **Slice** filter allows the user to specify a cutting **Plane**, **Box** or **Sphere** in the **Slice Type** menu by a **center** and **normal/radius** respectively. The user can manipulate the cutting plane like any other using the mouse.

The user can then run the **Contour** filter on the cut plane to generate contour lines.

6.1.7 Vector plots

Vector plots are created using the **Glyph** filter. The filter reads the field selected in **Vectors** and offers a range of **Glyph Types** for which the **Arrow** provides a clear vector plot images.

Each glyph has a selection of graphical controls in a panel which the user can manipulate to best effect.

The remainder of the **Properties** panel contains mainly the **Scale Mode** menu for the glyphs. The most common options are **Scale Mode** are: **Vector**, where the glyph length is proportional to the vector magnitude; and, **Off** where each glyph is the same length. The **Set Scale Factor** parameter controls the base length of the glyphs.

6.1.7.1 Plotting at cell centres

Vectors are by default plotted on cell vertices but, very often, we wish to plot data at cell centres. This is done by first applying the **Cell Centers** filter to the case module, and then applying the **Glyph** filter to the resulting cell centre data.

6.1.8 Streamlines

Streamlines are created by first creating tracer lines using the **Stream Tracer** filter. The tracer **Seed** panel specifies a distribution of tracer points over a **Line Source** or **Point Cloud**. The user can view the tracer source, *e.g.* the line, but it is displayed in white, so they may need to change the background colour in order to see it.

The distance the tracer travels and the length of steps the tracer takes are specified in the text boxes in the main **Stream Tracer** panel. The process of achieving desired tracer lines is largely one of trial and error in which the tracer lines obviously appear smoother as the step length is reduced but with the penalty of a longer calculation time.

Once the tracer lines have been created, the **Tubes** filter can be applied to the *Tracer* module to produce high quality images. The tubes follow each tracer line and are not strictly cylindrical but have a fixed number of sides and given radius. When the number of sides is set above, say, 10, the tubes do however appear cylindrical, but again this adds a computational cost.

6.1.9 Image output

The simplest way to output an image to file from **ParaView** is to select **Save Screenshot** from the **File** menu. On selection, a window appears in which the user can select the resolution for the image to save. There is a button that, when clicked, locks the aspect ratio, so if the user changes the resolution in one direction, the resolution is adjusted in the other direction automatically. After selecting the pixel resolution, the image can be saved. To achieve high quality output, the user might try setting the pixel resolution to 1000 or more in the *x*-direction so that when the image is scaled to a typical size of a figure in an A4 or US letter document, perhaps in a PDF document, the resolution is sharp.

6.1.10 Animation output

To create an animation, the user should first select **Save Animation** from the **File** menu. A dialogue window appears in which the user can specify a number of things including the image resolution. The user should specify the resolution as required. The other noteworthy setting is number of frames per timestep. While this would intuitively be set to 1, it can be set to a larger number in order to introduce more frames into the animation artificially.

This technique can be particularly useful to produce a slower animation because some movie players have limited speed control, particularly over `mpeg` movies.

On clicking the **Save Animation** button, another window appears in which the user specifies a file name *root* and file format for a set of images. On clicking OK, the set of files will be saved according to the naming convention “<fileRoot>_<imageNo>.<fileExt>”, *e.g.* the third image of a series with the file root “animation”, saved in `jpg` format would be named “animation_0002.jpg” (<imageNo> starts at 0000).

Once the set of images are saved the user can convert them into a movie using their software of choice. One option is to use the built in `foamCreateVideo` script from the command line whose usage is shown with the `-help` option.

6.2 Function Objects

OpenFOAM provides functionality that can be executed during a simulation by the user at run-time through a configuration in the *controlDict* file. For example, a user may wish to run a steady-state, incompressible, turbulent flow simulation of aerodynamics around a vehicle and from that simulation they wish to calculate the drag coefficient. While the simulation is performed by the `simpleFoam` solver, the additional force calculation for drag coefficient is included in a tool, called a *function object*, that can be requested by the user to be executed at certain times during the simulation.

| Function object | Description |
|-------------------------------------|--|
| <code>cellSource</code> | performs operations on cell values, <i>e.g.</i> sums, averages and integrations |
| <code>faceSource</code> | performs operations on face values, <i>e.g.</i> sums, averages and integrations |
| <code>fieldMinMax</code> | writes min/max values of fields |
| <code>fieldValue</code> | averaging/integration across sets of faces/cells, <i>e.g.</i> for flux across a plane |
| <code>fieldValueDelta</code> | Provides differencing between two <code>fieldValue</code> function objects, <i>e.g.</i> to calculate pressure drop |
| <code>forces</code> | calculates pressure/viscous forces and moments |
| <code>forceCoeffs</code> | calculates lift, drag and moment coefficients |
| <code>regionSizeDistribution</code> | creates a size distribution via interrogating a continuous phase fraction |
| <code>sampledSet</code> | data sampling along lines, <i>e.g.</i> for graph plotting |
| <code>probes</code> | data probing at point locations |
| <code>residuals</code> | writes initial residuals for selected fields |

Table 6.1: Function objects writing time-value data for monitoring/plotting

A large number of function objects exist in OpenFOAM that perform mainly a range of post-processing calculations but also some job control activities. Function objects can be broken down into the following categories.

- Table 6.1: write out tabulated data, typically containing time-values, usually at regular time intervals, for plotting graphs and/or monitoring, *e.g.* force coefficients.

| Function object | Description |
|---------------------------------|---|
| fieldAverage | temporal averaging of fields |
| writeRegistered-Object | writes fields that are not scheduled to be written |
| fieldCoordinate-SystemTransform | transforms fields between global to local co-ordinate system |
| turbulenceFields | stores turbulence fields on the mesh database |
| calcFvcDiv | calculates the divergence of a field |
| calcFvcGrad | calculates the gradient of a field |
| calcMag | calculates the magnitude of a field |
| CourantNo | outputs the Courant number field |
| Lambda2 | outputs Lambda2 |
| Peclet | outputs the Peclet number field |
| pressureTools | calculate pressure in different forms, static, total, <i>etc.</i> |
| Q | second invariant of the velocity gradient |
| vorticity | calculates vorticity field |
| processorField | writes a field of the local processor ID |
| partialWrite | allows registered objects to be written at specified times |
| readFields | reads fields from the time directories and adds to database |
| blendingFactor | outputs the blending factor used by the convection schemes |
| DESModelRegions | writes out an indicator field for DES turbulence |

Table 6.2: Function objects for writing/reading fields, typically writing to time directories

| Function object | Description |
|-----------------|--|
| nearWallFields | writes fields in cells adjacent to patches |
| wallShearStress | evaluates and outputs the shear stress at wall patches |
| yPlusLES | outputs turbulence y^+ for LES models |
| yPlusRAS | outputs turbulence y^+ for RAS models |

Table 6.3: Function objects for near wall fields

- Table 6.2: write out field data, usually at the normal time interval for writing fields into time directories.
- Table 6.3: write out field data on boundary patches, *e.g.* wall shear stress, usually at the time interval for writing fields into time directories.
- Table 6.4: write out image files, *e.g.* iso-surface for visualization.
- Table 6.5: function objects that manage job control, supplementary simulation, *etc.*

6.2.1 Using function objects

Function objects are specified in the *controlDict* file of a case through a dictionary named *functions*. One or more function objects can be specified, each within its own sub-dictionary. An example of specification of 2 function objects is shown below:

| Function object | Description |
|------------------------------------|---|
| <code>streamline</code> | streamline data from sampled fields |
| <code>surfaces</code> | iso-surfaces, cutting planes, patch surfaces, with field data |
| <code>wallBoundedStreamline</code> | streamlines constrained to a boundary patch |

Table 6.4: Function objects for creating post-processing images

| Function object | Description |
|--|---|
| <code>timeActivatedFile-Update</code> | modifies case settings at specified times in a simulation |
| <code>abortCalculation</code> | aborts simulation when named file appears in the case directory |
| <code>removeRegistered-Object</code> | removes specified registered objects in the database |
| <code>setTimeStepFunctionObject</code> | enables manual over-ride of the time step |
| <code>codedFunctionObject</code> | function object coded with <code>#codeStream</code> |
| <code>cloudInfo</code> | outputs Lagrangian cloud information |
| <code>scalarTransport</code> | solves a passive scalar transport equation |
| <code>systemCall</code> | makes any call to the system, <i>e.g.</i> sends an email |

Table 6.5: Miscellaneous function objects

```

functions
{
    pressureProbes
    {
        type                probes;
        functionObjectLibs ("libsampling.so");
        outputControl       timeStep;
        outputInterval      1;
        probeLocations
        (
            ( 1 0 0 )
            ( 2 0 0 )
        );
        fields
        (
            p
        );
    }

    meanVelocity
    {
        type                fieldAverage;
        functionObjectLibs ( "libfieldFunctionObjects.so" );
    }
}

```

```

        outputControl    outputTime;
        fields
        (
            U
            {
                mean        on;
                prime2Mean  off;
                base        time;
            }
        );
    }
}

```

For each function object, there are some mandatory keyword entries.

name Every function object requires a unique name, here `pressureProbes` and `meanVelocity` are used. The names can be used for naming output files and/or directories.

type The type of function object, *e.g.* `probes`.

functionObjectLibs A list of additional libraries that may need to be dynamically linked at run-time to access the relevant functionality. For example the `forceCoeffs` function object is compiled into the `libforces.so` library, so force coefficients cannot be calculated without linking that library.

outputControl Specifies when data should be calculated and output. Options are: `timeStep`, when data is output each `writeInterval` time steps; and, `outputTime` when data is written at scheduled times, *i.e.* when fields are written to time directories.

The remaining entries in the example above are specific to the particular function object. For example `probeLocations` describes the locations where pressure values are probed. For any other function object, how can the user find out the specific keyword entries required? One option is to access the code C++ documentation at either <http://openfoam.org/-docs/cpp> or <http://openfoam.github.io/Documentation-dev/html> and click the **post-processing** link. This takes the user to a set of lists of function objects, the class description of each function object providing documentation on its use.

Alternatively the user can scan the cases in `$FOAM_TUTORIALS` directory for examples of function objects in use. The `find` and `grep` command can help to locate relevant examples, *e.g.*

```
find $FOAM_TUTORIALS -name controlDict | xargs grep -l functions
```

6.2.2 Packaged function objects

From OpenFOAM v2.4, commonly used function objects are “packaged” in the distribution in `$FOAM_ETC/caseDicts/postProcessing`. The tools range from quite generic, *e.g.* `minMax` to monitor min and max values of a field, to some more application-oriented, *e.g.* `flowRate` to monitor flow rate.

The configuration of function objects includes both required input data and control parameters for the function object. This creates a lot of input that can be confusing to users. The packaged function objects separate the user input from control parameters. Control parameters are pre-configured in files with *.cfg* extension. For each tool, required user input is all in one file, for the users to copy into their case and set accordingly.

The tools can be used as follows, using an example of monitoring flow rate at an outlet patch named *outlet*.

1. Locate the *flowRatePatch* tool in the *flowRate* directory:
`$FOAM_ETC/caseDicts/postProcessing/flowRate`
2. Copy the *flowRatePatch* file into the case *system* directory (not *flowRatePatch.cfg*)
3. Edit *system/flowRatePatch* to set the patch name, replacing “patch <patchName>;” with “patch *outlet*;;”
4. Activate the function object by including the *flowRatePatch* file in functions sub-dictionary in the case *controlDict* file, *e.g.*

```
functions
{
    #include "flowRatePatch"
    ... other function objects here ...
}
```

Current packaged function objects are found in the following directories:

- *fields* calculate specific fields, *e.g.* *Q*
- *flowRate*: tools to calculate flow rate
- *forces*: forces and force coefficients for incompressible/compressible flows
- *graphs*: simple sampling for graph plotting, *e.g.* *singleGraph*
- *minMax*: range of minimum and maximum field monitoring, *e.g.* *cellMax*
- *numerical*: outputs information relating to numerics, *e.g.* *residuals*
- *pressure*: calculates different forms of pressure, pressure drop, etc
- *probes*: options for probing data
- *scalarTransport*: for plugin scalar transport calculations
- *visualization*: post-processing VTK files for cutting planes, streamlines, *etc.*
- *faceSource*: configuration for some of the tools above

6.3 Post-processing with Fluent

It is possible to use **Fluent** as a post-processor for the cases run in **OpenFOAM**. Two converters are supplied for the purpose: `foamMeshToFluent` which converts the **OpenFOAM** mesh into **Fluent** format and writes it out as a `.msh` file; and, `foamDataToFluent` converts the **OpenFOAM** results data into a `.dat` file readable by **Fluent**. `foamMeshToFluent` is executed in the usual manner. The resulting mesh is written out in a `fluentInterface` subdirectory of the case directory, *i.e.* `<caseName>/fluentInterface/<caseName>.msh`

`foamDataToFluent` converts the **OpenFOAM** data results into the **Fluent** format. The conversion is controlled by two files. First, the `controlDict` dictionary specifies `startTime`, giving the set of results to be converted. If you want to convert the latest result, `startFrom` can be set to `latestTime`. The second file which specifies the translation is the `foamDataToFluentDict` dictionary, located in the `constant` directory. An example `foamDataToFluentDict` dictionary is given below:

```

1  /*-----*- C++ -*-----*/
2  |=====|
3  |  \ \  /  F i e l d           | OpenFOAM: The Open Source CFD Toolbox
4  |  \ \  /  O p e r a t i o n   | Version:  3.0.1
5  |  \ \  /  A n d                | Web:      www.OpenFOAM.org
6  |  \ \  /  M a n i p u l a t i o n |
7  /*-----*- C++ -*-----*/
8  FoamFile
9  {
10     version      2.0;
11     format       ascii;
12     class        dictionary;
13     location     "system";
14     object       foamDataToFluentDict;
15 }
16 // ***** //
17
18 p                1;
19
20 U                2;
21
22 T                3;
23
24 h                4;
25
26 k                5;
27
28 epsilon          6;
29
30 alpha1           150;
31
32
33 // ***** //

```

The dictionary contains entries of the form

```
<fieldName> <fluentUnitNumber>
```

The `<fluentUnitNumber>` is a label used by the **Fluent** post-processor that only recognises a fixed set of fields. The basic set of `<fluentUnitNumber>` numbers are quoted in Table 6.6. The dictionary must contain all the entries the user requires to post-process, *e.g.* in our example we have entries for pressure `p` and velocity `U`. The list of default entries described in Table 6.6. The user can run `foamDataToFluent` like any utility.

To view the results using **Fluent**, go to the `fluentInterface` subdirectory of the case directory and start a 3 dimensional version of **Fluent** with

```
fluent 3d
```

| Fluent name | Unit number | Common OpenFOAM name |
|-------------------|-------------|----------------------|
| PRESSURE | 1 | p |
| MOMENTUM | 2 | U |
| TEMPERATURE | 3 | T |
| ENTHALPY | 4 | h |
| TKE | 5 | k |
| TED | 6 | epsilon |
| SPECIES | 7 | — |
| G | 8 | — |
| XF_RF_DATA_VOF | 150 | gamma |
| TOTAL_PRESSURE | 192 | — |
| TOTAL_TEMPERATURE | 193 | — |

Table 6.6: Fluent unit numbers for post-processing.

The mesh and data files can be loaded in and the results visualised. The mesh is read by selecting **Read Case** from the **File** menu. Support items should be selected to read certain data types, *e.g.* to read turbulence data for **k** and **epsilon**, the user would select **k-epsilon** from the **Define->Models->Viscous** menu. The data can then be read by selecting **Read Data** from the **File** menu.

A note of caution: users **MUST NOT** try to use an original **Fluent** mesh file that has been converted to OpenFOAM format in conjunction with the OpenFOAM solution that has been converted to **Fluent** format since the alignment of zone numbering cannot be guaranteed.

6.4 Post-processing with Fieldview

OpenFOAM offers the capability for post-processing OpenFOAM cases with **Fieldview**. The method involves running a post-processing utility **foamToFieldview** to convert case data from OpenFOAM to **Fieldview.uns** file format. For a given case, **foamToFieldview** is executed like any normal application. **foamToFieldview** creates a directory named *Fieldview* in the case directory, *deleting any existing Fieldview directory in the process*. By default the converter reads the data in all time directories and writes into a set of files of the form `<case>_nn.uns`, where *nn* is an incremental counter starting from 1 for the first time directory, 2 for the second and so on. The user may specify the conversion of a single time directory with the option `-time <time>`, where `<time>` is a time in general, scientific or fixed format.

Fieldview provides certain functions that require information about boundary conditions, *e.g.* drawing streamlines that uses information about wall boundaries. The converter tries, wherever possible, to include this information in the converted files by default. The user can disable the inclusion of this information by using the `-noWall` option in the execution command.

The data files for **Fieldview** have the *.uns* extension as mentioned already. If the original OpenFOAM case includes a dot '.', **Fieldview** may have problems interpreting a set of data files as a single case with multiple time steps.

6.5 Post-processing with EnSight

OpenFOAM offers the capability for post-processing OpenFOAM cases with EnSight, with a choice of 2 options:

- converting the OpenFOAM data to EnSight format with the `foamToEnSight` utility;
- reading the OpenFOAM data directly into EnSight using the `ensight74FoamExec` module.

6.5.1 Converting data to EnSight format

The `foamToEnSight` utility converts data from OpenFOAM to EnSight file format. For a given case, `foamToEnSight` is executed like any normal application. `foamToEnSight` creates a directory named *EnSight* in the case directory, *deleting any existing EnSight directory in the process*. The converter reads the data in all time directories and writes into a case file and a set of data files. The case file is named *EnSight_Case* and contains details of the data file names. Each data file has a name of the form *EnSight_nn.ext*, where *nn* is an incremental counter starting from 1 for the first time directory, 2 for the second and so on and *ext* is a file extension of the name of the field that the data refers to, as described in the case file, *e.g.* `T` for temperature, `mesh` for the mesh. Once converted, the data can be read into EnSight by the normal means:

1. from the EnSight GUI, the user should select **Data (Reader)** from the **File** menu;
2. the appropriate *EnSight_Case* file should be highlighted in the **Files** box;
3. the **Format** selector should be set to **Case**, the EnSight default setting;
4. the user should click **(Set) Case** and **Okay**.

6.5.2 The `ensight74FoamExec` reader module

EnSight provides the capability of using a user-defined module to read data from a format other than the standard EnSight format. OpenFOAM includes its own reader module `ensight74FoamExec` that is compiled into a library named `libuserd-foam`. It is this library that EnSight needs to use which means that it must be able to locate it on the filing system as described in the following section.

6.5.2.1 Configuration of EnSight for the reader module

In order to run the EnSight reader, it is necessary to set some environment variables correctly. The settings are made in the `bashrc` (or `cshrc`) file in the `$WM_PROJECT_DIR/etc/apps/-ensightFoam` directory. The environment variables associated with EnSight are prefixed by `$CEI_` or `$ENSIGHT7_` and listed in Table 6.7. With a standard user setup, only `$CEI_HOME` may need to be set manually, to the path of the EnSight installation.

| Environment variable | Description and options |
|--------------------------------|--|
| <code>\$CEI_HOME</code> | Path where EnSight is installed, eg <code>/usr/local/ensight</code> , added to the system path by default |
| <code>\$CEI_ARCH</code> | Machine architecture, from a choice of names corresponding to the machine directory names in <code>\$CEI_HOME/ensight74/machines</code> ; default settings include <code>linux_2.4</code> and <code>sgi_6.5_n32</code> |
| <code>\$ENSIGHT7_READER</code> | Path that EnSight searches for the user defined libuserd-foam reader library, set by default to <code>\$FOAM_LIBBIN</code> |
| <code>\$ENSIGHT7_INPUT</code> | Set by default to <code>dummy</code> |

Table 6.7: Environment variable settings for EnSight.

6.5.2.2 Using the reader module

The principal difficulty in using the EnSight reader lies in the fact that EnSight expects that a case to be defined by the contents of a particular file, rather than a directory as it is in OpenFOAM. Therefore in following the instructions for the using the reader below, the user should pay particular attention to the details of case selection, since EnSight does not permit selection of a directory name.

1. from the EnSight GUI, the user should select **Data (Reader)** from the **File** menu;
2. The user should now be able to select the **OpenFOAM** from the **Format** menu; if not, there is a problem with the configuration described above.
3. The user should find their case directory from the **File Selection** window, highlight one of top 2 entries in the **Directories** box ending in `/.` or `/..` and click **(Set) Geometry**.
4. The path field should now contain an entry for the case. The **(Set) Geometry** text box should contain a `'/'`.
5. The user may now click **Okay** and EnSight will begin reading the data.
6. When the data is read, a new **Data Part Loader** window will appear, asking which part(s) are to be read. The user should select **Load all**.
7. When the mesh is displayed in the EnSight window the user should close the **Data Part Loader** window, since some features of EnSight will not work with this window open.

6.6 Sampling data

OpenFOAM provides the `sample` utility to sample field data, either through a 1D line for plotting on graphs or a 2D plane for displaying as isosurface images. The sampling locations are specified for a case through a *sampleDict* dictionary in the case *system* directory. The data can be written in a range of formats including well-known graphing packages such as `Grace/xmgr`, `gnuplot` and `jPlot`.

The *sampleDict* dictionary can be generated by copying an example *sampleDict* from the `sample` source code directory at `$FOAM_UTILITIES/postProcessing/sampling/sample`. The

plateHole tutorial case in the `$FOAM_TUTORIALS/solidDisplacementFoam` directory also contains an example for 1D line sampling:

```

17 interpolationScheme cellPoint;
18
19 setFormat      raw;
20
21 sets
22 (
23   leftPatch
24   {
25     type      uniform;
26     axis      y;
27     start     (0 0.5 0.25);
28     end       (0 2 0.25);
29     nPoints   100;
30   }
31 );
32
33 fields         (sigmaEq);
34
35
36 // ***** //

```

| Keyword | Options | Description |
|---------------------|---|--|
| interpolationScheme | cell | Cell-centre value assumed constant over cell |
| | cellPoint | Linear weighted interpolation using cell values |
| | cellPointFace | Mixed linear weighted / cell-face interpolation |
| setFormat | raw | Raw ASCII data in columns |
| | gnuplot | Data in gnuplot format |
| | xmgr | Data in Grace/xmgr format |
| | jplot | Data in jPlot format |
| | surfaceFormat | null |
| fields | foamFile | <i>points, faces, values</i> file |
| | dx | DX scalar or vector format |
| | vtk | VTK ASCII format |
| | raw | <i>xyz</i> values for use with <i>e.g.gnuplotsplot</i> |
| | stl | ASCII STL; just surface, no values |
| | U | Writes all components of U |
| sets | List of 1D sets subdictionaries — see Table 6.9 | |
| surfaces | List of 2D surfaces subdictionaries — see Table 6.10 and Table 6.11 | |

Table 6.8: keyword entries for *sampleDict*.

The dictionary contains the following entries:

interpolationScheme the scheme of data interpolation;

sets the locations within the domain that the fields are line-sampled (1D).

surfaces the locations within the domain that the fields are surface-sampled (2D).

setFormat the format of line data output;

`surfaceFormat` the format of surface data output;

`fields` the fields to be sampled;

The `interpolationScheme` includes `cellPoint` and `cellPointFace` options in which each polyhedral cell is decomposed into tetrahedra and the sample values are interpolated from values at the tetrahedra vertices. With `cellPoint`, the tetrahedra vertices include the polyhedron cell centre and 3 face vertices. The vertex coincident with the cell centre inherits the cell centre field value and the other vertices take values interpolated from cell centres. With `cellPointFace`, one of the tetrahedra vertices is also coincident with a face centre, which inherits field values by conventional interpolation schemes using values at the centres of cells that the face intersects.

The `setFormat` entry for line sampling includes a raw data format and formats for `gnuplot`, `Grace/xmgr` and `jPlot` graph drawing packages. The data are written into a `sets` directory within the case directory. The directory is split into a set of time directories and the data files are contained therein. Each data file is given a name containing the field name, the sample set name, and an extension relating to the output format, including `.xy` for raw data, `.agr` for `Grace/xmgr` and `.dat` for `jPlot`. The `gnuplot` format has the data in raw form with an additional commands file, with `.gplt` extension, for generating the graph. *Note that any existing `sets` directory is deleted when `sample` is run.*

The `surfaceFormat` entry for surface sampling includes a raw data format and formats for `gnuplot`, `Grace/xmgr` and `jPlot` graph drawing packages. The data are written into a `surfaces` directory within the case directory. The directory is split into time directories and files are written much as with line sampling.

The `fields` list contains the fields that the user wishes to sample. The `sample` utility can parse the following restricted set of functions to enable the user to manipulate vector and tensor fields, *e.g.* for `U`:

`U.component(n)` writes the *n*th component of the vector/tensor, $n = 0, 1 \dots$;

`mag(U)` writes the magnitude of the vector/tensor.

The `sets` list contains sub-dictionaries of locations where the data is to be sampled. The sub-dictionary is named according to the name of the set and contains a set of entries, also listed in Table 6.9, that describes the locations where the data is to be sampled. For example, a `uniform` sampling provides a uniform distribution of `nPoints` sample locations along a line specified by a `start` and `end` point. All sample sets are also given: a `type`; and, means of specifying the length ordinate on a graph by the `axis` keyword.

The `surfaces` list contains sub-dictionaries of locations where the data is to be sampled. The sub-dictionary is named according to the name of the surface and contains a set of entries beginning with the `type`: either a `plane`, defined by point and normal direction, with additional sub-dictionary entries specified in Table 6.10; or, a `patch`, coinciding with an existing boundary patch, with additional sub-dictionary entries a specified in Table 6.11.

6.7 Monitoring and managing jobs

This section is concerned primarily with successful running of OpenFOAM jobs and extends on the basic execution of solvers described in section 3.3. When a solver is executed, it reports the status of equation solution to standard output, *i.e.* the screen, if the `level`

| Sampling type | Sample locations | Required entries | | | | | |
|-----------------|---|------------------|------|-------|-----|---------|--------|
| | | name | axis | start | end | nPoints | points |
| uniform | Uniformly distributed points on a line | • | • | • | • | • | |
| face | Intersection of specified line and cell faces | • | • | • | • | | |
| midPoint | Midpoint between line-face intersections | • | • | • | • | | |
| midPointAndFace | Combination of midPoint and face | • | • | • | • | | |
| curve | Specified points, tracked along a curve | • | • | | | | • |
| cloud | Specified points | • | • | | | | • |

| Entries | Description | Options |
|---------|----------------------------|---|
| type | Sampling type | see list above |
| axis | Output of sample location | x x ordinate y y ordinate z z ordinate xyz xyz coordinates distance distance from point 0 |
| start | Start point of sample line | <i>e.g.</i> (0.0 0.0 0.0) |
| end | End point of sample line | <i>e.g.</i> (0.0 2.0 0.0) |
| nPoints | Number of sampling points | <i>e.g.</i> 200 |
| points | List of sampling points | |

Table 6.9: Entries within `sets` sub-dictionaries.

| Keyword | Description | Options |
|--------------|---------------------------------|---------------------|
| basePoint | Point on plane | <i>e.g.</i> (0 0 0) |
| normalVector | Normal vector to plane | <i>e.g.</i> (1 0 0) |
| interpolate | Interpolate data? | true/false |
| triangulate | Triangulate surface? (optional) | true/false |

Table 6.10: Entries for a `plane` in `surfaces` sub-dictionaries.

debug switch is set to 1 or 2 (default) in `DebugSwitches` in the `$WM.PROJECT_DIR/etc/-controlDict` file. An example from the beginning of the solution of the `cavity` tutorial is shown below where it can be seen that, for each equation that is solved, a report line is written with the solver name, the variable that is solved, its initial and final residuals and number of iterations.

```

Starting time loop

Time = 0.005

Max Courant Number = 0
BICCG: Solving for Ux, Initial residual = 1, Final residual = 2.96338e-06, No Iterations 8
ICCG: Solving for p, Initial residual = 1, Final residual = 4.9336e-07, No Iterations 35
time step continuity errors : sum local = 3.29376e-09, global = -6.41065e-20, cumulative = -6.41065e-20
ICCG: Solving for p, Initial residual = 0.47484, Final residual = 5.41068e-07, No Iterations 34
time step continuity errors : sum local = 6.60947e-09, global = -6.22619e-19, cumulative = -6.86725e-19
ExecutionTime = 0.14 s

```

| Keyword | Description | Options |
|-------------|---------------------------------|------------------------|
| patchName | Name of patch | <i>e.g.</i> movingWall |
| interpolate | Interpolate data? | true/false |
| triangulate | Triangulate surface? (optional) | true/false |

Table 6.11: Entries for a patch in surfaces sub-dictionaries.

```
Time = 0.01
```

```
Max Courant Number = 0.585722
```

```
BICCG: Solving for Ux, Initial residual = 0.148584, Final residual = 7.15711e-06, No Iterations 6
```

```
BICCG: Solving for Uy, Initial residual = 0.256618, Final residual = 8.94127e-06, No Iterations 6
```

```
ICCG: Solving for p, Initial residual = 0.37146, Final residual = 6.67464e-07, No Iterations 33
```

```
time step continuity errors : sum local = 6.34431e-09, global = 1.20603e-19, cumulative = -5.66122e-19
```

```
ICCG: Solving for p, Initial residual = 0.271556, Final residual = 3.69316e-07, No Iterations 33
```

```
time step continuity errors : sum local = 3.96176e-09, global = 6.9814e-20, cumulative = -4.96308e-19
```

```
ExecutionTime = 0.16 s
```

```
Time = 0.015
```

```
Max Courant Number = 0.758267
```

```
BICCG: Solving for Ux, Initial residual = 0.0448679, Final residual = 2.42301e-06, No Iterations 6
```

```
BICCG: Solving for Uy, Initial residual = 0.0782042, Final residual = 1.47009e-06, No Iterations 7
```

```
ICCG: Solving for p, Initial residual = 0.107474, Final residual = 4.8362e-07, No Iterations 32
```

```
time step continuity errors : sum local = 3.99028e-09, global = -5.69762e-19, cumulative = -1.06607e-18
```

```
ICCG: Solving for p, Initial residual = 0.0806771, Final residual = 9.47171e-07, No Iterations 31
```

```
time step continuity errors : sum local = 7.92176e-09, global = 1.07533e-19, cumulative = -9.58537e-19
```

```
ExecutionTime = 0.19 s
```

6.7.1 The foamJob script for running jobs

The user may be happy to monitor the residuals, iterations, Courant number *etc.* as report data passes across the screen. Alternatively, the user can redirect the report to a log file which will improve the speed of the computation. The `foamJob` script provides useful options for this purpose with the following executing the specified `<solver>` as a background process and redirecting the output to a file named `log`:

```
foamJob <solver>
```

For further options the user should execute `foamJob -help`. The user may monitor the `log` file whenever they wish, using the `UNIXtail` command, typically with the `-f` 'follow' option which appends the new data as the `log` file grows:

```
tail -f log
```

6.7.2 The foamLog script for monitoring jobs

There are limitations to monitoring a job by reading the log file, in particular it is difficult to extract trends over a long period of time. The `foamLog` script is therefore provided to extract data of residuals, iterations, Courant number *etc.* from a log file and present it in a set of files that can be plotted graphically. The script is executed by:

```
foamLog <logfile>
```

The files are stored in a subdirectory of the case directory named *logs*. Each file has the name *<var>_<subIter>* where *<var>* is the name of the variable specified in the log file and *<subIter>* is the iteration number within the time step. Those variables that are solved for, the initial residual takes the variable name *<var>* and final residual takes *<var>FinalRes*. By default, the files are presented in two-column format of time and the extracted values.

For example, in the *cavity* tutorial we may wish to observe the initial residual of the *Ux* equation to see whether the solution is converging to a steady-state. In that case, we would plot the data from the *logs/Ux_0* file as shown in Figure 6.5. It can be seen here that the residual falls monotonically until it reaches the convergence tolerance of 10^{-5} .




Figure 6.5: Initial residual of *Ux* in the *cavity* tutorial

foamLog generates files for everything it feasibly can from the *log* file. In the *cavity* tutorial example, this includes:

- the Courant number, *Courant_0*;
- *Ux* equation initial and final residuals, *Ux_0* and *UxFinalRes_0*, and iterations, *UxIters_0* (and equivalent *Uy* data);
- cumulative, global and local continuity errors after each of the 2 *p* equations, *contCumulative_0*, *contGlobal_0*, *contLocal_0* and *contCumulative_1*, *contGlobal_1*, *contLocal_1*;
- residuals and iterations from the the 2 *p* equations *p_0*, *pFinalRes_0*, *pIters_0* and *p_1*, *pFinalRes_1*, *pIters_1*;
- and execution time, *executionTime*.

Chapter 7

Models and physical properties

OpenFOAM includes a large range of solvers each designed for a specific class of problem. The equations and algorithms differ from one solver to another so that the selection of a solver involves the user making some initial choices on the modelling for their particular case. The choice of solver typically involves scanning through their descriptions in Table 3.5 to find the one suitable for the case. It ultimately determines many of the parameters and physical properties required to define the case but leaves the user with some modelling options that can be specified at runtime through the entries in dictionary files in the *constant* directory of a case. This chapter deals with many of the more common models and associated properties that must be specified at runtime.

7.1 Thermophysical models

Thermophysical models are concerned with energy, heat and physical properties. The *thermophysicalProperties* dictionary is read by any solver that uses the *thermophysical* model library. A thermophysical model is constructed in OpenFOAM as a pressure-temperature $p - T$ system from which other properties are computed. There is one compulsory dictionary entry called `thermoType` which specifies the package of thermophysical modelling that is used in the simulation. OpenFOAM includes a large set of pre-compiled combinations of modelling, built within the code using C++ templates. This coding approach assembles thermophysical modelling packages beginning with the equation of state and then adding more layers of thermophysical modelling that derive properties from the previous layer(s). The keyword entries in `thermoType` reflects the multiple layers of modelling and the underlying framework in which they combined. Below is an example entry for `thermoType`:

```
thermoType
{
    type            hePsiThermo;
    mixture         pureMixture;
    transport       const;
    thermo          hConst;
    equationOfState perfectGas;
    specie          specie;
    energy          sensibleEnthalpy;
}
```

The keyword entries specify the choice of thermophysical models, *e.g.* constant `transport` (constant viscosity, thermal diffusion), Perfect Gas `equationOfState`, *etc.* In addition there is a keyword entry named `energy` that allows the user to specify the form of energy to be used in the solution and thermodynamics. The following sections explain the entries and options in the `thermoType` package.

7.1.1 Thermophysical and mixture models

Each solver that uses thermophysical modelling constructs an object of a particular thermophysical model class. The model classes are listed below.

`psiThermo` Thermophysical model for fixed composition, based on compressibility $\psi = (RT)^{-1}$, where R is Gas Constant and T is temperature. The solvers that construct `psiThermo` include the *compressible* family of solvers (`sonicFoam`, `simpleFoam`, *etc.*, excluding `rhoPorousSimpleFoam`) and `uncoupledKinematicParcelFoam` and `coldEngineFoam`.

`rhoThermo` Thermophysical model for fixed composition, based on density ρ . The solvers that construct `rhoThermo` include the *heatTransfer* family of solvers (`buoyantSimpleFoam`, CHT solvers, *etc.*, excluding Boussinesq solvers) and `rhoPorousSimpleFoam`, `twoPhaseEulerFoam` and `thermoFoam`.

`psiReactionThermo` Thermophysical model for reacting mixture, based on ψ . The solvers that construct `psiReactionThermo` include many of the *combustion* solvers, *e.g.* `sprayFoam`, `chemFoam`, `fireFoam` and `reactingFoam`, and some *lagrangian* solvers, *e.g.* `coalChemistryFoam` and `reactingParcelFilmFoam`.

`psiuReactionThermo` Thermophysical model for combustion, based on compressibility of unburnt gas ψ_u . The solvers that construct `psiuReactionThermo` include some *combustion* solvers, *e.g.* `rhoReactingFoam`, `rhoReactingBuoyantFoam`, and some *lagrangian* solvers, *e.g.* `reactingParcelFoam` and `simpleReactingParcelFoam`.

`rhoReactionThermo` Thermophysical model for reacting mixture, based on ρ . The solvers that construct `rhoReactionThermo` include *combustion* solvers that model combustion based on laminar flame speed and regress variable, *e.g.* `XiFoam`, `PDRFoam` and `engineFoam`.

`multiphaseMixtureThermo` Thermophysical models for multiple phases. The solvers that construct `multiphaseMixtureThermo` include compressible *multiphase* interface-capturing solvers, *e.g.* `compressibleInterFoam`, and `compressibleMultiphaseInterFoam`.

The `type` keyword specifies the underlying thermophysical model. Options are listed below.

- `hePsiThermo`: for solvers that construct `psiThermo` and `psiReactionThermo`.
- `heRhoThermo`: for solvers that construct `rhoThermo`, `rhoReactionThermo` and `multiphaseMixtureThermo`.
- `heheuPsiThermo`: for solvers that construct `psiuReactionThermo`.

The `mixture` specifies the mixture composition. The option typically used for thermophysical models without reactions is `pureMixture`, which represents a mixture with fixed composition. When `pureMixture` is specified, the thermophysical models coefficients are specified within a sub-dictionary called `mixture`.

For mixtures with variable composition, required by thermophysical models with reactions, the `reactingMixture` option is used. Species and reactions are listed in a chemistry file, specified by the `foamChemistryFile` keyword. The `reactingMixture` model then requires the thermophysical models coefficients to be specified for each specie within sub-dictionaries named after each specie, *e.g.* O2, N2.

For combustion based on laminar flame speed and regress variables, constituents are a set of mixtures, such as `fuel`, `oxidant` and `burntProducts`. The available mixture models for this combustion modelling are `homogeneousMixture`, `inhomogeneousMixture` and `veryInhomogeneousMixture`.

Other models for variable composition are `egrMixture`, `multiComponentMixture` and `singleStepReactingMixture`.

7.1.2 Transport model

The transport modelling concerns evaluating dynamic viscosity μ , thermal conductivity κ and thermal diffusivity α (for internal energy and enthalpy equations). The current `transport` models are as follows:

`const` assumes a constant μ and Prandtl number $Pr = c_p\mu/\kappa$ which is simply specified by a two keywords, `mu` and `Pr`, respectively.

`sutherland` calculates μ as a function of temperature T from a Sutherland coefficient A_s and Sutherland temperature T_s , specified by keywords `As` and `Ts`; μ is calculated according to:

$$\mu = \frac{A_s\sqrt{T}}{1 + T_s/T}. \quad (7.1)$$

`polynomial` calculates μ and κ as a function of temperature T from a polynomial of any order N , *e.g.*:

$$\mu = \sum_{i=0}^{N-1} a_i T^i. \quad (7.2)$$

7.1.3 Thermodynamic models

The thermodynamic models are concerned with evaluating the specific heat c_p from which other properties are derived. The current `thermo` models are as follows:

`hConst` assumes a constant c_p and a heat of fusion H_f which is simply specified by a two values c_p H_f , given by keywords `Cp` and `Hf`.

`eConst` assumes a constant c_v and a heat of fusion H_f which is simply specified by a two values c_v H_f , given by keywords `Cv` and `Hf`.

`janaf` calculates c_p as a function of temperature T from a set of coefficients taken from JANAF tables of thermodynamics. The ordered list of coefficients is given in Table 7.1. The function is valid between a lower and upper limit in temperature T_l and T_h respectively. Two sets of coefficients are specified, the first set for temperatures above a common temperature T_c (and below T_h), the second for temperatures below T_c (and above T_l). The function relating c_p to temperature is:

$$c_p = R(((a_4T + a_3)T + a_2)T + a_1)T + a_0. \quad (7.3)$$

In addition, there are constants of integration, a_5 and a_6 , both at high and low temperature, used to evaluating h and s respectively.

`hPolynomial` calculates c_p as a function of temperature by a polynomial of any order N :

$$c_p = \sum_{i=0}^{N-1} a_i T^i. \quad (7.4)$$

The following case provides an example of its use: `$FOAM_TUTORIALS/lagrangian/porousExplicitSourceReactingParcelFoam/filter`

| Description | Entry | Keyword |
|----------------------------------|-----------------|--|
| Lower temperature limit | T_l (K) | <code>Tlow</code> |
| Upper temperature limit | T_h (K) | <code>Thigh</code> |
| Common temperature | T_c (K) | <code>Tcommon</code> |
| High temperature coefficients | $a_0 \dots a_4$ | <code>highCpCoeffs (a0 a1 a2 a3 a4...</code> |
| High temperature enthalpy offset | a_5 | <code>a5...</code> |
| High temperature entropy offset | a_6 | <code>a6)</code> |
| Low temperature coefficients | $a_0 \dots a_4$ | <code>lowCpCoeffs (a0 a1 a2 a3 a4...</code> |
| Low temperature enthalpy offset | a_5 | <code>a5...</code> |
| Low temperature entropy offset | a_6 | <code>a6)</code> |

Table 7.1: JANAF thermodynamics coefficients.

7.1.4 Composition of each constituent

There is currently only one option for the `specie` model which specifies the composition of each constituent. That model is itself named `specie`, which is specified by the following entries.

- `nMoles`: number of moles of component. This entry is only used for combustion modelling based on regress variable with a homogeneous mixture of reactants; otherwise it is set to 1.
- `molWeight` in grams per mole of specie.

7.1.5 Equation of state

The following equations of state are available in the thermophysical modelling library.

rhoConst Constant density:

$$\rho = \text{constant.} \quad (7.5)$$

perfectGas Perfect gas:

$$\rho = \frac{1}{RT}p. \quad (7.6)$$

incompressiblePerfectGas Perfect gas for an incompressible fluid:

$$\rho = \frac{1}{RT}p_{\text{ref}}, \quad (7.7)$$

where p_{ref} is a reference pressure.

perfectFluid Perfect fluid:

$$\rho = \frac{1}{RT}p + \rho_0, \quad (7.8)$$

where ρ_0 is the density at $T = 0$.

linear Linear equation of state:

$$\rho = \psi p + \rho_0, \quad (7.9)$$

where ψ is compressibility (not necessarily $(RT)^{-1}$).

adiabaticPerfectFluid Adiabatic perfect fluid:

$$\rho = \rho_0 \left(\frac{p + B}{p_0 + B} \right)^{1/\gamma}, \quad (7.10)$$

where ρ_0, p_0 are reference density and pressure respectively, and B is a model constant.

PengRobinsonGas Peng Robinson equation of state:

$$\rho = \frac{1}{zRT}p, \quad (7.11)$$

where the complex function $z = z(p, T)$ can be referenced in the source code in *Peng-RobinsonGasI.H*, in the `$FOAM_SRC/thermophysicalModels/specie/equationOfState/` directory.

icoPolynomial Incompressible, polynomial equation of state:

$$\rho = \sum_{i=0}^{N-1} a_i T^i, \quad (7.12)$$

where a_i are polynomial coefficients of any order N .

7.1.6 Selection of energy variable

The user must specify the form of energy to be used in the solution, either internal energy e and enthalpy h , and in forms that include the heat of formation Δh_f or not. This choice is specified through the `energy` keyword.

We refer to *absolute* energy where heat of formation is included, and *sensible* energy where it is not. For example absolute enthalpy h is related to sensible enthalpy h_s by

$$h = h_s + \sum_i c_i \Delta h_f^i \quad (7.13)$$

where c_i and h_f^i are the molar fraction and heat of formation, respectively, of specie i . In most cases, we use the sensible form of energy, for which it is easier to account for energy change due to reactions. Keyword entries for `energy` therefore include *e.g.* `sensibleEnthalpy`, `sensibleInternalEnergy` and `absoluteEnthalpy`.

7.1.7 Thermophysical property data

The basic thermophysical properties are specified for each specie from input data. Data entries must contain the name of the specie as the keyword, *e.g.* `O2`, `H2O`, `mixture`, followed by sub-dictionaries of coefficients, including:

`specie` containing *i.e.* number of moles, `nMoles`, of the specie, and molecular weight, `molWeight` in units of g/mol;

`thermodynamics` containing coefficients for the chosen thermodynamic model (see below);

`transport` containing coefficients for the chosen transport model (see below).

The following is an example entry for a specie named `fuel` modelled using `sutherland` transport and `janaf` thermodynamics:

```
fuel
{
  specie
  {
    nMoles      1;
    molWeight   16.0428;
  }
  thermodynamics
  {
    Tlow        200;
    Thigh       6000;
    Tcommon     1000;
    highCpCoeffs (1.63543 0.0100844 -3.36924e-06 5.34973e-10
                  -3.15528e-14 -10005.6 9.9937);
    lowCpCoeffs (5.14988 -0.013671 4.91801e-05 -4.84744e-08
                 1.66694e-11 -10246.6 -4.64132);
  }
  transport
```

```

    {
      As      1.67212e-06;
      Ts      170.672;
    }
  }

```

The following is an example entry for a specie named `air` modelled using `const` transport and `hConst` thermodynamics:

```

air
{
  specie
  {
    nMoles      1;
    molWeight    28.96;
  }
  thermodynamics
  {
    Cp          1004.5;
    Hf          2.544e+06;
  }
  transport
  {
    mu          1.8e-05;
    Pr          0.7;
  }
}

```

7.2 Turbulence models

The *turbulenceProperties* dictionary is read by any solver that includes turbulence modelling. Within that file is the `simulationType` keyword that controls the type of turbulence modelling to be used, either:

`laminar` uses no turbulence models;

`RAS` uses Reynolds-averaged stress (RAS) modelling;

`LES` uses large-eddy simulation (LES) modelling.

Note for OpenFOAM versions prior to v3.0.0: the keyword options are instead `RASModel` and `LESModel` respectively.

If `RAS` is selected, the choice of RAS modelling is specified in a `RAS` sub-dictionary, also in the *constant* directory. The RAS turbulence model is selected by the `RASModel` entry from a long list of available models that are listed in Table 3.9. Similarly, if `LES` is selected, the choice of LES modelling is specified in a `LES` dictionary and the LES turbulence model is selected by the `LESModel` entry.

Note for OpenFOAM versions prior to v3.0.0: the RAS modelling is specified in a separate *RASProperties* file rather than in a RAS sub-dictionary of *turbulenceProperties*; similarly, LES modelling is in a separate *LESProperties* file.

The entries required in the RAS sub-dictionary are listed in Table 7.2 and those for LES sub-dictionary dictionaries are listed in Table 7.3. The incompressible and com-

| | |
|-------------------------------------|--|
| <code>RASModel</code> | Name of RAS turbulence model |
| <code>turbulence</code> | Switch to turn turbulence modelling on/off |
| <code>printCoeffs</code> | Switch to print model coeffs to terminal at simulation startup |
| <code><RASModel>Coeffs</code> | Optional dictionary of coefficients for the respective <code>RASModel</code> |

Table 7.2: Keyword entries in the RAS sub-dictionary.

| | |
|-------------------------------------|---|
| <code>LESModel</code> | Name of LES model |
| <code>delta</code> | Name of delta δ model |
| <code><LESModel>Coeffs</code> | Dictionary of coefficients for the respective <code>LESModel</code> |
| <code><delta>Coeffs</code> | Dictionary of coefficients for each <code>delta</code> model |

Table 7.3: Keyword entries in the LES sub-dictionary.

pressible RAS turbulence models, isochoric and anisochoric LES models and delta models are all named and described in Table 3.9. Examples of their use can be found in the *\$FOAM_TUTORIALS*.

7.2.1 Model coefficients

The coefficients for the RAS turbulence models are given default values in their respective source code. If the user wishes to override these default values, then they can do so by adding a sub-dictionary entry to the RAS sub-dictionary file, whose keyword name is that of the model with `Coeffs` appended, *e.g.* `kEpsilonCoeffs` for the `kEpsilon` model. If the `printCoeffs` switch is on in the RAS sub-dictionary, an example of the relevant `...Coeffs` dictionary is printed to standard output when the model is created at the beginning of a run. The user can simply copy this into the RAS sub-dictionary file and edit the entries as required.

7.2.2 Wall functions

A range of wall function models is available in OpenFOAM that are applied as boundary conditions on individual patches. This enables different wall function models to be applied to different wall regions. The choice of wall function model is specified through the turbulent viscosity field ν_t in the *0/nut* file. **Note for OpenFOAM versions prior to v3.0.0:** wall functions for compressible RAS are specified through the μ_t field in the *0/mut* file, through ν_{sgs} in the *0/nuSgs* file for incompressible LES and μ_{sgs} in the *0/muSgs* file for compressible LES. For example, a *0/nut* file:

```

17
18   dimensions      [0 2 -1 0 0 0 0];
19
```

```

20  internalField    uniform 0;
21
22  boundaryField
23  {
24      movingWall
25      {
26          type      nutkWallFunction;
27          value      uniform 0;
28      }
29      fixedWalls
30      {
31          type      nutkWallFunction;
32          value      uniform 0;
33      }
34      frontAndBack
35      {
36          type      empty;
37      }
38  }
39
40
41  // ***** //

```

There are a number of wall function models available in the release, *e.g.* `nutWallFunction`, `nutRoughWallFunction`, `nutUSpaldingWallFunction`, `nutkWallFunction` and `nutkAtmWallFunction`. The user can consult the relevant directories for a full list of wall function models:

```
find $FOAM_SRC/TurbulenceModels -name wallFunctions
```

Within each wall function boundary condition the user can over-ride default settings for E , κ and C_μ through optional `E`, `kappa` and `Cmu` keyword entries.

Having selected the particular wall functions on various patches in the `nut/mut` file, the user should select `epsilonWallFunction` on corresponding patches in the `epsilon` field and `kqRwallFunction` on corresponding patches in the turbulent fields k , q and R .

7.3 Transport/rheology models

In OpenFOAM, solvers that do not include energy/heat, include a library of models for viscosity ν . The models typically relate viscosity to strain rate $\dot{\gamma}$ and are specified by the user in the `transportProperties` dictionary. The available models are listed in the following sections.

7.3.1 Newtonian model

The Newtonian model assumes ν is constant. Viscosity is specified by a `dimensionedScalar` `nu` in `transportProperties`, *e.g.*

```

transportModel Newtonian;

nu          nu [ 0 2 -1 0 0 0 0 ] 1.5e-05;

```

Note the units for kinematic viscosity are L^2/T .

7.3.2 Bird-Carreau model

The Bird-Carreau model is:

$$\nu = \nu_{\infty} + (\nu_0 - \nu_{\infty}) [1 + (k\dot{\gamma})^a]^{(n-1)/a} \quad (7.14)$$

where the coefficient a has a default value of 2. An example specification of the model in *transportProperties* is:

```
transportModel BirdCarreau;
BirdCarreauCoeffs
{
    nu0          nu0    [ 0 2 -1 0 0 0 0 ] 1e-03;
    nuInf        nuInf  [ 0 2 -1 0 0 0 0 ] 1e-05;
    k            k      [ 0 0  1 0 0 0 0 ] 1;
    n            n      [ 0 0  0 0 0 0 0 ] 0.5;
}
```

7.3.3 Cross Power Law model

The Cross Power Law model is:

$$\nu = \nu_{\infty} + \frac{\nu_0 - \nu_{\infty}}{1 + (m\dot{\gamma})^n} \quad (7.15)$$

An example specification of the model in *transportProperties* is:

```
transportModel CrossPowerLaw;
CrossPowerLawCoeffs
{
    nu0          nu0    [ 0 2 -1 0 0 0 0 ] 1e-03;
    nuInf        nuInf  [ 0 2 -1 0 0 0 0 ] 1e-05;
    m            m      [ 0 0  1 0 0 0 0 ] 1;
    n            n      [ 0 0  0 0 0 0 0 ] 0.5;
}
```

7.3.4 Power Law model

The Power Law model provides a function for viscosity, limited by minimum and maximum values, ν_{\min} and ν_{\max} respectively. The function is:

$$\nu = k\dot{\gamma}^{n-1} \quad \nu_{\min} \leq \nu \leq \nu_{\max} \quad (7.16)$$

An example specification of the model in *transportProperties* is:

```
transportModel powerLaw;
powerLawCoeffs
{
    nuMax        nuMax  [ 0 2 -1 0 0 0 0 ] 1e-03;
}
```

```

    nuMin          nuMin [ 0 2 -1 0 0 0 0 ] 1e-05;
    k              k      [ 0 2 -1 0 0 0 0 ] 1e-05;
    n              n      [ 0 0  0 0 0 0 0 ] 1;
}

```

7.3.5 Herschel-Bulkley model

The Herschel-Bulkley model combines the effects of Bingham plastic and power-law behavior in a fluid. For low strain rates, the material is modelled as a very viscous fluid with viscosity ν_0 . Beyond a threshold in strain-rate corresponding to threshold stress τ_0 , the viscosity is described by a power law. The model is:

$$\nu = \min(\nu_0, \tau_0/\dot{\gamma} + k\dot{\gamma}^{n-1}) \quad (7.17)$$

An example specification of the model in *transportProperties* is:

```

transportModel HerschelBulkley;
HerschelBulkleyCoeffs
{
    nu0          nu0 [ 0 2 -1 0 0 0 0 ] 1e-03;
    tau0         tau0 [ 0 2 -2 0 0 0 0 ] 1;
    k            k      [ 0 2 -1 0 0 0 0 ] 1e-05;
    n            n      [ 0 0  0 0 0 0 0 ] 1;
}

```


Index

Symbols Numbers A B C D E F G H I J K L M N O P Q R S T U V W X Z

Symbols

- *
 - tensor member function, P-23
 - +
 - tensor member function, P-23
 - - tensor member function, P-23
 - /
 - tensor member function, P-23
 - /*...*/
 - C++ syntax, U-78
 - //
 - C++ syntax, U-78
 - OpenFOAM file syntax, U-106
 - # include
 - C++ syntax, U-72, U-78
 - &
 - tensor member function, P-23
 - &&
 - tensor member function, P-23
 - ^
 - tensor member function, P-23
 - <LESModel>Coeffs keyword, U-198
 - <RASModel>Coeffs keyword, U-198
 - <delta>Coeffs keyword, U-198
 - 0.000000e+00 directory, U-106
 - 1-dimensional mesh, U-133
 - 1D mesh, U-133
 - 2-dimensional mesh, U-133
 - 2D mesh, U-133
- ## Numbers
- 0 directory, U-106
- ## A
- access functions, P-21
 - addLayersControls keyword, U-150
 - adiabaticFlameT utility, U-97
 - adiabaticPerfectFluid model, U-101, U-195
 - adjointShapeOptimizationFoam solver, U-86
 - adjustableRunTime
 - keyword entry, U-62, U-114
 - adjustTimeStep keyword, U-62, U-115
 - agglomerator keyword, U-125
 - algorithms tools, U-98
 - alphaContactAngle
 - boundary condition, U-59
 - analytical solution, P-43
 - Animations window panel, U-174
 - anisotropicFilter model, U-103
 - Annotation window panel, U-24
 - ansysToFoam utility, U-91
 - APIfunctions model, U-102
 - applications, U-69
 - Apply button, U-170, U-174
 - applyBoundaryLayer utility, U-90
 - applyWallFunctionBoundaryConditions utility, U-90
 - arbitrarily unstructured, P-29
 - arc
 - keyword entry, U-142
 - arc keyword, U-141
 - As keyword, U-193
 - ascii
 - keyword entry, U-114
 - attachMesh utility, U-92
 - Auto Accept button, U-174
 - autoMesh
 - library, U-99
 - autoPatch utility, U-92
 - autoRefineMesh utility, U-93
 - axes
 - right-handed, U-140
 - right-handed rectangular Cartesian, P-13, U-18
 - axi-symmetric cases, U-137, U-148
 - axi-symmetric mesh, U-133

B

- background
 - process, U-24, U-81
- backward
 - keyword entry, U-122
- Backward differencing, P-37
- barotropicCompressibilityModels
 - library, U-101
- basicMultiComponentMixture model, U-100
- basicSolidThermo
 - library, U-102
- basicThermophysicalModels
 - library, U-100
- binary
 - keyword entry, U-114
- BirdCarreau model, U-104
- blended differencing, P-36
- block
 - expansion ratio, U-143
- block keyword, U-141
- blocking
 - keyword entry, U-80
- blockMesh
 - library, U-99
- blockMesh solver, P-45
- blockMesh utility, U-38, U-91, U-140
- blockMesh executable
 - vertex numbering, U-143
- blockMeshDict*
 - dictionary, U-18, U-20, U-36, U-49, U-140, U-149
- blocks keyword, U-20, U-31, U-142
- boundaries, U-133
- boundary, U-133
- boundary*
 - dictionary, U-132, U-140
- boundary keyword, U-145
- boundary condition
 - alphaContactAngle, U-59
 - buoyantPressure, U-139
 - calculated, U-138
 - cyclic, U-137, U-146
 - directionMixed, U-138
 - empty, P-63, P-69, U-18, U-133, U-137
 - fixedGradient, U-138
 - fixedValue, U-138
 - fluxCorrectedVelocity, U-139
 - inlet, P-69
 - inletOutlet, U-139
 - mixed, U-138
 - movingWallVelocity, U-139
 - outlet, P-69
 - outletInlet, U-139
 - partialSlip, U-139
 - patch, U-136
 - pressureDirectedInletVelocity, U-139
 - pressureInletVelocity, U-139
 - pressureOutlet, P-63
 - pressureTransmissive, U-139
 - processor, U-138
 - setup, U-20
 - slip, U-139
 - supersonicFreeStream, U-139
 - surfaceNormalFixedValue, U-139
 - symmetryPlane, P-63, U-137
 - totalPressure, U-139
 - turbulentInlet, U-139
 - wall, U-41
 - wall, P-63, P-69, U-59, U-137
 - wedge, U-133, U-137, U-148
 - zeroGradient, U-138
- boundary conditions, P-41
 - Dirichlet, P-41
 - inlet, P-42
 - Neumann, P-41
 - no-slip impermeable wall, P-42
 - outlet, P-42
 - physical, P-42
 - symmetry plane, P-42
- boundaryField keyword, U-21, U-110
- boundaryFoam solver, U-86
- bounded
 - keyword entry, U-120, U-121
- boxToCell keyword, U-60
- boxTurb utility, U-90
- breaking of a dam, U-56
- BSpline
 - keyword entry, U-142
- buoyantBoussinesqPimpleFoam solver, U-88
- buoyantBoussinesqSimpleFoam solver, U-88
- buoyantPimpleFoam solver, U-88
- buoyantPressure
 - boundary condition, U-139
- buoyantSimpleFoam solver, U-88
- burntProducts keyword, U-193
- button
 - Apply, U-170, U-174
 - Auto Accept, U-174
 - Camera Parallel Projection, U-174
 - Choose Preset, U-173

- Delete, U-170
 - Edit Color Map, U-172
 - Enable Line Series, U-35
 - Lights, U-174
 - Orientation Axes, U-24
 - Refresh Times, U-25, U-171
 - Rescale to Data Range, U-25
 - Reset, U-170
 - Set Ambient Color, U-173
 - Update GUI, U-171
 - Use Parallel Projection, U-24
- C**
- C++ syntax
 - /*...*/*, U-78
 - //*, U-78
 - # include*, U-72, U-78
 - cacheAgglomeration* keyword, U-126
 - calculated
 - boundary condition, U-138
 - cAlpha* keyword, U-63
 - Camera Parallel Projection button, U-174
 - cases, U-105
 - castellatedMesh* keyword, U-150
 - castellatedMeshControls*
 - dictionary, U-152–U-154
 - castellatedMeshControls* keyword, U-150
 - cavitatingDyMFoam* solver, U-87
 - cavitatingFoam* solver, U-87
 - cavity flow, U-17
 - CEI_ARCH
 - environment variable, U-184
 - CEI_HOME
 - environment variable, U-184
 - cell
 - expansion ratio, U-143
 - cell class, P-29
 - cell
 - keyword entry, U-185
 - cellLimited*
 - keyword entry, U-120
 - cellPoint*
 - keyword entry, U-185
 - cellPointFace*
 - keyword entry, U-185
 - cells*
 - dictionary, U-140
 - central differencing, P-36
 - cfTools* tools, U-98
 - cfx4ToFoam* utility, U-91, U-159
 - changeDictionary* utility, U-90
 - Charts window panel, U-174
 - checkMesh* utility, U-92, U-160
 - chemFoam* solver, U-88
 - chemistryModel*
 - library, U-102
 - chemistryModel* model, U-102
 - chemistrySolver* model, U-102
 - chemkinToFoam* utility, U-97
 - Choose Preset button, U-173
 - chtMultiRegionSimpleFoam* solver, U-88
 - chtMultiRegionFoam* solver, U-88
 - Chung
 - library, U-101
 - class
 - cell, P-29
 - dimensionSet*, P-24, P-30, P-31
 - face, P-29
 - finiteVolumeCalculus*, P-34
 - finiteVolumeMethod*, P-34
 - fvMesh*, P-29
 - fvSchemes*, P-36
 - fvC*, P-34
 - fvm*, P-34
 - pointField*, P-29
 - polyBoundaryMesh*, P-29
 - polyMesh*, P-29, U-129, U-131
 - polyPatchList*, P-29
 - polyPatch*, P-29
 - scalarField*, P-27
 - scalar*, P-22
 - slice*, P-29
 - symmTensorField*, P-27
 - symmTensorThirdField*, P-27
 - tensorField*, P-27
 - tensorThirdField*, P-27
 - tensor*, P-22
 - vectorField*, P-27
 - vector*, P-22, U-109
 - word*, P-24, P-29
 - class* keyword, U-107
 - clockTime*
 - keyword entry, U-114
 - cloud* keyword, U-187
 - cloudFunctionObjects*
 - library, U-98
 - cmptAv*
 - tensor member function, P-23
 - Co utility, U-93
 - coalChemistryFoam* solver, U-89
 - coalCombustion*

- library, U-99
 - cofactors
 - tensor member function, P-23
 - coldEngineFoam solver, U-88
 - collapseEdges utility, U-93
 - Color By menu, U-173
 - Color Legend window, U-29
 - Color Legend window panel, U-173
 - Color Scale window panel, U-173
 - Colors window panel, U-174
 - compressibleInterDyMFoam solver, U-87
 - compressibleInterFoam solver, U-87
 - compressibleMultiphaseInterFoam solver, U-87
 - combinePatchFaces utility, U-93
 - comments, U-78
 - commsType keyword, U-80
 - compressed
 - keyword entry, U-114
 - compressibleLESModels
 - library, U-104
 - compressibleRASModels
 - library, U-103
 - constant* directory, U-105, U-191
 - constant model, U-101
 - constTransport model, U-101
 - containers tools, U-98
 - continuum
 - mechanics, P-13
 - control
 - of time, U-113
 - controlDict*
 - dictionary, P-65, U-22, U-31, U-42, U-51, U-62, U-105, U-165
 - controlDict* file, P-48
 - convection, *see* divergence, P-36
 - convergence, U-39
 - conversion
 - library, U-99
 - convertToMeters keyword, U-140
 - convertToMeters keyword, U-141
 - coordinate
 - system, P-13
 - coordinate system, U-18
 - corrected
 - keyword entry, U-120, U-121
 - Courant number, P-40, U-22
 - Cp keyword, U-193
 - cpuTime
 - keyword entry, U-114
 - Crank Nicolson
 - temporal discretisation, P-41
 - CrankNicolson
 - keyword entry, U-122
 - createExternalCoupledPatchGeometry utility, U-90
 - createBaffles utility, U-92
 - createPatch utility, U-92
 - createTurbulenceFields utility, U-94
 - cross product, *see* tensor, vector cross product
 - CrossPowerLaw
 - keyword entry, U-60
 - CrossPowerLaw model, U-104
 - cubeRootVolDelta model, U-103
 - cubicCorrected
 - keyword entry, U-122
 - cubicCorrection
 - keyword entry, U-119
 - curl, P-35
 - curl
 - fvc member function, P-35
 - Current Time Controls menu, U-25, U-171
 - curve keyword, U-187
 - Cv keyword, U-193
 - cyclic
 - boundary condition, U-137, U-146
 - cyclic
 - keyword entry, U-137
 - cylinder
 - flow around a, P-43
- ## D
- d2dt2
 - fvc member function, P-35
 - fvm member function, P-35
 - dam
 - breaking of a, U-56
 - datToFoam utility, U-91
 - db tools, U-98
 - ddt
 - fvc member function, P-35
 - fvm member function, P-35
 - DeardorffDiffStress model, U-103, U-104
 - debug keyword, U-150
 - decompose model, U-100
 - decomposePar utility, U-82, U-83, U-97
 - decomposeParDict*
 - dictionary, U-82
 - decomposition
 - of field, U-82
 - of mesh, U-82
 - decompositionMethods

- library, U-99
- decompression of a tank, P-61
- defaultFieldValues keyword, U-60
- deformedGeom utility, U-92
- Delete button, U-170
- delta keyword, U-83, U-198
- deltaT keyword, U-114
- dependencies, U-72
- dependency lists, U-72
- det
 - tensor member function, P-23
- determinant, *see* tensor, determinant
- dev
 - tensor member function, P-23
- diag
 - tensor member function, P-23
- diagonal
 - keyword entry, U-124, U-125
- DIC
 - keyword entry, U-125
- DICGaussSeidel
 - keyword entry, U-125
- dictionary
 - PISO*, U-23
 - blockMeshDict*, U-18, U-20, U-36, U-49, U-140, U-149
 - boundary*, U-132, U-140
 - castellatedMeshControls*, U-152–U-154
 - cells*, U-140
 - controlDict*, P-65, U-22, U-31, U-42, U-51, U-62, U-105, U-165
 - decomposeParDict*, U-82
 - faces*, U-131, U-140
 - fvSchemes*, U-63, U-105, U-116
 - fvSolution*, U-105, U-123
 - mechanicalProperties*, U-51
 - neighbour*, U-132
 - owner*, U-131
 - points*, U-131, U-140
 - thermalProperties*, U-51
 - thermophysicalProperties*, U-191
 - transportProperties*, U-21, U-39, U-42, U-199
 - turbulenceProperties*, U-41, U-61, U-197
- differencing
 - Backward, P-37
 - blended, P-36
 - central, P-36
 - Euler implicit, P-37
 - Gamma, P-36
 - MINMOD, P-36
 - SUPERBEE, P-36
 - upwind, P-36
 - van Leer, P-36
- DILU
 - keyword entry, U-125
- dimension
 - checking in OpenFOAM, P-24, U-109
- dimensional units, U-109
- dimensioned<Type> template class, P-24
- dimensionedTypes tools, U-98
- dimensions keyword, U-21, U-110
- dimensionSet class, P-24, P-30, P-31
- dimensionSet tools, U-98
- directionMixed
 - boundary condition, U-138
- directory
 - 0.000000e+00*, U-106
 - 0*, U-106
 - Make*, U-73
 - constant*, U-105, U-191
 - fluentInterface*, U-181
 - polyMesh*, U-105, U-131
 - processorN*, U-83
 - run*, U-105
 - system*, P-48, U-105
 - tutorials*, P-43, U-17
- discretisation
 - equation, P-31
- Display window panel, U-24, U-25, U-170, U-172
- distance
 - keyword entry, U-154, U-187
- distributed model, U-100
- distributed keyword, U-83, U-84
- distributionModels
 - library, U-99
- div
 - fv member function, P-35
 - fvm member function, P-35
- divergence, P-35, P-37
- divSchemes keyword, U-116
- dnsFoam solver, U-88
- doLayers keyword, U-150
- double inner product, *see* tensor, double inner product
- DPMFoam solver, U-89
- driftFluxFoam solver, U-87
- dsmc
 - library, U-99
- dsmcFieldsCalc utility, U-95
- dsmcFoam solver, U-89

dsmcInitialise utility, U-90

dx

keyword entry, U-185

dynamicFvMesh

library, U-99

dynamicMesh

library, U-99

dynLagrangian model, U-103

dynOneEqEddy model, U-103

E

eConstThermo model, U-101

edgeGrading keyword, U-143

edgeMesh

library, U-99

edges keyword, U-141

Edit menu, U-174

Edit Color Map button, U-172

egrMixture model, U-100

egrMixture keyword, U-193

electrostaticFoam solver, U-89

empty

boundary condition, P-63, P-69, U-18, U-133, U-137

empty

keyword entry, U-137

Enable Line Series button, U-35

endTime keyword, U-22, U-113, U-114

energy keyword, U-192, U-196

engine

library, U-99

engineCompRatio utility, U-95

engineFoam solver, U-88

engineSwirl utility, U-90

ensight74FoamExec utility, U-183

ENSIGHT7_INPUT

environment variable, U-184

ENSIGHT7_READER

environment variable, U-184

ensightFoamReader utility, U-93

enstrophy utility, U-93

environment variable

CEL_ARCH, U-184

CEL_HOME, U-184

ENSIGHT7_INPUT, U-184

ENSIGHT7_READER, U-184

FOAM_RUN, U-105

WM_ARCH_OPTION, U-76

WM_ARCH, U-76

WM_COMPILER_BIN, U-76

WM_COMPILER_DIR, U-76

WM_COMPILER_LIB, U-76

WM_COMPILER, U-76

WM_COMPILE_OPTION, U-76

WM_DIR, U-76

WM_MPLIB, U-76

WM_OPTIONS, U-76

WM_PRECISION_OPTION, U-76

WM_PROJECT_DIR, U-76

WM_PROJECT_INST_DIR, U-76

WM_PROJECT_USER_DIR, U-76

WM_PROJECT_VERSION, U-76

WM_PROJECT, U-76

wmake, U-76

equationOfState keyword, U-192

equilibriumCO utility, U-97

equilibriumFlameT utility, U-97

errorReduction keyword, U-158

Euler

keyword entry, U-122

Euler implicit

differencing, P-37

temporal discretisation, P-40

examples

decompression of a tank, P-61

flow around a cylinder, P-43

flow over backward step, P-50

Hartmann problem, P-67

supersonic flow over forward step, P-58

execFlowFunctionObjects utility, U-95

expandDictionary utility, U-97

expansionRatio keyword, U-157

explicit

temporal discretisation, P-40

extrude2DMesh utility, U-91

extrudeMesh utility, U-91

extrudeToRegionMesh utility, U-91

F

face class, P-29

face keyword, U-187

faceAgglomerate utility, U-90

faceAreaPair

keyword entry, U-125

faceLimited

keyword entry, U-120

faces

dictionary, U-131, U-140

FDIC

keyword entry, U-125

featureAngle keyword, U-157

features keyword, U-152

- field
 - U, U-23
 - p, U-23
 - decomposition, U-82
- FieldField<Type> template class, P-30
- fieldFunctionObjects
 - library, U-98
- fields, P-27
 - mapping, U-165
- fields tools, U-98
- fields keyword, U-185
- Field<Type> template class, P-27
- fieldValues keyword, U-60
- file
 - Make/files*, U-75
 - controlDict*, P-48
 - files*, U-73
 - g*, U-60
 - options*, U-73
 - snappyHexMeshDict*, U-150
 - transportProperties*, U-60
- file format, U-106
- fileFormats
 - library, U-99
- fileModificationChecking keyword, U-80
- fileModificationSkew keyword, U-80
- files* file, U-73
- filteredLinear2
 - keyword entry, U-119
- finalLayerThickness keyword, U-157
- financialFoam solver, U-90
- find script/alias, U-179
- finite volume
 - discretisation, P-25
 - mesh, P-29
- finiteVolume
 - library, U-98
- finiteVolume tools, U-98
- finiteVolumeCalculus class, P-34
- finiteVolumeMethod class, P-34
- fireFoam solver, U-88
- firstTime keyword, U-113
- fixed
 - keyword entry, U-114
- fixedGradient
 - boundary condition, U-138
- fixedValue
 - boundary condition, U-138
- flattenMesh utility, U-92
- floatTransfer keyword, U-80
- flow
 - free surface, U-56
 - laminar, U-17
 - steady, turbulent, P-50
 - supersonic, P-58
 - turbulent, U-17
- flow around a cylinder, P-43
- flow over backward step, P-50
- flowType utility, U-93
- fluent3DMeshToFoam utility, U-91
- fluentInterface* directory, U-181
- fluentMeshToFoam utility, U-91, U-159
- fluxCorrectedVelocity
 - boundary condition, U-139
- fluxRequired keyword, U-116
- OpenFOAM
 - cases, U-105
- FOAM_RUN
 - environment variable, U-105
- foamCalc utility, U-33
- foamCalcFunctions
 - library, U-98
- foamChemistryFile keyword, U-193
- foamCorrectVrt script/alias, U-164
- foamDataToFluent utility, U-93, U-181
- foamDebugSwitches utility, U-97
- FoamFile keyword, U-107
- foamFile
 - keyword entry, U-185
- foamFormatConvert utility, U-97
- foamHelp utility, U-97
- foamInfoExec utility, U-97
- foamJob script/alias, U-188
- foamListTimes utility, U-95
- foamLog script/alias, U-188
- foamMeshToFluent utility, U-91, U-181
- foamToEnight utility, U-93
- foamToEnightParts utility, U-93
- foamToGMV utility, U-93
- foamToStarMesh utility, U-91
- foamToSurface utility, U-91
- foamToTecplot360 utility, U-93
- foamToTetDualMesh utility, U-93
- foamToVTK utility, U-93
- foamUpgradeCyclics utility, U-90
- foamUpgradeFvSolution utility, U-90
- foamyHexMeshBackgroundMesh utility, U-91
- foamyHexMeshSurfaceSimplify utility, U-91
- foamyHexMesh utility, U-91
- foamyQuadMesh utility, U-91

forces
 library, U-98
 foreground
 process, U-24
 format keyword, U-107
 fourth
 keyword entry, U-120, U-121
 fuel keyword, U-193
 functionObjectLibs keyword, U-179
 functions keyword, U-115, U-177
 fvc class, P-34
 fvc member function
 curl, P-35
 d2dt2, P-35
 ddt, P-35
 div, P-35
 gGrad, P-35
 grad, P-35
 laplacian, P-35
 lsGrad, P-35
 snGrad, P-35
 snGradCorrection, P-35
 sqrGradGrad, P-35
 fvDOM
 library, U-101
 FVFunctionObjects
 library, U-98
 fvm class, P-34
 fvm member function
 d2dt2, P-35
 ddt, P-35
 div, P-35
 laplacian, P-35
 Su, P-35
 SuSp, P-35
 fvMatrices tools, U-98
 fvMatrix template class, P-34
 fvMesh class, P-29
 fvMesh tools, U-98
 fvMotionSolvers
 library, U-99
 fvSchemes
 dictionary, U-63, U-105, U-116
 fvSchemes class, P-36
 fvSchemes
 menu entry, U-52
 fvSolution
 dictionary, U-105, U-123

G

g file, U-60

gambitToFoam utility, U-91, U-159
 GAMG
 keyword entry, U-53, U-124, U-125
 Gamma
 keyword entry, U-119
 Gamma differencing, P-36
 Gauss
 keyword entry, U-120
 Gauss's theorem, P-34
 GaussSeidel
 keyword entry, U-125
 General window panel, U-174
 general
 keyword entry, U-114
 genericFvPatchField
 library, U-99
 geometric-algebraic multi-grid, U-125
 GeometricBoundaryField template class, P-30
 geometricField<Type> template class, P-30
 geometry keyword, U-150
 gGrad
 fvc member function, P-35
 global tools, U-98
 gmshToFoam utility, U-91
 gnuplot
 keyword entry, U-115, U-185
 grad
 fvc member function, P-35
 (Grad Grad) squared, P-35
 gradient, P-35, P-38
 Gauss scheme, P-38
 Gauss's theorem, U-52
 least square fit, U-52
 least squares method, P-38, U-52
 surface normal, P-38
 gradSchemes keyword, U-116
 graph tools, U-98
 graphFormat keyword, U-115
 GuldersonEgRlaminarFlameSpeed model, U-101
 GuldersonLaminarFlameSpeed model, U-101

H

hConstThermo model, U-101
 heheuPsiThermo model, U-100
 heheuPsiThermo
 keyword entry, U-192
 Help menu, U-173
 hePsiThermo model, U-100
 hePsiThermo
 keyword entry, U-192
 heRhoThermo model, U-100

- heRhoThermo**
 keyword entry, U-192
HerschelBulkley model, U-104
hExponentialThermo
 library, U-102
Hf keyword, U-193
hierarchical
 keyword entry, U-82, U-83
highCpCoeffs keyword, U-194
homogenousDynOneEqEddy model, U-103, U-104
homogenousDynSmagorinsky model, U-103
homogeneousMixture model, U-100
homogeneousMixture keyword, U-193
hPolynomialThermo model, U-101
- ## I
- I**
 tensor member function, P-23
icoFoam solver, U-17, U-21, U-22, U-24, U-86
icoPolynomial model, U-101, U-195
icoUncoupledKinematicParcelFoam solver, U-89
ideasToFoam utility, U-159
ideasUnvToFoam utility, U-91
 identities, *see* tensor, identities
 identity, *see* tensor, identity
incompressibleLESMoels
 library, U-103
incompressiblePerfectGas model, U-101, U-195
incompressibleRASMoels
 library, U-102
incompressibleTransportMoels
 library, P-53, U-104
incompressibleTurbulenceMoels
 library, P-53
index
 notation, P-14, P-15
Information window panel, U-170
inhomogeneousMixture model, U-100
inhomogeneousMixture keyword, U-193
inlet
 boundary condition, P-69
inletOutlet
 boundary condition, U-139
inner product, *see* tensor, inner product
inotify
 keyword entry, U-80
inotifyMaster
 keyword entry, U-80
inside
 keyword entry, U-154
insideCells utility, U-92
interPhaseChangeDyMFoam solver, U-87
interPhaseChangeFoam solver, U-87
interfaceProperties
 library, U-104
interfaceProperties model, U-104
interFoam solver, U-87
interMixingFoam solver, U-87
internalField keyword, U-21, U-110
interpolation tools, U-98
interpolationScheme keyword, U-185
interpolations tools, U-98
interpolationSchemes keyword, U-116
inv
 tensor member function, P-23
iterations
 maximum, U-124
- ## J
- janafThermo** model, U-101
jobControl
 library, U-98
jplot
 keyword entry, U-115, U-185
- ## K
- kEpsilon** model, U-102, U-103
keyword
As, U-193
Cp, U-193
Cv, U-193
FoamFile, U-107
Hf, U-193
LESMoel, U-198
N2, U-193
O2, U-193
Pr, U-193
RASMoel, U-198
Tcommon, U-194
Thigh, U-194
Tlow, U-194
Ts, U-193
addLayersControls, U-150
adjustTimeStep, U-62, U-115
agglomerator, U-125
arc, U-141
blocks, U-20, U-31, U-142
block, U-141
boundaryField, U-21, U-110
boundary, U-145
boxToCell, U-60
burntProducts, U-193

- cAlpha, U-63
- cacheAgglomeration, U-126
- castellatedMeshControls, U-150
- castellatedMesh, U-150
- class, U-107
- cloud, U-187
- commsType, U-80
- convertToMeters, U-141
- convertToMeters, U-140
- curve, U-187
- debug, U-150
- defaultFieldValues, U-60
- deltaT, U-114
- delta, U-83, U-198
- dimensions, U-21, U-110
- distributed, U-83, U-84
- divSchemes, U-116
- doLayers, U-150
- edgeGrading, U-143
- edges, U-141
- egrMixture, U-193
- endTime, U-22, U-113, U-114
- energy, U-192, U-196
- equationOfState, U-192
- errorReduction, U-158
- expansionRatio, U-157
- face, U-187
- featureAngle, U-157
- features, U-152
- fieldValues, U-60
- fields, U-185
- fileModificationChecking, U-80
- fileModificationSkew, U-80
- finalLayerThickness, U-157
- firstTime, U-113
- floatTransfer, U-80
- fluxRequired, U-116
- foamChemistryFile, U-193
- format, U-107
- fuel, U-193
- functionObjectLibs, U-179
- functions, U-115, U-177
- geometry, U-150
- gradSchemes, U-116
- graphFormat, U-115
- highCpCoeffs, U-194
- homogeneousMixture, U-193
- inhomogeneousMixture, U-193
- internalField, U-21, U-110
- interpolationSchemes, U-116
- interpolationScheme, U-185
- laplacianSchemes, U-116
- latestTime, U-39
- layers, U-157
- leastSquares, U-52
- levels, U-154
- libs, U-80, U-115
- locationInMesh, U-152, U-154
- location, U-107
- lowCpCoeffs, U-194
- manualCoeffs, U-83
- maxAlphaCo, U-62
- maxBoundarySkewness, U-158
- maxConcave, U-158
- maxCo, U-62, U-115
- maxDeltaT, U-62
- maxFaceThicknessRatio, U-157
- maxGlobalCells, U-152
- maxInternalSkewness, U-158
- maxIter, U-124
- maxLocalCells, U-152
- maxNonOrtho, U-158
- maxThicknessToMedialRatio, U-157
- mergeLevels, U-126
- mergePatchPairs, U-141
- mergeTolerance, U-150
- meshQualityControls, U-150
- method, U-83
- midPointAndFace, U-187
- midPoint, U-187
- minArea, U-158
- minDeterminant, U-158
- minFaceWeight, U-158
- minFlatness, U-158
- minMedianAxisAngle, U-157
- minRefinementCells, U-152
- minThickness, U-157
- minTriangleTwist, U-158
- minTwist, U-158
- minVolRatio, U-158
- minVol, U-158
- mixture, U-193
- mode, U-154
- molWeight, U-196
- multiComponentMixture, U-193
- mu, U-193
- nAlphaSubCycles, U-63
- nBufferCellsNoExtrude, U-157
- nCellsBetweenLevels, U-152
- nFaces, U-132

- nFinestSweeps, U-126
- nGrow, U-157
- nLayerIter, U-157
- nMoles, U-196
- nPostSweeps, U-126
- nPreSweeps, U-126
- nRelaxIter, U-155, U-157
- nRelaxedIter, U-157
- nSmoothNormals, U-157
- nSmoothPatch, U-155
- nSmoothScale, U-158
- nSmoothSurfaceNormals, U-157
- nSmoothThickness, U-157
- nSolveIter, U-155
- neighbourPatch, U-146
- numberOfSubdomains, U-83
- nu, U-199
- n, U-83
- object, U-107
- order, U-83
- outputControl, U-179
- oxidant, U-193
- pRefCell, U-23, U-128
- pRefValue, U-23, U-127
- p_rhgRefCell, U-128
- p_rhgRefValue, U-128
- patchMap, U-166
- patches, U-141
- preconditioner, U-124, U-125
- pressure, U-51
- printCoeffs, U-42, U-198
- processorWeights, U-82
- processorWeights, U-83
- purgeWrite, U-114
- refGradient, U-138
- refinementRegions, U-152, U-154
- refinementSurfaces, U-152, U-153
- refinementRegions, U-154
- regions, U-60
- relTol, U-53, U-124
- relativeSizes, U-157
- relaxed, U-158
- resolveFeatureAngle, U-152, U-153
- roots, U-83, U-84
- runTimeModifiable, U-115
- scotchCoeffs, U-83
- setFormat, U-185
- sets, U-185
- simpleGrading, U-143
- simulationType, U-41, U-61, U-197
- singleStepReactingMixture, U-193
- smoother, U-126
- snGradSchemes, U-116
- snapControls, U-150
- snap, U-150
- solvers, U-123
- solver, U-53, U-123
- specie, U-196
- spline, U-141
- startFace, U-132
- startFrom, U-22, U-113
- startTime, U-22, U-113
- stopAt, U-113
- strategy, U-82, U-83
- surfaceFormat, U-185
- surfaces, U-185
- thermoType, U-191
- thermodynamics, U-196
- timeFormat, U-114
- timePrecision, U-115
- timeScheme, U-116
- tolerance, U-53, U-124, U-155
- topoSetSource, U-60
- traction, U-51
- transport, U-192, U-196
- turbulence, U-198
- type, U-135, U-192
- uniform, U-187
- valueFraction, U-138
- value, U-21, U-138
- version, U-107
- vertices, U-20, U-141
- veryInhomogeneousMixture, U-193
- writeCompression, U-114
- writeControl, U-22, U-62, U-114
- writeFormat, U-55, U-114
- writeInterval, U-23, U-32, U-114
- writePrecision, U-114
- <LESModel>Coeffs, U-198
- <RASModel>Coeffs, U-198
- <delta>Coeffs, U-198
- keyword entry
 - BSpline, U-142
 - CrankNicolson, U-122
 - CrossPowerLaw, U-60
 - DICGaussSeidel, U-125
 - DIC, U-125
 - DILU, U-125
 - Euler, U-122
 - FDIC, U-125

GAMG, U-53, U-124, U-125
Gamma, U-119
GaussSeidel, U-125
Gauss, U-120
LESModel, U-41
LES, U-41, U-197
MGridGen, U-125
MUSCL, U-119
Newtonian, U-60
PBiCG, U-124
PCG, U-124
QUICK, U-122
RASModel, U-41
RAS, U-41, U-197
SFCD, U-119, U-122
UMIST, U-117
adjustableRunTime, U-62, U-114
arc, U-142
ascii, U-114
backward, U-122
binary, U-114
blocking, U-80
bounded, U-120, U-121
cellLimited, U-120
cellPointFace, U-185
cellPoint, U-185
cell, U-185
clockTime, U-114
compressed, U-114
corrected, U-120, U-121
cpuTime, U-114
cubicCorrected, U-122
cubicCorrection, U-119
cyclic, U-137
diagonal, U-124, U-125
distance, U-154, U-187
dx, U-185
empty, U-137
faceAreaPair, U-125
faceLimited, U-120
filteredLinear2, U-119
fixed, U-114
foamFile, U-185
fourth, U-120, U-121
general, U-114
gnuplot, U-115, U-185
hePsiThermo, U-192
heRhoThermo, U-192
heheuPsiThermo, U-192
hierarchical, U-82, U-83
inotifyMaster, U-80
inotify, U-80
inside, U-154
jplot, U-115, U-185
laminar, U-41, U-197
latestTime, U-113
leastSquares, U-120
limitedCubic, U-119
limitedLinear, U-119
limited, U-120, U-121
linearUpwind, U-119, U-122
linear, U-119, U-122
line, U-142
localEuler, U-122
manual, U-82, U-83
metis, U-83
midPoint, U-119
nextWrite, U-114
noWriteNow, U-114
nonBlocking, U-80
none, U-117, U-125
null, U-185
outputTime, U-179
outside, U-154
patch, U-137, U-186
polyLine, U-142
processor, U-137
pureMixture, U-193
raw, U-115, U-185
reactingMixture, U-193
runTime, U-32, U-114
scheduled, U-80
scientific, U-114
scotch, U-82, U-83
simple, U-82, U-83
skewLinear, U-119, U-122
smoothSolver, U-124
spline, U-142
startTime, U-22, U-113
steadyState, U-122
stl, U-185
symmetryPlane, U-137
timeStampMaster, U-80
timeStamp, U-80
timeStep, U-23, U-32, U-114, U-179
uncompressed, U-114
uncorrected, U-120, U-121
upwind, U-119, U-122
vanLeer, U-119
vtk, U-185

- wall, U-137
 - wedge, U-137
 - writeControl, U-114
 - writeInterval, U-179
 - writeNow, U-113
 - xmgr, U-115, U-185
 - xyz, U-187
 - x, U-187
 - y, U-187
 - z, U-187
 - kivaToFoam utility, U-91
 - kkLOmega model, U-102
 - kOmega model, U-102
 - kOmegaSST model, U-102, U-103
 - kOmegaSSTSAS model, U-103
 - Kronecker delta, P-19
- L**
- lagrangian
 - library, U-99
 - lagrangianIntermediate
 - library, U-99
 - Lambda2 utility, U-94
 - LamBremhorstKE model, U-102
 - laminar model, U-102, U-103
 - laminar
 - keyword entry, U-41, U-197
 - laminarFlameSpeedModels
 - library, U-101
 - laplaceFilter model, U-103
 - Laplacian, P-36
 - laplacian, P-35
 - laplacian
 - fvc member function, P-35
 - fvm member function, P-35
 - laplacianFoam solver, U-86
 - laplacianSchemes keyword, U-116
 - latestTime
 - keyword entry, U-113
 - latestTime keyword, U-39
 - LaunderGibsonRSTM model, U-102, U-103
 - LaunderSharmaKE model, U-102, U-103
 - layers keyword, U-157
 - leastSquares
 - keyword entry, U-120
 - leastSquares keyword, U-52
 - LES
 - keyword entry, U-41, U-197
 - LESdeltas
 - library, U-103
 - LESfilters
 - library, U-103
 - LESModel
 - keyword entry, U-41
 - LESModel keyword, U-198
 - levels keyword, U-154
 - libraries, U-69
 - library
 - Chung, U-101
 - FVFunctionObjects, U-98
 - LESdeltas, U-103
 - LESfilters, U-103
 - MGridGenGAMGAgglomeration, U-99
 - ODE, U-99
 - OSspecific, U-99
 - OpenFOAM, U-98
 - P1, U-101
 - PV4FoamReader, U-169
 - SLGThermo, U-102
 - Wallis, U-101
 - autoMesh, U-99
 - barotropicCompressibilityModels, U-101
 - basicSolidThermo, U-102
 - basicThermophysicalModels, U-100
 - blockMesh, U-99
 - chemistryModel, U-102
 - cloudFunctionObjects, U-98
 - coalCombustion, U-99
 - compressibleLESModels, U-104
 - compressibleRASModels, U-103
 - conversion, U-99
 - decompositionMethods, U-99
 - distributionModels, U-99
 - dsmc, U-99
 - dynamicFvMesh, U-99
 - dynamicMesh, U-99
 - edgeMesh, U-99
 - engine, U-99
 - fieldFunctionObjects, U-98
 - fileFormats, U-99
 - finiteVolume, U-98
 - foamCalcFunctions, U-98
 - forces, U-98
 - fvDOM, U-101
 - fvmotionSolvers, U-99
 - genericFvPatchField, U-99
 - hExponentialThermo, U-102
 - incompressibleLESModels, U-103
 - incompressibleRASModels, U-102
 - incompressibleTransportModels, P-53, U-104
 - incompressibleTurbulenceModels, P-53

interfaceProperties, U-104
 jobControl, U-98
 lagrangianIntermediate, U-99
 lagrangian, U-99
 laminarFlameSpeedModels, U-101
 linear, U-101
 liquidMixtureProperties, U-102
 liquidProperties, U-102
 meshTools, U-99
 molecularMeasurements, U-99
 molecule, U-99
 opaqueSolid, U-101
 pairPatchAgglomeration, U-99
 postCalc, U-98
 potential, U-99
 primitive, P-21
 radiationModels, U-100
 randomProcesses, U-99
 reactionThermophysicalModels, U-100
 sampling, U-98
 solidChemistryModel, U-102
 solidMixtureProperties, U-102
 solidParticle, U-99
 solidProperties, U-102
 solidSpecie, U-102
 solidThermo, U-102
 specie, U-101
 spray, U-99
 surfMesh, U-99
 surfaceFilmModels, U-104
 systemCall, U-99
 thermophysicalFunctions, U-101
 thermophysical, U-191
 topoChangerFvMesh, U-99
 triSurface, U-99
 turbulence, U-99
 twoPhaseProperties, U-104
 utilityFunctionObjects, U-99
 viewFactor, U-101
 vtkPV4Foam, U-169
 libs keyword, U-80, U-115
 lid-driven cavity flow, U-17
 LienCubicKE model, U-102
 LienCubicKELowRe model, U-102
 LienLeschzinerLowRe model, U-102
 Lights button, U-174
 limited
 keyword entry, U-120, U-121
 limitedCubic
 keyword entry, U-119

limitedLinear
 keyword entry, U-119
 line
 keyword entry, U-142
 Line Style menu, U-35
 linear
 library, U-101
 linear model, U-195
 linear
 keyword entry, U-119, U-122
 linearUpwind
 keyword entry, U-119, U-122
 liquid
 electrically-conducting, P-67
 liquidMixtureProperties
 library, U-102
 liquidProperties
 library, U-102
 lists, P-27
 List<Type> template class, P-27
 localEuler
 keyword entry, U-122
 location keyword, U-107
 locationInMesh keyword, U-152, U-154
 lowCpCoeffs keyword, U-194
 lowReOneEqEddy model, U-104
 LRDDiffStress model, U-103
 LRR model, U-102, U-103
 lsGrad
 fvc member function, P-35

M

Mach utility, U-94
 mag
 tensor member function, P-23
 magneticFoam solver, U-89
 magnetohydrodynamics, P-67
 magSqr
 tensor member function, P-23
 Make directory, U-73
 make script/alias, U-71
 Make/files file, U-75
 manual
 keyword entry, U-82, U-83
 manualCoeffs keyword, U-83
 mapFields utility, U-31, U-38, U-42, U-56, U-90,
 U-165
 mapFieldsPar utility, U-90
 mapping
 fields, U-165
 Marker Style menu, U-35

- matrices tools, U-98
- max
 - tensor member function, P-23
- maxAlphaCo keyword, U-62
- maxBoundarySkewness keyword, U-158
- maxCo keyword, U-62, U-115
- maxConcave keyword, U-158
- maxDeltaT keyword, U-62
- maxDeltaxyz model, U-103
- maxFaceThicknessRatio keyword, U-157
- maxGlobalCells keyword, U-152
- maximum iterations, U-124
- maxInternalSkewness keyword, U-158
- maxIter keyword, U-124
- maxLocalCells keyword, U-152
- maxNonOrtho keyword, U-158
- maxThicknessToMedialRatio keyword, U-157
- mdEquilibrationFoam solver, U-89
- mdFoam solver, U-89
- mdlInitialise utility, U-90
- mechanicalProperties*
 - dictionary, U-51
- memory tools, U-98
- menu
 - Color By, U-173
 - Current Time Controls, U-25, U-171
 - Edit, U-174
 - Help, U-173
 - Line Style, U-35
 - Marker Style, U-35
 - VCR Controls, U-25, U-171
 - View, U-170, U-173
- menu entry
 - Plot Over Line, U-34
 - Save Animation, U-175
 - Save Screenshot, U-175
 - Settings, U-174
 - Solid Color, U-173
 - Toolbars, U-173
 - View Settings, U-24, U-173
 - Wireframe, U-173
 - fvSchemes, U-52
- mergeLevels keyword, U-126
- mergeMeshes utility, U-92
- mergeOrSplitBaffles utility, U-92
- mergePatchPairs keyword, U-141
- mergeTolerance keyword, U-150
- mesh
 - 1-dimensional, U-133
 - 1D, U-133
 - 2-dimensional, U-133
 - 2D, U-133
 - axi-symmetric, U-133
 - basic, P-29
 - block structured, U-140
 - decomposition, U-82
 - description, U-129
 - finite volume, P-29
 - generation, U-140, U-149
 - grading, U-140, U-143
 - grading, example of, P-50
 - non-orthogonal, P-43
 - refinement, P-61
 - resolution, U-29
 - specification, U-129
 - split-hex, U-149
 - Stereolithography (STL), U-149
 - surface, U-149
 - validity constraints, U-129
- Mesh Parts window panel, U-24
- meshes tools, U-98
- meshQualityControls keyword, U-150
- meshTools
 - library, U-99
- message passing interface
 - openMPI, U-84
- method keyword, U-83
- metis
 - keyword entry, U-83
- metisDecomp model, U-100
- MGridGenGAMGAgglomeration
 - library, U-99
- MGridGen
 - keyword entry, U-125
- mhdFoam solver, P-69, U-89
- midPoint
 - keyword entry, U-119
- midPoint keyword, U-187
- midPointAndFace keyword, U-187
- min
 - tensor member function, P-23
- minArea keyword, U-158
- minDeterminant keyword, U-158
- minFaceWeight keyword, U-158
- minFlatness keyword, U-158
- minMedianAxisAngle keyword, U-157
- MINMOD differencing, P-36
- minRefinementCells keyword, U-152
- minThickness keyword, U-157
- minTriangleTwist keyword, U-158

- minTwist keyword, U-158
- minVol keyword, U-158
- minVolRatio keyword, U-158
- mirrorMesh utility, U-92
- mixed
 - boundary condition, U-138
- mixedSmagorinsky model, U-103
- mixture keyword, U-193
- mixtureAdiabaticFlameT utility, U-97
- mode keyword, U-154
- model
 - APIfunctions, U-102
 - BirdCarreau, U-104
 - CrossPowerLaw, U-104
 - DeardorffDiffStress, U-103, U-104
 - GuldersEGRLaminarFlameSpeed, U-101
 - GuldersLaminarFlameSpeed, U-101
 - HerschelBulkley, U-104
 - LRDDiffStress, U-103
 - LRR, U-102, U-103
 - LamBremhorstKE, U-102
 - LaunderGibsonRSTM, U-102, U-103
 - LaunderSharmaKE, U-102, U-103
 - LienCubicKELowRe, U-102
 - LienCubicKE, U-102
 - LienLeschzinerLowRe, U-102
 - NSRDSfunctions, U-102
 - Newtonian, U-104
 - NonlinearKEShah, U-102
 - PengRobinsonGas, U-195
 - PrandtlDelta, U-103
 - RNGkEpsilon, U-102, U-103
 - RaviPetersen, U-101
 - Smagorinsky2, U-103
 - Smagorinsky, U-103, U-104
 - SpalartAllmarasDDES, U-104
 - SpalartAllmarasIDDES, U-104
 - SpalartAllmaras, U-102–U-104
 - adiabaticPerfectFluid, U-101, U-195
 - anisotropicFilter, U-103
 - basicMultiComponentMixture, U-100
 - chemistryModel, U-102
 - chemistrySolver, U-102
 - constTransport, U-101
 - constant, U-101
 - cubeRootVolDelta, U-103
 - decompose, U-100
 - distributed, U-100
 - dynLagrangian, U-103
 - dynOneEqEddy, U-103
 - eConstThermo, U-101
 - egrMixture, U-100
 - hConstThermo, U-101
 - hPolynomialThermo, U-101
 - hePsiThermo, U-100
 - heRhoThermo, U-100
 - heheuPsiThermo, U-100
 - homogenousDynOneEqEddy, U-103, U-104
 - homogenousDynSmagorinsky, U-103
 - homogeneousMixture, U-100
 - icoPolynomial, U-101, U-195
 - incompressiblePerfectGas, U-101, U-195
 - inhomogeneousMixture, U-100
 - interfaceProperties, U-104
 - janafThermo, U-101
 - kEpsilon, U-102, U-103
 - kOmegaSSTSAS, U-103
 - kOmegaSST, U-102, U-103
 - kOmega, U-102
 - kkLOmega, U-102
 - laminar, U-102, U-103
 - laplaceFilter, U-103
 - linear, U-195
 - lowReOneEqEddy, U-104
 - maxDeltaxyz, U-103
 - metisDecomp, U-100
 - mixedSmagorinsky, U-103
 - multiComponentMixture, U-100
 - multiphaseMixtureThermo, U-192
 - oneEqEddy, U-103, U-104
 - perfectFluid, U-101, U-195
 - perfectGas, U-195
 - polynomialTransport, U-101
 - powerLaw, U-104
 - psiReactionThermo, U-100, U-192
 - psiThermo, U-192
 - psiuReactionThermo, U-100, U-192
 - ptsotchDecomp, U-100
 - pureMixture, U-100
 - qZeta, U-102
 - reactingMixture, U-100
 - realizableKE, U-102, U-103
 - reconstruct, U-100
 - rhoConst, U-101, U-195
 - rhoReactionThermo, U-100, U-192
 - rhoThermo, U-192
 - scaleSimilarity, U-103
 - scotchDecomp, U-100
 - simpleFilter, U-103
 - singleStepReactingMixture, U-100

smoothDelta, U-103
 specieThermo, U-101
 spectEddyVisc, U-103
 sutherlandTransport, U-101
 v2f, U-103
 vanDriestDelta, U-104
 veryInhomogeneousMixture, U-100
 modifyMesh utility, U-93
 molecularMeasurements
 library, U-99
 molecule
 library, U-99
 molWeight keyword, U-196
 moveDynamicMesh utility, U-92
 moveEngineMesh utility, U-92
 moveMesh utility, U-92
 movingWallVelocity
 boundary condition, U-139
 MPI
 openMPI, U-84
 mshToFoam utility, U-91
 mu keyword, U-193
 multiComponentMixture model, U-100
 multiComponentMixture keyword, U-193
 multigrid
 geometric-algebraic, U-125
 multiphaseEulerFoam solver, U-87
 multiphaseInterFoam solver, U-87
 multiphaseMixtureThermo model, U-192
 MUSCL
 keyword entry, U-119

N

n keyword, U-83
 N2 keyword, U-193
 nabla
 operator, P-25
 nAlphaSubCycles keyword, U-63
 nBufferCellsNoExtrude keyword, U-157
 nCellsBetweenLevels keyword, U-152
neighbour
 dictionary, U-132
 neighbourPatch keyword, U-146
 netgenNeutralToFoam utility, U-91
 Newtonian
 keyword entry, U-60
 Newtonian model, U-104
 nextWrite
 keyword entry, U-114
 nFaces keyword, U-132
 nFinestSweeps keyword, U-126

nGrow keyword, U-157
 nLayerIter keyword, U-157
 nMoles keyword, U-196
 non-orthogonal mesh, P-43
 nonBlocking
 keyword entry, U-80
 none
 keyword entry, U-117, U-125
 NonlinearKEShik model, U-102
 nonNewtonianIcoFoam solver, U-86
 noWriteNow
 keyword entry, U-114
 nPostSweeps keyword, U-126
 nPreSweeps keyword, U-126
 nRelaxedIter keyword, U-157
 nRelaxIter keyword, U-155, U-157
 nSmoothNormals keyword, U-157
 nSmoothPatch keyword, U-155
 nSmoothScale keyword, U-158
 nSmoothSurfaceNormals keyword, U-157
 nSmoothThickness keyword, U-157
 nSolveIter keyword, U-155
 NSRDSfunctions model, U-102
 nu keyword, U-199
 null
 keyword entry, U-185
 numberOfSubdomains keyword, U-83

O

O2 keyword, U-193
 object keyword, U-107
 objToVTK utility, U-92
 ODE
 library, U-99
 oneEqEddy model, U-103, U-104
 Opacity text box, U-173
 opaqueSolid
 library, U-101
 OpenFOAM
 applications, U-69
 file format, U-106
 libraries, U-69
 OpenFOAM
 library, U-98
 OpenFOAM file syntax
 //, U-106
 openMPI
 message passing interface, U-84
 MPI, U-84
 operator
 scalar, P-26

vector, P-25
Options window, U-174
options file, U-73
order keyword, U-83
Orientation Axes button, U-24
orientFaceZone utility, U-92
OSspecific
 library, U-99
outer product, *see* tensor, outer product
outlet
 boundary condition, P-69
outletInlet
 boundary condition, U-139
outputControl keyword, U-179
outputTime
 keyword entry, U-179
outside
 keyword entry, U-154
owner
 dictionary, U-131
oxidant keyword, U-193

P

p field, U-23
P1
 library, U-101
p_rhgRefCell keyword, U-128
p_rhgRefValue keyword, U-128
pairPatchAgglomeration
 library, U-99
paraFoam, U-23, U-169
parallel
 running, U-81
Paramters window panel, U-171
partialSlip
 boundary condition, U-139
particleTracks utility, U-95
patch
 boundary condition, U-136
patch
 keyword entry, U-137, U-186
patchAverage utility, U-94
patches keyword, U-141
patchIntegrate utility, U-94
patchMap keyword, U-166
patchSummary utility, U-97
PBiCG
 keyword entry, U-124
PCG
 keyword entry, U-124
pdfPlot utility, U-95
PDRFoam solver, U-88
PDRMesh utility, U-93
Pe utility, U-94
PengRobinsonGas model, U-195
perfectFluid model, U-101, U-195
perfectGas model, U-195
permutation symbol, P-18
pimpleFoam solver, U-86
Pipeline Browser window, U-24, U-170
PISO
 dictionary, U-23
pisoFoam solver, U-17, U-86
Plot Over Line
 menu entry, U-34
plot3dToFoam utility, U-91
pointField class, P-29
pointField<Type> template class, P-31
points
 dictionary, U-131, U-140
polyBoundaryMesh class, P-29
polyDualMesh utility, U-92
polyLine
 keyword entry, U-142
polyMesh directory, U-105, U-131
polyMesh class, P-29, U-129, U-131
polynomialTransport model, U-101
polyPatch class, P-29
polyPatchList class, P-29
post-processing, U-169
 post-processing
 paraFoam, U-169
postCalc
 library, U-98
postChannel utility, U-95
potential
 library, U-99
potentialFreeSurfaceFoam solver, U-87
potentialFoam solver, P-44, U-86
pow
 tensor member function, P-23
powerLaw model, U-104
pPrime2 utility, U-94
Pr keyword, U-193
PrandtlDelta model, U-103
preconditioner keyword, U-124, U-125
pRefCell keyword, U-23, U-128
pRefValue keyword, U-23, U-127
pressure keyword, U-51
pressure waves
 in liquids, P-62

- pressureDirectedInletVelocity
 boundary condition, U-139
 pressureInletVelocity
 boundary condition, U-139
 pressureOutlet
 boundary condition, P-63
 pressureTransmissive
 boundary condition, U-139
 primitive
 library, P-21
 primitives tools, U-98
 printCoeffs keyword, U-42, U-198
 processorWeights keyword, U-82
 probeLocations utility, U-95
 process
 background, U-24, U-81
 foreground, U-24
 processor
 boundary condition, U-138
 processor
 keyword entry, U-137
processorN directory, U-83
 processorWeights keyword, U-83
 Properties window, U-171, U-172
 Properties window panel, U-25, U-170
 psiReactionThermo model, U-100, U-192
 psiThermo model, U-192
 psiuReactionThermo model, U-100, U-192
 ptot utility, U-95
 ptsotchDecomp model, U-100
 pureMixture model, U-100
 pureMixture
 keyword entry, U-193
 purgeWrite keyword, U-114
 PV4FoamReader
 library, U-169
- Q**
- Q utility, U-94
 QUICK
 keyword entry, U-122
 qZeta model, U-102
- R**
- R utility, U-94
 radiationModels
 library, U-100
 randomProcesses
 library, U-99
 RAS
 keyword entry, U-41, U-197
 RASModel
 keyword entry, U-41
 RASModel keyword, U-198
 RaviPetersen model, U-101
 raw
 keyword entry, U-115, U-185
 reactingEulerFoam solver, U-88
 reactingFoam solver, U-88
 reactingMixture model, U-100
 reactingMixture
 keyword entry, U-193
 reactingParcelFilmFoam solver, U-89
 reactingParcelFoam solver, U-89
 reactionThermophysicalModels
 library, U-100
 realizableKE model, U-102, U-103
 reconstruct model, U-100
 reconstructPar utility, U-85, U-97
 reconstructParMesh utility, U-97
 redistributePar utility, U-97
 refGradient keyword, U-138
 refineHexMesh utility, U-93
 refinementRegions keyword, U-154
 refinementLevel utility, U-93
 refinementRegions keyword, U-152, U-154
 refinementSurfaces keyword, U-152, U-153
 refineMesh utility, U-92
 refineWallLayer utility, U-93
 Refresh Times button, U-25, U-171
 regions keyword, U-60
 relative tolerance, U-124
 relativeSizes keyword, U-157
 relaxed keyword, U-158
 relTo1 keyword, U-53, U-124
 removeFaces utility, U-93
 Render View window, U-174
 Render View window panel, U-173, U-174
 renumberMesh utility, U-92
 Rescale to Data Range button, U-25
 Reset button, U-170
 resolveFeatureAngle keyword, U-152, U-153
 restart, U-39
 Reynolds number, U-17, U-21
 rhoPorousSimpleFoam solver, U-86
 rhoReactingBuoyantFoam solver, U-88
 rhoCentralDyMFoam solver, U-86
 rhoCentralFoam solver, U-86
 rhoConst model, U-101, U-195
 rhoPimpleFoam solver, U-86
 rhoReactingFoam solver, U-88

rhoReactionThermo model, U-100, U-192
 rhoSimpleFoam solver, U-86
 rhoSimplecFoam solver, U-86
 rhoThermo model, U-192
 rmdepall script/alias, U-77
 RNGkEpsilon model, U-102, U-103
 roots keyword, U-83, U-84
 rotateMesh utility, U-92
 run
 parallel, U-81
 run directory, U-105
 runTime
 keyword entry, U-32, U-114
 runTimeModifiable keyword, U-115

S

sammToFoam utility, U-91
 sample utility, U-95, U-184
 sampling
 library, U-98
 Save Animation
 menu entry, U-175
 Save Screenshot
 menu entry, U-175
 scalar, P-14
 operator, P-26
 scalar class, P-22
 scalarField class, P-27
 scalarTransportFoam solver, U-86
 scale
 tensor member function, P-23
 scalePoints utility, U-162
 scaleSimilarity model, U-103
 scheduled
 keyword entry, U-80
 scientific
 keyword entry, U-114
 scotch
 keyword entry, U-82, U-83
 scotchCoeffs keyword, U-83
 scotchDecomp model, U-100
 script/alias
 find, U-179
 foamCorrectVrt, U-164
 foamJob, U-188
 foamLog, U-188
 make, U-71
 rmdepall, U-77
 wclean, U-76
 wmake, U-71
 second time derivative, P-35
 Seed window, U-175
 selectCells utility, U-93
 Set Ambient Color button, U-173
 setFields utility, U-60, U-90
 setFormat keyword, U-185
 sets keyword, U-185
 setSet utility, U-92
 setsToZones utility, U-92
 Settings
 menu entry, U-174
 SFCD
 keyword entry, U-119, U-122
 shallowWaterFoam solver, U-86
 shape, U-143
 SI units, U-110
 simple
 keyword entry, U-82, U-83
 simpleFilter model, U-103
 simpleFoam solver, P-53, U-86
 simpleGrading keyword, U-143
 simulationType keyword, U-41, U-61, U-197
 singleCellMesh utility, U-92
 singleStepReactingMixture model, U-100
 singleStepReactingMixture keyword, U-193
 skew
 tensor member function, P-23
 skewLinear
 keyword entry, U-119, U-122
 SLGThermo
 library, U-102
 slice class, P-29
 slip
 boundary condition, U-139
 Smagorinsky model, U-103, U-104
 Smagorinsky2 model, U-103
 smapToFoam utility, U-93
 smoothDelta model, U-103
 smoother keyword, U-126
 smoothSolver
 keyword entry, U-124
 snap keyword, U-150
 snapControls keyword, U-150
 snappyHexMesh utility
 background mesh, U-151
 cell removal, U-154
 cell splitting, U-152
 mesh layers, U-155
 meshing process, U-149
 snapping to surfaces, U-155
 snappyHexMesh utility, U-91, U-149

- snappyHexMeshDict* file, U-150
- snGrad
 - fvc member function, P-35
- snGradCorrection
 - fvc member function, P-35
- snGradSchemes keyword, U-116
- Solid Color
 - menu entry, U-173
- solidChemistryModel
 - library, U-102
- solidDisplacementFoam solver, U-89
- solidDisplacementFoam solver, U-51
- solidEquilibriumDisplacementFoam solver, U-89
- solidMixtureProperties
 - library, U-102
- solidParticle
 - library, U-99
- solidProperties
 - library, U-102
- solidSpecie
 - library, U-102
- solidThermo
 - library, U-102
- solver
 - DPMFoam, U-89
 - PDRFoam, U-88
 - XiFoam, U-88
 - adjointShapeOptimizationFoam, U-86
 - blockMesh, P-45
 - boundaryFoam, U-86
 - buoyantBoussinesqPimpleFoam, U-88
 - buoyantBoussinesqSimpleFoam, U-88
 - buoyantPimpleFoam, U-88
 - buoyantSimpleFoam, U-88
 - cavitatingDyMFoam, U-87
 - cavitatingFoam, U-87
 - chemFoam, U-88
 - chtMultiRegionFoam, U-88
 - chtMultiRegionSimpleFoam, U-88
 - coalChemistryFoam, U-89
 - coldEngineFoam, U-88
 - compressibleInterDyMFoam, U-87
 - compressibleInterFoam, U-87
 - compressibleMultiphaseInterFoam, U-87
 - dnsFoam, U-88
 - driftFluxFoam, U-87
 - dsmcFoam, U-89
 - electrostaticFoam, U-89
 - engineFoam, U-88
 - financialFoam, U-90
 - fireFoam, U-88
 - icoFoam, U-17, U-21, U-22, U-24, U-86
 - icoUncoupledKinematicParcelFoam, U-89
 - interFoam, U-87
 - interMixingFoam, U-87
 - interPhaseChangeDyMFoam, U-87
 - interPhaseChangeFoam, U-87
 - laplacianFoam, U-86
 - magneticFoam, U-89
 - mdEquilibrationFoam, U-89
 - mdFoam, U-89
 - mhdFoam, P-69, U-89
 - multiphaseEulerFoam, U-87
 - multiphaseInterFoam, U-87
 - nonNewtonianIcoFoam, U-86
 - pimpleFoam, U-86
 - pisoFoam, U-17, U-86
 - potentialFoam, P-44, U-86
 - potentialFreeSurfaceFoam, U-87
 - reactingEulerFoam, U-88
 - reactingFoam, U-88
 - reactingParcelFilmFoam, U-89
 - reactingParcelFoam, U-89
 - rhoCentralDyMFoam, U-86
 - rhoCentralFoam, U-86
 - rhoPimpleFoam, U-86
 - rhoReactingFoam, U-88
 - rhoSimpleFoam, U-86
 - rhoSimplecFoam, U-86
 - rhoPorousSimpleFoam, U-86
 - rhoReactingBuoyantFoam, U-88
 - scalarTransportFoam, U-86
 - shallowWaterFoam, U-86
 - simpleFoam, P-53, U-86
 - solidDisplacementFoam, U-89
 - solidDisplacementFoam, U-51
 - solidEquilibriumDisplacementFoam, U-89
 - sonicDyMFoam, U-86
 - sonicFoam, P-59, U-87
 - sonicLiquidFoam, P-63, U-87
 - sprayFoam, U-89
 - thermoFoam, U-88
 - twoLiquidMixingFoam, U-88
 - twoPhaseEulerFoam, U-88
 - uncoupledKinematicParcelFoam, U-89
- solver keyword, U-53, U-123
- solver relative tolerance, U-124
- solver tolerance, U-124
- solvers keyword, U-123
- sonicDyMFoam solver, U-86

- sonicFoam solver, P-59, U-87
- sonicLiquidFoam solver, P-63, U-87
- source, P-35
- SpalartAllmaras model, U-102–U-104
- SpalartAllmarasDDES model, U-104
- SpalartAllmarasIDDES model, U-104
- specie
 - library, U-101
- specie keyword, U-196
- specieThermo model, U-101
- spectEddyVisc model, U-103
- spline
 - keyword entry, U-142
- spline keyword, U-141
- splitCells utility, U-93
- splitMesh utility, U-92
- splitMeshRegions utility, U-92
- spray
 - library, U-99
- sprayFoam solver, U-89
- sqr
 - tensor member function, P-23
- sqrGradGrad
 - fvc member function, P-35
- star3ToFoam utility, U-91
- star4ToFoam utility, U-91
- startFace keyword, U-132
- startFrom keyword, U-22, U-113
- starToFoam utility, U-159
- startTime
 - keyword entry, U-22, U-113
- startTime keyword, U-22, U-113
- steady flow
 - turbulent, P-50
- steadyParticleTracks utility, U-95
- steadyState
 - keyword entry, U-122
- Stereolithography (STL), U-149
- stitchMesh utility, U-92
- stl
 - keyword entry, U-185
- stopAt keyword, U-113
- strategy keyword, U-82, U-83
- streamFunction utility, U-94
- stress analysis of plate with hole, U-46
- stressComponents utility, U-94
- Style window panel, U-173
- Su
 - fvm member function, P-35
- subsetMesh utility, U-93
- summation convention, P-15
- SUPERBEE differencing, P-36
- supersonic flow, P-58
- supersonic flow over forward step, P-58
- supersonicFreeStream
 - boundary condition, U-139
- surfaceLambdaMuSmooth utility, U-96
- surface mesh, U-149
- surfaceAdd utility, U-95
- surfaceAutoPatch utility, U-95
- surfaceBooleanFeatures utility, U-95
- surfaceCheck utility, U-95
- surfaceClean utility, U-95
- surfaceCoarsen utility, U-95
- surfaceConvert utility, U-95
- surfaceFeatureConvert utility, U-95
- surfaceFeatureExtract utility, U-95, U-153
- surfaceField<Type> template class, P-31
- surfaceFilmModels
 - library, U-104
- surfaceFind utility, U-95
- surfaceFormat keyword, U-185
- surfaceHookUp utility, U-95
- surfaceInertia utility, U-96
- surfaceMesh tools, U-98
- surfaceMeshConvert utility, U-96
- surfaceMeshConvertTesting utility, U-96
- surfaceMeshExport utility, U-96
- surfaceMeshImport utility, U-96
- surfaceMeshInfo utility, U-96
- surfaceMeshTriangulate utility, U-96
- surfaceNormalFixedValue
 - boundary condition, U-139
- surfaceOrient utility, U-96
- surfacePointMerge utility, U-96
- surfaceRedistributePar utility, U-96
- surfaceRefineRedGreen utility, U-96
- surfaces keyword, U-185
- surfaceSplitByPatch utility, U-96
- surfaceSplitByTopology utility, U-96
- surfaceSplitNonManifolds utility, U-96
- surfaceSubset utility, U-96
- surfaceToPatch utility, U-96
- surfaceTransformPoints utility, U-96
- surfMesh
 - library, U-99
- SuSp
 - fvm member function, P-35
- sutherlandTransport model, U-101
- symm

tensor member function, P-23
 symmetryPlane
 boundary condition, P-63, U-137
 symmetryPlane
 keyword entry, U-137
 symmTensorField class, P-27
 symmTensorThirdField class, P-27
 system directory, P-48, U-105
 systemCall
 library, U-99

T

T()

 tensor member function, P-23

Tcommon keyword, U-194

template class

 GeometricBoundaryField, P-30

 fvMatrix, P-34

 dimensioned<Type>, P-24

 FieldField<Type>, P-30

 Field<Type>, P-27

 geometricField<Type>, P-30

 List<Type>, P-27

 pointField<Type>, P-31

 surfaceField<Type>, P-31

 volField<Type>, P-31

temporal discretisation, P-40

 Crank Nicolson, P-41

 Euler implicit, P-40

 explicit, P-40

 in OpenFOAM, P-41

temporalInterpolate utility, U-95

tensor, P-13

 addition, P-16

 algebraic operations, P-16

 algebraic operations in OpenFOAM, P-22

 antisymmetric, *see* tensor, skew

 calculus, P-25

 classes in OpenFOAM, P-21

 cofactors, P-20

 component average, P-18

 component maximum, P-18

 component minimum, P-18

 determinant, P-20

 deviatoric, P-20

 diagonal, P-20

 dimension, P-14

 double inner product, P-17

 geometric transformation, P-19

 Hodge dual, P-21

 hydrostatic, P-20

 identities, P-19

 identity, P-19

 inner product, P-16

 inverse, P-21

 magnitude, P-18

 magnitude squared, P-18

 mathematics, P-13

 notation, P-15

 nth power, P-18

 outer product, P-17

 rank, P-14

 rank 3, P-15

 scalar division, P-16

 scalar multiplication, P-16

 scale function, P-18

 second rank, P-14

 skew, P-20

 square of, P-18

 subtraction, P-16

 symmetric, P-20

 symmetric rank 2, P-14

 symmetric rank 3, P-15

 trace, P-20

 transformation, P-19

 transpose, P-14, P-20

 triple inner product, P-17

 vector cross product, P-18

tensor class, P-22

tensor member function

 *, P-23

 +, P-23

 -, P-23

 /, P-23

 &, P-23

 &&, P-23

 ~, P-23

 cmptAv, P-23

 cofactors, P-23

 det, P-23

 dev, P-23

 diag, P-23

 I, P-23

 inv, P-23

 mag, P-23

 magSqr, P-23

 max, P-23

 min, P-23

 pow, P-23

 scale, P-23

 skew, P-23

- sqr, P-23
- symm, P-23
- T(), P-23
- tr, P-23
- transform, P-23
- tensorField class, P-27
- tensorThirdField class, P-27
- tetgenToFoam utility, U-91
- text box
 - Opacity, U-173
- thermalProperties*
 - dictionary, U-51
- thermodynamics keyword, U-196
- thermoFoam solver, U-88
- thermophysical
 - library, U-191
- thermophysicalFunctions
 - library, U-101
- thermophysicalProperties*
 - dictionary, U-191
- thermoType keyword, U-191
- Thigh keyword, U-194
- time
 - control, U-113
- time derivative, P-35
 - first, P-37
 - second, P-35, P-37
- time step, U-22
- timeFormat keyword, U-114
- timePrecision keyword, U-115
- timeScheme keyword, U-116
- timeStamp
 - keyword entry, U-80
- timeStampMaster
 - keyword entry, U-80
- timeStep
 - keyword entry, U-23, U-32, U-114, U-179
- Tlow keyword, U-194
- tolerance
 - solver, U-124
 - solver relative, U-124
- tolerance keyword, U-53, U-124, U-155
- Toolbars
 - menu entry, U-173
- tools
 - algorithms, U-98
 - cfTools, U-98
 - containers, U-98
 - db, U-98
 - dimensionSet, U-98
 - dimensionedTypes, U-98
 - fields, U-98
 - finiteVolume, U-98
 - fvMatrices, U-98
 - fvMesh, U-98
 - global, U-98
 - graph, U-98
 - interpolations, U-98
 - interpolation, U-98
 - matrices, U-98
 - memory, U-98
 - meshes, U-98
 - primitives, U-98
 - surfaceMesh, U-98
 - volMesh, U-98
- topoChangerFvMesh
 - library, U-99
- topoSet utility, U-93
- topoSetSource keyword, U-60
- totalPressure
 - boundary condition, U-139
- tr
 - tensor member function, P-23
- trace, *see* tensor, trace
- traction keyword, U-51
- transform
 - tensor member function, P-23
- transformPoints utility, U-93
- transport keyword, U-192, U-196
- transportProperties*
 - dictionary, U-21, U-39, U-42, U-199
- transportProperties* file, U-60
- triple inner product, P-17
- triSurface
 - library, U-99
- Ts keyword, U-193
- turbulence
 - dissipation, U-40
 - kinetic energy, U-40
 - length scale, U-41
- turbulence
 - library, U-99
- turbulence keyword, U-198
- turbulence model
 - RAS, U-40
- turbulenceProperties*
 - dictionary, U-41, U-61, U-197
- turbulent flow
 - steady, P-50
- turbulentInlet

boundary condition, U-139
 tutorials
 breaking of a dam, U-56
 lid-driven cavity flow, U-17
 stress analysis of plate with hole, U-46
tutorials directory, P-43, U-17
 twoLiquidMixingFoam solver, U-88
 twoPhaseEulerFoam solver, U-88
 twoPhaseProperties
 library, U-104
 type keyword, U-135, U-192

U

U field, U-23
 Ucomponents utility, P-70
 UMIST
 keyword entry, U-117
 uncompressed
 keyword entry, U-114
 uncorrected
 keyword entry, U-120, U-121
 uncoupledKinematicParcelFoam solver, U-89
 uniform keyword, U-187
 units
 base, U-110
 of measurement, P-24, U-109
 S.I. base, P-24
 SI, U-110
 Système International, U-110
 United States Customary System, U-110
 USCS, U-110
 Update GUI button, U-171
 uprime utility, U-94
 upwind
 keyword entry, U-119, U-122
 upwind differencing, P-36, U-63
 USCS units, U-110
 Use Parallel Projection button, U-24
 utility
 Co, U-93
 Lambda2, U-94
 Mach, U-94
 PDRMesh, U-93
 Pe, U-94
 Q, U-94
 R, U-94
 Ucomponents, P-70
 adiabaticFlameT, U-97
 ansysToFoam, U-91
 applyBoundaryLayer, U-90
 applyWallFunctionBoundaryConditions, U-90
 attachMesh, U-92
 autoPatch, U-92
 autoRefineMesh, U-93
 blockMesh, U-38, U-91, U-140
 boxTurb, U-90
 cfx4ToFoam, U-91, U-159
 changeDictionary, U-90
 checkMesh, U-92, U-160
 chemkinToFoam, U-97
 collapseEdges, U-93
 combinePatchFaces, U-93
 createBaffles, U-92
 createPatch, U-92
 createTurbulenceFields, U-94
 createExternalCoupledPatchGeometry, U-90
 datToFoam, U-91
 decomposePar, U-82, U-83, U-97
 deformedGeom, U-92
 dsmcFieldsCalc, U-95
 dsmcInitialise, U-90
 engineCompRatio, U-95
 engineSwirl, U-90
 ensight74FoamExec, U-183
 ensightFoamReader, U-93
 enstrophy, U-93
 equilibriumCO, U-97
 equilibriumFlameT, U-97
 execFlowFunctionObjects, U-95
 expandDictionary, U-97
 extrude2DMesh, U-91
 extrudeMesh, U-91
 extrudeToRegionMesh, U-91
 faceAgglomerate, U-90
 flattenMesh, U-92
 flowType, U-93
 fluent3DMeshToFoam, U-91
 fluentMeshToFoam, U-91, U-159
 foamCalc, U-33
 foamDataToFluent, U-93, U-181
 foamDebugSwitches, U-97
 foamFormatConvert, U-97
 foamHelp, U-97
 foamInfoExec, U-97
 foamListTimes, U-95
 foamMeshToFluent, U-91, U-181
 foamToEnightParts, U-93
 foamToEnight, U-93
 foamToGMV, U-93
 foamToStarMesh, U-91
 foamToSurface, U-91

- foamToTecplot360, U-93
- foamToTetDualMesh, U-93
- foamToVTK, U-93
- foamUpgradeCyclics, U-90
- foamUpgradeFvSolution, U-90
- foamyHexMesh, U-91
- foamyQuadMesh, U-91
- foamyHexMeshBackgroundMesh, U-91
- foamyHexMeshSurfaceSimplify, U-91
- gambitToFoam, U-91, U-159
- gmshToFoam, U-91
- ideasToFoam, U-159
- ideasUnvToFoam, U-91
- insideCells, U-92
- kivaToFoam, U-91
- mapFieldsPar, U-90
- mapFields, U-31, U-38, U-42, U-56, U-90, U-165
- mdlInitialise, U-90
- mergeMeshes, U-92
- mergeOrSplitBaffles, U-92
- mirrorMesh, U-92
- mixtureAdiabaticFlameT, U-97
- modifyMesh, U-93
- moveDynamicMesh, U-92
- moveEngineMesh, U-92
- moveMesh, U-92
- mshToFoam, U-91
- netgenNeutralToFoam, U-91
- objToVTK, U-92
- orientFaceZone, U-92
- pPrime2, U-94
- particleTracks, U-95
- patchAverage, U-94
- patchIntegrate, U-94
- patchSummary, U-97
- pdfPlot, U-95
- plot3dToFoam, U-91
- polyDualMesh, U-92
- postChannel, U-95
- probeLocations, U-95
- ptot, U-95
- reconstructParMesh, U-97
- reconstructPar, U-85, U-97
- redistributePar, U-97
- refineHexMesh, U-93
- refineMesh, U-92
- refineWallLayer, U-93
- refinementLevel, U-93
- removeFaces, U-93
- renumberMesh, U-92
- rotateMesh, U-92
- sammToFoam, U-91
- sample, U-95, U-184
- scalePoints, U-162
- selectCells, U-93
- setFields, U-60, U-90
- setSet, U-92
- setsToZones, U-92
- singleCellMesh, U-92
- smapToFoam, U-93
- snappyHexMesh, U-91, U-149
- splitCells, U-93
- splitMeshRegions, U-92
- splitMesh, U-92
- star3ToFoam, U-91
- star4ToFoam, U-91
- starToFoam, U-159
- steadyParticleTracks, U-95
- stitchMesh, U-92
- streamFunction, U-94
- stressComponents, U-94
- subsetMesh, U-93
- surfaceLambdaMuSmooth, U-96
- surfaceAdd, U-95
- surfaceAutoPatch, U-95
- surfaceBooleanFeatures, U-95
- surfaceCheck, U-95
- surfaceClean, U-95
- surfaceCoarsen, U-95
- surfaceConvert, U-95
- surfaceFeatureConvert, U-95
- surfaceFeatureExtract, U-95, U-153
- surfaceFind, U-95
- surfaceHookUp, U-95
- surfaceInertia, U-96
- surfaceMeshConvertTesting, U-96
- surfaceMeshConvert, U-96
- surfaceMeshExport, U-96
- surfaceMeshImport, U-96
- surfaceMeshInfo, U-96
- surfaceMeshTriangulate, U-96
- surfaceOrient, U-96
- surfacePointMerge, U-96
- surfaceRedistributePar, U-96
- surfaceRefineRedGreen, U-96
- surfaceSplitByPatch, U-96
- surfaceSplitByTopology, U-96
- surfaceSplitNonManifolds, U-96
- surfaceSubset, U-96

surfaceToPatch, U-96
 surfaceTransformPoints, U-96
 temporalInterpolate, U-95
 tetgenToFoam, U-91
 topoSet, U-93
 transformPoints, U-93
 uprime, U-94
 viewFactorsGen, U-90
 vorticity, U-94
 vtkUnstructuredToFoam, U-92
 wallFunctionTable, U-90
 wallGradU, U-94
 wallHeatFlux, U-94
 wallShearStress, U-94
 wdot, U-95
 writeCellCentres, U-95
 writeMeshObj, U-92
 yPlus, U-94
 zipUpMesh, U-93
 utilityFunctionObjects
 library, U-99

V

v2f model, U-103
 value keyword, U-21, U-138
 valueFraction keyword, U-138
 van Leer differencing, P-36
 vanDriestDelta model, U-104
 vanLeer
 keyword entry, U-119
 VCR Controls menu, U-25, U-171
 vector, P-14
 operator, P-25
 unit, P-18
 vector class, P-22, U-109
 vector product, *see* tensor, vector cross product
 vectorField class, P-27
 version keyword, U-107
 vertices keyword, U-20, U-141
 veryInhomogeneousMixture model, U-100
 veryInhomogeneousMixture keyword, U-193
 View menu, U-170, U-173
 View Render window panel, U-24
 View Settings
 menu entry, U-24, U-173
 viewFactor
 library, U-101
 viewFactorsGen utility, U-90
 viscosity
 kinematic, U-22, U-42
 volField<Type> template class, P-31

volMesh tools, U-98
 vorticity utility, U-94
 vtk
 keyword entry, U-185
 vtkPV4Foam
 library, U-169
 vtkUnstructuredToFoam utility, U-92

W

wall
 boundary condition, P-63, P-69, U-59, U-137
 wall
 keyword entry, U-137
 wallFunctionTable utility, U-90
 wallGradU utility, U-94
 wallHeatFlux utility, U-94
 Wallis
 library, U-101
 wallShearStress utility, U-94
 wclean script/alias, U-76
 wdot utility, U-95
 wedge
 boundary condition, U-133, U-137, U-148
 wedge
 keyword entry, U-137
 window
 Color Legend, U-29
 Options, U-174
 Pipeline Browser, U-24, U-170
 Properties, U-171, U-172
 Render View, U-174
 Seed, U-175
 window panel
 Animations, U-174
 Annotation, U-24
 Charts, U-174
 Color Legend, U-173
 Color Scale, U-173
 Colors, U-174
 Display, U-24, U-25, U-170, U-172
 General, U-174
 Information, U-170
 Mesh Parts, U-24
 Parameters, U-171
 Properties, U-25, U-170
 Render View, U-173, U-174
 Style, U-173
 View Render, U-24
 Wireframe
 menu entry, U-173
 WM_ARCH

environment variable, U-76
WM_ARCH_OPTION
environment variable, U-76
WM_COMPILE_OPTION
environment variable, U-76
WM_COMPILER
environment variable, U-76
WM_COMPILER_BIN
environment variable, U-76
WM_COMPILER_DIR
environment variable, U-76
WM_COMPILER_LIB
environment variable, U-76
WM_DIR
environment variable, U-76
WM_MPLIB
environment variable, U-76
WM_OPTIONS
environment variable, U-76
WM_PRECISION_OPTION
environment variable, U-76
WM_PROJECT
environment variable, U-76
WM_PROJECT_DIR
environment variable, U-76
WM_PROJECT_INST_DIR
environment variable, U-76
WM_PROJECT_USER_DIR
environment variable, U-76
WM_PROJECT_VERSION
environment variable, U-76
wmake
platforms, U-73
wmake script/alias, U-71

word class, P-24, P-29
writeCellCentres utility, U-95
writeCompression keyword, U-114
writeControl
keyword entry, U-114
writeControl keyword, U-22, U-62, U-114
writeFormat keyword, U-55, U-114
writeInterval
keyword entry, U-179
writeInterval keyword, U-23, U-32, U-114
writeMeshObj utility, U-92
writeNow
keyword entry, U-113
writePrecision keyword, U-114

X

x
keyword entry, U-187
XiFoam solver, U-88
xmgr
keyword entry, U-115, U-185
xyz
keyword entry, U-187

Y

y
keyword entry, U-187
yPlus utility, U-94

Z

z
keyword entry, U-187
zeroGradient
boundary condition, U-138
zipUpMesh utility, U-93