
cattr Documentation

Release 22.2.0

Tin Tvrtković

Jan 26, 2023

CONTENTS

1	cattr	3
1.1	Features	5
1.2	Additional documentation	5
1.3	Credits	6
2	Installation	7
2.1	Stable release	7
2.2	From sources	7
3	Converters	9
3.1	Global converter	9
3.2	Converter objects	9
3.3	<code>cattr.Converter</code>	10
3.4	<code>cattr.BaseConverter</code>	10
4	Common usage examples	11
4.1	Using Pendulum for Dates and Time	11
4.2	Using factory hooks	12
5	What you can structure and how	17
5.1	Primitive values	17
5.2	Collections and other generics	18
5.3	<code>cattr</code> classes and dataclasses	22
5.4	Using attribute types and converters	22
5.5	Registering custom structuring hooks	24
5.6	Structuring hook factories	25
6	What you can unstructure and how	27
6.1	Primitive types and collections	27
6.2	Customizing collection unstructuring	27
6.3	<code>typing.Annotated</code>	28
6.4	<code>typing.NewType</code>	28
6.5	<code>cattr</code> classes and dataclasses	29
6.6	Unstructuring hook factories	30
7	Validation	31
7.1	Detailed validation	31
7.2	Non-detailed validation	32
8	Preconfigured converters	33
8.1	Standard library <code>json</code>	34

8.2	<code>ujson</code>	34
8.3	<code>orjson</code>	34
8.4	<code>msgpack</code>	34
8.5	<code>bson</code>	34
8.6	<code>pyyaml</code>	35
8.7	<code>tomlkit</code>	35
9	Customizing class un/structuring	37
9.1	Using <code>cattr.Converter</code>	37
9.2	Manual un/structuring hooks	37
9.3	Using <code>cattr.gen</code> generators	37
10	Tips for handling unions	41
10.1	Unstructuring unions with extra metadata	41
11	Benchmarking	43
11.1	A Sample Workflow	43
12	Contributing	45
12.1	Types of Contributions	45
12.2	Get Started!	46
12.3	Pull Request Guidelines	47
12.4	Tips	47
13	History	49
13.1	22.2.0 (2022-10-03)	49
13.2	22.1.0 (2022-04-03)	49
13.3	1.10.0 (2022-01-04)	50
13.4	1.9.0 (2021-12-06)	50
13.5	1.8.0 (2021-08-13)	50
13.6	1.7.1 (2021-05-28)	51
13.7	1.7.0 (2021-05-26)	51
13.8	1.6.0 (2021-04-28)	51
13.9	1.5.0 (2021-04-15)	51
13.10	1.4.0 (2021-03-21)	52
13.11	1.3.0 (2021-02-25)	52
13.12	1.2.0 (2021-01-31)	52
13.13	1.1.2 (2020-11-29)	52
13.14	1.1.1 (2020-10-30)	53
13.15	1.1.0 (2020-10-29)	53
13.16	1.0.0 (2019-12-27)	53
13.17	0.9.1 (2019-10-26)	53
13.18	0.9.0 (2018-07-22)	53
13.19	0.8.1 (2018-06-19)	54
13.20	0.8.0 (2018-04-14)	54
13.21	0.7.0 (2018-04-12)	54
13.22	0.6.0 (2017-12-25)	54
13.23	0.5.0 (2017-12-11)	54
13.24	0.4.0 (2017-07-17)	55
13.25	0.3.0 (2017-03-18)	55
13.26	0.2.0 (2016-10-02)	55
13.27	0.1.0 (2016-08-13)	55
14	Indices and tables	57

Contents:

CATTRS

`cattr`s is an open source Python library for structuring and unstructuring data. `cattr`s works best with `attrs` classes, dataclasses and the usual Python collections, but other kinds of classes are supported by manually registering converters.

Python has a rich set of powerful, easy to use, built-in data types like dictionaries, lists and tuples. These data types are also the lingua franca of most data serialization libraries, for formats like json, msgpack, yaml or toml.

Data types like this, and mappings like `dict`s in particular, represent unstructured data. Your data is, in all likelihood, structured: not all combinations of field names or values are valid inputs to your programs. In Python, structured data is better represented with classes and enumerations. `attrs` is an excellent library for declaratively describing the structure of your data, and validating it.

When you're handed unstructured data (by your network, file system, database...), `cattr`s helps to convert this data into structured data. When you have to convert your structured data into data types other libraries can handle, `cattr`s turns your classes and enumerations into dictionaries, integers and strings.

Here's a simple taste. The list containing a float, an int and a string gets converted into a tuple of three ints.

```
>>> import cattr
>>>
>>> cattr.structure([1.0, 2, "3"], tuple[int, int, int])
(1, 2, 3)
```

`cattr`s works well with `attrs` classes out of the box.

```
>>> from attrs import frozen
>>> import cattr
>>>
>>> @frozen # It works with non-frozen classes too.
... class C:
...     a: int
...     b: str
... 
```

(continues on next page)

(continued from previous page)

```
>>> instance = C(1, 'a')
>>> cattr.unstructure(instance)
{'a': 1, 'b': 'a'}
>>> cattr.structure({'a': 1, 'b': 'a'}, C)
C(a=1, b='a')
```

Here's a much more complex example, involving attr classes with type metadata.

```
>>> from enum import unique, Enum
>>> from typing import Optional, Sequence, Union
>>> from cattr import structure, unstructure
>>> from attr import define, field
>>>
>>> @unique
... class CatBreed(Enum):
...     SIAMESE = "siamese"
...     MAINE_COON = "maine_coon"
...     SACRED_BIRMAN = "birman"
...
>>> @define
... class Cat:
...     breed: CatBreed
...     names: Sequence[str]
...
>>> @define
... class DogMicrochip:
...     chip_id = field() # Type annotations are optional, but recommended
...     time_chipped: float = field()
...
>>> @define
... class Dog:
...     cuteness: int
...     chip: Optional[DogMicrochip] = None
...
>>> p = unstructure([Dog(cuteness=1, chip=DogMicrochip(chip_id=1, time_chipped=10.0)),
...                  Cat(breed=CatBreed.MAINE_COON, names=('Fluffly', 'Fluffer'))])
>>> print(p)
[{'cuteness': 1, 'chip': {'chip_id': 1, 'time_chipped': 10.0}}, {'breed': 'maine_coon',
↪ 'names': ('Fluffly', 'Fluffer')}]
>>> print(structure(p, list[Union[Dog, Cat]]))
[Dog(cuteness=1, chip=DogMicrochip(chip_id=1, time_chipped=10.0)), Cat(breed=<CatBreed.
↪ MAINE_COON: 'maine_coon'>, names=['Fluffly', 'Fluffer'])]
```

Consider unstructured data a low-level representation that needs to be converted to structured data to be handled, and use `structure`. When you're done, `unstructure` the data to its unstructured form and pass it along to another library or module. Use `attr` type metadata to add type metadata to attributes, so `cattr` will know how to structure and destructure them.

- Free software: MIT license
- Documentation: <https://cattr.readthedocs.io>.
- Python versions supported: 3.7 and up. (Older Python versions, like 2.7, 3.5 and 3.6 are supported by older

versions; see the changelog.)

1.1 Features

- Converts structured data into unstructured data, recursively:
 - `attrs` classes and dataclasses are converted into dictionaries in a way similar to `attrs.asdict`, or into tuples in a way similar to `attrs.astuple`.
 - Enumeration instances are converted to their values.
 - Other types are let through without conversion. This includes types such as integers, dictionaries, lists and instances of non-`attrs` classes.
 - Custom converters for any type can be registered using `register_unstructure_hook`.
- Converts unstructured data into structured data, recursively, according to your specification given as a type. The following types are supported:
 - `typing.Optional[T]`.
 - `typing.List[T]`, `typing.MutableSequence[T]`, `typing.Sequence[T]` (converts to a list).
 - `typing.Tuple` (both variants, `Tuple[T, ...]` and `Tuple[X, Y, Z]`).
 - `typing.MutableSet[T]`, `typing.Set[T]` (converts to a set).
 - `typing.FrozenSet[T]` (converts to a frozenset).
 - `typing.Dict[K, V]`, `typing.MutableMapping[K, V]`, `typing.Mapping[K, V]` (converts to a dict).
 - `attrs` classes with simple attributes and the usual `__init__`.
 - * Simple attributes are attributes that can be assigned unstructured data, like numbers, strings, and collections of unstructured data.
 - All `attrs` classes and dataclasses with the usual `__init__`, if their complex attributes have type metadata.
 - `typing.Union` s of supported `attrs` classes, given that all of the classes have a unique field.
 - `typing.Union` s of anything, given that you provide a disambiguation function for it.
 - Custom converters for any type can be registered using `register_structure_hook`.

`cattr` comes with preconfigured converters for a number of serialization libraries, including json, msgpack, bson, yaml and toml. For details, see the [cattr.preconf package](#).

1.2 Additional documentation

- [On structured and unstructured data, or the case for cattr](#)
- [Why I use attrs instead of pydantic](#)
- [cattr I: un/structuring speed](#)

1.3 Credits

Major credits to Hynek Schlawack for creating `attrs` and its predecessor, `characteristic`.

`cattr` is tested with `Hypothesis`, by David R. MacIver.

`cattr` is benchmarked using `perf` and `pytest-benchmark`.

This package was created with `Cookiecutter` and the `audreyr/cookiecutter-pypackage` project template.

INSTALLATION

2.1 Stable release

To install cattr, run this command in your terminal:

```
$ pip install cattr
```

This is the preferred method to install cattr, as it will always install the most recent stable release.

If you don't have [pip](#) installed, this [Python installation guide](#) can guide you through the process.

2.2 From sources

The sources for cattr can be downloaded from the [Github repo](#).

You can either clone the public repository:

```
$ git clone git://github.com/python-attrs/cattr
```

Or download the [tarball](#):

```
$ curl -OL https://github.com/python-attrs/cattr/tarball/master
```

Once you have a copy of the source, you can install it with:

```
$ pip install -e .
```


CONVERTERS

All `cattr`s functionality is exposed through a `cattr`s.`Converter` object. Global `cattr`s functions, such as `cattr`s.`unstructure()`, use a single global converter. Changes done to this global converter, such as registering new `structure` and `unstructure` hooks, affect all code using the global functions.

3.1 Global converter

A global converter is provided for convenience as `cattr`s.`global_converter`. The following functions implicitly use this global converter:

- `cattr`s.`structure`
- `cattr`s.`unstructure`
- `cattr`s.`structure_attrs_fromtuple`
- `cattr`s.`structure_attrs_fromdict`

Changes made to the global converter will affect the behavior of these functions.

Larger applications are strongly encouraged to create and customize a different, private instance of `Converter`.

3.2 Converter objects

To create a private converter, simply instantiate a `cattr`s.`Converter`. Currently, a converter contains the following state:

- a registry of `unstructure` hooks, backed by a `singledispatch` and a `function_dispatch`.
- a registry of `structure` hooks, backed by a different `singledispatch` and `function_dispatch`.
- a LRU cache of union disambiguation functions.
- a reference to an unstructuring strategy (either `AS_DICT` or `AS_TUPLE`).
- a `dict_factory` callable, used for creating dicts when dumping `attr`s classes using `AS_DICT`.

Converters may be cloned using the `cattr`s.`Converter`.`copy` method. The new copy may be changed through the `copy` arguments, but will retain all manually registered hooks from the original.

3.3 cattrs.Converter

The `Converter` is a converter variant that automatically generates, compiles and caches specialized structuring and unstructuring hooks for `attrs` classes.

`Converter` differs from the `cattrs.BaseConverter` in the following ways:

- structuring and unstructuring of `attrs` classes is slower the first time, but faster every subsequent time
- structuring and unstructuring can be customized
- support for `attrs` classes with PEP563 (postponed) annotations
- support for generic `attrs` classes
- support for easy overriding collection unstructuring

3.4 cattrs.BaseConverter

The `BaseConverter` is a simpler and slower `Converter` variant. It does no code generation, so it may be faster on first-use which can be useful in specific cases, like CLI applications where startup time is more important than throughput.

COMMON USAGE EXAMPLES

This section covers common use examples of cattr's features.

4.1 Using Pendulum for Dates and Time

To use the excellent [Pendulum](#) library for datetimes, we need to register structuring and unstructuring hooks for it.

First, we need to decide on the unstructured representation of a datetime instance. Since all our datetimes will use the UTC time zone, we decide to use the UNIX epoch timestamp as our unstructured representation.

Define a class using Pendulum's `DateTime`:

```
import pendulum
from pendulum import DateTime

@define
class MyRecord:
    a_string: str
    a_datetime: DateTime
```

Next, we register hooks for the `DateTime` class on a new `Converter` instance.

```
converter = Converter()

converter.register_unstructure_hook(DateTime, lambda dt: dt.timestamp())

converter.register_structure_hook(DateTime, lambda ts, _: pendulum.from_timestamp(ts))
```

And we can proceed with unstructuring and structuring instances of `MyRecord`.

```
>>> my_record = MyRecord('test', pendulum.datetime(2018, 7, 28, 18, 24))
>>> my_record
MyRecord(a_string='test', a_datetime=DateTime(2018, 7, 28, 18, 24, 0, tzinfo=Timezone(
↪ 'UTC'))))

>>> converter.unstructure(my_record)
{'a_string': 'test', 'a_datetime': 1532802240.0}

>>> converter.structure({'a_string': 'test', 'a_datetime': 1532802240.0}, MyRecord)
MyRecord(a_string='test', a_datetime=DateTime(2018, 7, 28, 18, 24, 0, tzinfo=Timezone(
↪ 'UTC'))))
```

After a while, we realize we *will* need our datetimes to have timezone information. We decide to switch to using the ISO 8601 format for our unstructured datetime instances.

```
>>> converter = cattr.Converter()
>>> converter.register_unstructure_hook(DateTime, lambda dt: dt.to_iso8601_string())
>>> converter.register_structure_hook(DateTime, lambda isostring, _: pendulum.
↳ parse(isostring))

>>> my_record = MyRecord('test', pendulum.datetime(2018, 7, 28, 18, 24, tz='Europe/Paris
↳ '))
>>> my_record
MyRecord(a_string='test', a_datetime=DateTime(2018, 7, 28, 18, 24, 0, tzinfo=Timezone(
↳ 'Europe/Paris'))))

>>> converter.unstructure(my_record)
{'a_string': 'test', 'a_datetime': '2018-07-28T18:24:00+02:00'}

>>> converter.structure({'a_string': 'test', 'a_datetime': '2018-07-28T18:24:00+02:00'},
↳ MyRecord)
MyRecord(a_string='test', a_datetime=DateTime(2018, 7, 28, 18, 24, 0, tzinfo=Timezone(
↳ '+02:00'))))
```

4.2 Using factory hooks

For this example, let's assume you have some attr classes with snake case attributes, and you want to un/structure them as camel case.

Warning: A simpler and better approach to this problem is to simply make your class attributes camel case. However, this is a good example of the power of hook factories and cattr's component-based design.

Here's our simple data model:

```
@define
class Inner:
    a_snake_case_int: int
    a_snake_case_float: float
    a_snake_case_str: str

@define
class Outer:
    a_snake_case_inner: Inner
```

Let's examine our options one by one, starting with the simplest: writing manual un/structuring hooks.

We just write the code by hand and register it:

```
def unstructure_inner(inner):
    return {
        "aSnakeCaseInt": inner.a_snake_case_int,
        "aSnakeCaseFloat": inner.a_snake_case_float,
        "aSnakeCaseStr": inner.a_snake_case_str
```

(continues on next page)

(continued from previous page)

```

    }

converter.register_unstructure_hook(Inner, unstructure_inner)

```

(Let's skip the other unstructure hook and 2 structure hooks due to verbosity.)

This will get us where we want to go, but the drawbacks are immediately obvious: we'd need to write a ton of code ourselves, wasting effort, increasing our maintenance burden and risking bugs. Obviously this won't do.

Why write code when we can write code to write code for us? In this case this code has already been written for you. `cattr` contains a module, `cattr.gen`, with functions to automatically generate hooks exactly like this. These functions also take parameters to customize the generated hooks.

We can generate and register the renaming hooks we need:

```

from cattr.gen import make_dict_unstructure_fn, override

converter.register_unstructure_hook(
    Inner,
    make_dict_unstructure_fn(
        Inner,
        converter,
        a_snake_case_int=override(rename="aSnakeCaseInt"),
        a_snake_case_float=override(rename="aSnakeCaseFloat"),
        a_snake_case_str=override(rename="aSnakeCaseStr"),
    )
)

```

(Again skipping the other hooks due to verbosity.)

This is still too verbose and manual for our tastes, so let's automate it further. We need a way to convert snake case identifiers to camel case, so let's grab one from Stack Overflow:

```

def to_camel_case(snake_str: str) -> str:
    components = snake_str.split("_")
    return components[0] + "".join(x.title() for x in components[1:])

```

We can combine this with `attr.fields` to save us some typing:

```

from attr import fields
from cattr.gen import make_dict_unstructure_fn, override

converter.register_unstructure_hook(
    Inner,
    make_dict_unstructure_fn(
        Inner,
        converter,
        **{a.name: override(rename=to_camel_case(a.name)) for a in fields(Inner)}
    )
)

converter.register_unstructure_hook(
    Outer,
    make_dict_unstructure_fn(
        Outer,

```

(continues on next page)

(continued from previous page)

```

        converter,
        **{a.name: override(rename=to_camel_case(a.name)) for a in fields(Outer)}
    )
)

```

(Skipping the structuring hooks due to verbosity.)

Now we're getting somewhere, but we still need to do this for each class separately. The final step is using hook factories instead of hooks directly.

Hook factories are functions that return hooks. They are also registered using predicates instead of being attached to classes directly, like normal un/structure hooks. Predicates are functions that given a type return a boolean whether they handle it.

We want our hook factories to trigger for all attr classes, so we need a predicate to recognize whether a type is an attr class. Luckily, attr comes with `attr.has`, which is exactly this.

As the final step, we can combine all of this into two hook factories:

```

from attr import has, fields
from cattr import Converter
from cattr.gen import make_dict_unstructure_fn, make_dict_structure_fn, override

converter = Converter()

def to_camel_case(snake_str: str) -> str:
    components = snake_str.split("_")
    return components[0] + "".join(x.title() for x in components[1:])

def to_camel_case_unstructure(cls):
    return make_dict_unstructure_fn(
        cls,
        converter,
        **{
            a.name: override(rename=to_camel_case(a.name))
            for a in fields(cls)
        }
    )

def to_camel_case_structure(cls):
    return make_dict_structure_fn(
        cls,
        converter,
        **{
            a.name: override(rename=to_camel_case(a.name))
            for a in fields(cls)
        }
    )

converter.register_unstructure_hook_factory(
    has, to_camel_case_unstructure
)
converter.register_structure_hook_factory(
    has, to_camel_case_structure
)

```

(continues on next page)

(continued from previous page)

```
)
```

The `converter` instance will now un/structure every `attrs` class to camel case. Nothing has been omitted from this final example; it's complete.

WHAT YOU CAN STRUCTURE AND HOW

The philosophy of `cattr`s structuring is simple: give it an instance of Python built-in types and collections, and a type describing the data you want out. `cattr`s will convert the input data into the type you want, or throw an exception.

All structuring conversions are composable, where applicable. This is demonstrated further in the examples.

5.1 Primitive values

5.1.1 `typing.Any`

Use `typing.Any` to avoid applying any conversions to the object you're structuring; it will simply be passed through.

```
>>> cattr.structure(1, Any)
1
>>> d = {1: 1}
>>> cattr.structure(d, Any) is d
True
```

5.1.2 `int`, `float`, `str`, `bytes`

Use any of these primitive types to convert the object to the type.

```
>>> cattr.structure(1, str)
'1'
>>> cattr.structure("1", float)
1.0
```

In case the conversion isn't possible, the expected exceptions will be propagated out. The particular exceptions are the same as if you'd tried to do the conversion yourself, directly.

```
>>> cattr.structure("not-an-int", int)
Traceback (most recent call last):
...
ValueError: invalid literal for int() with base 10: 'not-an-int'
```

5.1.3 Enums

Enums will be structured by their values. This works even for complex values, like tuples.

```
>>> @unique
... class CatBreed(Enum):
...     SIAMESE = "siamese"
...     MAINE_COON = "maine_coon"
...     SACRED_BIRMAN = "birman"
...
>>> cattr.structure("siamese", CatBreed)
<CatBreed.SIAMESE: 'siamese'>
```

Again, in case of errors, the expected exceptions will fly out.

```
>>> cattr.structure("alsatian", CatBreed)
Traceback (most recent call last):
...
ValueError: 'alsatian' is not a valid CatBreed
```

5.2 Collections and other generics

5.2.1 Optionals

Optional primitives and collections are supported out of the box.

```
>>> cattr.structure(None, int)
Traceback (most recent call last):
...
TypeError: int() argument must be a string, a bytes-like object or a number, not
↳ 'NoneType'
>>> cattr.structure(None, Optional[int])
>>> # None was returned.
```

Bare `Optional` s (non-parameterized, just `Optional`, as opposed to `Optional[str]`) aren't supported, use `Optional[Any]` instead.

This generic type is composable with all other converters.

```
>>> cattr.structure(1, Optional[float])
1.0
```

5.2.2 Lists

Lists can be produced from any iterable object. Types converting to lists are:

- `Sequence[T]`
- `MutableSequence[T]`
- `List[T]`
- `list[T]`

In all cases, a new list will be returned, so this operation can be used to copy an iterable into a list. A bare type, for example `Sequence` instead of `Sequence[int]`, is equivalent to `Sequence[Any]`.

```
>>> cattrs.structure((1, 2, 3), MutableSequence[int])
[1, 2, 3]
```

These generic types are composable with all other converters.

```
>>> cattrs.structure((1, None, 3), list[Optional[str]])
['1', None, '3']
```

5.2.3 Sets and frozensets

Sets and frozensets can be produced from any iterable object. Types converting to sets are:

- `Set[T]`
- `MutableSet[T]`
- `set[T]`

Types converting to frozensets are:

- `FrozenSet[T]`
- `frozenset[T]`

In all cases, a new set or frozenset will be returned, so this operation can be used to copy an iterable into a set. A bare type, for example `MutableSet` instead of `MutableSet[int]`, is equivalent to `MutableSet[Any]`.

```
>>> cattrs.structure([1, 2, 3, 4], Set)
{1, 2, 3, 4}
```

These generic types are composable with all other converters.

```
>>> cattrs.structure([[1, 2], [3, 4]], set[frozenset[str]])
{frozenset({'1', '2'}), frozenset({'4', '3'})}
```

5.2.4 Dictionaries

Dicts can be produced from other mapping objects. To be more precise, the object being converted must expose an `items()` method producing an iterable key-value tuples, and be able to be passed to the `dict` constructor as an argument. Types converting to dictionaries are:

- `Dict[K, V]`
- `MutableMapping[K, V]`
- `Mapping[K, V]`
- `dict[K, V]`

In all cases, a new dict will be returned, so this operation can be used to copy a mapping into a dict. Any type parameters set to `typing.Any` will be passed through unconverted. If both type parameters are absent, they will be treated as `Any` too.

```
>>> from collections import OrderedDict
>>> cattr.structure(OrderedDict([(1, 2), (3, 4)]), Dict)
{1: 2, 3: 4}
```

These generic types are composable with all other converters. Note both keys and values can be converted.

```
>>> cattr.structure({1: None, 2: 2.0}, dict[str, Optional[int]])
{'1': None, '2': 2}
```

5.2.5 Homogeneous and heterogeneous tuples

Homogeneous and heterogeneous tuples can be produced from iterable objects. Heterogeneous tuples require an iterable with the number of elements matching the number of type parameters exactly. Use:

- `Tuple[A, B, C, D]`
- `tuple[A, B, C, D]`

Homogeneous tuples use:

- `Tuple[T, ...]`
- `tuple[T, ...]`

In all cases a tuple will be returned. Any type parameters set to `typing.Any` will be passed through unconverted.

```
>>> cattr.structure([1, 2, 3], tuple[int, str, float])
(1, '2', 3.0)
```

The tuple conversion is composable with all other converters.

```
>>> cattr.structure([{'1': 1}, {'2': 2}], tuple[dict[str, float], ...])
({'1': 1.0}, {'2': 2.0})
```

5.2.6 Unions

Unions of `NoneType` and a single other type are supported (also known as `Optional` s). All other unions require a disambiguation function.

Automatic Disambiguation

In the case of a union consisting exclusively of `cattr` classes, `cattr` will attempt to generate a disambiguation function automatically; this will succeed only if each class has a unique field. Given the following classes:

```
>>> @define
... class A:
...     a = field()
...     x = field()
...
>>> @define
... class B:
...     a = field()
...     y = field()
```

(continues on next page)

(continued from previous page)

```

...
>>> @define
... class C:
...     a = field()
...     z = field()
...

```

cattr can deduce only instances of A will contain *x*, only instances of B will contain *y*, etc. A disambiguation function using this information will then be generated and cached. This will happen automatically, the first time an appropriate union is structured.

Manual Disambiguation

To support arbitrary unions, register a custom structuring hook for the union (see [Registering custom structuring hooks](#)).

5.2.7 typing.Annotated

PEP 593 annotations (`typing.Annotated[type, ...]`) are supported and are matched using the first type present in the annotated type.

5.2.8 typing.NewType

`NewTypes` are supported and are structured according to the rules for their underlying type. Their hooks can also be overridden using `cattr.Converter.register_structure_hook`.

```

>>> from typing import NewType
>>> from datetime import datetime

>>> IsoDate = NewType("IsoDate", datetime)

>>> converter = cattr.Converter()
>>> converter.register_structure_hook(IsoDate, lambda v, _: datetime.fromisoformat(v))

>>> converter.structure("2022-01-01", IsoDate)
datetime.datetime(2022, 1, 1, 0, 0)

```

New in version 22.2.0.

See also:

Unstructuring NewTypes.

Note: `NewTypes` are not supported by the legacy `BaseConverter`.

5.3 attrs classes and dataclasses

5.3.1 Simple attrs classes and dataclasses

attrs classes and dataclasses using primitives, collections of primitives and their own converters work out of the box. Given a mapping `d` and class `A`, `catrs` will simply instantiate `A` with `d` unpacked.

```
>>> @define
... class A:
...     a: int
...     b: int
...
>>> catrs.structure({'a': 1, 'b': '2'}, A)
A(a=1, b=2)
```

Classes like these deconstructed into tuples can be structured using `catrs.structure_attrs_fromtuple` (`fromtuple` as in the opposite of `attr.astuple` and `converter.unstructure_attrs_astuple`).

```
>>> @define
... class A:
...     a: str
...     b: int
...
>>> catrs.structure_attrs_fromtuple(['string', '2'], A)
A(a='string', b=2)
```

Loading from tuples can be made the default by creating a new `Converter` with `unstruct_strat=catrs.UnstructureStrategy.AS_TUPLE`.

```
>>> converter = catrs.Converter(unstruct_strat=catrs.UnstructureStrategy.AS_TUPLE)
>>> @define
... class A:
...     a: str
...     b: int
...
>>> converter.structure(['string', '2'], A)
A(a='string', b=2)
```

Structuring from tuples can also be made the default for specific classes only; see registering custom structure hooks below.

5.4 Using attribute types and converters

By default, calling “structure” will use hooks registered using `catrs.register_structure_hook`, to convert values to the attribute type, and fallback to invoking any converters registered on attributes with `attrib`.

```
>>> from ipaddress import IPv4Address, ip_address
>>> converter = catrs.Converter()

# Note: register_structure_hook has not been called, so this will fallback to 'ip_address
↪ '
```

(continues on next page)

(continued from previous page)

```
>>> @define
... class A:
...     a: IPv4Address = field(converter=ip_address)

>>> converter.structure({'a': '127.0.0.1'}, A)
A(a=IPv4Address('127.0.0.1'))
```

Priority is still given to hooks registered with `cattr.register_structure_hook`, but this priority can be inverted by setting `prefer_attrib_converters` to `True`.

```
>>> converter = cattr.Converter(prefer_attrib_converters=True)

>>> converter.register_structure_hook(int, lambda v, t: int(v))

>>> @define
... class A:
...     a: int = field(converter=lambda v: int(v) + 5)

>>> converter.structure({'a': '10'}, A)
A(a=15)
```

5.4.1 Complex attr classes and dataclasses

Complex attr classes and dataclasses are classes with type information available for some or all attributes. These classes support almost arbitrary nesting.

Type information is supported by attr directly, and can be set using type annotations when using Python 3.6+, or by passing the appropriate type to `attr.ib`.

```
>>> @define
... class A:
...     a: int
...
>>> attr.fields(A).a
Attribute(name='a', default=NOTHING, validator=None, repr=True, eq=True, eq_key=None,
↳ order=True, order_key=None, hash=None, init=True, metadata=mappingproxy({}), type=
↳ <class 'int'>, converter=None, kw_only=False, inherited=False, on_setattr=None)
```

Type information, when provided, can be used for all attribute types, not only attributes holding attr classes and dataclasses.

```
>>> @define
... class A:
...     a: int = 0
...
>>> @define
... class B:
...     b: A
...
>>> cattr.structure({'b': {'a': '1'}}, B)
B(b=A(a=1))
```

5.5 Registering custom structuring hooks

cattr doesn't know how to structure non-attrs classes by default, so it has to be taught. This can be done by registering structuring hooks on a converter instance (including the global converter).

Here's an example involving a simple, classic (i.e. non-attrs) Python class.

```
>>> class C:
...     def __init__(self, a):
...         self.a = a
...     def __repr__(self):
...         return f'C(a={self.a})'
>>> cattr.structure({'a': 1}, C)
Traceback (most recent call last):
...
StructureHandlerNotFoundError: Unsupported type: <class '__main__.C'>. Register a
↳ structure hook for it.
>>>
>>> cattr.register_structure_hook(C, lambda d, t: C(**d))
>>> cattr.structure({'a': 1}, C)
C(a=1)
```

The structuring hooks are callables that take two arguments: the object to convert to the desired class and the type to convert to. The type may seem redundant but is useful when dealing with generic types.

When using `cattr.register_structure_hook`, the hook will be registered on the global converter. If you want to avoid changing the global converter, create an instance of `cattr.Converter` and register the hook on that.

In some situations, it is not possible to decide on the converter using typing mechanisms alone (such as with attrs classes). In these situations, cattr provides a `register_structure_func_hook` instead, which accepts a predicate function to determine whether that type can be handled instead.

The function-based hooks are evaluated after the class-based hooks. In the case where both a class-based hook and a function-based hook are present, the class-based hook will be used.

```
>>> class D:
...     custom = True
...     def __init__(self, a):
...         self.a = a
...     def __repr__(self):
...         return f'D(a={self.a})'
...     @classmethod
...     def deserialize(cls, data):
...         return cls(data["a"])
>>> cattr.register_structure_hook_func(lambda cls: getattr(cls, "custom", False),
↳ lambda d, t: t.deserialize(d))
>>> cattr.structure({'a': 2}, D)
D(a=2)
```

5.6 Structuring hook factories

Hook factories operate one level higher than structuring hooks; structuring hooks are functions registered to a class or predicate, and hook factories are functions (registered via a predicate) that produce structuring hooks.

Structuring hooks factories are registered using `cattr.Converter.register_structure_hook_factory`.

Here's a small example showing how to use factory hooks to apply the *forbid_extra_keys* to all attr classes:

```
>>> from attr import define, has
>>> from cattr.gen import make_dict_structure_fn

>>> c = cattr.Converter()
>>> c.register_structure_hook_factory(has, lambda cl: make_dict_structure_fn(cl, c, _
↳ cattr.forbid_extra_keys=True, _cattr_detailed_validation=False))

>>> @define
... class E:
...     an_int: int

>>> c.structure({"an_int": 1, "else": 2}, E)
Traceback (most recent call last):
...
cattr.errors.ForbiddenExtraKeysError: Extra fields in constructor for E: else
```

A complex use case for hook factories is described over at *Using factory hooks*.

WHAT YOU CAN UNSTRUCTURE AND HOW

Unstructuring is intended to convert high-level, structured Python data (like instances of complex classes) into simple, unstructured data (like dictionaries).

Unstructuring is simpler than structuring in that no target types are required. Simply provide an argument to `unstructure` and `cattrs` will produce a result based on the registered unstructuring hooks. A number of default unstructuring hooks are documented [here](#).

Unstructuring is primarily done using `Converter.unstructure`.

6.1 Primitive types and collections

Primitive types (integers, floats, strings...) are simply passed through. Collections are copied. There's relatively little value in unstructuring these types directly as they are already unstructured and third-party libraries tend to support them directly.

A useful use case for unstructuring collections is to create a deep copy of a complex or recursive collection.

```
>>> # A dictionary of strings to lists of tuples of floats.
>>> data = {'a': [[1.0, 2.0], [3.0, 4.0]]}
>>>
>>> copy = cattrs.unstructure(data)
>>> data == copy
True
>>> data is copy
False
```

6.2 Customizing collection unstructuring

Important: This feature is supported for Python 3.9 and later.

Sometimes it's useful to be able to override collection unstructuring in a generic way. A common example is using a JSON library that doesn't support sets, but expects lists and tuples instead.

Using ordinary unstructuring hooks for this is unwieldy due to the semantics of `singledispatch`; in other words, you'd need to register hooks for all specific types of set you're using (`set[int]`, `set[float]`, `set[str]`...), which is not useful.

Function-based hooks can be used instead, but come with their own set of challenges - they're complicated to write efficiently.

The `Converter` supports easy customizations of collection unstructuring using its `unstruct_collection_overrides` parameter. For example, to unstructure all sets into lists, try the following:

```
>>> from collections.abc import Set
>>> converter = cattr.Converter(unstruct_collection_overrides={Set: list})
>>>
>>> converter.unstructure({1, 2, 3})
[1, 2, 3]
```

Going even further, the `Converter` contains heuristics to support the following Python types, in order of decreasing generality:

- `Sequence`, `MutableSequence`, `list`, `tuple`
- `Set`, `frozenset`, `MutableSet`, `set`
- `Mapping`, `MutableMapping`, `dict`, `Counter`

For example, if you override the `unstructure` type for `Sequence`, but not for `MutableSequence`, `list` or `tuple`, the override will also affect those types. An easy way to remember the rule:

- all `MutableSequence` `s` are `Sequence` `s`, so the override will apply
- all `list` `s` are `MutableSequence` `s`, so the override will apply
- all `tuple` `s` are `Sequence` `s`, so the override will apply

If, however, you override only `MutableSequence`, fields annotated as `Sequence` will not be affected (since not all sequences are mutable sequences), and fields annotated as tuples will not be affected (since tuples are not mutable sequences in the first place).

Similar logic applies to the set and mapping hierarchies.

Make sure you're using the types from `collections.abc` on Python 3.9+, and from `typing` on older Python versions.

6.3 `typing.Annotated`

Fields marked as `typing.Annotated[type, ...]` are supported and are matched using the first type present in the annotated type.

6.4 `typing.NewType`

`NewTypes` are supported and are unstructured according to the rules for their underlying type. Their hooks can also be overridden using `cattr.Converter.register_unstructure_hook`.

New in version 22.2.0.

See also:

Structuring NewTypes.

Note: `NewTypes` are not supported by the legacy `BaseConverter`.

6.5 attr classes and dataclasses

attr classes and dataclasses are supported out of the box. `cattrs.Converter`s support two unstructuring strategies:

- `UnstructureStrategy.AS_DICT` - similar to `attr.asdict`, unstructures attr and dataclass instances into dictionaries. This is the default.
- `UnstructureStrategy.AS_TUPLE` - similar to `attr.astuple`, unstructures attr and dataclass instances into tuples.

```
>>> @define
... class C:
...     a = field()
...     b = field()
...
>>> inst = C(1, 'a')
>>>
>>> converter = cattrs.Converter(unstruct_strat=cattrs.UnstructureStrategy.AS_TUPLE)
>>>
>>> converter.unstructure(inst)
(1, 'a')
```

6.5.1 Mixing and matching strategies

Converters publicly expose two helper methods, `Converter.unstructure_attrs_asdict()` and `Converter.unstructure_attrs_astuple()`. These methods can be used with custom unstructuring hooks to selectively apply one strategy to instances of particular classes.

Assume two nested attr classes, `Inner` and `Outer`; instances of `Outer` contain instances of `Inner`. Instances of `Outer` should be unstructured as dictionaries, and instances of `Inner` as tuples. Here's how to do this.

```
>>> @define
... class Inner:
...     a: int
...
>>> @define
... class Outer:
...     i: Inner
...
>>> inst = Outer(i=Inner(a=1))
>>>
>>> converter = cattrs.Converter()
>>> converter.register_unstructure_hook(Inner, converter.unstructure_attrs_astuple)
>>>
>>> converter.unstructure(inst)
{'i': (1,)}
```

Of course, these methods can be used directly as well, without changing the converter strategy.

```
>>> @define
... class C:
...     a: int
...     b: str
```

(continues on next page)

(continued from previous page)

```
...
>>> inst = C(1, 'a')
>>>
>>> converter = cattr.Converter()
>>>
>>> converter.unstructure_attrs_astuple(inst) # Default is AS_DICT.
(1, 'a')
```

6.6 Unstructuring hook factories

Hook factories operate one level higher than unstructuring hooks; unstructuring hooks are functions registered to a class or predicate, and hook factories are functions (registered via a predicate) that produce unstructuring hooks.

Unstructuring hooks factories are registered using `cattr.Converter.register_unstructure_hook_factory`.

Here's a small example showing how to use factory hooks to skip unstructuring `init=False` attributes on all *cattr* classes.

```
>>> from attr import define, has, field, fields
>>> from cattr import override
>>> from cattr.gen import make_dict_unstructure_fn

>>> c = cattr.Converter()
>>> c.register_unstructure_hook_factory(has, lambda cl: make_dict_unstructure_fn(cl, c,
↳ **{a.name: override(omit=True) for a in fields(cl) if not a.init}))

>>> @define
... class E:
...     an_int: int
...     another_int: int = field(init=False)

>>> inst = E(1)
>>> inst.another_int = 5
>>> c.unstructure(inst)
{'an_int': 1}
```

A complex use case for hook factories is described over at *Using factory hooks*.

VALIDATION

*cattr*s has a detailed validation mode since version 22.1.0, and this mode is enabled by default. When running under detailed validation, the un/structuring hooks are slightly slower but produce more precise and exhaustive error messages.

7.1 Detailed validation

In detailed validation mode, any un/structuring errors will be grouped and raised together as a *cattr*s.
`BaseValidationError`, which is a [PEP 654](#) `ExceptionGroup`. `ExceptionGroups` are special exceptions which contain lists of other exceptions, which may themselves be other `ExceptionGroups`. In essence, `ExceptionGroups` are trees of exceptions.

When un/structuring a class, *cattr*s will gather any exceptions on a field-by-field basis and raise them as a *cattr*s.
`ClassValidationError`, which is a subclass of `BaseValidationError`. When structuring sequences and mappings, *cattr*s will gather any exceptions on a key- or index-basis and raise them as a *cattr*s.
`IterableValidationError`, which is a subclass of `BaseValidationError`.

The exceptions will also have their `__notes__` attributes set, as per [PEP 678](#), showing the field, key or index for each inner exception.

A simple example involving a class containing a list and a dictionary:

```
@define
class Class:
    a_list: list[int]
    a_dict: dict[str, int]

>>> structure({"a_list": ["a"], "a_dict": {"str": "a"}})
+ Exception Group Traceback (most recent call last):
|   File "<stdin>", line 1, in <module>
|   File "/Users/tintvrtkovic/pg/cattr/src/cattr/converters.py", line 276, in _
↳ structure
|     return self._structure_func.dispatch(cl)(obj, cl)
|   File "<cattr generated structure __main__.Class>", line 14, in structure_Class
|     if errors: raise __c_cve('While structuring Class', errors, __cl)
| cattr.errors.ClassValidationError: While structuring Class
+----- 1 -----
| Exception Group Traceback (most recent call last):
|   File "<cattr generated structure __main__.Class>", line 5, in structure_Class
|     res['a_list'] = __c_structure_a_list(o['a_list'], __c_type_a_list)
|   File "/Users/tintvrtkovic/pg/cattr/src/cattr/converters.py", line 457, in _
↳ structure_list
```

(continues on next page)

(continued from previous page)

```

|         raise IterableValidationError(
| cattr.errors.IterableValidationError: While structuring list[int]
| Structuring class Class @ attribute a_list
+----- 1 -----
| Traceback (most recent call last):
|   File "/Users/tintvrtkovic/pg/cattr/src/cattr/converters.py", line 450, in _
↪structure_list
|     res.append(handler(e, elem_type))
|   File "/Users/tintvrtkovic/pg/cattr/src/cattr/converters.py", line 375, in _
↪structure_call
|     return cl(obj)
| ValueError: invalid literal for int() with base 10: 'a'
| Structuring list[int] @ index 0
+-----
+----- 2 -----
| Exception Group Traceback (most recent call last):
|   File "<cattr generated structure __main__.Class>", line 10, in structure_Class
|     res['a_dict'] = __c_structure_a_dict(o['a_dict'], __c_type_a_dict)
|   File "", line 17, in structure_mapping
| cattr.errors.IterableValidationError: While structuring dict
| Structuring class Class @ attribute a_dict
+----- 1 -----
| Traceback (most recent call last):
|   File "", line 5, in structure_mapping
| ValueError: invalid literal for int() with base 10: 'a'
| Structuring mapping value @ key 'str'
+-----

```

7.2 Non-detailed validation

Non-detailed validation can be enabled by initializing any of the converters with `detailed_validation=False`. In this mode, any errors during un/structuring will bubble up directly as soon as they happen.

PRECONFIGURED CONVERTERS

The `cattr.preconf` package contains factories for preconfigured converters, specifically adjusted for particular serialization libraries.

For example, to get a converter configured for BSON:

```
>>> from cattr.preconf.bson import make_converter
>>> converter = make_converter() # Takes the same parameters as the ``Converter``
```

Converters obtained this way can be customized further, just like any other converter.

These converters support the following classes and type annotations, both for structuring and unstructuring:

- `str`, `bytes`, `int`, `float`, `int` enums, `string` enums
- `attrs` classes and `dataclasses`
- lists, homogenous tuples, heterogenous tuples, dictionaries, counters, sets, frozensets
- optionals
- sequences, mutable sequences, mappings, mutable mappings, sets, mutable sets
- `datetime.datetime`

New in version 22.1.0: All preconf converters now have `loads` and `dumps` methods, which combine un/structuring and the de/serialization logic from their underlying libraries.

```
>>> from cattr.preconf.json import make_converter
>>> converter = make_converter()

>>> @define
... class Test:
...     a: int
>>>

>>> converter.dumps(Test(1))
'{"a": 1}'
```

Particular libraries may have additional constraints documented below.

8.1 Standard library json

Found at `cattr.preconf.json`.

Bytes are serialized as base 85 strings. Counters are serialized as dictionaries. Sets are serialized as lists, and deserialized back into sets. `datetime` s are serialized as ISO 8601 strings.

8.2 ujson

Found at `cattr.preconf.ujson`.

Bytes are serialized as base 85 strings. Sets are serialized as lists, and deserialized back into sets. `datetime` s are serialized as ISO 8601 strings.

`ujson` doesn't support integers less than -9223372036854775808, and greater than 9223372036854775807, nor does it support `float('inf')`.

8.3 orjson

Found at `cattr.preconf.orjson`.

Bytes are serialized as base 85 strings. Sets are serialized as lists, and deserialized back into sets. `datetime` s are serialized as ISO 8601 strings.

`orjson` doesn't support integers less than -9223372036854775808, and greater than 9223372036854775807. `orjson` only supports mappings with string keys so mappings will have their keys stringified before serialization, and destringified during deserialization.

8.4 msgpack

Found at `cattr.preconf.msgpack`.

Sets are serialized as lists, and deserialized back into sets. `datetime` s are serialized as UNIX timestamp float values.

`msgpack` doesn't support integers less than -9223372036854775808, and greater than 18446744073709551615.

When parsing `msgpack` data from bytes, the library needs to be passed `strict_map_key=False` to get the full range of compatibility.

8.5 bson

Found at `cattr.preconf.bson`. Tested against the `bson` module bundled with the `pymongo` library, not the standalone PyPI `bson` package.

Sets are serialized as lists, and deserialized back into sets.

`bson` doesn't support integers less than -9223372036854775808 or greater than 9223372036854775807 (64-bit signed). `bson` does not support null bytes in mapping keys. `bson` only supports mappings with string keys so mappings will have their keys stringified before serialization, and destringified during deserialization. The `bson` `datetime` representation doesn't support microsecond accuracy.

When encoding and decoding, the library needs to be passed `codec_options=bson.CodecOptions(tz_aware=True)` to get the full range of compatibility.

8.6 pyyaml

Found at `cattr.preconf.pyyaml`.

Frozensets are serialized as lists, and deserialized back into frozensets.

8.7 tomlkit

Found at `cattr.preconf.tomlkit`.

Bytes are serialized as base 85 strings. Sets are serialized as lists, and deserialized back into sets. Tuples are serialized as lists, and deserialized back into tuples. `tomlkit` only supports mappings with string keys so mappings will have their keys stringified before serialization, and destringified during deserialization.

CUSTOMIZING CLASS UN/STRUCTURING

This section deals with customizing the unstructuring and structuring processes in *cattr*s.

9.1 Using `cattr.Converter`

The default `Converter`, upon first encountering an `attrs` class, will use the generation functions mentioned here to generate the specialized hooks for it, register the hooks and use them.

9.2 Manual un/structuring hooks

You can write your own structuring and unstructuring functions and register them for types using `Converter.register_structure_hook` and `Converter.register_unstructure_hook`. This approach is the most flexible but also requires the most amount of boilerplate.

9.3 Using `cattr.gen` generators

*cattr*s includes a module, `cattr.gen`, which allows for generating and compiling specialized functions for unstructuring `attrs` classes.

One reason for generating these functions in advance is that they can bypass a lot of *cattr*s machinery and be significantly faster than normal *cattr*s.

Another reason is that it's possible to override behavior on a per-attribute basis.

Currently, the overrides only support generating dictionary un/structuring functions (as opposed to tuples), and support `omit_if_default`, `forbid_extra_keys`, `rename` and `omit`.

9.3.1 `omit_if_default`

This override can be applied on a per-class or per-attribute basis. The generated unstructuring function will skip unstructuring values that are equal to their default or factory values.

```
>>> from cattr.gen import make_dict_unstructure_fn, override
>>>
>>> @define
... class WithDefault:
...     a: int
```

(continues on next page)

(continued from previous page)

```

...     b: dict = Factory(dict)
>>>
>>> c = cattr.Converter()
>>> c.register_unstructure_hook(WithDefault, make_dict_unstructure_fn(WithDefault, c,
↳b=override(omit_if_default=True)))
>>> c.unstructure(WithDefault(1))
{'a': 1}

```

Note that the per-attribute value overrides the per-class value. A side-effect of this is the ability to force the presence of a subset of fields. For example, consider a class with a *DateTime* field and a factory for it: skipping the unstructuring of the *DateTime* field would be inconsistent and based on the current time. So we apply the *omit_if_default* rule to the class, but not to the *DateTime* field.

Note: The parameter to *make_dict_unstructure_function* is named `_cattr_omit_if_default` instead of just `omit_if_default` to avoid potential collisions with an override for a field named `omit_if_default`.

```

>>> from pendulum import DateTime
>>> from cattr.gen import make_dict_unstructure_fn, override
>>>
>>> @define
... class TestClass:
...     a: Optional[int] = None
...     b: DateTime = Factory(DateTime.utcnow)
>>>
>>> c = cattr.Converter()
>>> hook = make_dict_unstructure_fn(TestClass, c, _cattr_omit_if_default=True,
↳b=override(omit_if_default=False))
>>> c.register_unstructure_hook(TestClass, hook)
>>> c.unstructure(TestClass())
{'b': ...}

```

This override has no effect when generating structuring functions.

9.3.2 forbid_extra_keys

By default `cattr` is lenient in accepting unstructured input. If extra keys are present in a dictionary, they will be ignored when generating a structured object. Sometimes it may be desirable to enforce a stricter contract, and to raise an error when unknown keys are present - in particular when fields have default values this may help with catching typos. *forbid_extra_keys* can also be enabled (or disabled) on a per-class basis when creating structure hooks with *make_dict_structure_fn*.

```

>>> from cattr.gen import make_dict_structure_fn
>>>
>>> @define
... class TestClass:
...     number: int = 1
>>>
>>> c = cattr.Converter(forbid_extra_keys=True)
>>> c.structure({"number": 2}, TestClass)
Traceback (most recent call last):

```

(continues on next page)

(continued from previous page)

```
...
ForbiddenExtraKeyError: Extra fields in constructor for TestClass: number
>>> hook = make_dict_structure_fn(TestClass, c, _cattr_forbid_extra_keys=False)
>>> c.register_structure_hook(TestClass, hook)
>>> c.structure({"nummber": 2}, TestClass)
TestClass(number=1)
```

This behavior can only be applied to classes or to the default for the *Converter*, and has no effect when generating unstructuring functions.

9.3.3 rename

Using the rename override makes cattr simply use the provided name instead of the real attribute name. This is useful if an attribute name is a reserved keyword in Python.

```
>>> from pendulum import DateTime
>>> from cattr.gen import make_dict_unstructure_fn, make_dict_structure_fn, override
>>>
>>> @define
... class ExampleClass:
...     klass: Optional[int]
>>>
>>> c = cattr.Converter()
>>> unst_hook = make_dict_unstructure_fn(ExampleClass, c, klass=override(rename="class"))
>>> st_hook = make_dict_structure_fn(ExampleClass, c, klass=override(rename="class"))
>>> c.register_unstructure_hook(ExampleClass, unst_hook)
>>> c.register_structure_hook(ExampleClass, st_hook)
>>> c.unstructure(ExampleClass(1))
{'class': 1}
>>> c.structure({'class': 1}, ExampleClass)
ExampleClass(klass=1)
```

9.3.4 omit

This override can only be applied to individual attributes. Using the omit override will simply skip the attribute completely when generating a structuring or unstructuring function.

```
>>> from cattr.gen import make_dict_unstructure_fn, override
>>>
>>> @define
... class ExampleClass:
...     an_int: int
>>>
>>> c = cattr.Converter()
>>> unst_hook = make_dict_unstructure_fn(ExampleClass, c, an_int=override(omit=True))
>>> c.register_unstructure_hook(ExampleClass, unst_hook)
>>> c.unstructure(ExampleClass(1))
{}
```


TIPS FOR HANDLING UNIONS

This section contains information for advanced union handling.

As mentioned in the structuring section, `cattrs` is able to handle simple unions of `attrs` classes automatically. More complex cases require converter customization (since there are many ways of handling unions).

10.1 Unstructuring unions with extra metadata

Let's assume a simple scenario of two classes, `ClassA` and `ClassB`, both of which have no distinct fields and so cannot be used automatically with `cattrs`.

```
@define
class ClassA:
    a_string: str

@define
class ClassB:
    a_string: str
```

A naive approach to unstructuring either of these would yield identical dictionaries, and not enough information to restructure the classes.

```
>>> converter.unstructure(ClassA("test"))
{'a_string': 'test'} # Is this ClassA or ClassB? Who knows!
```

What we can do is ensure some extra information is present in the unstructured data, and then use that information to help structure later.

First, we register an unstructure hook for the `Union[ClassA, ClassB]` type.

```
>>> converter.register_unstructure_hook(
...     Union[ClassA, ClassB],
...     lambda o: {"_type": type(o).__name__, **converter.unstructure(o)}
... )
>>> converter.unstructure(ClassA("test"), unstructure_as=Union[ClassA, ClassB])
{'_type': 'ClassA', 'a_string': 'test'}
```

Note that when unstructuring, we had to provide the `unstructure_as` parameter or `cattrs` would have just applied the usual unstructuring rules to `ClassA`, instead of our special union hook.

Now that the unstructured data contains some information, we can create a structuring hook to put it to use:

```
>>> converter.register_structure_hook(
...     Union[ClassA, ClassB],
...     lambda o, _: converter.structure(o, ClassA if o["_type"] == "ClassA" else ClassB)
... )
>>> converter.structure({"_type": "ClassA", "a_string": "test"}, Union[ClassA, ClassB])
ClassA(a_string='test')
```

In the future, *cattr*s will gain additional tools to make union handling even easier and automate generating these hooks.

BENCHMARKING

cattr includes a benchmarking suite to help detect performance regressions and guide performance optimizations.

The suite is based on `pytest` and `pytest-benchmark`. Benchmarks are similar to tests, with the exception of being stored in the *bench/* directory and being used to verify performance instead of correctness.

11.1 A Sample Workflow

First, ensure the system you're benchmarking on is as stable as possible. For example, the `pyperf` library has a *system tune* command that can tweak CPU frequency governors. You also might want to quit as many applications as possible and run the benchmark suite on isolated CPU cores (*taskset* can be used for this purpose on Linux).

Then, generate a baseline using *make bench*. This will run the benchmark suite and save it into a file.

Following that, implement the changes you have in mind. Run the test suite to ensure correctness. Then, compare the performance of the new code to the saved baseline using *make bench-cmp*. If the code is still correct but faster, congratulations!

CONTRIBUTING

Contributions are welcome, and they are greatly appreciated! Every little bit helps, and credit will always be given. You can contribute in many ways:

12.1 Types of Contributions

12.1.1 Report Bugs

Report bugs at <https://github.com/python-attrs/cattrs/issues>.

If you are reporting a bug, please include:

- Your operating system name and version.
- Any details about your local setup that might be helpful in troubleshooting.
- Detailed steps to reproduce the bug.

12.1.2 Fix Bugs

Look through the GitHub issues for bugs. Anything tagged with “bug” and “help wanted” is open to whoever wants to implement it.

12.1.3 Implement Features

Look through the GitHub issues for features. Anything tagged with “enhancement” and “help wanted” is open to whoever wants to implement it.

12.1.4 Write Documentation

cattrs could always use more documentation, whether as part of the official cattrs docs, in docstrings, or even on the web in blog posts, articles, and such.

12.1.5 Submit Feedback

The best way to send feedback is to file an issue at <https://github.com/python-attrs/cattr/issues>.

If you are proposing a feature:

- Explain in detail how it would work.
- Keep the scope as narrow as possible, to make it easier to implement.
- Remember that this is a volunteer-driven project, and that contributions are welcome :)

12.2 Get Started!

Ready to contribute? Here's how to set up *cattr* for local development.

1. Fork the *cattr* repo on GitHub.
2. Clone your fork locally:

```
$ git clone git@github.com:your_name_here/cattr.git
```

3. Install your local copy into a virtualenv. Assuming you have poetry installed, this is how you set up your fork for local development:

```
$ cd cattr/  
$ poetry install
```

4. Create a branch for local development:

```
$ git checkout -b name-of-your-bugfix-or-feature
```

Now you can make your changes locally.

5. When you're done making changes, check that your changes pass flake8 and the tests, including testing other Python versions with tox:

```
$ poetry shell  
$ flake8 src tests  
$ pytest  
$ tox
```

6. Commit your changes and push your branch to GitHub:

```
$ git add .  
$ git commit -m "Your detailed description of your changes."  
$ git push origin name-of-your-bugfix-or-feature
```

7. Submit a pull request through the GitHub website.

12.3 Pull Request Guidelines

Before you submit a pull request, check that it meets these guidelines:

1. The pull request should include tests.
2. If the pull request adds functionality, the docs should be updated. Put your new functionality into a function with a docstring, and add the feature to the list in README.rst.
3. The pull request should work for all supported Python versions. Check <https://github.com/python-attrs/cattrs/actions> and make sure that the tests pass for all supported Python versions.

12.4 Tips

To run a subset of tests:

```
$ pytest tests.test_unstructure
```


HISTORY

13.1 22.2.0 (2022-10-03)

- *Potentially breaking*: `cattr.Converter` has been renamed to `cattr.BaseConverter`, and `cattr.GenConverter` to `cattr.Converter`. The `GenConverter` name is still available for backwards compatibility, but is deprecated. If you were depending on functionality specific to the old `Converter`, change your import to `from cattr import BaseConverter`.
- `NewTypes` are now supported by the `cattr.Converter`. (#255, #94, #297)
- `cattr.Converter` and `cattr.BaseConverter` can now copy themselves using the `copy` method. (#284)
- Python 3.11 support.
- `cattr` now supports un/structuring `kw_only` fields on `attrs` classes into/from dictionaries. (#247)
- PyPy support (and tests, using a minimal Hypothesis profile) restored. (#253)
- Fix propagating the `detailed_validation` flag to mapping and counter structuring generators.
- Fix `typing.Set` applying too broadly when used with the `GenConverter`. `unstruct_collection_overrides` parameter on Python versions below 3.9. Switch to `typing.AbstractSet` on those versions to restore the old behavior. (#264)
- Uncap the required Python version, to avoid problems detailed in <https://iscinumpy.dev/post/bound-version-constraints/#pinning-the-python-version-is-special> (#275)
- Fix `Converter.register_structure_hook_factory` and `cattr.gen.make_dict_unstructure_fn` type annotations. (#281)
- Expose all error classes in the `cattr.errors` namespace. Note that it is deprecated, just use `cattr.errors`. (#252)
- Fix generating structuring functions for types with quotes in the name. (#291 #277)
- Fix usage of notes for the final version of PEP 678, supported since `exceptiongroup>=1.0.0rc4`. (#303 <303)

13.2 22.1.0 (2022-04-03)

- `cattr` now uses the CalVer versioning convention.
- `cattr` now has a detailed validation mode, which is enabled by default. Learn more [here](#). The old behavior can be restored by creating the converter with `detailed_validation=False`.
- `attrs` and `dataclass` structuring is now ~25% faster.
- Fix an issue structuring bare `typing.List`s on Pythons lower than 3.9. (#209)

- Fix structuring of non-parametrized containers like `list/dict/...` on Pythons lower than 3.9. (#218)
- Fix structuring bare `typing.Tuple` on Pythons lower than 3.9. (#218)
- Fix a wrong `AttributeError` of an missing `__parameters__` attribute. This could happen when inheriting certain generic classes – for example `typing.*` classes are affected. (#217)
- Fix structuring of `enum.Enum` instances in `typing.Literal` types. (#231)
- Fix unstructuring all tuples - unannotated, variable-length, homogenous and heterogenous - to `list`. (#226)
- For `forbid_extra_keys` raise custom `ForbiddenExtraKeyError` instead of generic `Exception`. (#225)
- All preconf converters now support loads and dumps directly. See an example [here](#).
- Fix mappings with byte keys for the orjson, bson and tomlkit converters. (#241)

13.3 1.10.0 (2022-01-04)

- Add PEP 563 (string annotations) support for dataclasses. (#195)
- Fix handling of dictionaries with string Enum keys for bson, orjson, and tomlkit.
- Rename the `cattr.gen.make_dict_unstructure_fn.omit_if_default` parameter to `_cattr_omit_if_default`, for consistency. The `omit_if_default` parameters to `GenConverter` and `override` are unchanged.
- Following the changes in `attrs 21.3.0`, add a `cattr` package mirroring the existing `cattr` package. Both package names may be used as desired, and the `cattr` package isn't going away.

13.4 1.9.0 (2021-12-06)

- Python 3.10 support, including support for the new union syntax (`A | B` vs `Union[A, B]`).
- The `GenConverter` can now properly structure generic classes with generic collection fields. (#149)
- `omit=True` now also affects generated structuring functions. (#166)
- `cattr.gen.{make_dict_structure_fn, make_dict_unstructure_fn}` now resolve type annotations automatically when PEP 563 is used. (#169)
- Protocols are now unstructured as their runtime types. (#177)
- Fix an issue generating structuring functions with renaming and `_cattr_forbid_extra_keys=True`. (#190)

13.5 1.8.0 (2021-08-13)

- Fix `GenConverter` mapping structuring for unannotated dicts on Python 3.8. (#151)
- The source code for generated un/structuring functions is stored in the `linecache` cache, which enables more informative stack traces when un/structuring errors happen using the `GenConverter`. This behavior can optionally be disabled to save memory.
- Support using the `attr` converter callback during structure. By default, this is a method of last resort, but it can be elevated to the default by setting `prefer_attr_converters=True` on `Converter` or `GenConverter`. (#138)
- Fix structuring recursive classes. (#159)

- Converters now support un/structuring hook factories. This is the most powerful and complex venue for customizing un/structuring. This had previously been an internal feature.
- The [Common Usage Examples](#) documentation page now has a section on advanced hook factory usage.
- `cattr.override` now supports the `omit` parameter, which makes `cattr` skip the attribute entirely when unstructuring.
- The `cattr.preconf.bson` module is now tested against the `bson` module bundled with the `pymongo` package, because that package is much more popular than the standalone PyPI `bson` package.

13.6 1.7.1 (2021-05-28)

- `Literal` s are not supported on Python 3.9.0 (supported on 3.9.1 and later), so we skip importing them there. ([#150](#))

13.7 1.7.0 (2021-05-26)

- `cattr.global_converter` (which provides `cattr.unstructure`, `cattr.structure` etc.) is now an instance of `cattr.GenConverter`.
- `Literal` s are now supported and validated when structuring.
- Fix dependency metadata information for `attrs`. ([#147](#))
- Fix `GenConverter` mapping structuring for unannotated dicts. ([#148](#))

13.8 1.6.0 (2021-04-28)

- `cattr` now uses Poetry.
- `GenConverter` mapping structuring is now ~25% faster, and unstructuring heterogenous tuples is significantly faster.
- Add `cattr.preconf`. This package contains modules for making converters for particular serialization libraries. We currently support the standard library `json`, and third-party `ujson`, `orjson`, `msgpack`, `bson`, `pyyaml` and `tomlkit` libraries.

13.9 1.5.0 (2021-04-15)

- Fix an issue with `GenConverter` unstructuring `attrs` classes and dataclasses with generic fields. ([#65](#))
- `GenConverter` has support for easy overriding of collection unstructuring types (for example, `unstructure` all sets to lists) through its `unstruct_collection_overrides` argument. ([#137](#))
- Unstructuring mappings with `GenConverter` is significantly faster.
- `GenConverter` supports strict handling of unexpected dictionary keys through its `forbid_extra_keys` argument. ([#142](#))

13.10 1.4.0 (2021-03-21)

- Fix an issue with `GenConverter` un/structuring hooks when a function hook is registered after the converter has already been used.
- Add support for `collections.abc.{Sequence, MutableSequence, Set, MutableSet}`. These should be used on 3.9+ instead of their typing alternatives, which are deprecated. (#128)
- The `GenConverter` will unstructure iterables (`list[T]`, `tuple[T, ...]`, `set[T]`) using their type argument instead of the runtime class if its elements, if possible. These unstructuring operations are up to 40% faster. (#129)
- Flesh out `Converter` and `GenConverter` initializer type annotations. (#131)
- Add support for `typing.Annotated` on Python 3.9+. `cattr` will use the first annotation present. `cattr` specific annotations may be added in the future. (#127)
- Add support for dataclasses. (#43)

13.11 1.3.0 (2021-02-25)

- `cattr` now has a benchmark suite to help make and keep `cattr` the fastest it can be. The instructions on using it can be found under the *Benchmarking* <<https://cattr.readthedocs.io/en/latest/benchmarking.html>> section in the docs. (#123)
- Fix an issue unstructuring tuples of non-primitives. (#125)
- `cattr` now calls `attr.resolve_types` on `attrs` classes when registering un/structuring hooks.
- `GenConverter` structuring and unstructuring of `attrs` classes is significantly faster.

13.12 1.2.0 (2021-01-31)

- `converter.unstructure` now supports an optional parameter, `unstructure_as`, which can be used to unstructure something as a different type. Useful for unions.
- Improve support for union un/structuring hooks. Flesh out docs for advanced union handling. (#115)
- Fix `GenConverter` behavior with inheritance hierarchies of `attrs` classes. (#117) (#116)
- Refactor `GenConverter.un/structure_attrs_fromdict` into `GenConverter.gen_un/structure_attrs_fromdict` to allow calling back to `Converter.un/structure_attrs_fromdict` without sideeffects. (#118)

13.13 1.1.2 (2020-11-29)

- The default disambiguator will not consider non-required fields any more. (#108)
- Fix a couple type annotations. (#107) (#105)
- Fix a `GenConverter` unstructuring issue and tests.

13.14 1.1.1 (2020-10-30)

- Add metadata for supported Python versions. (#103)

13.15 1.1.0 (2020-10-29)

- Python 2, 3.5 and 3.6 support removal. If you need it, use a version below 1.1.0.
- Python 3.9 support, including support for built-in generic types (`list[int]` vs `typing.List[int]`).
- `cattr` now includes functions to generate specialized structuring and unstructuring hooks. Specialized hooks are faster and support overrides (`omit_if_default` and `rename`). See the `cattr.gen` module.
- `cattr` now includes a converter variant, `cattr.GenConverter`, that automatically generates specialized hooks for `attrs` classes. This converter will become the default in the future.
- Generating specialized structuring hooks now invokes `attr.resolve_types` on a class if the class makes use of the new PEP 563 annotations.
- `cattr` now depends on `attrs >= 20.1.0`, because of `attr.resolve_types`.
- Specialized hooks now support generic classes. The default converter will generate and use a specialized hook upon encountering a generic class.

13.16 1.0.0 (2019-12-27)

- `attrs` classes with private attributes can now be structured by default.
- Structuring from dictionaries is now more lenient: extra keys are ignored.
- `cattr` has improved type annotations for use with Mypy.
- Unstructuring sets and frozensets now works properly.

13.17 0.9.1 (2019-10-26)

- Python 3.8 support.

13.18 0.9.0 (2018-07-22)

- Python 3.7 support.

13.19 0.8.1 (2018-06-19)

- The disambiguation function generator now supports unions of `attrs` classes and `NoneType`.

13.20 0.8.0 (2018-04-14)

- Distribution fix.

13.21 0.7.0 (2018-04-12)

- Removed the undocumented `Converter.unstruct_strat` property setter.
- Removed the ability to set the `Converter.structure_attrs` instance field.
As an alternative, create a new `Converter`:

```
.. code-block:: python
```

```
>>> converter = cattr.Converter(unstruct_strat=cattr.UnstructureStrategy.AS_TUPLE)
```

- Some micro-optimizations were applied; a `structure(unstructure(obj))` roundtrip is now up to 2 times faster.

13.22 0.6.0 (2017-12-25)

- Packaging fixes. (#17)

13.23 0.5.0 (2017-12-11)

- `structure/unstructure` now supports using functions as well as classes for deciding the appropriate function.
- added `Converter.register_structure_hook_func`, to register a function instead of a class for determining handler func.
- added `Converter.register_unstructure_hook_func`, to register a function instead of a class for determining handler func.
- vendored typing is no longer needed, nor provided.
- Attributes with default values can now be structured if they are missing in the input. (#15)
- *Optional* attributes can no longer be structured if they are missing in the input.
In other words, this no longer works:

```
.. code-block:: python
```

```
@attr.s
class A:
    a: Optional[int] = attr.ib()
```

```
>>> cattr.structure({}, A)
```

- `cattr.typed` removed since the functionality is now present in `attrs` itself. Replace instances of `cattr.typed(type)` with `attr.ib(type=type)`.

13.24 0.4.0 (2017-07-17)

- *Converter.loads* is now *Converter.structure*, and *Converter.dumps* is now *Converter.unstructure*.
- Python 2.7 is supported.
- Moved `cattr.typing` to `cattr.vendor.typing` to support different vendored versions of `typing.py` for Python 2 and Python 3.
- Type metadata can be added to `attrs` classes using `cattr.typed`.

13.25 0.3.0 (2017-03-18)

- Python 3.4 is no longer supported.
- Introduced `cattr.typing` for use with Python versions 3.5.2 and 3.6.0.
- Minor changes to work with newer versions of `typing`.
 - Bare Optionals are not supported any more (use `Optional[Any]`).
- Attempting to load unrecognized classes will result in a `ValueError`, and a helpful message to register a loads hook.
- Loading `attrs` classes is now documented.
- The global converter is now documented.
- `cattr.loads_attrs_fromtuple` and `cattr.loads_attrs_fromdict` are now exposed.

13.26 0.2.0 (2016-10-02)

- Tests and documentation.

13.27 0.1.0 (2016-08-13)

- First release on PyPI.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`